

1. Variable Initialization

Question: Write a program that declares an integer variable, initializes it with a value of 42, and prints the value to the console.

ANS::

```
#include<stdio.h>

int main(){

    int a=42;

    printf("Value of a= %d",a);

    return 0;

}
```

Value of a= 42

2. Swapping Variables

Question: Create a program that swaps the values of two integer variables without using a temporary variable. Demonstrate this by printing the values before and after the swap.

ANS::

```
#include<stdio.h>

int main(){

    int a=10;

    printf("a=%d\n",a);

    int b=20;

    printf("b=%d\n",b);

    printf("After Swapping\n");

    a=a+b;

    b=a-b;

    a=a-b;

    printf("a=%d\n",a);

}
```

```
printf("b=%d\n",b);

return 0;

}
```

a=10

b=20

After Swapping

a=20

b=10

3. User Input and Output

Question: Write a program that prompts the user to enter their name and age, stores these values in appropriate variables, and then prints a greeting message that includes both the name and age.

ANS::

```
#include<stdio.h>

int main() {

    char a[10];

    int b;

    printf("Enter your name::");

    scanf("%s",&a);

    printf("\nEnter your age::");

    scanf("%d",&b);

    printf("\nHello! %s,%d",a,b);

    return 0;

}
```

Enter your name::Ananthu

Enter your age::23

Hello! Ananthu,23

4. Data Type Conversion

Question: Write a program that declares an integer variable, assigns it a value of 10, and then converts it to a float variable. Print both the integer and float values to show the conversion.

ANS::

```
#include<stdio.h>

int main(){

    int a=10;

    float b = (float)a;

    printf("Integer::%d",a);

    printf("\nFloat::%f\n",b);

    return 0;

}
```

Integer::10

Float::10.000000

5. Constants vs. Variables

Question: Using `#define`, create a constant for the value of Pi (3.14). Write a program that calculates the area of a circle given its radius (stored in a variable) and prints the result using the constant for Pi.

ANS::

```
#include<stdio.h>

#define pi 3.14

int main(){

    int r;
```

```

float a;

printf("Enter radius::");

scanf("%d",&r);

a=pi*r*r;

printf("\nArea::%f",a);

return 0;

}

```

Enter radius::4

Area::50.240002

6. Scope of Variables

Question: Write a program that demonstrates the concept of variable scope by declaring a global variable and modifying it within a function. Print the value of the global variable before and after modification.

ANS::

```

#include<stdio.h>

int a =10;

void modify(){

    a =20;

}

int main(){

    printf("Global value of a::%d",a);

    modify();

    printf("\nAfter Modification value of a::%d",a);

    return 0;
}

```

```
}
```

Global value of a::10

After Modification value of a::20

8. Using Augmented Assignment Operators

Question: Write a program that uses augmented assignment operators (**+=**, **-=**, ***=**, **/=**) to perform calculations on an integer variable initialized to 100. Print the value after each operation.

ANS::

```
#include<stdio.h>

int main(){

    int a =100;

    printf("Initially a=%d",a);

    a+=20;

    printf("\nAfter +=20 a=%d",a);

    a-=20;

    printf("\nAfter -=20 a=%d",a);

    a*=20;

    printf("\nAfter *=20 a=%d",a);

    a/=20;

    printf("\nAfter /=20 a=%d",a);

    return 0;

}
```

Initially a=100

After +=20 a=120

After -=20 a=100

After *=20 a=2000

After /=20 a=100

9. Array of Variables

Question: Create an array of integers with five elements. Initialize it with values of your choice, then write a program to calculate and print the sum of all elements in the array.

ANS::

```
#include<stdio.h>
int main(){
    int i,a[5];
    printf("Enter values into array");
    for (i=0;i<5;i++)
    {
        scanf("%d",&a[i]);
    }
    int sum =0;
    for (i=0;i<5;i++)
    {
        sum+=a[i];
    }
    printf("\nSUM of Array Values::%d",sum);
    return 0;
}
```

Enter values into array 1 2 3 4 5

SUM of Array Values::15

Assignment: User Authentication Program

Objective

Create a C program that prompts the user for a username and password, then checks if the entered credentials match predefined values. Use logical operators to determine if the authentication is successful.

Requirements

1. Define two constants for the correct username and password.
2. Prompt the user to enter their username and password.
3. Use logical operators (&&, ||, !) to check if:
4. If both are correct, display a success message.
5. Implement additional checks:
 - If the username is empty, display a message indicating that the username cannot be empty.

- If the password is empty, display a message indicating that the password cannot be empty.
- The username matches the predefined username AND the password matches the predefined password.
- If either the username or password is incorrect, display an appropriate error message.

ANS::

```
#include<stdio.h>
int main(){
    char u[10],p[10];
    printf("Enter USERNAME::\n");
    scanf("%s",&u);
    if(u != NULL)
    {
        if(p != NULL)
        {
            if((strcmp(u,"user")==0) || (strcmp(u,"admin")==0))
            {
                printf("Enter PASSWORD::\n");
                scanf("%s",&p);
                if((strcmp(u,"user")==0) && (strcmp(p,"user")==0))
                {
                    printf("WELCOME USER\n");
                }
                else if ((strcmp(u,"admin")==0) &&
(strcmp(p,"admin")==0))
                {
                    printf("WELCOME ADMIN\n");
                }
                else
                {
                    printf("Wrong password\n");
                }
            }
        }
        else
        {
            printf("INVALID USERNAME\n");
        }
    }
}
```

```

        else
        {
            printf("Password can't be empty\n");
        }

    }
    else
    {
        printf("Username can't be empty\n");
    }
    return 0;
}

```

Enter USERNAME::

user

Enter PASSWORD::

user

WELCOME USER

Enter USERNAME::

admin

Enter PASSWORD::

admin

WELCOME ADMIN

Enter USERNAME::

user

Enter PASSWORD::

admin

Wrong password

Enter USERNAME::

wrong

INVALID USERNAME

Find a Number is even or odd without using arithmetic operator?

ANS::

```

#include<stdio.h>
int main(){
    int a;
    printf("Enter a number\n");
    scanf("%d",&a);
    if(a & 1)
    {
        printf("ODD Number");
    }
}

```



```
}  
else  
{  
    printf("EVEN Number");  
}  
return 0;  
}
```

Enter a number

7

ODD Number

Enter a number

8

EVEN Number