

Spider Vault 60.0

Comparison Sheet



SPIDER VAULT 60.0 — BESS

	Usage	Lifts + Multiple ACs + Data Centre + All 3-Phase Industrial Loads
	Output Signal	Pure Sine Wave — Safe for all sensitive equipment
	Surge Capacity	60 kVA (60,000 VA, equal to rated) — Handles all 3-phase industrial loads
	Running Cost	₹0/hr via Solar · Grid top-up ~₹6–8/unit only
	Transfer Time	10 ms — Zero perceptible interruption to any load
	Noise Level	< 50 dB — Runs silently indoors, no enclosure needed
	Emissions	Zero Emissions — No CO ₂ , no NOx, no fumes
	Backup & Solar	60 kWh Battery · 14 units · 66 kW Solar (12 MPPT) — Continuous with solar
	Life / Warranty	Up to 12 Years · 5 Yr Warranty + Extended 12 Yr Option
	Maintenance	Zero Maintenance — No oil, no filters, no AMC required
	Connectivity	Wi-Fi · Bluetooth · CAN · AI Cloud · Remote Monitoring
	System Efficiency	~94% Peak Efficiency · ≥99% MPPT Efficiency · IP65 Outdoor Rated

VS

60 KVA DIESEL GENERATOR SET

	Basic 3-phase loads only — not suitable for sensitive IT equipment	×
	Alternator output — voltage spikes & harmonics damage electronics	×
	Fixed 60 KVA rated output — trips & shuts down on motor surges	×
	₹1,250–₹1,300/hr diesel — 11.5 L/hr at full load @₹109–113/L (industrial, 2026)	×
	10–30 sec startup delay — servers crash, lifts stop mid-floor	×
	≤75 dBA — Requires dedicated enclosure room with exhaust ducting	×
	CO ₂ + NOx + diesel fumes — health hazard, CPCB permits required	×
	~10–13 hrs (120 L tank) — stops when fuel runs out, refuelling needed	×
	5–7 Year lifespan · 1–2 Year Warranty (Kirloskar / Ashok Leyland)	×
	Oil change every 200 hrs · AMC ₹25,000–₹38,000/yr + spare parts	×
	No remote monitoring, no data logging, no smart connectivity	×
	~30–35% thermodynamic efficiency — 65–70% energy wasted as heat	×