

Copying Report

1. Setting namespace (Optional)

Command:

\$ setcontext.sh <namespace_name>

Example:

\$ setcontext.sh gtapi

2. List the Cougar pods

\$ kubectl get pods -n <namespace> | grep cougar

\$ kubectl get pods -n gtapi | grep cougar

3. Login to the pod

\$ kubectl exec -it <pod_name> -n <namespace> bash

\$ kubectl exec -it cougar-gtapi-asd768dsaf789a8df8 -n gtapi bash

4. Navigate to reports directory

\$ cd webapps/ROOT/WEB-INF/

5. Create zip file of the report directory

\$ tar zcvf report.tgz ./report

6. exit from the pod

\$ ctrl + d or type "exit"

7. Navigate to the directory called 'report-engine-2'

\$ cd /opt/k8s/k8s-workloads/<namespace>/report-engine-2

Example:

\$ cd /opt/k8s/k8s-workloads/gtapi/report-engine-2

8. Delete the existing report.tgz and backup of the report directory

\$ rm report.tgz

\$ rm -r report-bkp

Rename the 'report' directory to 'report-bkp' to create a backup.

\$ mv report report-bkp

9. To copy the zipped report folder from the pod to new report engine, first we will copy it to the respective namespace's report-engine-2 directory.

Command:

\$ kubectl -n {namespace} cp

<pod_name>:/usr/local/tomcat/webapps/ROOT/WEB-INF/report.tgz ./report.tgz

Example:

kubectl -n gtapi cp

cougar-gtapi-bf4d7c986-mpv7w:/usr/local/tomcat/webapps/ROOT/WEB-INF/report.tgz ./report.tgz

Output:

You will get the following output if it get copied successfully:

Defaulting container name to app.

tar: Removing leading `/' from member names

10. Now since we successfully copied the compressed report file into the respective namespace. Now we are going to untar(unzip) it and start the final step to copy the report folder to new report engine. To untar the tar file which we just copied:

Command:

\$ tar zxvf report.tgz

Here(in the same directory) you will get a new directory named 'report'.

11. Then finally we are going to copy the report directory to new report engine by running the script present in same(Cougar) directory named "cp-scripts.sh".

\$./cp-reports.sh

12. The changes will get reflect only if we restart the report pod named "{namespace}-report-engine-report-engine-2-12a345b67c89-g23b56".
For example "gtapi-report-engine-report-engine-2-676bc6846c-s76xp"

13. To do so navigate to report-engine-2 directory (/opt/k8s/k8s-workloads/{namespace}/report-engine-2, for example: /opt/k8s/k8s-workloads/gtapi/report-engine-2).

14. To restart it run the following command:

\$ helminst.sh

Output:

Executing: helm install --namespace gtapi -n gtapi-report-engine -f values.yaml
greytip/report-engine-2

Error: a release named gtapi-report-engine already exists.

Run: helm ls --all gtapi-report-engine; to check the status of the release

Or run: **helm del --purge gtapi-report-engine;** to delete it

15. Copy and run the purge command from the output we got in our last step.

Example:

\$ helm del --purge gtapi-report-engine;

By doing this we are going to stop the report engine.

16. As we already stopped the report engine, now we are going to start the report engine again. To do so run the "helminst" command once again:

\$ helminst.sh

17. To ensure that the report engine pod is up, we have to list the all pods:

Command:

\$ kubectl get pods -n {namespace}

Example:

\$ kubectl get pods -n gtapi

Note: Here if the number of pods are x/x (fully up) of report engine then our task is done

Summary:

```
setcontext.sh <name_space>
```

```
cd /opt/k8s/k8s-workloads/<namespace>/report-engine-2
```

```
rm -r report-bkp
```

```
mv report report-bkp
```

```
mkdir report
```

```
kubectl -n {namespace} cp <pod_name>:/usr/local/tomcat/webapps/ROOT/WEB-INF/report ./report
```

```
sh cp-script.sh
```

```
kubect delete pod <report_engine_pod_name>
```