

Practical -06 Client Server Application

A)

Terminal 1

```
shreenitha@shreenitha2203:~$ gcc server.c
shreenitha@shreenitha2203:~$ ./a.out
Server waiting for client...
Client says: hello this is my os class

shreenitha@shreenitha2203:~$ |
```

Terminal 2

```
shreenitha@shreenitha2203:~$ gcc client.c
shreenitha@shreenitha2203:~$ ./a.out
Enter message: hello this is my os class
Server says: Message received by server
shreenitha@shreenitha2203:~$ |
```

B)

Terminal 1

```
shreenitha@shreenitha2203:~$ nano signal3.c
shreenitha@shreenitha2203:~$ gcc signal3.c
shreenitha@shreenitha2203:~$ ./a.out
Process ID: 6434
Waiting for signals...
```

Ctrl+c enter

```
shreenitha@shreenitha2203:~$ nano signal3.c
shreenitha@shreenitha2203:~$ gcc signal3.c
shreenitha@shreenitha2203:~$ ./a.out
Process ID: 6434
Waiting for signals...
^C
SIGINT received
```

Terminal 2

```
shreenitha@shreenitha2203:~$ kill -SIGUSR1 6434
```

In terminal1

Output -

```
shreenitha@shreenitha2203:~$ nano signal3.c
shreenitha@shreenitha2203:~$ gcc signal3.c
shreenitha@shreenitha2203:~$ ./a.out
Process ID: 6434
Waiting for signals...
^C
SIGINT received
SIGUSR1 received
|
```