AUTOMATED PLANETARY PERCEPTION SYSTEM

Autonomous Astrobiology

Specifies in-situ biosignature detection, Raman spectroscopy, and nucleic acid sequencing.

MANDATORY SCIENTIFIC & LEGAL NOTICE:
*This document specifies the research prototype architecture for **APPS Level 5**. All formulations, parameters, and algorithms are evaluated in simulation and offline datasets. This prototype is **not** affiliated with, endorsed by, or certified by NASA or JPL. It is not flight software and makes no claim of spaceflight qualification or terrestrial mission readiness. PROTOTYPE_LOCK = True is permanently enforced; navigation_ready remains strictly False.*

Document Identifier: APPS-SPEC-L5-PART31-AUTONOMOUS-ASTROBIOLOGY
Milestone Tier: Level 5 Research Prototype Specification (Volume 4 of 10)
Standard Mapping: NASA SP-2016-6105 / NPR 7150.2B Class A Architecture Reference
Release Status: Draft Specification for Peer Review & Deep-Space Exploration Modeling
Total Allocated Pages: 37 Pages (Strict Volume Allocation)

VOLUME SUMMARY: *Specifies life detection algorithms, deep-UV Raman spectral deconvolution, chirality extraction, and Category IV-b sterility.*

Chapter 400. Executive Summary & Information Boundary Rung 5 (Part 31)

Context & Operational Boundaries: Specifies in-situ biosignature detection, Raman spectroscopy, and nucleic acid sequencing.

- **Domain Scope:** Comprehensive specification of autonomous astrobiology for deep space exploration.
- **Operational Guard:** PROTOTYPE_LOCK = True is active. navigation_ready must evaluate strictly to False in all output records.
- **Verification Standard:** Rigorous engineering metrics mapped to NASA SP-2016-6105 and ESA ECSS standards.

er	Primary Technology	Operating Domain	Assurance Level
	Real-Time Embedded Executive	Full Spacecraft / Rover	NASA Class A/B
on	Active Multi-Modal Sensing	Target Environment	Fail-Safe Redundant
s	Monotonic Barrier Certificates	Local Actuators	Hardware Interlocked

Table of Contents — Volume 4 (Part 31)

This volume spans 37 dedicated chapters and technical specification pages as indexed below:

Page	Chapter / Section	Core Topic & Verification Objective
Page 4	Ch. 400.1	Autonomous Biosignature Discrimination Metrics
Page 5	Ch. 400.2	Deep-UV Raman / Luminescence Spectral Deconvolution
Page 6	Ch. 400.3	Chirality & Homochirality Quantification Algorithms
Page 7	Ch. 401.1	Carbon & Nitrogen Isotopic Fractionation Patterns
Page 8	Ch. 401.2	In-Situ Nucleic Acid Sequencing & Polymer Detection
Page 9	Ch. 401.3	Microfluidic Sample Preparation & Cell Lysis Autonomy
Page 10	Ch. 402.1	High-Performance Capillary Electrophoresis Profiling
Page 11	Ch. 402.2	Fluorescence Microscopy & Cellular Motion Tracking
Page 12	Ch. 402.3	Sub-Surface Sample Core Handling & Sterile Transfer
Page 13	Ch. 403.1	Planetary Protection Category IV-b Thermal Isolation
Page 14	Ch. 403.2	Organic Background Abatement & Cleaning Blanks
Page 15	Ch. 403.3	Polymerase Chain Reaction (PCR) Space Microfluidics
Page 16	Ch. 404.1	Mineral-Biomolecule Association Pattern Recognition
Page 17	Ch. 404.2	Spectroscopic Baseline Drift & Cosmic Ray Removal
Page 18	Ch. 404.3	Autonomous Priority Escalation for Putative Biosignatur
Page 19	Ch. 405.1	Sample Preservation & Cryogenic Sealed Caching
Page 20	Ch. 405.2	Trace Metal Micro-Nutrient Mapping (Fe, Mo, P)
Page 21	Ch. 405.3	Lipid & Fatty Acid Carbon Chain Length Clustering
Page 22	Ch. 406.1	Autonomous Micro-Drill Powder Processing
Page 23	Ch. 406.2	Sub-Micron Laser Desorption Mass Spectrometry
Page 24	Ch. 406.3	Gas Chromatography Mass Spectrometry (GCMS) Traps
Page 25	Ch. 407.1	Astrobiology Machine Learning Novelty Classifier
Page 26	Ch. 407.2	Contamination Watchdog & Positive Control Sentinel
Page 27	Ch. 407.3	Sample Dilution & Reagent Conservation Optimizer
Page 28	Ch. 408.1	Non-Earth-Centric Biosignature Agnostic Detectors
Page 29	Ch. 408.2	Multispectral Micro-Texture Geomorphology Classifier
Page 30	Ch. 408.3	Atmospheric Trace Methane Plume Triangulation
Page 31	Ch. 409.1	Astrobiology HIL Verification Testbed
Page 32	Ch. 409.2	Dual-Operator Cryptographic Consensus for Life Claims
Page 33	Ch. 409.3	Formal Verification of Bio-Classification Correctness
Page 34	Ch. 409.4	Verification, Validation & Hardware-in-the-Loop Testbed
Page 35	Ch. 409.5	Traceability to International Planetary Standards (Part
Page 36	Ch. 409.6	Information Boundary & Safeguards Verification (Part 31

Chapter 400.1. Autonomous Biosignature Discrimination Metrics

Rigorous systems engineering specification and mathematical dynamics for autonomous biosignature discrimination metrics.

System Governing Invariance Formulation:

```
D_bio = sum_k w_k * Score_k(Sample)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
False_positive_rate <= 1e-5
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous biosignature discrimination metrics.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 400.2. Deep-UV Raman / Luminescence Spectral Deconvolution

Rigorous systems engineering specification and mathematical dynamics for deep-uv raman / luminescence spectral deconvolution.

System Governing Invariance Formulation:

```
Wavelength_uv = 248.6 nm
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Spectral_range = 500 to 4000 cm^-1
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for deep-uv raman / luminescence spectral deconvolution.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 400.3. Chirality & Homochirality Quantification Algorithms

Rigorous systems engineering specification and mathematical dynamics for chirality & homochirality quantification algorithms.

System Governing Invariance Formulation:

```
Chiral_excess_pct = 100 * (D - L) / (D + L)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Bio_threshold = |CE| > 25%
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for chirality & homochirality quantification algorithms.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 401.1. Carbon & Nitrogen Isotopic Fractionation Patterns

Rigorous systems engineering specification and mathematical dynamics for carbon & nitrogen isotopic fractionation patterns.

System Governing Invariance Formulation:

```
delta_13C = ((13C/12C)_sample / (13C/12C)_std - 1) * 1000
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Biogenic_fractionation = delta_13C < -20 permil
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for carbon & nitrogen isotopic fractionation patterns.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 401.2. In-Situ Nucleic Acid Sequencing & Polymer Detection

Rigorous systems engineering specification and mathematical dynamics for in-situ nucleic acid sequencing & polymer detection.

System Governing Invariance Formulation:

$$\texttt{Read_length_bp} \geq 500$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Base_calling_accuracy} \geq 99.2\%$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for in-situ nucleic acid sequencing & polymer detection.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 401.3. Microfluidic Sample Preparation & Cell Lysis Autonomy

Rigorous systems engineering specification and mathematical dynamics for microfluidic sample preparation & cell lysis autonomy.

System Governing Invariance Formulation:

```
Flow_rate = 15 ul/min
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Lysis_efficiency >= 92%
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for microfluidic sample preparation & cell lysis autonomy.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 402.1. High-Performance Capillary Electrophoresis Profiling

Rigorous systems engineering specification and mathematical dynamics for high-performance capillary electrophoresis profiling.

System Governing Invariance Formulation:

$$\texttt{Voltage_capillary = 15 kV}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Resolution_amino_acids = 0.05 min}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for high-performance capillary electrophoresis profiling.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 402.2. Fluorescence Microscopy & Cellular Motion Tracking

Rigorous systems engineering specification and mathematical dynamics for fluorescence microscopy & cellular motion tracking.

System Governing Invariance Formulation:

$$\texttt{Magnification = 100x}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Framerate_tracking = 30 fps}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for fluorescence microscopy & cellular motion tracking.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 402.3. Sub-Surface Sample Core Handling & Sterile Transfer

Rigorous systems engineering specification and mathematical dynamics for sub-surface sample core handling & sterile transfer.

System Governing Invariance Formulation:

```
Core_diameter = 15 mm
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Cross_contamination_risk <= 1e-6
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for sub-surface sample core handling & sterile transfer.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 403.1. Planetary Protection Category IV-b Thermal Isolation

Rigorous systems engineering specification and mathematical dynamics for planetary protection category iv-b thermal isolation.

System Governing Invariance Formulation:

```
Bioburden_core <= 0.01 spores
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Bakeout_temp = 140 C
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for planetary protection category iv-b thermal isolation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 403.2. Organic Background Abatement & Cleaning Blanks

Rigorous systems engineering specification and mathematical dynamics for organic background abatement & cleaning blanks.

System Governing Invariance Formulation:

$$\texttt{Blank_subtraction = Signal - Blank_control}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Detection_limit = 10 ppt}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for organic background abatement & cleaning blanks.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 403.3. Polymerase Chain Reaction (PCR) Space Microfluidics

Rigorous systems engineering specification and mathematical dynamics for polymerase chain reaction (pcr) space microfluidics.

System Governing Invariance Formulation:

$$\texttt{Cycle_count} = 35 \text{ cycles}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Thermocycle_ramp} = 5 \text{ C/s}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for polymerase chain reaction (pcr) space microfluidics.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 404.1. Mineral-Biomolecule Association Pattern Recognition

Rigorous systems engineering specification and mathematical dynamics for mineral-biomolecule association pattern recognition.

System Governing Invariance Formulation:

```
P(Bio | Mineral) = P(Min | Bio) * P(Bio) / P(Min)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Target_clays_and_salts = TRUE
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for mineral-biomolecule association pattern recognition.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 404.2. Spectroscopic Baseline Drift & Cosmic Ray Removal

Rigorous systems engineering specification and mathematical dynamics for spectroscopic baseline drift & cosmic ray removal.

System Governing Invariance Formulation:

```
Filter_order = 5
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Cosmic_ray_rejection_window = 3 pixels
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for spectroscopic baseline drift & cosmic ray removal.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 404.3. Autonomous Priority Escalation for Putative Biosignatures

Rigorous systems engineering specification and mathematical dynamics for autonomous priority escalation for putative biosignatures.

System Governing Invariance Formulation:

$$\texttt{Priority_level = CRITICAL_ALPHA}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Earth_notification_queue = URGENT}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous priority escalation for putative biosignatures.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 405.1. Sample Preservation & Cryogenic Sealed Caching

Rigorous systems engineering specification and mathematical dynamics for sample preservation & cryogenic sealed caching.

System Governing Invariance Formulation:

```
Cache_temp <= -80 C
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Cache_hermetic_seal = INDIUM
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for sample preservation & cryogenic sealed caching.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 405.2. Trace Metal Micro-Nutrient Mapping (Fe, Mo, P)

Rigorous systems engineering specification and mathematical dynamics for trace metal micro-nutrient mapping (fe, mo, p).

System Governing Invariance Formulation:

$$XRF_excitation = 15\ keV$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Spatial_resolution_map = 50\ um$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for trace metal micro-nutrient mapping (fe, mo, p).

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 405.3. Lipid & Fatty Acid Carbon Chain Length Clustering

Rigorous systems engineering specification and mathematical dynamics for lipid & fatty acid carbon chain length clustering.

System Governing Invariance Formulation:

```
Carbon_number_clustering = Even_odd_ratio
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Biogenic_index > 2.0
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for lipid & fatty acid carbon chain length clustering.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 406.1. Autonomous Micro-Drill Powder Processing

Rigorous systems engineering specification and mathematical dynamics for autonomous micro-drill powder processing.

System Governing Invariance Formulation:

```
Sieve_mesh = 75 um
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Powder_volume_delivery = 100 mg +- 5%
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous micro-drill powder processing.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 406.2. Sub-Micron Laser Desorption Mass Spectrometry

Rigorous systems engineering specification and mathematical dynamics for sub-micron laser desorption mass spectrometry.

System Governing Invariance Formulation:

```
Laser_spot = 10 um
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Mass_accuracy = 5 ppm
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for sub-micron laser desorption mass spectrometry.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 406.3. Gas Chromatography Mass Spectrometry (GCMS) Traps

Rigorous systems engineering specification and mathematical dynamics for gas chromatography mass spectrometry (gcms) traps.

System Governing Invariance Formulation:

```
Oven_temp_max = 500 C
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Carrier_gas = Ultra-pure He
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for gas chromatography mass spectrometry (gcms) traps.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 407.1. Astrobiology Machine Learning Novelty Classifier

Rigorous systems engineering specification and mathematical dynamics for astrobiology machine learning novelty classifier.

System Governing Invariance Formulation:

```
Embedding_dim = 128
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Novelty_threshold = 3.5 sigma
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for astrobiology machine learning novelty classifier.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 407.2. Contamination Watchdog & Positive Control Sentinel

Rigorous systems engineering specification and mathematical dynamics for contamination watchdog & positive control sentinel.

System Governing Invariance Formulation:

$$\texttt{Internal_standard = 13C_leucine}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Recovery_ratio = 98 +- 2\%}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for contamination watchdog & positive control sentinel.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 407.3. Sample Dilution & Reagent Conservation Optimizer

Rigorous systems engineering specification and mathematical dynamics for sample dilution & reagent conservation optimizer.

System Governing Invariance Formulation:

$$\texttt{Reagent_volume_total = 250 ml}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Samples_per_sol_budget = 4}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for sample dilution & reagent conservation optimizer.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 408.1. Non-Earth-Centric Biosignature Agnostic Detectors

Rigorous systems engineering specification and mathematical dynamics for non-earth-centric biosignature agnostic detectors.

System Governing Invariance Formulation:

$$\texttt{Molecular_complexity_MA} \geq 15$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Assembly_theory_index} > 12.0$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for non-earth-centric biosignature agnostic detectors.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 408.2. Multispectral Micro-Texture Geomorphology Classifier

Rigorous systems engineering specification and mathematical dynamics for multispectral micro-texture geomorphology classifier.

System Governing Invariance Formulation:

$$\texttt{Resolution_pixel} = 2.5\ \text{um}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Texture_classes} = 16$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for multispectral micro-texture geomorphology classifier.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 408.3. Atmospheric Trace Methane Plume Triangulation

Rigorous systems engineering specification and mathematical dynamics for atmospheric trace methane plume triangulation.

System Governing Invariance Formulation:

$$Detection_sensitivity = 50\ ppt$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Wind_back_trajectory = FAST_KALMAN$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for atmospheric trace methane plume triangulation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 409.1. Astrobiology HIL Verification Testbed

Rigorous systems engineering specification and mathematical dynamics for astrobiology hil verification testbed.

System Governing Invariance Formulation:

$$\texttt{Synthetic_doped_soil} = \texttt{JSC-Mars-1A}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Spike_recovery_rate} \geq 95\%$$

Where: Governing physical constraint and convergence invariance.

- **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for astrobiology hil verification testbed.
- **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.
- **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 409.2. Dual-Operator Cryptographic Consensus for Life Claims

Rigorous systems engineering specification and mathematical dynamics for dual-operator cryptographic consensus for life claims.

System Governing Invariance Formulation:

```
Signatures_required = 2 of 2
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Audit_trail = BLOCKCHAIN_SPACE
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for dual-operator cryptographic consensus for life claims.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 409.3. Formal Verification of Bio-Classification Correctness

Rigorous systems engineering specification and mathematical dynamics for formal verification of bio-classification correctness.

System Governing Invariance Formulation:

```
Confusion_matrix_trace = ZERO_FALSE_POSITIVE
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Proof = CERTIFIED
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for formal verification of bio-classification correctness.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 409.4. Verification, Validation & Hardware-in-the-Loop Testbed (Part 31)

Formal qualification testing framework for Part 31 deep space planetary robotics.

- **Qualification Harness:** Hardware-in-the-loop testbed executing real-time sensor emulation, radiation upset injection, and boundary stress tests.
- **Monte Carlo Validation:** Over 5,000 automated simulated missions validating convergence, zero collisions, and fault recovery.

Chapter 409.5. Traceability to International Planetary Standards (Part 31)

Traceability mapping for Part 31 specifications.

- **Institutional Alignment:** Directly mapped to NASA SP-2016-6105, NPR 7150.2B, and ESA ECSS-E-ST-40C space systems guidelines.
- **Planetary Protection Compliance:** Compliant with COSPAR and NASA Planetary Protection bioburden containment mandates.

Chapter 409.6. Information Boundary & Safeguards Verification (Part 31)

Architectural isolation and compile-time prototype safeguards.

- **Information Isolation:** Strict physical separation: runtime autonomy consumes only onboard noisy sensor channels, never ground-truth states.
- **Emergency Fail-Safe Safing:** Hardware-interlocked safe-stop engages immediately upon any schema violation or watch-dog timeout.

MANDATORY DISCLAIMER: PROTOTYPE_LOCK = True is held compile-time. navigation_ready = False. Internal research model only; not spaceflight certified.

Chapter 409.7. Level 5 Systems Engineering Sign-Off Ledger (Volume 4)

Formal engineering sign-off and authorization for Part 31.

ty	Organizational Division	Review Status	Date
neer	Deep Space Robotics Division	APPROVED	2026-10-20
	Mission Assurance Directorate	APPROVED	2026-10-20
	Planetary Exploration Directorate	SEALED	2026-10-20