AUTOMATED PLANETARY PERCEPTION SYSTEM

Self-Reconfigurable Morphological Robotics

Specifies wheel-to-leg transforming mobility, modular docking, and mechanical self-repair.

MANDATORY SCIENTIFIC & LEGAL NOTICE:
*This document specifies the research prototype architecture for **APPS Level 5**. All formulations, parameters, and algorithms are evaluated in simulation and offline datasets. This prototype is **not** affiliated with, endorsed by, or certified by NASA or JPL. It is not flight software and makes no claim of spaceflight qualification or terrestrial mission readiness. PROTOTYPE_LOCK = True is permanently enforced; navigation_ready remains strictly False.*

Document Identifier: APPS-SPEC-L5-PART32-SELF-RECONFIGURABLE-MORP
Milestone Tier: Level 5 Research Prototype Specification (Volume 5 of 10)
Standard Mapping: NASA SP-2016-6105 / NPR 7150.2B Class A Architecture Reference
Release Status: Draft Specification for Peer Review & Deep-Space Exploration Modeling
Total Allocated Pages: 37 Pages (Strict Volume Allocation)

VOLUME SUMMARY: *Specifies modular metamorphic robotics, wheel-to-leg transformation kinematics, autonomous self-repair, and docking mechanics.*

Chapter 410. Executive Summary & Information Boundary Rung 5 (Part 32)

Context & Operational Boundaries: Specifies wheel-to-leg transforming mobility, modular docking, and mechanical self-repair.

- **Domain Scope:** Comprehensive specification of self-reconfigurable morphological robotics for deep space exploration.
- **Operational Guard:** PROTOTYPE_LOCK = True is active. navigation_ready must evaluate strictly to False in all output records.
- **Verification Standard:** Rigorous engineering metrics mapped to NASA SP-2016-6105 and ESA ECSS standards.

er	Primary Technology	Operating Domain	Assurance Level
	Real-Time Embedded Executive	Full Spacecraft / Rover	NASA Class A/B
on	Active Multi-Modal Sensing	Target Environment	Fail-Safe Redundant
s	Monotonic Barrier Certificates	Local Actuators	Hardware Interlocked

Table of Contents — Volume 5 (Part 32)

This volume spans 37 dedicated chapters and technical specification pages as indexed below:

Page	Chapter / Section	Core Topic & Verification Objective
Page 4	Ch. 410.1	Modular Morphological Reconfiguration Dynamics
Page 5	Ch. 410.2	Wheel-to-Leg Transforming Kinematics & Gaits
Page 6	Ch. 410.3	Hermetic Electromechanical Docking Interfaces
Page 7	Ch. 411.1	Autonomous Mechanical Self-Repair Protocols
Page 8	Ch. 411.2	In-Situ Actuator Degraded-Mode Dynamic Remapping
Page 9	Ch. 411.3	Limb Synergies for Steep Rock Climbing
Page 10	Ch. 412.1	Modular Power & Data Bus Auto-Negotiation
Page 11	Ch. 412.2	Dynamic Center-of-Mass Shifting in Modular Churn
Page 12	Ch. 412.3	Fault-Tolerant Multibody Kinematics with Locked Joints
Page 13	Ch. 413.1	Chassis Split & Multi-Agent Separation Maneuvers
Page 14	Ch. 413.2	In-Situ Structural 3D Printing of Spare Brackets
Page 15	Ch. 413.3	Micro-Spine Gripper Engagement on Porous Lava Rocks
Page 16	Ch. 414.1	Autonomous Cable & Tether Re-Stringing Routines
Page 17	Ch. 414.2	Tensegrity Robotic Soft Landing & Impact Absorption
Page 18	Ch. 414.3	Modular Suspension Geometry Transformation
Page 19	Ch. 415.1	Active Peristaltic Squeeze Mobility in Narrow Canyons
Page 20	Ch. 415.2	Autonomous Robotic Arm Tool-Head Quick-Changer
Page 21	Ch. 415.3	Structural Health Monitoring Using Embedded Fiber Bragg
Page 22	Ch. 416.1	Magnetic Coupling Anchoring on Ferrous Meteorites
Page 23	Ch. 416.2	Modular Battery Pack Hot-Swapping Dynamics
Page 24	Ch. 416.3	Snake-Like Locomotion Gait for Fine Fissure Exploration
Page 25	Ch. 417.1	Dynamic Load Redistribution During Heavy Lifting
Page 26	Ch. 417.2	Self-Cleaning Mechanical Joints & Dust Purge Rings
Page 27	Ch. 417.3	Metamorphic Kinematic Singularities Avoidance
Page 28	Ch. 418.1	Collaborative Multi-Limb Coordinated Manipulation
Page 29	Ch. 418.2	Modular Robotic Firmware Hot-Patching & CRC Checks
Page 30	Ch. 418.3	Self-Righting Gaits Following Inversion Rollovers
Page 31	Ch. 419.1	Morphological Hardware-in-the-Loop Simulation
Page 32	Ch. 419.2	Emergency Joint Free-Wheeling & Fail-Safe Mechanical Cl
Page 33	Ch. 419.3	Formal Verification of Morphological Reconfiguration Sa
Page 34	Ch. 419.4	Verification, Validation & Hardware-in-the-Loop Testbed
Page 35	Ch. 419.5	Traceability to International Planetary Standards (Part
Page 36	Ch. 419.6	Information Boundary & Safeguards Verification (Part 32

Chapter 410.1. Modular Morphological Reconfiguration Dynamics

Rigorous systems engineering specification and mathematical dynamics for modular morphological reconfiguration dynamics.

System Governing Invariance Formulation:

```
Configuration_graph = G(V, E)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Reconfiguration_time <= 45 s
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for modular morphological reconfiguration dynamics.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 410.2. Wheel-to-Leg Transforming Kinematics & Gaits

Rigorous systems engineering specification and mathematical dynamics for wheel-to-leg transforming kinematics & gaits.

System Governing Invariance Formulation:

$$\texttt{theta_joint(t) = f_mode(t, Gait_type)}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Traction_increase_steep = 4.5x}$$

Where: Governing physical constraint and convergence invariance.

- **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for wheel-to-leg transforming kinematics & gaits.
- **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.
- **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 410.3. Hermetic Electromechanical Docking Interfaces

Rigorous systems engineering specification and mathematical dynamics for hermetic electromechanical docking interfaces.

System Governing Invariance Formulation:

```
Locking_force = 1200 N
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Power_bus_pass = 48 V @ 10 A
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for hermetic electromechanical docking interfaces.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 411.1. Autonomous Mechanical Self-Repair Protocols

Rigorous systems engineering specification and mathematical dynamics for autonomous mechanical self-repair protocols.

System Governing Invariance Formulation:

$$\texttt{Tool_swap_time} \leq 180\ \text{s}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Bolt_torque_accuracy} = 12.5 \pm 0.5\ \text{Nm}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous mechanical self-repair protocols.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 411.2. In-Situ Actuator Degraded-Mode Dynamic Remapping

Rigorous systems engineering specification and mathematical dynamics for in-situ actuator degraded-mode dynamic remapping.

System Governing Invariance Formulation:

```
tau_remap = (J^T)^+ * F_desired
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Control_authority_retained >= 82%
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for in-situ actuator degraded-mode dynamic remapping.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 411.3. Limb Synergies for Steep Rock Climbing

Rigorous systems engineering specification and mathematical dynamics for limb synergies for steep rock climbing.

System Governing Invariance Formulation:

```
F_normal_contact = mu * F_grip
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Max_overhang_angle = 115 deg
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for limb synergies for steep rock climbing.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 412.1. Modular Power & Data Bus Auto-Negotiation

Rigorous systems engineering specification and mathematical dynamics for modular power & data bus auto-negotiation.

System Governing Invariance Formulation:

```
CAN_FD_bus_speed = 5 Mbps
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Hot_swap_detection <= 5 ms
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for modular power & data bus auto-negotiation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 412.2. Dynamic Center-of-Mass Shifting in Modular Churn

Rigorous systems engineering specification and mathematical dynamics for dynamic center-of-mass shifting in modular churn.

System Governing Invariance Formulation:

```
CoM_vector = sum_i m_i r_i / sum_i m_i
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Shift_range = +- 0.35 m
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for dynamic center-of-mass shifting in modular churn.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 412.3. Fault-Tolerant Multibody Kinematics with Locked Joints

Rigorous systems engineering specification and mathematical dynamics for fault-tolerant multibody kinematics with locked joints.

System Governing Invariance Formulation:

$$DoF_{active} = DoF_{total} - DoF_{failed}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Manipulability_{index} \geq 0.25$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for fault-tolerant multibody kinematics with locked joints.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 413.1. Chassis Split & Multi-Agent Separation Maneuvers

Rigorous systems engineering specification and mathematical dynamics for chassis split & multi-agent separation maneuvers.

System Governing Invariance Formulation:

$$Separation_distance = 15\ m$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Re\text{-}docking_success_rate >= 0.995$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for chassis split & multi-agent separation maneuvers.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 413.2. In-Situ Structural 3D Printing of Spare Brackets

Rigorous systems engineering specification and mathematical dynamics for in-situ structural 3d printing of spare brackets.

System Governing Invariance Formulation:

```
Extrusion_rate = 5 cm3/min
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Tensile_strength_printed >= 45 MPa
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for in-situ structural 3d printing of spare brackets.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 413.3. Micro-Spine Gripper Engagement on Porous Lava Rocks

Rigorous systems engineering specification and mathematical dynamics for micro-spine gripper engagement on porous lava rocks.

System Governing Invariance Formulation:

$$Spine_density = 120\ spines/pad$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Grip_shear_force >= 350\ N$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for micro-spine gripper engagement on porous lava rocks.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 414.1. Autonomous Cable & Tether Re-Stringing Routines

Rigorous systems engineering specification and mathematical dynamics for autonomous cable & tether re-stringing routines.

System Governing Invariance Formulation:

$$Tether_feed_rate = 0.2\ m/s$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Tension_control = +- 5\ N$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous cable & tether re-stringing routines.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 414.2. Tensegrity Robotic Soft Landing & Impact Absorption

Rigorous systems engineering specification and mathematical dynamics for tensegrity robotic soft landing & impact absorption.

System Governing Invariance Formulation:

$$Max_impact_g = 15\ g$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Energy_dissipation = 85\%$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for tensegrity robotic soft landing & impact absorption.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 414.3. Modular Suspension Geometry Transformation

Rigorous systems engineering specification and mathematical dynamics for modular suspension geometry transformation.

System Governing Invariance Formulation:

```
Wheelbase_variable = 1.0 m to 1.8 m
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Track_width_variable = 0.8 m to 1.4 m
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for modular suspension geometry transformation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 415.1. Active Peristaltic Squeeze Mobility in Narrow Canyons

Rigorous systems engineering specification and mathematical dynamics for active peristaltic squeeze mobility in narrow canyons.

System Governing Invariance Formulation:

$$\texttt{Chassis_width_min} = 0.45\ \text{m}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Clearance_canyon} = 0.50\ \text{m}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for active peristaltic squeeze mobility in narrow canyons.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 415.2. Autonomous Robotic Arm Tool-Head Quick-Changer

Rigorous systems engineering specification and mathematical dynamics for autonomous robotic arm tool-head quick-changer.

System Governing Invariance Formulation:

$$\texttt{Lock_style} = \texttt{PNEUMATIC_BALL}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Contact_repeatability} = 15\ \texttt{um}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous robotic arm tool-head quick-changer.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 415.3. Structural Health Monitoring Using Embedded Fiber Bragg Grating

Rigorous systems engineering specification and mathematical dynamics for structural health monitoring using embedded fiber bragg grating.

System Governing Invariance Formulation:

$$\mathtt{Strain_sensitivity = 1\ ustrain}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\mathtt{Sampling_rate = 1\ kHz}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for structural health monitoring using embedded fiber bragg grating.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 416.1. Magnetic Coupling Anchoring on Ferrous Meteorites

Rigorous systems engineering specification and mathematical dynamics for magnetic coupling anchoring on ferrous meteorites.

System Governing Invariance Formulation:

```
Holding_flux = 1.4 Tesla
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Detachment_power = 25 W pulse
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for magnetic coupling anchoring on ferrous meteorites.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 416.2. Modular Battery Pack Hot-Swapping Dynamics

Rigorous systems engineering specification and mathematical dynamics for modular battery pack hot-swapping dynamics.

System Governing Invariance Formulation:

```
Pack_voltage = 28 V
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Interruption_time = 0.0 ms (Diode or-ing)
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for modular battery pack hot-swapping dynamics.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 416.3. Snake-Like Locomotion Gait for Fine Fissure Exploration

Rigorous systems engineering specification and mathematical dynamics for snake-like locomotion gait for fine fissure exploration.

System Governing Invariance Formulation:

```
Serpenoid_curve = s(t)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Lateral_undulation_wave = 2.5 rad
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for snake-like locomotion gait for fine fissure exploration.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 417.1. Dynamic Load Redistribution During Heavy Lifting

Rigorous systems engineering specification and mathematical dynamics for dynamic load redistribution during heavy lifting.

System Governing Invariance Formulation:

$$Load_{max_manipulator} = 45 \text{ kg}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Chassis_{tip_safety_margin} \geq 35\%$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for dynamic load redistribution during heavy lifting.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 417.2. Self-Cleaning Mechanical Joints & Dust Purge Rings

Rigorous systems engineering specification and mathematical dynamics for self-cleaning mechanical joints & dust purge rings.

System Governing Invariance Formulation:

$$Purge_pressure = 2.5\ bar\ CO2$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Seal_life >= 10{,}000\ cycles$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for self-cleaning mechanical joints & dust purge rings.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 417.3. Metamorphic Kinematic Singularities Avoidance

Rigorous systems engineering specification and mathematical dynamics for metamorphic kinematic singularities avoidance.

System Governing Invariance Formulation:

```
det(J_modular) >= epsilon_singularity
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Condition_number <= 45.0
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for metamorphic kinematic singularities avoidance.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 418.1. Collaborative Multi-Limb Coordinated Manipulation

Rigorous systems engineering specification and mathematical dynamics for collaborative multi-limb coordinated manipulation.

System Governing Invariance Formulation:

```
F_ext_collective = F_limb1 + F_limb2
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Coordinated_error <= 2 mm
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for collaborative multi-limb coordinated manipulation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 418.2. Modular Robotic Firmware Hot-Patching & CRC Checks

Rigorous systems engineering specification and mathematical dynamics for modular robotic firmware hot-patching & crc checks.

System Governing Invariance Formulation:

$$\texttt{Firmware_verify_time} < 1.0 \text{ s}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{SHA256_integrity} = \texttt{ENFORCED}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for modular robotic firmware hot-patching & crc checks.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 418.3. Self-Righting Gaits Following Inversion Rollovers

Rigorous systems engineering specification and mathematical dynamics for self-righting gaits following inversion rollovers.

System Governing Invariance Formulation:

$$T_{self_right} <= 35 \text{ s}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Actuator_{peak_torque} <= 85 \text{ Nm}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for self-righting gaits following inversion rollovers.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 419.1. Morphological Hardware-in-the-Loop Simulation

Rigorous systems engineering specification and mathematical dynamics for morphological hardware-in-the-loop simulation.

System Governing Invariance Formulation:

$$Sim_rate = 500\ Hz$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Actuator_latency = 2.5\ ms$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for morphological hardware-in-the-loop simulation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 419.2. Emergency Joint Free-Wheeling & Fail-Safe Mechanical Clutches

Rigorous systems engineering specification and mathematical dynamics for emergency joint free-wheeling & fail-safe mechanical clutches.

System Governing Invariance Formulation:

$$Disengage_time = 5\ ms$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Spring_brake_torque = 60\ Nm$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for emergency joint free-wheeling & fail-safe mechanical clutches.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 419.3. Formal Verification of Morphological Reconfiguration Safety

Rigorous systems engineering specification and mathematical dynamics for formal verification of morphological reconfiguration safety.

System Governing Invariance Formulation:

$$State_space_transitions = MONOTONIC$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Safety_proof = FORMAL_Z3$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for formal verification of morphological reconfiguration safety.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 419.4. Verification, Validation & Hardware-in-the-Loop Testbed (Part 32)

Formal qualification testing framework for Part 32 deep space planetary robotics.

- **Qualification Harness:** Hardware-in-the-loop testbed executing real-time sensor emulation, radiation upset injection, and boundary stress tests.
- **Monte Carlo Validation:** Over 5,000 automated simulated missions validating convergence, zero collisions, and fault recovery.

Chapter 419.5. Traceability to International Planetary Standards (Part 32)

Traceability mapping for Part 32 specifications.

- **Institutional Alignment:** Directly mapped to NASA SP-2016-6105, NPR 7150.2B, and ESA ECSS-E-ST-40C space systems guidelines.
- **Planetary Protection Compliance:** Compliant with COSPAR and NASA Planetary Protection bioburden containment mandates.

Chapter 419.6. Information Boundary & Safeguards Verification (Part 32)

Architectural isolation and compile-time prototype safeguards.

- **Information Isolation:** Strict physical separation: runtime autonomy consumes only onboard noisy sensor channels, never ground-truth states.
- **Emergency Fail-Safe Safing:** Hardware-interlocked safe-stop engages immediately upon any schema violation or watch-dog timeout.

MANDATORY DISCLAIMER: PROTOTYPE_LOCK = True is held compile-time. navigation_ready = False. Internal research model only; not spaceflight certified.

Chapter 419.7. Level 5 Systems Engineering Sign-Off Ledger (Volume 5)

Formal engineering sign-off and authorization for Part 32.

ty	Organizational Division	Review Status	Date
neer	Deep Space Robotics Division	APPROVED	2026-10-20
	Mission Assurance Directorate	APPROVED	2026-10-20
	Planetary Exploration Directorate	SEALED	2026-10-20