AUTOMATED PLANETARY PERCEPTION SYSTEM

Decadal Continual Learning & Aging

Specifies multi-year continual learning without catastrophic forgetting and mechanical aging.

MANDATORY SCIENTIFIC & LEGAL NOTICE:
*This document specifies the research prototype architecture for **APPS Level 5**. All formulations, parameters, and algorithms are evaluated in simulation and offline datasets. This prototype is **not** affiliated with, endorsed by, or certified by NASA or JPL. It is not flight software and makes no claim of spaceflight qualification or terrestrial mission readiness. PROTOTYPE_LOCK = True is permanently enforced; navigation_ready remains strictly False.*

Document Identifier: APPS-SPEC-L5-PART36-DECADAL-CONTINUAL-LEARNI
Milestone Tier: Level 5 Research Prototype Specification (Volume 9 of 10)
Standard Mapping: NASA SP-2016-6105 / NPR 7150.2B Class A Architecture Reference
Release Status: Draft Specification for Peer Review & Deep-Space Exploration Modeling
Total Allocated Pages: 37 Pages (Strict Volume Allocation)

VOLUME SUMMARY: *Specifies decadal autonomous operations (10+ years), lifelong learning, mechanical wear compensation, and aging dynamics.*

Chapter 450. Executive Summary & Information Boundary Rung 5 (Part 36)

Context & Operational Boundaries: Specifies multi-year continual learning without catastrophic forgetting and mechanical aging.

- **Domain Scope:** Comprehensive specification of decadal continual learning & aging for deep space exploration.
- **Operational Guard:** PROTOTYPE_LOCK = True is active. navigation_ready must evaluate strictly to False in all output records.
- **Verification Standard:** Rigorous engineering metrics mapped to NASA SP-2016-6105 and ESA ECSS standards.

er	Primary Technology	Operating Domain	Assurance Level
	Real-Time Embedded Executive	Full Spacecraft / Rover	NASA Class A/B
on	Active Multi-Modal Sensing	Target Environment	Fail-Safe Redundant
s	Monotonic Barrier Certificates	Local Actuators	Hardware Interlocked

Table of Contents — Volume 9 (Part 36)

This volume spans 37 dedicated chapters and technical specification pages as indexed below:

Page	Chapter / Section	Core Topic & Verification Objective
Page 4	Ch. 450.1	Continual Lifelong Reinforcement Learning Without Forge
Page 5	Ch. 450.2	Bayesian Episodic Memory Replay for Planetary Habitats
Page 6	Ch. 450.3	Mechanical Wear & Actuator Degradation Online Estimatio
Page 7	Ch. 451.1	Solar Panel Dust Deposition & Aging Transmittance Curve
Page 8	Ch. 451.2	Battery Capacity Fade & Solid-Electrolyte Interphase (S
Page 9	Ch. 451.3	Radiation-Induced Transistor Leakage & Vth Shift Compen
Page 10	Ch. 452.1	Self-Supervised Online Perception Domain Adaptation
Page 11	Ch. 452.2	Metamorphic Structural Fatigue & Crack Propagation Moni
Page 12	Ch. 452.3	Optical Lens Radiation Browning & Deep-Color Center Ble
Page 13	Ch. 453.1	Wheel Grouser Abrasion & Puncture Autonomous Compensato
Page 14	Ch. 453.2	Thermal Insulation (MLI) Degradation & Mylar Embrittlem
Page 15	Ch. 453.3	Autonomous Sensor Self-Calibration & Cross-Sensor Consi
Page 16	Ch. 454.1	Long-Horizon Markov Decision Processes (MDP) Discountin
Page 17	Ch. 454.2	Scientific Value Preservation Across Multi-Year Campaig
Page 18	Ch. 454.3	Firmware Degradation & Flash Memory Bit-Rot Scrubbing E
Page 19	Ch. 455.1	Drive Motor Demagnetization Modeling Under High Tempera
Page 20	Ch. 455.2	Autonomous Retirement of Failed Sensors & Graceful Degr
Page 21	Ch. 455.3	Dynamic Re-Planning of Decadal Extended Science Objecti
Page 22	Ch. 456.1	Lubricant Outgassing & Cold-Welding Vacuum Mitigation
Page 23	Ch. 456.2	Evolutionary Meta-Learning for Unseen Geological Terran
Page 24	Ch. 456.3	Structural Damping & Fastener Preload Loss Detection
Page 25	Ch. 457.1	Radioisotope Thermoelectric Generator (RTG) Power Decay
Page 26	Ch. 457.2	Thermal Cycle Fatigue in Solder Joints & Electronic Ass
Page 27	Ch. 457.3	Dynamic Re-Tuning of Flight Control Gains Under System
Page 28	Ch. 458.1	Autonomous Knowledge Distillation into Low-Power Infere
Page 29	Ch. 458.2	Micro-Meteoroid Impact Pitting & Hull Integrity Monitor
Page 30	Ch. 458.3	Decadal Flight Software Autonomic Garbage Collection &
Page 31	Ch. 459.1	Decadal Lifelong Learning HIL Emulation (Simulated 10 Y
Page 32	Ch. 459.2	Autonomous End-of-Life Disposal & Planetary Protection
Page 33	Ch. 459.3	Formal Proof of Bounded Parameter Drift in Decadal Adap
Page 34	Ch. 459.4	Verification, Validation & Hardware-in-the-Loop Testbed
Page 35	Ch. 459.5	Traceability to International Planetary Standards (Part
Page 36	Ch. 459.6	Information Boundary & Safeguards Verification (Part 36

Chapter 450.1. Continual Lifelong Reinforcement Learning Without Forgetting

Rigorous systems engineering specification and mathematical dynamics for continual lifelong reinforcement learning without forgetting.

System Governing Invariance Formulation:

```
Loss_continual = L_current + lambda_ewc * sum_i F_i (theta_i - theta_i^*)^2
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Retained_performance >= 96%
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for continual lifelong reinforcement learning without forgetting.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 450.2. Bayesian Episodic Memory Replay for Planetary Habitats

Rigorous systems engineering specification and mathematical dynamics for bayesian episodic memory replay for planetary habitats.

System Governing Invariance Formulation:

$$Buffer_size_replays = 50{,}000$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Priority_weight = TD_error$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for bayesian episodic memory replay for planetary habitats.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 450.3. Mechanical Wear & Actuator Degradation Online Estimation

Rigorous systems engineering specification and mathematical dynamics for mechanical wear & actuator degradation online estimation.

System Governing Invariance Formulation:

```
Backlash_accum_mm = k_wear * sum F * dx
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Friction_coulomb_drift = +35% @ 10 yr
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for mechanical wear & actuator degradation online estimation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 451.1. Solar Panel Dust Deposition & Aging Transmittance Curves

Rigorous systems engineering specification and mathematical dynamics for solar panel dust deposition & aging transmittance curves.

System Governing Invariance Formulation:

```
Transmittance(t) = D_0 * exp(-lambda_dust * t) + Cleaning_events
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Half_life_dust = 450 sols
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for solar panel dust deposition & aging transmittance curves.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 451.2. Battery Capacity Fade & Solid-Electrolyte Interphase (SEI) Models

Rigorous systems engineering specification and mathematical dynamics for battery capacity fade & solid-electrolyte interphase (sei) models.

System Governing Invariance Formulation:

```
Cap_loss_pct = B * exp(-E_a / (R*T)) * t^0.5
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Cycle_life >= 10,000 cycles
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for battery capacity fade & solid-electrolyte interphase (sei) models.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 451.3. Radiation-Induced Transistor Leakage & Vth Shift Compensation

Rigorous systems engineering specification and mathematical dynamics for radiation-induced transistor leakage & vth shift compensation.

System Governing Invariance Formulation:

```
Delta_Vth = C_ox * Q_trapped
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Adaptive_body_biasing = ACTIVE
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for radiation-induced transistor leakage & vth shift compensation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 452.1. Self-Supervised Online Perception Domain Adaptation

Rigorous systems engineering specification and mathematical dynamics for self-supervised online perception domain adaptation.

System Governing Invariance Formulation:

$$\texttt{Domain_discrim_loss = min_G max_D L_adv}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Domain_shift_adapt_time < 30 min}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for self-supervised online perception domain adaptation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 452.2. Metamorphic Structural Fatigue & Crack Propagation Monitoring

Rigorous systems engineering specification and mathematical dynamics for metamorphic structural fatigue & crack propagation monitoring.

System Governing Invariance Formulation:

```
da/dN = C * (Delta_K)^m (Paris Law)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Inspection_interval = 50 sols
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for metamorphic structural fatigue & crack propagation monitoring.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 452.3. Optical Lens Radiation Browning & Deep-Color Center Bleaching

Rigorous systems engineering specification and mathematical dynamics for optical lens radiation browning & deep-color center bleaching.

System Governing Invariance Formulation:

$$\texttt{Optical_transmittance_bleach = 532 nm LED anneal}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Recovery_gain >= 18\%}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for optical lens radiation browning & deep-color center bleaching.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 453.1. Wheel Grouser Abrasion & Puncture Autonomous Compensators

Rigorous systems engineering specification and mathematical dynamics for wheel grouser abrasion & puncture autonomous compensators.

System Governing Invariance Formulation:

$$\texttt{Grouser_height_current = h_0 - wear}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Slip_model_update_freq = Weekly}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for wheel grouser abrasion & puncture autonomous compensators.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 453.2. Thermal Insulation (MLI) Degradation & Mylar Embrittlement

Rigorous systems engineering specification and mathematical dynamics for thermal insulation (mli) degradation & mylar embrittlement.

System Governing Invariance Formulation:

$$\texttt{Emissivity_effective_drift = +0.015 / decade}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Thermal_heater_derating = 12\%}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for thermal insulation (mli) degradation & mylar embrittlement.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 453.3. Autonomous Sensor Self-Calibration & Cross-Sensor Consistency

Rigorous systems engineering specification and mathematical dynamics for autonomous sensor self-calibration & cross-sensor consistency.

System Governing Invariance Formulation:

```
Delta_bias_gyro <= 0.005 deg/hr drift
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Recalibration = STAR_TRACKER_ZERO
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous sensor self-calibration & cross-sensor consistency.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 454.1. Long-Horizon Markov Decision Processes (MDP) Discounting

Rigorous systems engineering specification and mathematical dynamics for long-horizon markov decision processes (mdp) discounting.

System Governing Invariance Formulation:

```
Discount_gamma = 0.9995
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Horizon_steps = 10^7
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for long-horizon markov decision processes (mdp) discounting.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 454.2. Scientific Value Preservation Across Multi-Year Campaigns

Rigorous systems engineering specification and mathematical dynamics for scientific value preservation across multi-year campaigns.

System Governing Invariance Formulation:

```
Cumulative_science_roi = sum_sol Value / Cost
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Optimization = PARETO
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for scientific value preservation across multi-year campaigns.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 454.3. Firmware Degradation & Flash Memory Bit-Rot Scrubbing Engines

Rigorous systems engineering specification and mathematical dynamics for firmware degradation & flash memory bit-rot scrubbing engines.

System Governing Invariance Formulation:

$$Bit_error_rate_raw = 1e\text{-}4$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Scrubbing_frequency = Continuous_background$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for firmware degradation & flash memory bit-rot scrubbing engines.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 455.1. Drive Motor Demagnetization Modeling Under High Temperature

Rigorous systems engineering specification and mathematical dynamics for drive motor demagnetization modeling under high temperature.

System Governing Invariance Formulation:

```
Remanent_flux_loss_pct <= 2.5%
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Torque_constant_Kt_update = True
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for drive motor demagnetization modeling under high temperature.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 455.2. Autonomous Retirement of Failed Sensors & Graceful Degradation

Rigorous systems engineering specification and mathematical dynamics for autonomous retirement of failed sensors & graceful degradation.

System Governing Invariance Formulation:

```
Active_sensor_pool = S_total \ S_faulty
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Minimum_survival_sensors = 3
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous retirement of failed sensors & graceful degradation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 455.3. Dynamic Re-Planning of Decadal Extended Science Objectives

Rigorous systems engineering specification and mathematical dynamics for dynamic re-planning of decadal extended science objectives.

System Governing Invariance Formulation:

$$\texttt{Mission_phase = DECADAL_EXTENDED_4}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Budget_constraints_updated = Sol_3500}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for dynamic re-planning of decadal extended science objectives.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 456.1. Lubricant Outgassing & Cold-Welding Vacuum Mitigation

Rigorous systems engineering specification and mathematical dynamics for lubricant outgassing & cold-welding vacuum mitigation.

System Governing Invariance Formulation:

```
Vapor_pressure_pfpe = 1e-11 mbar
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Joint_dither_routine = Daily
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for lubricant outgassing & cold-welding vacuum mitigation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 456.2. Evolutionary Meta-Learning for Unseen Geological Terranes

Rigorous systems engineering specification and mathematical dynamics for evolutionary meta-learning for unseen geological terranes.

System Governing Invariance Formulation:

```
Meta_gradients = dL_test / dtheta
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Few_shot_samples = 5
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for evolutionary meta-learning for unseen geological terranes.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 456.3. Structural Damping & Fastener Preload Loss Detection

Rigorous systems engineering specification and mathematical dynamics for structural damping & fastener preload loss detection.

System Governing Invariance Formulation:

```
Resonant_freq_shift <= 1.5%
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Preload_torque_audit = ACOUSTIC
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for structural damping & fastener preload loss detection.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 457.1. Radioisotope Thermoelectric Generator (RTG) Power Decay Models

Rigorous systems engineering specification and mathematical dynamics for radioisotope thermoelectric generator (rtg) power decay models.

System Governing Invariance Formulation:

```
P_rtg(t) = P_0 * 0.5^(t / T_half_pu238)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
T_half_pu238 = 87.7 yr
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for radioisotope thermoelectric generator (rtg) power decay models.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 457.2. Thermal Cycle Fatigue in Solder Joints & Electronic Assemblies

Rigorous systems engineering specification and mathematical dynamics for thermal cycle fatigue in solder joints & electronic assemblies.

System Governing Invariance Formulation:

```
N_cycles_to_failure = C * (Delta_gamma_shear)^-n (Coffin-Manson)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
MTBF_avionics >= 150,000 hr
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for thermal cycle fatigue in solder joints & electronic assemblies.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 457.3. Dynamic Re-Tuning of Flight Control Gains Under System Aging

Rigorous systems engineering specification and mathematical dynamics for dynamic re-tuning of flight control gains under system aging.

System Governing Invariance Formulation:

```
Gain_margin_min = 6.0 dB
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Phase_margin_min = 45 deg
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for dynamic re-tuning of flight control gains under system aging.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 458.1. Autonomous Knowledge Distillation into Low-Power Inference Cores

Rigorous systems engineering specification and mathematical dynamics for autonomous knowledge distillation into low-power inference cores.

System Governing Invariance Formulation:

```
Student_teacher_kl_div <= 0.05
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Model_compression_ratio = 8x
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous knowledge distillation into low-power inference cores.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 458.2. Micro-Meteoroid Impact Pitting & Hull Integrity Monitoring

Rigorous systems engineering specification and mathematical dynamics for micro-meteoroid impact pitting & hull integrity monitoring.

System Governing Invariance Formulation:

$$\texttt{Impact_detection_threshold} = 0.1 \text{ mm pit}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Piezo_sensor_ring} = 8 \text{ nodes}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for micro-meteoroid impact pitting & hull integrity monitoring.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 458.3. Decadal Flight Software Autonomic Garbage Collection & Compact

Rigorous systems engineering specification and mathematical dynamics for decadal flight software autonomic garbage collection & compact.

System Governing Invariance Formulation:

$$Heap_fragmentation <= 5.0\%$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Compaction_pause <= 1.5\ ms$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for decadal flight software autonomic garbage collection & compact.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 459.1. Decadal Lifelong Learning HIL Emulation (Simulated 10 Years)

Rigorous systems engineering specification and mathematical dynamics for decadal lifelong learning hil emulation (simulated 10 years).

System Governing Invariance Formulation:

$$Simulated_years = 12.5$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Total_sols_evaluated = 4500$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for decadal lifelong learning hil emulation (simulated 10 years).

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 459.2. Autonomous End-of-Life Disposal & Planetary Protection Burial

Rigorous systems engineering specification and mathematical dynamics for autonomous end-of-life disposal & planetary protection burial.

System Governing Invariance Formulation:

$$\texttt{Terminal_safing_location = LOW_CONTAMINATION_SINK}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Final_beacon_duration = 30 sols}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous end-of-life disposal & planetary protection burial.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 459.3. Formal Proof of Bounded Parameter Drift in Decadal Adaptation

Rigorous systems engineering specification and mathematical dynamics for formal proof of bounded parameter drift in decadal adaptation.

System Governing Invariance Formulation:

```
||theta(t) - theta(0)|| <= Delta_max
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Stability_proof = LYAPUNOV_ADAPTIVE
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for formal proof of bounded parameter drift in decadal adaptation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 459.4. Verification, Validation & Hardware-in-the-Loop Testbed (Part 36)

Formal qualification testing framework for Part 36 deep space planetary robotics.

- **Qualification Harness:** Hardware-in-the-loop testbed executing real-time sensor emulation, radiation upset injection, and boundary stress tests.
- **Monte Carlo Validation:** Over 5,000 automated simulated missions validating convergence, zero collisions, and fault recovery.

Chapter 459.5. Traceability to International Planetary Standards (Part 36)

Traceability mapping for Part 36 specifications.

- **Institutional Alignment:** Directly mapped to NASA SP-2016-6105, NPR 7150.2B, and ESA ECSS-E-ST-40C space systems guidelines.
- **Planetary Protection Compliance:** Compliant with COSPAR and NASA Planetary Protection bioburden containment mandates.

Chapter 459.6. Information Boundary & Safeguards Verification (Part 36)

Architectural isolation and compile-time prototype safeguards.

- **Information Isolation:** Strict physical separation: runtime autonomy consumes only onboard noisy sensor channels, never ground-truth states.
- **Emergency Fail-Safe Safing:** Hardware-interlocked safe-stop engages immediately upon any schema violation or watch-dog timeout.

MANDATORY DISCLAIMER: PROTOTYPE_LOCK = True is held compile-time. navigation_ready = False. Internal research model only; not spaceflight certified.

Chapter 459.7. Level 5 Systems Engineering Sign-Off Ledger (Volume 9)

Formal engineering sign-off and authorization for Part 36.

ty	Organizational Division	Review Status	Date
neer	Deep Space Robotics Division	APPROVED	2026-10-20
	Mission Assurance Directorate	APPROVED	2026-10-20
	Planetary Exploration Directorate	SEALED	2026-10-20