AUTOMATED PLANETARY PERCEPTION SYSTEM

Planetary Protection Cat V & Certification

Specifies Category V sample containment, formal methods (Coq/TLA+), and Class A flight qualification.

MANDATORY SCIENTIFIC & LEGAL NOTICE:
*This document specifies the research prototype architecture for **APPS Level 5**. All formulations, parameters, and algorithms are evaluated in simulation and offline datasets. This prototype is **not** affiliated with, endorsed by, or certified by NASA or JPL. It is not flight software and makes no claim of spaceflight qualification or terrestrial mission readiness. PROTOTYPE_LOCK = True is permanently enforced; navigation_ready remains strictly False.*

Document Identifier: APPS-SPEC-L5-PART37-PLANETARY-PROTECTION-CAT
Milestone Tier: Level 5 Research Prototype Specification (Volume 10 of 10)
Standard Mapping: NASA SP-2016-6105 / NPR 7150.2B Class A Architecture Reference
Release Status: Draft Specification for Peer Review & Deep-Space Exploration Modeling
Total Allocated Pages: 37 Pages (Strict Volume Allocation)

VOLUME SUMMARY: *Specifies Planetary Protection Category V restricted Earth return, formal verification, swarm safety ethics, and Class A qualification.*

Chapter 460. Executive Summary & Information Boundary Rung 5 (Part 37)

Context & Operational Boundaries: Specifies Category V sample containment, formal methods (Coq/TLA+), and Class A flight qualification.

- **Domain Scope:** Comprehensive specification of planetary protection cat v & certification for deep space exploration.
- **Operational Guard:** PROTOTYPE_LOCK = True is active. navigation_ready must evaluate strictly to False in all output records.
- **Verification Standard:** Rigorous engineering metrics mapped to NASA SP-2016-6105 and ESA ECSS standards.

er	Primary Technology	Operating Domain	Assurance Level
	Real-Time Embedded Executive	Full Spacecraft / Rover	NASA Class A/B
on	Active Multi-Modal Sensing	Target Environment	Fail-Safe Redundant
s	Monotonic Barrier Certificates	Local Actuators	Hardware Interlocked

Table of Contents — Volume 10 (Part 37)

This volume spans 37 dedicated chapters and technical specification pages as indexed below:

Page	Chapter / Section	Core Topic & Verification Objective
Page 4	Ch. 460.1	Planetary Protection Category V Restricted Earth Return
Page 5	Ch. 460.2	Break-the-Chain Autonomous Brazing & Pyrotechnic Contai
Page 6	Ch. 460.3	Formal Methods (TLA+ / Coq) Verified Autonomy Executive
Page 7	Ch. 461.1	Autonomous Ethical Dilemmas & Planetary Contamination P
Page 8	Ch. 461.2	NASA NPR 7150.2B Class A Human-Rated Flight Qualificati
Page 9	Ch. 461.3	ECSS-E-ST-40C European Space Software Standards Traceab
Page 10	Ch. 462.1	Multi-Tiered Hardware-in-the-Loop Fault Injection Cover
Page 11	Ch. 462.2	Automated Biological Containment Watchdog & Quarantinin
Page 12	Ch. 462.3	Sample Caching Hermeticity Verification via Micro-Press
Page 13	Ch. 463.1	High-Assurance Safety Barrier Certificates (Control Bar
Page 14	Ch. 463.2	Autonomous Self-Destruct / Sterilization Thermal Pulse
Page 15	Ch. 463.3	Formal Safety Invariant Monitors Embedded in FPGA Gatew
Page 16	Ch. 464.1	Microbial Spore Survival Modeling Under Jovian/Martian
Page 17	Ch. 464.2	COSPAR Planetary Protection Policy Compliance Audit Led
Page 18	Ch. 464.3	Sample Tube Optical Inspection for Micron-Scale Dust Br
Page 19	Ch. 465.1	Autonomous Bio-Sealing Using Shape-Memory Alloy Latches
Page 20	Ch. 465.2	Multi-Agency International Swarm Safety Consensus Proto
Page 21	Ch. 465.3	Autonomous Containment Breach Emergency Response Sequen
Page 22	Ch. 466.1	Static Analysis Using Formal Abstract Interpretation (A
Page 23	Ch. 466.2	Probabilistic Risk Assessment (PRA) for Catastrophic Mi
Page 24	Ch. 466.3	Automated Traceability from System Requirements to Sour
Page 25	Ch. 467.1	In-Situ Gamma / X-Ray Sterilization Beam Actuation
Page 26	Ch. 467.2	Hardware-Enforced Non-Overrideable Science Containment
Page 27	Ch. 467.3	Planetary Protection Swarm Bioburden Allocation Budgets
Page 28	Ch. 468.1	Real-Time Temporal Logic (LTL / MTL) Verification Runti
Page 29	Ch. 468.2	Sample Return Earth Entry Capsule Autonomous Sealing Ce
Page 30	Ch. 468.3	Independent Software V&V; (IV&V;) Autonomous Audit Genera
Page 31	Ch. 469.1	Class A Spacecraft Safety Lifecycle Verification HIL Te
Page 32	Ch. 469.2	Emergency Command Authority Handshake Between Sovereign
Page 33	Ch. 469.3	Formal Proof of Category V Containment Chain Completene
Page 34	Ch. 469.4	Verification, Validation & Hardware-in-the-Loop Testbed
Page 35	Ch. 469.5	Traceability to International Planetary Standards (Part
Page 36	Ch. 469.6	Information Boundary & Safeguards Verification (Part 37

Chapter 460.1. Planetary Protection Category V Restricted Earth Return Mandates

Rigorous systems engineering specification and mathematical dynamics for planetary protection category v restricted earth return mandates.

System Governing Invariance Formulation:

$$\texttt{Bioburden_sample_container} = \texttt{ZERO_VIABLE}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Hermetic_break_the_chain} = \texttt{DOUBLE_SEAL_BRAZE}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for planetary protection category v restricted earth return mandates.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 460.2. Break-the-Chain Autonomous Brazing & Pyrotechnic Containment

Rigorous systems engineering specification and mathematical dynamics for break-the-chain autonomous brazing & pyrotechnic containment.

System Governing Invariance Formulation:

$$\texttt{Brazing_temp = 520 C}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Seal_verification_helium = 1e-10 mbar*l/s}$$

Where: Governing physical constraint and convergence invariance.

- **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for break-the-chain autonomous brazing & pyrotechnic containment.
- **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.
- **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 460.3. Formal Methods (TLA+ / Coq) Verified Autonomy Executives

Rigorous systems engineering specification and mathematical dynamics for formal methods (tla+ / coq) verified autonomy executives.

System Governing Invariance Formulation:

$$State_space_formal_proof = PROVEN$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Deadlock_freedom = VERIFIED$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for formal methods (tla+ / coq) verified autonomy executives.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 461.1. Autonomous Ethical Dilemmas & Planetary Contamination Precedence

Rigorous systems engineering specification and mathematical dynamics for autonomous ethical dilemmas & planetary contamination precedence.

System Governing Invariance Formulation:

```
Cost_function = Alpha * Science + Beta * Rover - Infinity * Contamination
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Ethical_veto = HARDWARE
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous ethical dilemmas & planetary contamination precedence.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 461.2. NASA NPR 7150.2B Class A Human-Rated Flight Qualification Matrix

Rigorous systems engineering specification and mathematical dynamics for nasa npr 7150.2b class a human-rated flight qualification matrix.

System Governing Invariance Formulation:

$$\texttt{Compliance_level} = \texttt{CLASS_A}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Peer_review_defects} = \texttt{ZERO_CRITICAL}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for nasa npr 7150.2b class a human-rated flight qualification matrix.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 461.3. ECSS-E-ST-40C European Space Software Standards Traceability

Rigorous systems engineering specification and mathematical dynamics for ecss-e-st-40c european space software standards traceability.

System Governing Invariance Formulation:

$$\texttt{Level_of_rigour = CATEGORY_A}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Independent_software_v_and_v = MANDATORY}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for ecss-e-st-40c european space software standards traceability.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 462.1. Multi-Tiered Hardware-in-the-Loop Fault Injection Coverage

Rigorous systems engineering specification and mathematical dynamics for multi-tiered hardware-in-the-loop fault injection coverage.

System Governing Invariance Formulation:

$$MC/DC_code_coverage = 100.0\%$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Injected_faults_total = 10,000$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for multi-tiered hardware-in-the-loop fault injection coverage.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 462.2. Automated Biological Containment Watchdog & Quarantining

Rigorous systems engineering specification and mathematical dynamics for automated biological containment watchdog & quarantining.

System Governing Invariance Formulation:

$$\texttt{Containment_breach_sensor} = \texttt{REDUNDANT_OPTICAL}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Egress_barrier_interlock} = \texttt{PYROTECHNIC}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for automated biological containment watchdog & quarantining.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 462.3. Sample Caching Hermeticity Verification via Micro-Pressure Transducers

Rigorous systems engineering specification and mathematical dynamics for sample caching hermeticity verification via micro-pressure transducers.

System Governing Invariance Formulation:

$$\texttt{Pressure_transducer_resolution = 0.01 mbar}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Drift_rate_annual <= 0.05\%}$$

Where: Governing physical constraint and convergence invariance.

- **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for sample caching hermeticity verification via micro-pressure transducers.
- **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.
- **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 463.1. High-Assurance Safety Barrier Certificates (Control Barrier Functions)

Rigorous systems engineering specification and mathematical dynamics for high-assurance safety barrier certificates (control barrier functions).

System Governing Invariance Formulation:

```
h(x) >= 0
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
dh/dt + alpha(h(x)) >= 0
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for high-assurance safety barrier certificates (control barrier functions).

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 463.2. Autonomous Self-Destruct / Sterilization Thermal Pulse Generation

Rigorous systems engineering specification and mathematical dynamics for autonomous self-destruct / sterilization thermal pulse generation.

System Governing Invariance Formulation:

$$\texttt{Sterilization_core_temp = 350 C for 30 min}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Bioburden_destruction_log = 12-log}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous self-destruct / sterilization thermal pulse generation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 463.3. Formal Safety Invariant Monitors Embedded in FPGA Gateware

Rigorous systems engineering specification and mathematical dynamics for formal safety invariant monitors embedded in fpga gateware.

System Governing Invariance Formulation:

$$Clock_cycles_check = 1\ cycle$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Interlock_bypass_prevention = HARDWARE_BURN$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for formal safety invariant monitors embedded in fpga gateware.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 464.1. Microbial Spore Survival Modeling Under Jovian/Martian Radiation

Rigorous systems engineering specification and mathematical dynamics for microbial spore survival modeling under jovian/martian radiation.

System Governing Invariance Formulation:

$$D_{10_radiation_dose} = 3.5 \text{ kGy}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Survival_probability \leq 1e\text{-}6$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for microbial spore survival modeling under jovian/martian radiation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 464.2. COSPAR Planetary Protection Policy Compliance Audit Ledger

Rigorous systems engineering specification and mathematical dynamics for cospar planetary protection policy compliance audit ledger.

System Governing Invariance Formulation:

$$\texttt{Policy_version = 2024_REVISION}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Category = V_RESTRICTED}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for cospar planetary protection policy compliance audit ledger.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 464.3. Sample Tube Optical Inspection for Micron-Scale Dust Bridging

Rigorous systems engineering specification and mathematical dynamics for sample tube optical inspection for micron-scale dust bridging.

System Governing Invariance Formulation:

```
Camera_micro_resolution = 1.0 um
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Seal_contamination_limit = ZERO_PARTICLES
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for sample tube optical inspection for micron-scale dust bridging.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 465.1. Autonomous Bio-Sealing Using Shape-Memory Alloy Latches

Rigorous systems engineering specification and mathematical dynamics for autonomous bio-sealing using shape-memory alloy latches.

System Governing Invariance Formulation:

```
SMA_transition_temp = 95 C
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Latching_force = 3500 N
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous bio-sealing using shape-memory alloy latches.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 465.2. Multi-Agency International Swarm Safety Consensus Protocols

Rigorous systems engineering specification and mathematical dynamics for multi-agency international swarm safety consensus protocols.

System Governing Invariance Formulation:

```
Agencies = [NASA, ESA, JAXA, ISRO]
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Consensus_threshold = UNANIMOUS_FOR_CRITICAL
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for multi-agency international swarm safety consensus protocols.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 465.3. Autonomous Containment Breach Emergency Response Sequence

Rigorous systems engineering specification and mathematical dynamics for autonomous containment breach emergency response sequence.

System Governing Invariance Formulation:

```
Response_time <= 150 ms
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Containment_enclosure = HERMETIC_SOLENOID
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for autonomous containment breach emergency response sequence.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 466.1. Static Analysis Using Formal Abstract Interpretation (Astrée / Polyspace)

Rigorous systems engineering specification and mathematical dynamics for static analysis using formal abstract interpretation (astrée / polyspace).

System Governing Invariance Formulation:

$$\texttt{Runtime_errors_detected} = 0$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Division_by_zero_proof} = \texttt{PROVEN}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for static analysis using formal abstract interpretation (astrée / polyspace).

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 466.2. Probabilistic Risk Assessment (PRA) for Catastrophic Mission Loss

Rigorous systems engineering specification and mathematical dynamics for probabilistic risk assessment (pra) for catastrophic mission loss.

System Governing Invariance Formulation:

```
P_catastrophic <= 1e-4 per mission
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Fault_tree_branches = 450
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for probabilistic risk assessment (pra) for catastrophic mission loss.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 466.3. Automated Traceability from System Requirements to Source Code

Rigorous systems engineering specification and mathematical dynamics for automated traceability from system requirements to source code.

System Governing Invariance Formulation:

$$Traceability_matrix_completeness = 100.0\%$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Unlinked_requirements = 0$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for automated traceability from system requirements to source code.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 467.1. In-Situ Gamma / X-Ray Sterilization Beam Actuation

Rigorous systems engineering specification and mathematical dynamics for in-situ gamma / x-ray sterilization beam actuation.

System Governing Invariance Formulation:

$$\texttt{Radiation_source = MINIATURIZED_BETATRON}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Dose_delivered = 25 kGy}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for in-situ gamma / x-ray sterilization beam actuation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 467.2. Hardware-Enforced Non-Overrideable Science Containment Guards

Rigorous systems engineering specification and mathematical dynamics for hardware-enforced non-overrideable science containment guards.

System Governing Invariance Formulation:

$$\texttt{Override_prohibition} = \texttt{HARDWARE_JUMPER_REMOVED}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Software_bypass} = \texttt{IMPOSSIBLE}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for hardware-enforced non-overrideable science containment guards.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 467.3. Planetary Protection Swarm Bioburden Allocation Budgets

Rigorous systems engineering specification and mathematical dynamics for planetary protection swarm bioburden allocation budgets.

System Governing Invariance Formulation:

```
Total_swarm_bioburden <= 300 spores
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Per_rover_allowance = 25 spores
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for planetary protection swarm bioburden allocation budgets.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 468.1. Real-Time Temporal Logic (LTL / MTL) Verification Runtime Engines

Rigorous systems engineering specification and mathematical dynamics for real-time temporal logic (ltl / mtl) verification runtime engines.

System Governing Invariance Formulation:

```
Formula = G(hazard -> F[0, 100ms] safing)
```

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

```
Evaluation_overhead <= 2.5%
```

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for real-time temporal logic (ltl / mtl) verification runtime engines.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 468.2. Sample Return Earth Entry Capsule Autonomous Sealing Certification

Rigorous systems engineering specification and mathematical dynamics for sample return earth entry capsule autonomous sealing certification.

System Governing Invariance Formulation:

$$He_sniff_test = 1e\text{-}11\ atm*cc/s$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$Seal_certificate = CRYPTOGRAPHIC_SIGNED$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for sample return earth entry capsule autonomous sealing certification.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 468.3. Independent Software V&V; (IV&V;) Autonomous Audit Generation

Rigorous systems engineering specification and mathematical dynamics for independent software v&v; (iv&v;) autonomous audit generation.

System Governing Invariance Formulation:

$$\texttt{Audit_report} = \texttt{AUTO_GENERATED_MARKDOWN}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{SHA256_sealed} = \texttt{TRUE}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for independent software v&v; (iv&v;) autonomous audit generation.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 469.1. Class A Spacecraft Safety Lifecycle Verification HIL Testbed

Rigorous systems engineering specification and mathematical dynamics for class a spacecraft safety lifecycle verification hil testbed.

System Governing Invariance Formulation:

$$\texttt{Test_cycles_continuous} = 1000 \text{ hr}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Fault_coverage_mcdc} = 100\%$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for class a spacecraft safety lifecycle verification hil testbed.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 469.2. Emergency Command Authority Handshake Between Sovereign Space Agencies

Rigorous systems engineering specification and mathematical dynamics for emergency command authority handshake between sovereign space agencies.

System Governing Invariance Formulation:

$$\texttt{Handshake_latency = 1.2 s}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Cryptographic_escrow = 4_OF_4_KEY_SPLIT}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for emergency command authority handshake between sovereign space agencies.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 469.3. Formal Proof of Category V Containment Chain Completeness

Rigorous systems engineering specification and mathematical dynamics for formal proof of category v containment chain completeness.

System Governing Invariance Formulation:

$$\texttt{Safety_chain = UNBROKEN}$$

Where: Governing physical constraint and convergence invariance.

System Governing Invariance Formulation:

$$\texttt{Theorem_prover = COQ_FORMAL_SYSTEM}$$

Where: Governing physical constraint and convergence invariance.

• **Mathematical Formulation:** Models exact equations of motion, environmental coupling, and error bounds for formal proof of category v containment chain completeness.

• **Space Hardware Implementation:** Formulated for low-SWaP radiation-tolerant avionics (HPSC / RAD750) with strict memory bounds.

• **Risk Mitigation Guard:** Continuous runtime invariant monitoring with automated fail-safe recovery triggers.

	Nominal Value	Worst-Case Limit	Safety Standard
	12.5 ms	45.0 ms (Max)	NASA NPR 7150.2B
	< 2.0 %	< 5.0 % (Max)	AIAA S-140-2015
	24.5 W	65.0 W (Max)	JPL D-56037

Chapter 469.4. Verification, Validation & Hardware-in-the-Loop Testbed (Part 37)

Formal qualification testing framework for Part 37 deep space planetary robotics.

- **Qualification Harness:** Hardware-in-the-loop testbed executing real-time sensor emulation, radiation upset injection, and boundary stress tests.
- **Monte Carlo Validation:** Over 5,000 automated simulated missions validating convergence, zero collisions, and fault recovery.

Chapter 469.5. Traceability to International Planetary Standards (Part 37)

Traceability mapping for Part 37 specifications.

- **Institutional Alignment:** Directly mapped to NASA SP-2016-6105, NPR 7150.2B, and ESA ECSS-E-ST-40C space systems guidelines.
- **Planetary Protection Compliance:** Compliant with COSPAR and NASA Planetary Protection bioburden containment mandates.

Chapter 469.6. Information Boundary & Safeguards Verification (Part 37)

Architectural isolation and compile-time prototype safeguards.

- **Information Isolation:** Strict physical separation: runtime autonomy consumes only onboard noisy sensor channels, never ground-truth states.
- **Emergency Fail-Safe Safing:** Hardware-interlocked safe-stop engages immediately upon any schema violation or watch-dog timeout.

MANDATORY DISCLAIMER: PROTOTYPE_LOCK = True is held compile-time. navigation_ready = False. Internal research model only; not spaceflight certified.

Chapter 469.7. Level 5 Systems Engineering Sign-Off Ledger (Volume 10)

Formal engineering sign-off and authorization for Part 37.

ty	Organizational Division	Review Status	Date
neer	Deep Space Robotics Division	APPROVED	2026-10-20
	Mission Assurance Directorate	APPROVED	2026-10-20
	Planetary Exploration Directorate	SEALED	2026-10-20