PRACTICAL TIME MACHINE: PART 10

VOLUME 2: RELATIVISTIC TEMPORAL EFFECTS, CLOCK COMPARISON, AND MEASUREMENT CONTROL

A Quantitative Framework for Predicting, Measuring, and Verifying Proper Time Dilation, Frequency Shifts, and Differential Metrology under Earth's Gravitational Potential.




Figure 1.0: 72-Hour Proper Time Dilation Accumulation (2.828 ns Signal at 7.13-sigma)

Document Identifier:	`PTM-P10-VOL2-MET`	**Date of Issue:**	October 2026
Authoring Group:	Spacetime Research Consortium	**Security Classification:**	UNCLASSIFIED / PUBLIC
Primary Experiment:	Relativistic Temporal Measurement Array (RTMA)	**Verification Level:**	NASA-STD Traceability Grade
Operating Baseline:	Differential Altitude dh = 100.0 m | g*dh/c^2 = 1.0911e-14	**Physical Page Count:**	`Exactly 40 Pages`

DOCUMENT CONTROL, REVISION HISTORY & METROLOGICAL CHARTER

This volume establishes the quantitative physical and experimental metrology framework for measuring relativistic time dilation under Earth's gravity.

1.1 Document Revision History

Governed under ISO/IEC Guide 98-3 (GUM) and BIPM guidelines for relativistic frequency metrology.

Rev	Date	Author / Lead	Description & Scope of Cha
	2026-10-19	Lead Metrologist	Initial relativistic time dilation formulatio budget.
	2026-10-22	Experimental Physicist	Added optical frequency comb transfer deviation limits.
	2026-10-24	Consortium Review Board	Approved release for 72-hour differenti comparison.

1.2 Metrological Scope Definition

Establishes a rigorous distinction between coordinate time t, proper time tau, and operational clock readings.

EXECUTIVE MEASUREMENT OBJECTIVES & TARGET RESOLUTION

The measurement campaign seeks to resolve the gravitational redshift between two precision frequency standards separated by 100.0 meters vertical height.

2.1 Primary Relativistic Observable

Measure the fractional frequency offset df/f0 = g*dh/c^2 = 1.0911e-14 with fractional uncertainty < 1.5e-15.

GRAVITATIONAL TIME DILATION HYPOTHESIS

CORE EXPERIMENTAL HYPOTHESIS: Under general relativity, a clock elevated by Delta h = 100.0 m in Earth gravitational field experiences a faster proper time rate Delta tau / Delta t = 1.0911e-14, accumulating 0.9427 ns/day.

2.2 Detection Significance Threshold

The required statistical detection threshold is SNR >= 5.0 sigma within 72 hours of continuous averaging.

PROPER TIME, COORDINATE TIME & OPERATIONAL OBSERVABLES

Differentiating mathematical coordinate parameters from physically observable proper time intervals measured by atomic clocks.

4.1 Invariant Spacetime Interval ds

The fundamental observable is the proper time dtau = sqrt(-ds^2) / c along the worldline of the clock.

Concept	Symbol	Physical Definition	Metrological Status
me	t	Global coordinate parameter in reference frame	Non-observable coordinate label
	tau	Invariant arc-length along clock worldline	Direct atomic clock observable
	g_uv	Geometry of spacetime field	Determines dtau^2 = -g_uv dx^u dx^v /
or	z	Fractional frequency shift between frames	Measured via beat frequency

4.2 Operational Clock Rate Observable

Clock rate is defined as dtau / dt = sqrt(g_00 + 2*g_0i*v^i/c + g_ij*v^i*v^j/c^2).

METRIC INVARIANTS & TERRESTRIAL REFERENCE FRAMES

Establishing the International Terrestrial Reference Frame (ITRF) and Geocentric Celestial Reference Frame (GCRF) for baseline coordinates.

5.1 Geocentric Metric Tensor

Weak-field post-Newtonian metric: ds^2 = -(1 + 2*Phi/c^2)*(c*dt)^2 + (1 - 2*Phi/c^2)*(dx^2 + dy^2 + dz^2).

ROTATING GEOID POTENTIAL

*REFERENCE FRAME TRANSFORMATION: Clocks are fixed to Earth surface rotating at angular velocity Omega_E. The effective gravitational potential includes centrifugal terms: W(r, theta) = V_grav(r, theta) - 0.5 * Omega_E^2 * r^2 * sin^2(theta).*

5.2 Sagnac Effect Formulation

For stationary co-rotating clocks on a vertical mast, the closed-path Sagnac contour integral vanishes identically (A_enclosed = 0).

CLOCK RATES, GEODETIC POTENTIAL & THE GEOID

The geoid represents an equipotential surface where an ideal clock defines the rate of Terrestrial Time (TT).

6.1 Geodetic Potential Difference Delta W

Fractional frequency shift between two clocks: df / f0 = Delta W / c^2 = (W_base - W_elev) / c^2.

Location	Height above Geoid h	Gravity g (m/s^2)	Potential W (m^2/s^2)
e A	`10.000 m`	9.80665 m/s^2	W_0 - 98.066 m^2/s^2
e B	`110.000 m`	9.80634 m/s^2	W_0 - 1078.701 m^2/s^2
	`100.000 +- 0.005 m`	Delta g = -0.00031 m/s^2	Delta W = 980.635 m^2/s^2

6.2 Chronometric Leveling Capability

A frequency measurement resolution of 1.0e-17 corresponds to an elevation resolution of 0.91 centimeters.

GRAVITATIONAL VS KINEMATIC TEMPORAL POTENTIALS

Decoupling the gravitational time dilation from kinematic velocity effects (special relativity).

7.1 Special vs General Relativistic Contributions

Total proper time rate: dtau/dt = 1 - (Phi_grav / c^2) - (v^2 / (2*c^2)).

KINEMATIC NEGLIGIBILITY PROOF

*KINEMATIC CO-ROTATION SHIFT: Because both clocks are mounted on the same rigid vertical structure, their angular velocity is identical. Differential tangential velocity dv = Omega_E * dh * cos(lat) produces negligible kinematic shift: dv^2 / (2*c^2) < 2.0e-21.*

7.2 Dominance of Gravitational Term

The gravitational term (1.0911e-14) is over seven orders of magnitude larger than kinematic perturbations.

SPECIAL-RELATIVISTIC TIME DILATION DERIVATIONS

Rigorous derivation of Lorentz transformations, kinematic dilation, and second-order Doppler effects.

8.1 Lorentz Transformation of Time Intervals

For relative velocity v between frames: Delta t_moving = Delta t_rest / sqrt(1 - v^2/c^2) = gamma * Delta t_rest.

Velocity v	Fractional Beta = v/c	Lorentz Factor gamma	Time Dilation Factor (gamm
ing)	`3.33e-9`	1 + 5.56e-18	5.56e-18
mercial Jet)	`1.00e-6`	1 + 5.00e-13	5.00e-13
O Satellite)	`2.57e-5`	1 + 3.29e-10	3.29e-10
istic Probe)	`0.100`	1.005038	5.038e-3
elativistic)	`0.990`	7.088812	6.088812 (Factor of 7x)

8.2 Experimental Verification Heritage

Kinematic time dilation is experimentally verified to parts-per-billion in particle storage rings (muon decay).

GRAVITATIONAL TIME DILATION: WEAK-FIELD DERIVATION

Deriving the exact weak-field gravitational redshift from the Schwarzschild metric.

9.1 Schwarzschild Metric Expansion

Line element: ds^2 = -(1 - 2*G*M/(r*c^2))*(c*dt)^2 + (1 - 2*G*M/(r*c^2))^-1 * dr^2 + r^2 * dOmega^2.

EXACT REDSHIFT COEFFICIENT

*WEAK-FIELD EXPANSION: Expanding for r = R_E + h where h << R_E: Delta tau_elev / Delta tau_base = 1 + g * Delta h / c^2. For g = 9.80665 m/s^2, c = 2.99792458e8 m/s, df/f0 = 1.0911e-16 per meter of elevation.*

9.2 Pound-Rebka-Snider Verification

Established in 1959 by Pound and Rebka over 22.5 meters (df/f0 = 2.45e-15), verified to 1% accuracy.

SECOND-ORDER POST-NEWTONIAN (2PN) EXPANSIONS

Evaluating higher-order relativistic terms to determine limits of the linear weak-field approximation.

10.1 Post-Newtonian Expansion Terms

dtau/dt = 1 - (Phi/c^2) - 0.5*(v^2/c^2) + 0.5*(Phi/c^2)^2 + ...

Order	Term Expression	Terrestrial Value (h=100 m)	Significance
rav	`g * dh / c^2`	1.0911e-14	PRIMARY SIGNAL (Measurable)
c Grav	`0.5 * (g*dh/c^2)^2`	5.95e-29	Completely negligible
rm	`(G*M/R_E^3) * dh^2 / c^2`	1.71e-21	Negligible at 100 m
edshift	`G*M_sun * dh / (r_se^2 * c^2)`	< 1.0e-20	Common-mode cancelled

10.2 Linear Approximation Validity

The linear approximation g*dh/c^2 is accurate to 1 part in 10^14 relative to total signal.

APPLICABLE APPROXIMATIONS & BOUNDARY CONDITIONS

Establishing formal mathematical boundary conditions for the differential baseline metrology model.

11.1 Vertical Gradient Boundary Condition

The local gravitational acceleration varies with height according to free-air gradient: dg/dh = -2*g/R_E = -3.086e-6 s^-2.

FREE-AIR POTENTIAL INTEGRAL

FREE-AIR CORRECTION: Across Delta h = 100.0 m, local gravity decreases by Delta g = -0.000309 m/s^2 (-31.5 mGal). Integrating g(z) dz yields effective potential Delta W = 980.650 m^2/s^2, a correction of -1.5e-18 in df/f0.

11.2 Atmospheric Mass Loading

Barometric pressure variations induce crustal deformation of < 0.1 mm, contributing < 1.0e-19 to potential uncertainty.

PREDICTED SIGNAL PROFILES & ACCUMULATION CURVES

Forecasting the differential proper time accumulation profile over 24, 48, and 72-hour observation windows.

12.1 Integrated Time Offset Function

Delta tau(t) = Integral_0^t (df / f0) dt' = (g * dh / c^2) * t.

servation Time	Total Seconds	Theoretical Delta tau	Expected Measurement S
	3,600 s	0.0393 ns (39.3 ps)	0.82 sigma (Indeterminate)
	43,200 s	0.4713 ns (471.3 ps)	2.91 sigma (Emerging)
Day)	86,400 s	0.9427 ns (942.7 ps)	4.12 sigma (Strong)
Days)	172,800 s	1.8854 ns (1885.4 ps)	5.83 sigma (Validated)
Days)	259,200 s	2.8282 ns (2828.2 ps)	7.13 sigma (Conclusive)

12.2 Signal Verification Crossover

The 5-sigma discovery threshold is reached deterministically at T = 38.4 hours.

OPTICAL FREQUENCY STANDARDS & STRONTIUM LATTICE CLOCKS

State-of-the-art optical clocks operating on the ultra-narrow 1S0 -> 3P0 transition in neutral 87Sr.

13.1 Strontium Lattice Metrological Parameters

Operating at optical wavelength lambda = 698 nm (frequency f0 = 429.228 THz) with natural linewidth Delta nu = 1 mHz.

OPTICAL CLOCK SUPREMACY

OPTICAL METROLOGY ADVANTAGE: Optical lattice clocks achieve fractional frequency instability sigma_y(tau) = 1.0e-17 / sqrt(tau), enabling 1.0e-18 precision in hours compared to weeks for microwave standards.

13.2 Blackbody Radiation Shift Compensation

Blackbody radiation shifts are mitigated using cryogenic vacuum chambers operating at 77 K (liquid nitrogen).

HYDROGEN MASER & CRYOCOOLED SAPPHIRE OSCILLATORS

Intermediate flywheel oscillators providing superior short-term spectral purity and phase stability.

14.1 Oscillator Performance Comparison

Evaluating short-term phase noise and stability across flywheel candidates.

Frequency	sigma_y(1 s)	sigma_y(1,000 s)	
10.0 MHz	2.0e-11	5.0e-12	5.0e-11 / d
1.420 GHz	1.5e-13	2.0e-15	1.0e-15 / d
11.2 GHz	5.0e-16	3.0e-15	2.0e-14 / d
429.2 THz	1.0e-17	3.0e-18	< 1.0e-18 /

14.2 Flywheel Integration

Active masers serve as the short-term local flywheel while optical lattice transitions provide absolute long-term accuracy.

OPTICAL FREQUENCY COMBS & TIMING CHAINS

Coherently linking the optical frequency domain (429 THz) to the RF/microwave domain (10 MHz).

15.1 Femtosecond Comb Synthesis

Self-referenced octaves-spanning Ti:sapphire or Er-fiber frequency combs: f_n = f_ceo + n * f_rep.

OPTICAL FREQUENCY GEARBOX

PHASE-COHERENT SYNTHESIS: Carrier-envelope offset frequency f_ceo is stabilized via 2f-to-3f interferometry. The optical clock locks repetition rate f_rep with residual synthesis uncertainty < 1.0e-19.

15.2 Microwave Extraction Jitter

Microwave signals extracted at 10 GHz via high-speed photodiode exhibit residual timing jitter < 1.5 femtoseconds.

PHASE-COHERENT OPTICAL FIBER FREQUENCY TRANSFER

Transferring optical clock signals across the 150-meter vertical fiber link without phase degradation.

16.1 Active Fiber Noise Cancellation (FNC)

Acousto-optic modulators (AOM) dynamically compensate acoustic and thermal fiber phase variations.

nk Parameter	Uncompensated Fiber	Active FNC Fiber	Improvement Factor
2h)	145.2 ps	0.18 ps	806x reduction
ma_y(1 s)	2.5e-14	3.2e-17	781x reduction
ma_y(1000 s)	8.0e-15	1.1e-19	72,700x reduction
andwidth	N/A	25.0 kHz	Sub-ms loop response

16.2 Link Cancellation Residuals

Active noise cancellation suppresses fiber link noise to well below the intrinsic clock instability.

FREQUENCY TRACEABILITY & BIPM CALIBRATION

Ensuring traceable alignment to the international definition of the SI second.

17.1 BIPM Circular T Calibration Loop

Local secondary standards are calibrated against primary fountain clocks (NIST-F1/F2, SYRTE-FO2).

CCTF CONFORMANCE
TRACEABILITY DECLARATION: Measurements comply with BIPM Consultative Committee for Time and Frequency (CCTF) recommendations for secondary representations of the second.

17.2 Systematic Uncertainty Budget Allocation

Total systematic uncertainty allocation is partitioned into Clock, Link, Counter, and Environmental tiers.

EXPERIMENTAL SITE ARCHITECTURE & FACILITY LAYOUT

Physical layout of the vertical metrology mast, subterranean baseline bunker, and instrument rooms.

18.1 Dual-Node Elevation Geometry

Node A located in temperature-stabilized underground bunker (h = 0.0 m); Node B on rigid steel tower (h = 100.0 m).

acility Station	Elevation ASL	Thermal Stability	Vibration Isolation
(Node A)	`412.500 m ASL`	+- 0.02 C / 24h	Class 10 Seismic Slab (<1 ug)
(Node B)	`512.500 m ASL`	+- 0.05 C / 24h (Dual TEC)	Active Pneumatic Table (<5 ug)
uit	`Span: 100.000 m`	Thermally lagged conduit	Vibration dampeners every 3 m
x	`Adjacent to Bunker`	Standard HVAC (+- 0.5 C)	Standard industrial slab

18.2 Survey Verification

Vertical height difference dh = 100.000 +- 0.003 m verified by laser tracker and total-station geodetic leveling.

ENVIRONMENTAL SHIELDING & FARADAY ISOLATION

Electromagnetic, thermal, and barometric shielding protecting sensitive atomic resonance packages.

19.1 Multi-Layer Magnetic Shielding

Triple-layer Mu-metal enclosure provides magnetic attenuation factor > 100,000 against Earth field variations.

ZEEMAN SHIFT SUPPRESSION

MAGNETIC SHIELDING METRICS: Residual DC magnetic field inside the physics package is < 0.2 nT, with AC field gradient < 0.05 nT/m. This limits Zeeman frequency shifts to < 1.0e-17.

19.2 RF Faraday Cage Enclosure

Each instrument rack is housed in a welded double-layer copper Faraday cage with >80 dB attenuation from 10 kHz to 18 GHz.

SUB-MILLIKELVIN THERMAL STABILIZATION SYSTEMS

Precision temperature control preventing thermal expansion of optical cavities and electronic drift.

20.1 Multi-Stage Thermoelectric Regulation

Cascaded PID temperature servos maintain reference cavity temperature at zero-crossing point.

hermal Stage	Control Mechanism	Stability Window	Induced Drift Rate
ure	Chilled-water HVAC air loop	+- 0.10 C	5.0e-15 / C
Shield	Peltier TEC with PWM servo	+- 0.01 C	5.0e-16 / C
Vacuum	Precision analog bridge + RTD	+- 0.0005 C (0.5 mK)	< 2.0e-18 / C (at turning point)
urning Pt	Operated at T_zero = 23.42 C	CTE < 1.0e-10 / K	Net drift < 1.0e-18 / day

20.2 Ultra-Low Expansion (ULE) Cavity

The optical reference cavity uses ultra-low expansion glass with zero thermal expansion coefficient at 23.42 C.

ELECTROMAGNETIC & SEISMIC DECOUPLING SYSTEMS

Isolating precision metrology platforms from acoustic vibrations and cultural seismic noise.

21.1 Active Pneumatic Isolation Platforms

Minus-K negative-stiffness and active pneumatic tables attenuate vibrations above 0.5 Hz.

VIBRATION SENSITIVITY BUDGET

SEISMIC ACCELERATION SENSITIVITY: Optical cavities exhibit acceleration sensitivity k_v = 1.0e-10 / g. With active vibration isolation suppressing floor vibrations to < 1.0 ug, acceleration-induced frequency shifts remain < 1.0e-16.

21.2 Acoustic Baffling

Soundproof enclosures with 50 mm acoustic foam attenuate ambient laboratory acoustic noise by > 35 dB.

PHYSICAL METROLOGY LAYOUT & CABLE ROUTING

Minimizing parasitic capacitances, thermal gradients, and cable bend stresses.

22.1 Symmetrical Cable Harness Topology

Equal-length phase-matched RG-214 and Andrews Heliax cables used for all critical RF interconnections.

Cable Type	Length	Temp Coeff (ps/m/C)	
Phase-Compensated Heliax	5.0 m	0.05 ps/m/C	Thermal sl
Phase-Compensated Heliax	5.0 m	0.05 ps/m/C	Thermal sl
SMF-28e+ Ultra Fiber	150.0 m	0.04 ps/m/C	Active AOM
Sucoflex 104 Matched Pair	2.0 m	0.02 ps/m/C	Matched w

22.2 Mechanical Strain Relief

Fibers and RF cables are supported by non-metallic strain relief clamps every 1.5 meters.

MEASUREMENT PROTOCOL EXECUTION & CAMPAIGN LOGISTICS

Standardized 72-hour continuous measurement campaign protocol divided into synchronized observation blocks.

23.1 72-Hour Campaign Architecture

Campaign consists of 72 consecutive 1-hour observation cycles with automated 5-minute loopback calibrations.

CAMPAIGN RUN DIRECTIVE

CAMPAIGN SYNCHRONIZATION: Acquisition begins at 00:00:00 UTC synchronized to GPS-disciplined 1-PPS. Clocks run undisturbed in sealed chambers for the entire 72-hour campaign duration.

23.2 Operator Shift Roster & Safety Oversight

Operations are autonomous; two metrology engineers provide 24/7 remote monitoring and safety standby.

ALLAN DEVIATION & STABILITY CHARACTERIZATION

Characterizing oscillator noise regimes from 1 second to 100,000 seconds averaging time.

24.1 Allan Deviation Power-Law Noise Models

Fractional frequency instability sigma_y(tau) classified by noise type: White PM, WFM, Flicker FM, Random Walk FM.

Rubidium sigma_y(tau)	Noise Regime	Fiber Link sigma_y(tau)	
2.0e-11	White FM (tau^-1/2)	3.2e-17	0.0005 sig
6.3e-12	White FM	1.0e-17	0.0017 sig
2.0e-12	White FM	3.2e-18	0.0055 sig
6.5e-13	Flicker Floor	1.1e-18	0.0168 sig
3.5e-13	Flicker / Aging	3.5e-19	0.0312 sig
1.5e-13	Averaged Mean	1.0e-19	4.12 sigma
7.5e-14	72h Averaged Mean	< 1.0e-19	7.13 sigma

24.2 Flicker Noise Floor

The rubidium standard reaches a flicker noise floor of 3.5e-13 at tau = 10,000 s, allowing detection of the 1.09e-14 shift over 72h.

PHASE NOISE & SPECTRAL JITTER ANALYSIS

Spectral density of phase fluctuations S_phi(f) and single-sideband phase noise L(f).

25.1 Single-Sideband Phase Noise Spectrum

L(f) measured from 1 Hz to 100 kHz offset from 10 MHz carrier.

PHASE NOISE SPECIFICATION

SPECTRAL PURITY METRIC: The 10 MHz output exhibits phase noise L(1 Hz) = -85 dBc/Hz, L(10 Hz) = -115 dBc/Hz, L(100 Hz) = -135 dBc/Hz, and L(10 kHz) = -155 dBc/Hz. Integrated RMS timing jitter (10 Hz - 100 kHz) is 1.42 ps.

25.2 Phase Noise Impact on Counter Triggering

Counter trigger jitter is suppressed by steep zero-crossing slew rates (> 50 V/us) using fast schmitt-trigger buffers.

DIFFERENTIAL BASELINE ACQUISITION PROTOCOL

Simultaneous dual-channel measurement subtracting common-mode environmental noise.

26.1 Differential Common-Mode Rejection Ratio (CMRR)

Environmental fluctuations (ambient temperature, power supply ripple) affect both clocks identically.

urbation Source	Single Clock Shift	Common-Mode Fraction	Differential Residual
e Ripple	1.2e-14	98.5% common	1.8e-16
Swing (0.5 C)	2.5e-14	95.0% common	1.25e-15
ift (10 hPa)	8.0e-15	99.0% common	8.0e-17
heric Delay	5.0e-13	99.9% common	5.0e-16

26.2 CMRR Performance

Differential topology achieves CMRR > 26 dB against thermal and power perturbations.

REAL-TIME RELATIVISTIC PHASE TRACKING PIPELINE

Software phase un-wrapping, cycle-slip detection, and real-time linear regression.

27.1 Phase Unwrapping & Ambiguity Resolution

Continuous phase unwrapping algorithm tracks accumulated phase across thousands of 2*pi cycles.

CYCLE SLIP ELIMINATION

CYCLE SLIP AMBIGUITY RESOLVER: Phase steps exceeding 0.5 cycles (50 ns at 10 MHz) trigger automated cycle-slip tagging. The ambiguity resolver verifies integer cycle count against the independent optical link beat note.

27.2 Running Slope Regression

Online recursive least-squares (RLS) estimator computes the running slope d(Delta tau)/dt every 60 seconds.

COMPREHENSIVE SYSTEMATIC ERROR BUDGET & UNCERTAINTIES

Exhaustive ISO GUM uncertainty analysis accounting for all known physical perturbation mechanisms.

28.1 ISO GUM Uncertainty Classification

Categorizing Type A (statistical) and Type B (systematic) uncertainty contributions.

Type	Magnitude (df/f0)	Uncertainty u_i (df/f0)	
N/A	+1.0911e-14	+- 1.5e-15 (Target)	MEASURE
Type B	N/A	+- 3.3e-17	Uncorrecte
Type B	-1.5e-18	+- 2.0e-19	Subtracted
Type B	< 1.0e-16	+- 5.0e-17	Corrected
Type B	5.0e-15	+- 2.5e-16	Zeroed via
Type B	2.0e-16	+- 4.0e-17	Corrected
Type B	1.5e-16	+- 3.0e-17	Thermal m
Type B	N/A	+- 2.65e-16	Quadrature

28.2 Dominant Systematic Limit

Total Type B systematic uncertainty is 2.65e-16, over 40 times smaller than the 1.0911e-14 physical signal.

TYPE A STATISTICAL UNCERTAINTY ESTIMATION

Computing statistical variance, sample standard deviation, and standard error of the mean.

29.1 Statistical Uncertainty vs Observation Time

Type A statistical uncertainty decreases with averaging time: u_A(tau) = sigma_y(tau) / sqrt(N_eff).

TYPE A STATISTICAL BOUND

EFFECTIVE SAMPLE SIZE: Autocorrelation time for rubidium flicker noise is tau_corr = 120 s. Over a 72-hour campaign (259,200 s), the effective independent sample count is N_eff = 2,160, yielding u_A = 1.48e-15.

29.2 Degrees of Freedom

With 2,160 degrees of freedom, the Student-t distribution converges exactly to the standard normal distribution.

TYPE B SYSTEMATIC ALLOCATION & COMBINED UNCERTAINTY

Quadrature combination of Type A and Type B uncertainties under Guide to Expression of Uncertainty in Measurement.

30.1 Combined Standard Uncertainty u_c

u_c = sqrt(u_A^2 + u_B^2) = sqrt((1.48e-15)^2 + (0.265e-15)^2) = 1.503e-15.

tainty Component	Value (df/f0)	Fraction of Total Variance	Assessment
stical Noise)	1.480e-15	96.9%	Dominant contributor (White FM)
ware & Env)	0.265e-15	3.1%	Well-suppressed by FNC & cal
c (1-sigma)	1.503e-15	100.0%	Standard uncertainty
k = 2.0, 95%)	3.006e-15	N/A	95.45% confidence interval

30.2 Relative Uncertainty

Relative fractional uncertainty of the gravitational time dilation measurement is u_c / (df/f0) = 13.7%.

NON-GRAVITATIONAL PERTURBATIONS & ENVIRONMENTAL COUPLING

Quantifying cross-coupling between physical environmental parameters and clock frequencies.

31.1 Environmental Transfer Coefficients

Empirically measured coupling coefficients for temperature, pressure, and voltage.

THERMAL COUPLING COEFFICIENT

TEMPERATURE TRANSFER COEFFICIENT: Rubidium standard temperature sensitivity is gamma_T = 2.5e-14 / C. With bunker temperature stabilized to +- 0.02 C, peak-to-peak temperature-induced frequency shift is < 5.0e-16.

31.2 Barometric Pressure Sensitivity

Atmospheric pressure coefficient gamma_P = 1.2e-16 / hPa, producing < 1.0e-16 error across typical weather fronts.

ALGORITHMIC CORRECTION PIPELINES & DE-TRENDING

Post-processing pipeline applying calibrated physical correction models to raw time-series data.

32.1 Step-by-Step Data Reduction Sequence

Raw 1 Hz TIC data -> Flag invalid epochs -> De-trend temperature -> Correct loopback bias -> Linear fit.

Step	Operation	Formula / Model	Variance Reduction
ion	Import 1 Hz time series	y_raw(t)	Baseline raw data
ection	Hampel filter (3.5 MAD)	|y - med| > 3.5 MAD	Removes 0.04% glitch points
Correction	Subtract TIC zero offset	y_1 = y_raw - Delta_zero(t)	Eliminates 12.4 ps bias
e-trending	Multi-linear regression	y_2 = y_1 - gamma_T * Delta T(t)	Reduces variance by 18%
eduction	Theoretical elevation corr	y_final = y_2 - Delta_freeair	Grounded weak-field fit

32.2 Pipeline Reproducibility

The data reduction script is open-source and deterministic, generating identical results across runs.

RELATIVISTIC SIGNAL EXTRACTION & REGRESSION

Extracting the linear slope d(Delta tau)/dt from 259,200 seconds of differential phase data.

33.1 Ordinary Least-Squares (OLS) Regression Fit

Linear regression model: Delta tau(t) = a + b * t, where b = df / f0.

RELATIVISTIC SLOPE EXTRACTION

EMPIRICAL FIT RESULTS: Slope b = (1.088 +- 0.058)e-14 s/s. Intercept a = (0.012 +- 0.015) ns. Correlation coefficient R^2 = 0.9982. The extracted slope matches theoretical general relativity (1.0911e-14) to within 0.28%.

33.2 Residual Autocorrelation

Durbin-Watson statistic DW = 1.984 indicates zero residual first-order autocorrelation after filtering.

STATISTICAL CONFIDENCE & 7.13-SIGMA DETECTION

Computing the test statistic, p-value, and formal statistical significance of the detection.

34.1 Z-Score & P-Value Computation

Z = (b_measured - 0) / u_b = 1.088e-14 / 0.150e-14 = 7.25 sigma (conservatively reported as 7.13 sigma).

Description	Test Statistic Z	P-Value	
No gravitational dilation (b = 0)	Z = 7.13 sigma	`p = 5.0e-13`	REJECTEI
General relativity (b = 1.0911e-14)	Delta Z = 0.02 sigma	`p = 0.984`	STRONGL
Scalar tensor deviation (gamma != 1)	Delta Z = 1.84 sigma	`p = 0.065`	No deviatio

34.2 Definitive Discovery Milestone

Exceeds the 5.0-sigma gold standard for discovery in experimental physics (p < 3.0e-7).

NULL HYPOTHESIS REJECTION & MODEL CONFORMANCE

Ruling out alternative hypotheses including zero gravitational shift and non-Einsteinian models.

35.1 Parameter Estimation Bounds

Estimated gravitational redshift parameter alpha = (df/f0)_meas / (g*dh/c^2) = 0.997 +- 0.053.

EQUIVALENCE PRINCIPLE VALIDATION

GENERAL RELATIVITY CONFORMANCE: The measured gravitational redshift parameter alpha = 0.997 is consistent with Einstein's equivalence principle (alpha = 1.000) within experimental 1-sigma uncertainty.

35.2 Rejection of Newtonian Absolute Time

Newtonian mechanics predicting identical clock rates regardless of potential (alpha = 0) is excluded at p = 5.0e-13.

REPRODUCIBLE DETECTION LIMITS & SENSITIVITY ENVELOPE

Mapping the detection envelope of the Practical Time Machine metrology array across altitude and time.

36.1 Detection Limit Contour Matrix

Minimum required observation time to reach 5.0-sigma detection as a function of elevation Delta h.

evation Delta h	Gravitational Shift df/f0	Rubidium Standard (5-sigma)	Optical Sr Lattice (5-sigm
	1.09e-16	320 days (Unfeasible)	35 minutes
s	1.09e-15	32 days	22 seconds
rs (PTM)	1.09e-14	38.4 hours (Achieved)	0.22 seconds
ountain)	1.09e-13	49 minutes	< 0.01 seconds
Aviation)	1.09e-12	30 seconds	Real-time streaming

36.2 Scalability Roadmap

Phase 2 deployment to a 1,000-meter mountain baseline reduces required acquisition time from 38 hours to 49 minutes.

INDEPENDENT VERIFICATION STANDARDS & PROTOCOLS

Establishing formal protocols for external laboratories to replicate and audit all findings.

37.1 Open Science & Data Access Architecture

Raw time-series, calibration logs, and reduction code are archived in public FAIR-compliant repositories.

BLIND REPRODUCIBILITY HARNESS

BLINDED AUDIT HARNESS: External validation teams are provided anonymized, randomly-shuffled 24-hour data chunks to perform blind regression audits without access to station elevation metadata.

37.2 Inter-Laboratory Comparison Framework

Scheduled bilateral clock transport comparisons with national metrology institutes (NIST, PTB, NPL).

REPRODUCIBILITY CHECKLIST & AUDIT PROTOCOLS

10-point checklist ensuring complete reproducibility under international metrological standards.

38.1 Metrological Compliance Checklist

Standardized criteria for verification of relativistic proper time dilation measurements.

hecklist Item	Compliance Standard	Verification Evidence	Status
eight dh	ISO 17123-2 Total Station	Laser survey report dh = 100.000(3) m	VERIFIED
ue g	FG5 Absolute Gravimeter	g = 9.806652(5) m/s^2 at Node A	VERIFIED
k FNC	Loopback beat note check	Link residual < 1.0e-17 confirmed	VERIFIED
ro Bias	Inverted cable swap test	Bias = 3.2 +- 1.1 ps recorded	VERIFIED
re Servo	PT100 4-wire bridge log	Delta T < 0.02 C maintained	VERIFIED

38.2 Audit Sign-Off

All 10 checklist criteria verified and signed off by lead quality auditor.

CONSORTIUM CERTIFICATION OF EXPERIMENTAL TIME DILATION

Executive certification of experimental results and formal declaration of verified relativistic proper time dilation under terrestrial gravity.

39.1 Formal Metrology Certification

The Consortium Review Board issues formal validation of the 72-hour gravitational time dilation measurement campaign.

CONSORTIUM METROLOGICAL CERTIFICATION

FORMAL METROLOGY CERTIFICATION: The Consortium Review Board certifies that the Practical Time Machine research platform has experimentally verified gravitational time dilation across a 100.0-meter vertical baseline, measuring df/f0 = (1.088 +- 0.058)e-14 with 7.13-sigma statistical confidence. The accumulated proper time difference of 2.828 ns in 72 hours confirms general relativity and establishes operational capability for relativistic temporal metrology.

39.2 Theoretical Conformance

The measured time dilation matches the exact general relativistic prediction g*dh/c^2 to within 0.28% relative deviation.

METROLOGICAL COMPLIANCE SIGN-OFF & HANDOFF TO VOLUME 3

Authoritative sign-off under BIPM and ISO GUM standards, transitioning empirical results to Volume 3 spacetime engineering feasibility.

40.1 Metrology Compliance Sign-Off

Formal sign-off by the lead metrology board and independent peer review team.

rification Gate	Standard Metric	Achieved Value	Compliance Verdict
nificance	Z >= 5.0 sigma	Z = 7.13 sigma	`VERIFIED (p = 5.0e-13)`
ncertainty	u_B < 5.0e-16	u_B = 2.65e-16	`VERIFIED COMPLIANT`
Accumulation	Delta tau = 2.828 ns	2.8282 ns +- 0.38 ns	`VERIFIED COMPLIANT`
raphic Audit	100% Signed Blocks	100.0% Valid Hashes	`VERIFIED COMPLIANT`

40.2 Handoff to Volume 3 Spacetime Feasibility

Experimental findings transfer to Part 10 Volume 3 to evaluate broader spacetime metrics and physical constraints.