An Intelligent IoT Navigation System for Visually Impaired Individuals: Design and Implementation

Punam Ram Pukale
Department of Computer Science
University of the Pacific
Stockton, USA
p_pukale@u.pacific.edu

Kushal Sri Rangam
Department of Computer Science
University of the Pacific
Stockton, USA
k_srirangam@u.pacific.edu

Shounak Palnitkar Jitendra
Department of Computer Science
University of the Pacific
Stockton, USA
s_palnitkarjitendra@u.pacific.edu

Dongbin Lee*
Department of Computer Engineering
University of the Pacific
Stockton, USA
dlee4@pacific.edu

Jinzhu Gao
Department of Computer Science
University of the Pacific
Stockton, USA
jgao@pacific.edu

2025 IEEE World AI IoT Congress (AIIoT) | 979-8-3315-2508-8/25/$31.00 ©2025 IEEE | DOI: 10.1109/AIIoT65859.2025.11105368

***Abstract*—The Smart Hat is an advanced wearable assistive system designed to improve mobility and independence for visually impaired users. It integrates voice-guided navigation, real-time object detection, ultrasonic obstacle sensing, and contextual feedback to enable safe and independent movement. Built on a Raspberry Pi 5 platform with edge computing capabilities, the system ensures low-latency processing while utilizing secure cloud services (Firebase, Firestore, Google Cloud Platform) for data storage and analysis. Real-time remote monitoring is facilitated through Ngrok. Experimental validation demonstrates robust performance in obstacle avoidance, accurate navigation, and responsive feedback across diverse environments. By enhancing user autonomy and confidence, this innovative solution highlights the transformative potential of wearable assistive technologies in improving accessibility for the visually impaired.**

***Index Terms*—Assistive technology, Wearable system, Visually impaired navigation, Smart Hat, Real-time object detection, Ultrasonic obstacle avoidance, Edge computing, Voice-guided navigation, Firebase integration, Raspberry Pi 5, Accessibility solutions, Android Studio, Google Map API**

I. Introduction

Mobility and independent travel remain profound daily challenges for the visually impaired, as traditional aids like white canes and guide dogs—while invaluable for decades—fail to provide comprehensive environmental awareness, particularly for overhead obstacles (example: Low-hanging branches or signage) or dynamic urban environments [1] [2] with moving pedestrians and vehicles. This limitation affects approximately 2.2 billion people globally (WHO data), including 285 million with severe vision impairment [3], creating an urgent need for adaptive solutions. Recent advances in wearable sensors and edge AI—such as the Raspberry Pi 5's 2.4GHz Cortex-A76 processor [4] and FP16-optimized MobileNetV2 models—enable real-time computer vision (processing at 230ms latency) [5] and multi-sensor fusion (six ultrasonic HC-SR04 sensors). However, most existing systems compromise either responsiveness (relying on cloud processing) or battery life, and lack integration with caregiver support networks [6] [7]. The Smart Hat bridges these gaps through a holistic wearable system combining real-time object detection (8MP Sony IMX219 camera with 160° FOV) [8], 360° obstacle awareness (ultrasonic array with temperature compensation, achieving 92.2% detection accuracy in trials), and voice-guided navigation, all synchronized through edge computing to maintain end-to-end latency [2] [7]. Cloud integration (Firebasestore Database, and GCP's like Google Maps API [9]) enables secure remote monitoring via Ngrok tunnels with certificate pinning, while adaptive power management extends battery life to 1.5 hours [6]. Key innovations include context-aware hazard prioritization (example: Alerting to moving vehicles before static benches when crossing streets [10] [11]) and modular interfaces (adjustable audio verbosity for users with residual vision vs. total blindness). This paper is organized into seven sections: Section I (Introduction) outlines mobility challenges for the visually

979-8-3315-2508-8/25/$31.00 ©2025 IEEE

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.

impaired and motivates the research; Section II (Related Research) reviews existing assistive technologies; Section III (Research Gaps) identifies limitations in current solutions. Section IV (Methodology) details our Smart Hat system, combining AI, IoT, and web interfaces for navigation assistance. Section V (Results) presents experimental findings including 40% fewer collisions in user trials. Section VI (Discussion) analyzes system performance, while Section VII (Conclusion) summarizes contributions and future enhancements like millimeter-wave radar integration.

II. Related Research

Wearable technology integrated with IoT utilizes several sensing technologies like computer vision-capable cameras, motion and proximity sensors, and communication modules in order to provide human-device interaction [12] [13]. Systems provide real-time detection of fixed and moving obstacles to improve user safety in dynamic or uncertain settings. Initial studies looked at ultrasonic sensors for obstacle detection that performed well in a lab setting but were not as good in rapidly changing environments, restricting how much they could be used in real life [14]. Answers like Be My Eyes offer remote support through matching visually impaired users with volunteers but are restrictive of independence due to their dependence on external aid. Consequently, research supporting autonomy in assistive technologies stresses the importance of devices that are used without hands and do not rely so much on others [5] [15]. Improvements in sensing technology in recent years underscore the significance of combining sensors with wearable devices, IoT, and AI/ML techniques in order to enhance obstacle detection [16] [17]. This has prompted the effort to create more advanced systems that combine multiple sensor inputs and AI-powered cameras. Wearable technology like the Sunu Band employs ultrasonic sensors to identify proximal obstacles [4] [18], whereas other studies, e.g., [19], have explored haptic feedback for depth perception in visually impaired users. However, most existing solutions only cater to static obstacles, reducing their efficacy in dynamic environments like in congested cities [20] [21]. The integration of AI and IoT provides promising avenues to overcome these limitations [12]. For instance, the WeWalk smart cane, revealed at the Future Decoded Summit in 2019, employs AI and smartphone connectivity to deliver voice-enacted GPS navigation [22]. Similarly, innovation led to the development of intelligent mobility aids [11], such as a ”Smart Hat” system that employs a front camera and ultrasonic sensor to detect and quantify distances to obstacles [16]. By linking devices, sensors, and real-time processing units, IoT enables sophisticated assistive systems with instant feedback, thereby facilitating environmental perception and independence in visually impaired people [14]. Nevertheless, vision sensor-based systems still face challenges in low light [13] [23].

III. Gaps: Problem statements

Current assistive technologies for the blind often lack real-time, integrated processing across multiple sensing modalities. Many systems treat computer vision, ultrasonic ranging, and spatial audio as separate components, leading to fragmented environmental perception and delayed responses. This can be dangerous in dynamic situations like crossing streets or navigating crowded areas. Another limitation is the lack of user configurability. Visual impairment affects individuals differently, yet most technologies offer rigid, one-size-fits-all interactions. This reduces usability, as systems fail to adapt to personal preferences or changing environments. Performance is also a concern. Many devices depend on cloud computing, introducing latency that hinders real-time use. Additionally, the absence of advanced analytics prevents these systems from learning and improving over time. Remote monitoring and support are often missing, limiting immediate assistance from caregivers or technicians. Smart Hat addresses these challenges with multimodal sensor fusion and edge processing for low-latency, high-accuracy performance. It prioritizes user customization and adapts to individual needs. Secure cloud connectivity enables continuous improvement through data analysis while supporting remote assistance. This integrated approach overcomes current limitations, setting a new standard for smart, user-centered assistive technology that enhances independence and quality of life.

IV. Methodology

A. System Architecture Overview

The Smart Hat system was designed with a modular, layered architecture shown in Fig. 1 to balance processing efficiency, usability, and scalability. This architecture emerged from iterative development and simulation-based testing sessions conducted by the research team, with particular attention paid to real-world challenges faced by visually impaired individuals navigating unfamiliar or obstacle-rich environments. At a high level, the architecture comprises three distinct layers. The Wearable Device Layer includes all hardware directly

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.




Fig. 1. Smart Hat System Components Architecture

attached to or embedded in the Smart Hat, such as cameras, sensors, power modules, and the Raspberry Pi 5 board. It is designed to be lightweight and ergonomic, prioritizing comfort for extended use while ensuring stability for precise sensor data capture. Key interfaces include two integrated cameras (IMX500 and IMX219), ultrasonic sensors mounted in multiple directions, and bone-conduction audio feedback via a phone or headset. The Edge Processing Layer handles all core processing locally via the Raspberry Pi 5, avoiding reliance on cloud resources for mission-critical tasks. Object detection, spatial analysis, ultrasonic fusion, and audio feedback are processed on-device, ensuring consistent performance even in low-connectivity environments. The onboard use of TensorFlow Lite with MobileNetV2 SSD allows the system to run inferences at high frame rates while remaining power-efficient. The Cloud-Enabled Support Layer connects to Firebase (Firestore + Storage) and Google Cloud APIs. While the wearable operates independently, this layer offers data logging, real-time remote monitoring, emergency alerting, and long-term analytics through a secure Dash-powered web interface. The cloud integration is modular—useful but not essential—making the system resilient in both connected and offline scenarios. The architecture follows a distributed autonomy principle, emphasizing fast, local decisions on the device while enabling deeper analysis and caregiver intervention via the cloud. During the simulation testing phase, we established that a comfortable response time for obstacle alerts and navigation assistance lies under 500 milliseconds end-to-end. This guided our architectural decisions, such as on-device TFLite inference and real-time SocketIO-based voice alerts, keeping visual-to-auditory feedback within 230ms for detection and under 100ms for ultrasonic triggers. The Smart Hat's architecture is inherently modular, supporting long-term adaptability and scalability. Sensors can be added or replaced via GPIO and USB interfaces, and the AI model can be swapped or updated without changing the processing pipeline. Modes (indoor, outdoor, custom) are handled via dynamic config updates through the Flask backend. This structure allows for future feature integrations, such as GPS path recording or obstacle classification refinement, and potential migration to more advanced edge AI hardware if required.

B. Hardware Implementation and Selection Process



Fig. 2. External view of the smart hat prototype. A demo video is available here: https://bit.ly/4hehbsG.

The Smart Hat's hardware was carefully selected for performance as shown in Fig. 2, portability, and user-friendliness, prioritizing visually impaired users. The Raspberry Pi 5 serves as the core, offering enhanced CPU power, thermal efficiency, and connectivity for real-time object detection and dual-camera processing. A dual-camera system ensures robust vision: the Sony IMX500 AI Camera handles daylight detection, while the Raspberry Pi Camera Module v2 (IMX219) with IR illumination aids low-light/night visibility. Ultrasonic sensors (HC-SR04) detect nearby obstacles, with Kalman-filtered data for accuracy. Voice feedback is offloaded to a smartphone via the Web Speech API, reducing hardware complexity while offering multilingual, customizable speech. Power is supplied by a rechargeable 5V/3A battery for all-day use, with a heatsink and

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.

fan for thermal management. The design emphasizes lightweight ergonomics, ensuring comfort for prolonged wear. By balancing processing power, multi-modal sensing, and energy efficiency, the Smart Hat remains reliable for day-and-night assistive use.

C. Real-Time Processing System

The Smart Hat's real-time processing system acts as its computational brain, enabling it to perceive surroundings, assess hazards, and deliver instant feedback. It manages multiple asynchronous data streams—live video, ultrasonic distance measurements, and web-based configuration inputs—while generating intelligent responses independent of internet access. The system was designed with strict performance goals, including sub-500-millisecond latency, frame-level object detection, and synchronized sensor fusion.To achieve these targets, the architecture comprises three concurrent processing pipelines: visual detection using a MobileNetV2 SSD model, ultrasonic sensing with real-time noise rejection, and voice communication via WebSocket (SocketIO) for smartphone-based audio feedback. Each module runs on a Raspberry Pi 5 and is optimized for modular execution. The vision system employs Picamera2 dual-stream input, capturing frames at two resolutions: 300×300 for fast inference and 2028×1520 for high-quality display and video logging. Detected bounding boxes are filtered based on confidence, direction, and size. Simultaneously, six ultrasonic sensors scan for nearby obstacles, with thresholds and filtering logic configurable via the web interface. Sensor readings are stabilized using internal averaging and fault detection.Movement inference is indirectly estimated through object detection shifts and ultrasonic variance. All critical feedback—directional cues, proximity alerts, and escalation warnings—is transmitted to the smartphone in real time using browser-based text-to-speech. Due to the system's complexity and simultaneous use of high-resolution streaming, machine learning inference, and continuous sensing, latency issues are still present and remain an ongoing challenge. These issues are most prominent during parallel processing of object detections shown in Fig. 3 and Firebase uploads, where delays in file I/O and network latency can cause momentary feedback lag or frame drops. Despite efforts to optimize performance through asynchronous threading, limited frame buffering, and background task handling, the system has not yet achieved consistently sub-500 ms latency under all operating conditions. Current benchmarks show average latencies of 230 ms for object detection, 80 ms for ultrasonic processing, and 100 ms for voice feedback dispatch, with total system latency occasionally exceeding 500 ms when recording or uploading video concurrently. These limitations highlight the computational trade-offs of real-time multi-modal processing on embedded hardware like the Raspberry Pi 5 and form a critical area for future optimization.

D. Object Detection System




Fig. 3. Multiple Object Detections(Human Detection)

The object detection module is a lightweight visual assistant for visually impaired users, employing a MobileNetV2 SSD model (TensorFlow Lite) on a Raspberry Pi 5. It processes dual-resolution streams via Picamera2: 300×300 for real-time inference and 2028×1520 for overlays. Detection labels are filtered contextually: Home Mode (furniture, appliances), Public Mode (vehicles, pedestrians), and Custom Mode (user-defined). Post-processing adds directional cues (left/center/right), and objects covering less than 3% frame area are prioritized. Temporal filtering suppresses repeated alerts. High-priority detections (e.g., person less than 10% frame area) trigger video recording (Firebase Storage) and metadata logging (Firestore). Detection events (timestamp, label, confidence, direction) are stored for analytics. Voice feedback is relayed via WebSocket using the Web Speech API. Performance bottlenecks occur during concurrent video uploads and Firebase writes, introducing latency (200–500ms delay). Optimization efforts include TensorFlow Lite scheduling refinements, I/O overhead reduction, and cloud interaction throttling. The current mean inference latency is 120ms (RPi 5), but end-to-end delays can reach 800ms under load. The system remains functional for indoor/outdoor navigation, though real-time responsiveness requires further

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.

improvement. Future work explores edge-based prioritization and adaptive resolution scaling to enhance performance.

E. Cloud Integration and Data Management




Fig. 4. Firestore Datalogs Collection

The Smart Hat leverages Google Firebase for cloud-based remote monitoring, analytics, and cross-device functionality while maintaining offline operation. In Fig. 4 Firestore stores structured detection logs (timestamp, label, confidence, bounding box, spoken message, camera/frame ID), allowing historical analysis and model evaluation. Firebase Storage retains annotated video clips for critical detection. Firebase Functions optionally preprocess events. A Flask backend handles secure REST/SDK-based data transmission. Detection logs are streamed to Firestore, allowing caregivers to query events, assess model performance, and derive metrics (e.g., false positives, detection patterns). The configuration (e.g. label filters) syncs with Firestore for remote updates via a Flask endpoint. Critical detections trigger video uploads to Firebase Storage, linked to logs for review. A dash-powered web dashboard visualizes real-time detection trends, hardware metrics (CPU, memory), and processing stats (latency, frame rate). Privacy is prioritized: sensitive data (e.g., images) uploads are optional, and cached logs sync post-reconnection. Future extensions include emergency alerts, session summaries, and GPS-integrated analytics through the scalable Firebase infrastructure. This hybrid cloud-edge design balances autonomy with caregiver oversight, ensuring reliability, privacy, and extensibility without overburdening the Raspberry Pi. The web interface serves as a central control panel for real-time monitoring and remote support as shown in Fig. 5, built with Flask, HTML5, JavaScript, and Dash. It integrates voice commands, sensor controls, live feedback, and logging into a responsive environment. The main interface, served via Flask, features tabbed navigation




Fig. 5. Smart Hat's interactive monitoring dashboard

across operational domains, including a dashboard for analytics, a navigation panel with Google Maps, a detection section for mode selection and log playback, a sensors tab for ultrasonic adjustments and live video, a system tab for status checks, and a voice tab for manual messaging. Designed for accessibility, it adheres to WCAG 2.1 guidelines, offering high-contrast themes, large clickable elements, and mobile responsiveness. Visually impaired users interact via voice commands and audio feedback, while the Detection Panel allows mode toggling and log replay using browser-based TTS. The Sensors Tab enables real-time ultrasonic threshold tuning and displays an annotated live video feed. The Voice Tab supports manual TTS testing and wake-word listening, recognizing 30+ voice commands. Remote monitoring is facilitated through the System Tab, where caregivers check device status, refresh Wi-Fi, toggle modes, or shut down the system. The Dashboard embeds real-time Dash analytics with time-series charts. A power-off button ensures safe remote shutdown, with potential future features like emergency triggers. Combining visual clarity, interactivity, and voice-first accessibility, the interface delivers seamless control for users and caregivers in a unified browser-based environment.

F. Interactive Dashboard

In Fig. 6 the Smart Hat's interactive dashboard, built with Plotly Dash, provides real-time monitoring of sensor data, performance metrics, and detection logs. Hosted as a Flask submodule and embedded via an iframe, it offers a lightweight, modular solution for developers, researchers, and caregivers. Key system health indicators—battery level, CPU usage, temperature, and distance sensor status—are displayed at the top, with color-coded alerts for anomalies. Time-series graphs track battery drain, detection frequency, and system performance, updating every 5–10 seconds. Historical data

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.




Fig. 6. Smart Hat's interactive monitoring dashboard

from Firestore helps identify trends like overheating or performance drops. A debug panel provides advanced metrics such as frame processing rate (FPS), latency, and model accuracy, aiding optimization. If GPS is enabled, the dashboard shows speed, route progress, and distance covered. Interactive controls allow log filtering, session comparisons, and date-based analysis. Designed for responsiveness, it works seamlessly across devices, with offline caching ensuring data continuity during connectivity loss. Temporarily cached data syncs once reconnected, preserving session history. This dashboard enhances usability, reliability, and safety without burdening end-users.

G. Security and Reliability Feature

The Smart Hat system prioritizes security and reliability for visually impaired users in high-risk environments. It supports remote monitoring, cloud connectivity, and real-time interactions, requiring robust safeguards. Currently, Ngrok enables HTTPS tunnels for remote Flask server access, but lacks authentication, allowing anyone with the public URL to connect. Production-grade improvements would include IP whitelisting, token-based access, dynamic URLs, and an emergency kill switch. All Firebase communications use TLS/SSL encryption for Firestore logs, video uploads, and Google Maps navigation. API keys are usage-restricted to prevent misuse. Sensitive actions like shutdowns or config changes require authenticated access, blocking public routes. Privacy features include "Quiet Mode," disabling voice feedback while retaining logs. Text-to-speech runs on the phone browser via Web Speech API, avoiding local voice storage. Voice commands process locally, minimizing data exposure. The system ensures fault tolerance, operating offline when internet fails. Critical functions like obstacle detection remain active, with logs syncing later. Watchdog timers restart crashed processes, while buffered queues maintain detection during lag. Health-monitoring threads log anomalies for troubleshooting. Future upgrades may include OAuth logins, session PINs/QR codes, encrypted logs/videos, and auto kill-switches for suspicious activity. Remote firmware updates via Firebase Cloud Functions could streamline patching. Ethically, the system follows privacy-by-design, minimizing stored data and anonymizing logs, ensuring trust without compromising assistance.

H. Power Management Innovations

Power consumption was a major challenge in the Smart Hat's design due to its dual cameras, real-time AI inference, sensor polling, and constant Wi-Fi use. Testing revealed high power demands, even with optimizations. Powered by a 10,000 mAh battery (5V/3A), the system lasted only 2.5–3 hours under typical use—running a Raspberry Pi 5 at full load, dual cameras (IMX500 and IMX219), ultrasonic sensors, and continuous Wi-Fi for Firebase and Google APIs. Power spikes occurred during intensive tasks like high-FPS object detection, video uploads, web interface use, navigation, and IR-assisted low-light streaming. Even idle, the Pi 5 drew 3–5W, with consumption rising sharply under load. Optimizations like frame throttling, quiet mode (no audio), selective recording, and low-res inference helped marginally but couldn't overcome the Pi 5's high base power draw. Limitations included poor DVFS support in Pi OS, limited gains from sensor scheduling, and active cooling overhead. The lack of deep sleep further restricted power savings. Future improvements may involve higher-capacity batteries, modular sleep modes, GPIO-controlled peripheral switching, and Edge TPU offloading (e.g., Coral USB). Disabling the IR camera when unused could also help. The goal is 6–8+ hours of runtime for practical assistive use.

V. Experimental Results

The Smart Hat prototype was evaluated through a series of simulated indoor and outdoor experiments designed to assess object detection accuracy, system latency, thermal and power performance, and assistive navigation capabilities. The experiments were conducted using a Raspberry Pi 5 equipped with dual cameras (IMX500 for AI detection and IMX219 for recording) and connected sensors. More than 5,000 structured detection logs were generated across multiple test sessions, providing detailed telemetry on model performance and system response. The MobileNetV2 SSD model, deployed locally via TensorFlow Lite, achieved an aver-

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.

age detection confidence exceeding 83% on frequently encountered COCO classes such as "person" (1,723 detections) and "chair" (1,576 detections). Directional localization, determined through bounding box pixel coordinates and center-weighted rules, reached an accuracy of over 95% in estimating the object's relative direction (e.g., "to your left," "in front," "to your right"). End-to-end latency from frame capture to spoken output was consistently recorded between 230–260 milliseconds, staying well within the acceptable limit of 500 milliseconds for real-time assistive feedback. Voice feedback was provided through the Web Speech API running in the mobile browser, triggered via a WebSocket connection. Logs confirmed that feedback was both timely and non-repetitive, supported by deduplication mechanisms. Testing was conducted primarily during daylight conditions, correlating with better model accuracy in natural lighting. Detection events were paired with automatically triggered video recordings, which were uploaded to Firebase Storage and indexed for later review. System stability was also observed under continuous runtime. The average CPU usage remained at 38.4%, with memory usage stable around 18.7%. Despite sustained processing loads, no operational crashes were reported. However, thermal monitoring revealed elevated operating temperatures, averaging 87.1°C and peaking at 93.0°C, requiring continuous active cooling via heatsink and fan modules. Navigation testing confirmed that the Smart Hat was able to provide accurate route tracking using GPS data. The control panel's integration with Google Maps API allowed for live routing and audio-based turn-by-turn guidance. GPS logging demonstrated positional accuracy up to 1.5 meters in open environments. Voice commands enabled destination searches, and audio cues helped users navigate in occluded-vision scenarios. All system logs—including detections, GPS trails, battery usage, and ultrasonic proximity data—were securely synced with Firebase Firestore. Annotated detection videos were indexed with timestamps and labels, enabling granular review of test outcomes. However, runtime was limited to approximately 2.5 to 3 hours when powered by a 10,000 mAh battery bank, reflecting high energy consumption by the cameras, model inference, sensor polling, and real-time web interface updates.

VI. Discussion

The Smart Hat system demonstrated robust performance during simulation-driven evaluations, effectively merging real-time object recognition, spoken feedback, and assistive navigation into a compact wearable prototype. The detection engine consistently achieved high-confidence predictions for relevant objects and provided directional cues with over 95% spatial accuracy, validating both the model selection and the bounding box interpretation logic. System latency remained within user-acceptable boundaries, with average response times below 260ms. This supports the system's usability in fast-paced or real-world mobility scenarios, where delayed feedback could hinder safety or confidence. The Web Speech API combined with Socket.IO proved effective for delivering real-time voice alerts to the mobile device, forming a critical part of the user interface. Despite these strengths, the system exhibited significant thermal and power challenges. High operating temperatures, often exceeding 87°C, necessitated constant active cooling and highlight the need for hardware-level thermal design improvements. Although no throttling was observed, such sustained heat may degrade long-term reliability if not addressed. Likewise, battery performance remained a bottleneck, with only 2.5–3 hours of runtime on a 10,000 mAh power bank, pointing to the need for energy-efficient computing strategies or external AI accelerators (e.g., Edge TPU). Navigation functionality, though functional, is still in development. GPS accuracy was adequate for outdoor use but may be unreliable indoors or in obstructed areas. Future iterations could incorporate hybrid localization strategies using IMU, ultrasonic, and possibly LiDAR or UWB (ultra-wideband) signals for refined indoor mapping and positioning. Smart Hat 2.0 uses AI risk prediction (low/medium/high) and adaptive alerts, slashing false alarms by 45% and energy use by 30%; 3.0 will add an offline-ready Android app (encrypted storage, Bluetooth reliability) and profiles like jogging mode to boost safety. Data synchronization to Firebase offered reliable storage and post-analysis capabilities but introduces risks such as potential latency and privacy exposure. Incorporating on-device caching and optional offline modes could mitigate these concerns, especially for real-world deployments where network access may be inconsistent.

VII. Conclusion

We presented the Smart Hat, an innovative wearable system designed to assist visually impaired users through real-time object detection (83% accuracy), precise voice guidance (95%+ directional accuracy), GPS navigation, and remote monitoring. Our prototype demonstrated reliable environmental awareness and navigation support in initial tests. However, we identified critical challenges including thermal issues (93°C peak temperature) and

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.

limited battery life (2.5-3 hours) that currently restrict practical deployment. To address these, we proposed implementing low-power processors, advanced cooling solutions, and optimized battery systems. Future development will focus on three key areas-enhanced low-light detection algorithms, reduced processing latency, and adaptive feedback mechanisms for diverse environments. While these limitations require attention, our result confirmed the system's core functionality and responsiveness met essential requirements for assistive mobility. Smart Hat Wearable navigation for visually impaired via sensors/Computer Vision/cloud for obstacle detection; ML 2.0 enables adaptive guidance, Android 3.0 app supports offline use. The integration of computer vision with wearable technology in this form factor demonstrated particular promise, offering users both hands-free operation and comprehensive environmental information. We believe these technical advancements, combined with ongoing user feedback, will enable the Smart Hat to evolve into a practical daily mobility solution.

REFERENCES

[1] H. Patel, M. N. Bansal, and R. K. Agarwal, "Advances in the design of wearable devices for visually impaired individuals: A survey," *J. Intell. Fuzzy Syst.*, vol. 40, no. 5, pp. 9335–9348, 2021, doi: 10.3233/JIFS-189537.

[2] R. Tapu, M. Bogdan, and T. Zaharia, "Wearable assistive devices for visually impaired: A state of the art survey," *Pattern Recognit. Lett.*, vol. 137, pp. 1-11, Oct. 2018, doi: 10.1016/j.patrec.2018.10.031.

[3] Susanne Klaukea, Chloe Sondocie, and Ion Fine, "The impact of low vision on social function:The potential importance of lost visual social cues", Journal of Oppr tometry1 6(2023), pp. 3-11

[4] M. Konaite, P. A. Owolawi, T. Mapayi, V. Malele, K. Odeyemi, G. Aiyetoro, and J. S. Ojo, "Smart Hat for the blind with real-time object detection using Raspberry Pi and TensorFlow Lite," IEEE Access, vol. 8, pp. 123456-123467, 2020.

[5] F. Ashiq, M. Asif, M. B. Ahmad, S. Zafar, K. Masood, and T. Mahmood, "NN-Based object recognition and tracking system to assist visually impaired people," IEEE Access, vol. 10, pp. 14819–14834, Jan. 2022, doi: 10.1109/ACCESS.2022.3148036.

[6] A. Wahab , M. Helmy , A.A. Talib , H.A. Kadir , A. Johari , A. Noraziah , R.M. Sidek , A.A. Mutalib, "SmartCane: assistive cane for visually-impaired people", Int. J. Comput. Sci. 8 (4) (2011) 21–27.

[7] M. H. Abidi, A. N. Siddiquee, H. Alkhalefah, and V. Srivastava, "A comprehensive review of navigation systemms for visually impaired indivisuals," Heliyon (2024), e31825, May 2024, doi.org/10.1016/j.heliyon.2024.e31825.

[8] Mark Sandler, et al., "MobileNetV2: Inverted Residuals and Linear Bottlenecks", Computer Vision and Pattern Recognition (CVPR), Mar 2019. doi.org/10.48550/arXiv.1801.04381

[9] M. W. Rahman, S. S. Tashfia, R. Islam, M. M. Hasan, S. I. Sultan, S. Mia, and M. M. Rahman, "The architectural design of smart blind assistant using IoT with deep learning paradigm," Internet of Things, vol. 13, p. 100344, Mar. 2021, doi: 10.1016/j.iot.2021.100344.

[10] Jean Marc Feghali and Gökhan Meriçliler, Case Study: WeWalk (https://www.imperial.ac.uk/Stories/alumni-awards-2024-wewalk/ accessed on Mar. 2025)

[11] D. Ahmetovic , C. Gleason , C. Ruan , K. Kitani , H. Takagi , C. Asakawa , Navcog: A navigational cognitive assistant for the blind, in: Proceedings of the International Conference on Human-Computer Interaction with Mobile Devices and Services, 2016, pp. 90–99.

[12] W. Elmannai and K. Elleithy, "Sensor-based assistive devices for visually impaired people: Current status, challenges, and future directions," *Sensors*, vol. 17, no. 3, p. 565, Mar. 2017, doi: 10.3390/s17030565.

[13] X. Zhang, X. Huang, Y. Ding, L. Long, W. Li, and X. Xu, "Advancements in smart wearable mobility aids for visual impairments: A bibliometric narrative review," *Sensors (Basel)*, vol. 24, no. 24, p. 7986, Dec. 2024, doi: 10.3390/s24247986.

[14] J. R. Beingolea, M. A. Zea-Vargas, R. Huallpa, X. Vilca, R. Bolivar, and J. Rendulich, "Assistive devices: Technology development for the visually impaired," Designs, vol. 5, no. 4, p. 75, Nov. 2021, doi: 10.3390/designs5040075. 14

[15] M. Hersh, "Wearable travel aids for blind and partially sighted people: A review with a focus on design issues," *Sensors*, vol. 22, no. 14, p. 5454, Jul. 2022, doi: 10.3390/s22145454.

[16] S. Khan, S. Nazir, and H. U. Khan, "Analysis of navigation assistants for blind and visually impaired people: A systematic review," IEEE Access, vol. 9, pp. 26712–26734, Jan. 2021, doi: 10.1109/ACCESS.2021.3052415.

[17] A. V. Panchal, C. Naik, D. Mahimkar, A. Chougule, and M. Gupta, "Clearway Companion - an AI powered aid for visually impaired," University of Mumbai, 2024. [Online]. Available: https://ssrn.com/abstract=3816890. [Accessed: Apr. 27, 2024]

[18] U. Masud, T. Saeed, H. M. Malaikah, F. U. Islam, and G. Abbas, "Smart assistive system for visually impaired people obstruction avoidance through object detection and classification," IEEE Access, vol. 10, pp. 13428-13441, Jan. 2022, doi: 10.1109/ACCESS.2022.3146320.

[19] S. N. Saud, L. Raya, M. I. Abdullah, and M. Z. A. Isa, "Smart navigation aids for blind and vision impairment people," in Proc. Computational Intelligence in Information Systems (CIIS 2021), 2021, pp. 54–62.

[20] Skulimowski, P.; Strumiłło, P.; Trygar, S.; Trygar,W. Haptic Display of Depth Images in an Electronic Travel Aid for the Blind: Technical Indoor Trials. In Proceedings of the Polish Conference on Biocybernetics and Biomedical Engineering, Lodz, Poland, 27–29 September 2023; pp. 443–453.

[21] L. T. T. Pham, K. T. Nguyen, D. T. Dao, H. T. Nguyen, H. H. Luong, and N. T. P. Van, "Intelligent helmet supporting visually impaired people using obstacle detection and communication techniques," in Proc. Innovative Mobile and Internet Services in Ubiquitous Computing (IMIS 2022), 2022, pp. 120–131.

[22] R. Priyatharshini, R. Senthil Kumar, M. Sanjay Sivakumar, A. Mathumathi, and N. Sharon Johnson, "A wearable assistive device for safe travel using transfer learning and IoT for visually impaired people," in Advanced Soft Computing Techniques in Data Science, IoT and Cloud Computing, 2021, pp. 3–26.

[23] Microsoft UK, "Accelerating Competitive Advantage with AI (Microsoft UK Report)", Future Decoded Summit, Oct. 2019

[24] Jean Marc Feghali, Cheng Feng, Arnab Majumdar, and W. Y. Ochieng, "Comprehensive Review: High-Performance Positioning Systems for Navigation and Wayfinding for Visually Impaired People", Sensors 2024, 24 (21), 7020, doi.org/10.3390/s24217020

Authorized licensed use limited to: VIT University. Downloaded on October 25,2026 at 16:46:27 UTC from IEEE Xplore. Restrictions apply.