

232859

## OS practical

### Program :

```
#include <pthread.h>
#include <semaphore.h>
#include <stdio.h>

#define N 5
#define THINKING 2
#define HUNGRY 1
#define EATING 0
#define LEFT (phnum + 4) % N
#define RIGHT (phnum + 1) % N

int state[N];
int phil[N] = { 0, 1, 2, 3, 4 };

sem_t mutex;
sem_t S[N];

void test(int phnum)
{
    if (state[phnum] == HUNGRY
        && state[LEFT] != EATING
        && state[RIGHT] != EATING) {
        // state that eating
        state[phnum] = EATING;

        sleep(2);

        printf("Philosopher %d takes fork %d and %d\n",
            phnum + 1, LEFT + 1, phnum + 1);

        printf("Philosopher %d is Eating\n", phnum + 1);

        // sem_post(&S[phnum]) has no effect
        // during takefork
        // used to wake up hungry philosophers
        // during putfork
        sem_post(&S[phnum]);
    }
}

// take up chopsticks
```

```

void take_fork(int phnum)
{

    sem_wait(&mutex);

    // state that hungry
    state[phnum] = HUNGRY;

    printf("Philosopher %d is Hungry\n", phnum + 1);

    // eat if neighbours are not eating
    test(phnum);

    sem_post(&mutex);

    // if unable to eat wait to be signalled
    sem_wait(&S[phnum]);

    sleep(1);
}

// put down chopsticks
void put_fork(int phnum)
{

    sem_wait(&mutex);

    // state that thinking
    state[phnum] = THINKING;

    printf("Philosopher %d putting fork %d and %d down\n",
        phnum + 1, LEFT + 1, phnum + 1);
    printf("Philosopher %d is thinking\n", phnum + 1);

    test(LEFT);
    test(RIGHT);

    sem_post(&mutex);
}

void* philosopher(void* num)
{

    while (1) {

        int* i = num;

```

```

    sleep(1);

    take_fork(*i);

    sleep(0);

    put_fork(*i);
}
}

int main()
{

    int i;
    pthread_t thread_id[N];

    // initialize the semaphores
    sem_init(&mutex, 0, 1);

    for (i = 0; i < N; i++)

        sem_init(&S[i], 0, 0);

    for (i = 0; i < N; i++) {

        // create philosopher processes
        pthread_create(&thread_id[i], NULL,
                      philosopher, &phil[i]);

        printf("Philosopher %d is thinking\n", i + 1);
    }

    for (i = 0; i < N; i++)

        pthread_join(thread_id[i], NULL);
}

```

Output :

```
Philosopher 5 takes fork 4 and 5
Philosopher 5 is Eating
Philosopher 4 is Hungry
Philosopher 3 putting fork 2 and 3 down
Philosopher 3 is thinking
Philosopher 2 takes fork 1 and 2
Philosopher 2 is Eating
Philosopher 1 is Hungry
Philosopher 5 putting fork 4 and 5 down
Philosopher 5 is thinking
Philosopher 4 takes fork 3 and 4
Philosopher 4 is Eating
Philosopher 3 is Hungry
Philosopher 2 putting fork 1 and 2 down
Philosopher 2 is thinking
|
```