


DN2012

Evaluation systems, power supplies

replaced by: DN3012



Product characteristics

Switched-mode power supply 24 V DC

Primary switched mode

Output current 5 A, regulated

Application

Application regulated power supply for sensors, actuators, evaluation electronics and plcs

Electrical data

Input voltage range	[V]	85...132 AC / 176...264 AC, 210...375 DC
Nominal voltage	[V]	115 / 230 AC
Nominal frequency	[Hz]	47...63
Output voltage	[V]	24 DC (+5% / -1%) to SELV/PELV
Output current	[A]	5
Residual ripple	[%]	< 0.1
Switch-on peak current	[A]	< 15
Efficiency	[%]	90
Short-circuit protection		yes
Overload protection		yes
Power-on delay time	[ms]	< 20
Derating		3 W/K (+60...+70°C)
Mains buffering time	[ms]	> 37
Protection class		I
Overvoltage protection (OVP) [V]		29

Outputs

Output Output current 5 A, regulated

Environment

Ambient temperature [°C] -10...60

Protection IP 20

Tests / approvals

DN2012

Evaluation systems, power supplies

EMC	EN 50081-1 EN 61000-6-2
-----	----------------------------

MTTF [Years]	241
--------------	-----

Mechanical data

Housing materials	aluminium
Installation	rail TH35 (to EN 60715)
Weight [kg]	0.699

Displays / operating elements


Function display	LED	green: output voltage
------------------	-----	-----------------------

Electrical connection

Connection	terminals 1.5 up to 6 mm ²
------------	---------------------------------------

Wiring

1: primary, 2: secondary



Remarks

Remarks	Protection class according to IEC 61140
---------	---

ifm electronic gmbh • Friedrichstraße 1 • 45128 Essen — We reserve the right to make technical alterations without prior notice. — GB — DN2012 — 26.11.2004

replaced by: DN3012