

```

1  #include <ESP8266WiFi.h>
2  #include <ESP8266WebServer.h>
3  #include <LoRa.h>
4  #include <SPI.h>
5
6  ESP8266WebServer server(80);
7
8  String latestLat = "0";
9  String latestLon = "0";
10
11 // SX1278 LoRa Pins
12 #define LORA_SS 15 // D8
13 #define LORA_RST 16 // D0
14 #define LORA_DIO0 4 // D2
15
16 void handleRoot() {
17   String html = "<html><head><title>LoRa GPS Tracker</title>"
18               " <meta name='viewport' content='width=device-width, initial-scale=1'"
19               " <style>body{text-align:center;font-family:Arial;}#map{height:90vh;width:100%;}</style>"
20               "</head><body>"

```

Output Serial Monitor X

Message (Enter to send message to 'NodeMCU 1.0 (ESP-12E Module)' on 'COM8')

Both NL & CR 9600 baud

```

3fffffc0: feefeffe feefeffe 3fffdab0 40100ddd
<<<stack<<<

```

----- CUT HERE FOR EXCEPTION DECODER -----

```

H: 3 (~) 8a0800 00:00:00 Starting Receiver...
Connect to WiFi: GPS_Tracker
Open browser IP: 192.168.4.1
Web Server Started
LoRa init success!

```