


ZF 7600

TECHNICAL DATA SHEET

ZF 7600 SERIES PRODUCT DETAILS



Description

- 3 shaft, reverse reduction transmission with hydraulic clutch mounted on the input shaft and another one mounted on the reverse shaft. Input drive on opposite side to output drive.
- Non-reversing NR version also available
- Fully works tested, reliable and simple to install
- Suitable for commercial vessels in all applications as well as for motoryachts etc
- Design, manufacture and quality control standards comply with ISO 9001 and AQAP
- Compatible with all types of engines and propulsion systems, including waterjets and surface-piercing propellers and cpp's

Features

- Lightweight and robust aluminum alloy casing (sea water resistant)
- Case hardened and precisely ground gear teeth for long life and smooth running
- Output shaft thrust bearing designed to take maximum propeller thrust astern and ahead
- Smooth and reliable hydraulic shifting with control lever for attachment of push-pull cable or other operating system
- Compact, space-saving design, complete with oil cooler, pump and full flow filter
- Suitable for multi engine installation (same ratio and torque capacity engine wise or counter engine wise)



ZF 7600

RATINGS

Ratios	Power Factor		Input Power Capacity						Max.	Max.	Max.
	kW/RPM	hp/RPM	kW	hp	kW	hp	kW	hp	kW	hp	RPM
Pleasure Duty - Diesel			1800 RPM		2000 RPM		2100 RPM				
1.545*, 1.828*, 2.037, 2.231*, 2.565, 2.773*, 2.905	1.3717	1.8395	2469	3311	2743	3679	2880	3862	2880	3862	2300
3.174*	1.2954	1.7372	2332	3127	2591	3474	2720	3647	2720	3647	2300
Light Duty - Diesel			1800 RPM		2000 RPM		2100 RPM				
1.545*, 1.828*, 2.037, 2.231*, 2.565, 2.773*, 2.905	1.3403	1.7974	2413	3235	2681	3595	2814	3773	2814	3773	2300
3.174*	1.2954	1.7372	2332	3127	2591	3474	2720	3647	2720	3647	2300
Medium Duty - Diesel			1600 RPM		1800 RPM		2000 RPM				
1.545*, 1.828*, 2.037, 2.231*, 2.565, 2.773*	1.2356	1.6570	1977	2651	2224	2983	2471	3313	2471	3313	2300
2.905	1.1937	1.6008	1910	2561	2149	2881	2387	3201	2387	3201	2300
3.174*	1.0577	1.4184	1692	2269	1904	2553	2115	2836	2115	2836	2300
Continuous Duty - Diesel			1200 RPM		1600 RPM		1800 RPM				
1.545*, 1.828*, 2.037, 2.231*, 2.565, 2.773*	1.0262	1.3762	1231	1651	1642	2202	1847	2477	1847	2477	1800
2.905	1.0052	1.3480	1206	1618	1608	2157	1809	2426	1809	2426	1800
3.174*	0.9319	1.2497	1118	1500	1491	2000	1677	2249	1677	2249	1800

* Special Order Ratio

ZF 7600


DIMENSIONS



A	B1	B2	H1	H2	L	L1	L2
Millimeter (mm)							
340.0	500.0	500.0	348.0	694.0	759.0	640.0	146.0
Inch (in)							
13.39	19.69	19.69	13.7	27.32	29.88	25.2	5.75
Weight (kg)		Weight (lb)		Amount of Oil (l)		Amount of Oil (qt)	
970		2138		75.0		79.5	

BELL HOUSING DIMENSIONS

Name	A		B		C		L3		Bolt Holes		
									No.	Diameter	
	mm	in	mm	in	mm	in	mm	in		mm	in
SAE 00	787.4	31.0	850.9	33.5	882.65	34.75	280.0	11.02	16	13.49	0.53



OUTPUT FLANGE DIMENSIONS

A		B		C		D		Bolt Holes		
								No.	Diameter (E)	
mm	in	mm	in	mm	in	mm	in		mm	in
320.0	12.6	280.0	11.02	230.0	9.06	30.0	1.18	16	24.2	0.95



GENERAL INFORMATION

Duty Definitions

Pleasure Duty

Highly intermittent operation with very large variations in engine speed and power.

Average engine operating hours limit:	500 hours/year 300 hours/year for mechanical gearboxes
Typical hull forms:	Planing
Applications:	Private, non-commercial, non-charter leisure activities, no racing

Light Duty

Intermittent operation with large variations in engine speed and power.

Average engine operating hours limit:	2500 hours/year (for hydraulic transmissions smaller than ZF 2000 series, 2000 hours/year)
Typical hull forms:	Planing and semi-displacement
Typical applications:	Private and charter, sport/leisure activities, naval and police activities

Medium Duty

Intermittent operation with some variations in engine speed and power.

Average engine operating hours limit:	4000 hours/year (for hydraulic transmissions smaller than ZF 2000 series and workboat ZF W2700 series, 3500 hours/year)
Typical hull forms:	Semi-displacement and displacement
Typical applications:	Charter and commercial craft (example: crew boats), and naval and police activities

Continuous Duty

Continuous operation with little or no variations in engine speed and power.

Average engine operating hours limit:	Unlimited
Typical hull forms:	Displacement
Typical applications:	Heavy duty commercial vessels

Technical Notes

Duty Ratings

Ratings apply to marine diesel engines at the indicated speeds. At other engine speeds, the respective power capacity (kW) of the transmission can be obtained by multiplying the Power/Speed ratio by the speed. Approximate conversion factors:

- 1 kW = 1.36 metric hp
- 1 kW = 1.34 U.S. hp (SAE)
- 1 U.S. hp = 1.014 metric hp
- 1 Nm = 0.74 lb.ft.
- 1 Kg = 0.454 lb

Ratings apply to right hand turning engines, i.e. engines having counterclockwise rotating flywheels when viewing the flywheel end of the engine. These ratings allow full power through forward and reverse gear trains, unless otherwise stated. Contact your nearest ZF Sales and Service office for ratings applicable to gas turbines, as well as left hand turning engines, and marine transmissions for large horsepower capacity engines. Ratings apply to marine transmissions currently in production or in development and are subject to change without prior notice.

NOTE: The maximum rated input power must not be exceeded (see respective ratings in the technical data sheets).

Safe Operating Notice

The safe operation of ZF products depends upon adherence to technical data presented in our brochures. Safe operation also depends upon proper installation, operation and routine maintenance and inspection under prevailing conditions and recommendations set forth by ZF. Damage to transmission caused by repeated or continuous emergency manoeuvres or abnormal operation is not covered under warranty. It is the responsibility of users and not ZF to provide and install guards and safety devices, which may be required by recognized safety standards of the respective country (e.g. for U.S.A. - the Occupational Safety Act of 1970 and its subsequent provisions).

Monitoring Notice

The safe operation of ZF products depends upon adherence to ZF monitoring recommendations presented in our operating manuals, etc. It is the responsibility of users and not ZF to provide and install monitoring devices and safety interlock systems as may be deemed prudent by ZF. Consult ZF for details and recommendations.

Survey Society Classification

In most cases, the maximum medium and continuous duty ratings permitted by ZF are accepted in full by major classification societies. If classification is required, contact ZF regarding proper procedures (also for yacht service and ice classifications service).

Dimensions and Weights

Dimensions and weights refer to transmissions with bell housing (where appropriate) but excluding options such as: trolling valves, power take-offs, propeller shaft companion flanges, torsional couplings etc.

Torsional Vibration and Torsional Couplings

The responsibility for ensuring torsional vibration compatibility rests with the overall propulsion system integration responsible party. Compatibility check of torsional vibration must include excitations induced by engine governor. ZF cannot accept any liability for gearbox noise or for damage to the gearbox, the flexible coupling or to other parts of the drive unit caused by torsional vibrations. Contact ZF for further information and assistance.

For single engine powered boats, where loss of propulsion can result in loss of control, ZF recommends the use of a torsional limit stop. It is the buyer's responsibility to specify this option. ZF cannot accept any liability for personal injury, loss of life or damage or loss of property due to the failure of the buyer to specify a torsional limit stop.

ZF selects torsional couplings on the basis of nominal input torque at commonly rated engine speeds. Consult ZF for details concerning speed limits of standard offered torsional couplings, which can be below transmission limits. Special torsional couplings may be required for Survey Society requirements.