Agentic Lab

Architecture: roles, logic, conventions

Framework reference, as of main `53bd0d8`

October 2026

Abstract

Agentic Lab is a framework in which a small team of humans and AI agents run a scientific lab together. Members talk to their *manager* agents in Slack; managers delegate work to *worker* agents on GPU machines; a *secretary* keeps the lab running. Every agent runs Claude (through the Claude Agent SDK) on a human member's Claude seat, inside Claude Code's built-in sandbox, as its own Unix user. Anything an agent can't do inside its sandbox is asked of a human in a Slack DM. The lab is described by one file, `lab.yaml`, kept in the lab's private configuration repository; only what is merged to that repository's `main` is ever deployed. This document describes the roles, the mechanisms that bind them together, and the conventions the framework relies on.

Contents

1 Principles **3**

2 Roles **3**
- 2.1 Humans . . . 3
- 2.2 Agents . . . 3
- 2.3 Services that are not agents . . . 4
- 2.4 Hosts . . . 4

3 The big picture **4**

4 Identity, users and tokens **5**

5 The sandbox and permissions **5**
- 5.1 Inside the sandbox: no questions . . . 5
- 5.2 Outside the sandbox: a human decides . . . 6

6 Work: managers and workers **6**
- 6.1 Workers . . . 6
- 6.2 Managers . . . 6
- 6.3 Who may use what . . . 7

7 The secretary **7**
- 7.1 State and the web UI . . . 7
- 7.2 Claude usage . . . 7
- 7.3 Machines . . . 8

7.4 Notices 8

8 Configuration: lab.yaml and the config repository **8**
8.1 lab.yaml 8
8.2 Only reviewed configuration is deployed 8
8.3 What lab apply does 9

9 Administering the lab from Slack **9**

10 Secrets **10**

11 GitHub for agents **10**

12 Observability **10**

13 Security summary **11**

14 Conventions **11**

15 Command reference **12**

16 Not in this version **12**

1 Principles

1. **Humans decide, agents do.** Agents never approve anything: not each other's actions, not their own, not pull requests. Approvals come from the human the action is for, in a Slack DM, from a dedicated app.
2. **Sandbox the environment, not the commands.** There is no command parsing or classifier. Inside Claude Code's sandbox an agent may do anything; leaving it (the internet, writes outside its folders) needs a human.
3. **Secrets belong to services, not to agents.** Each agent's service holds its tokens in a folder the agent's sandbox can't read. Secrets never pass through a chat: they arrive through one-time links and hidden prompts.
4. **One file describes the lab, and git is its history.** `lab.yaml` declares humans, agents, hosts and grants. Every change is a reviewed pull request in the lab's private configuration repository; deployment takes only `main`.
5. **Every agent is attached to a human, in terms of tokens.** An agent runs on one member's Claude seat. Who may *use* an agent is a separate setting.
6. **Transparency over limits.** No spend limits; instead the web UI and the secretary show usage per Claude account, with when and from where each number was read.
7. **Simple, generic, portable.** No hard-coded hosts, organisations or project tools. Experiment trackers and similar tools are extensions a lab adds itself.

2 Roles

2.1 Humans

Member A person in `lab.yaml` (`humans:`), with a Slack member id. Talks to managers and the secretary in Slack, receives the approvals for work done for them, and lends their Claude seat to the agents attached to them.

Admin A member with `admin: true` and a `tailscale_login`. Only admins can read agents' logs in the web UI, change the lab (through the secretary or the console), deploy, power off a busy machine, or ask for someone else's token.

2.2 Agents

Secretary Exactly one per lab, on an always-on host. Keeps the lab running: collects its state, serves the web UI, powers cloud machines on and off (and stops idle ones), warns about expiring tokens, answers questions about the lab in Slack, and is how admins administer the lab after the install (§9). It refuses research work and points to the member's manager.

Manager A member's team-mate in Slack: it understands requests, delegates work to workers, follows the tasks and reports back with summaries, plots and files. It never approves; it relays. A manager is *dedicated* (serves one member) or *shared* (serves every member, with a separate memory for each).

Worker An agent on a GPU machine that takes tasks over MCP, one at a time, first come first served, and reports progress and a result. Also *dedicated* or *shared*.

2.3 Services that are not agents

Broker On the secretary host, as `lab-broker`. Receives every permission request from every agent, works out which human decides, and asks them through the *Lab Approvals* Slack app. Holds active grants.

Intake On the secretary host. Receives secrets through one-time codes: web forms (`/s/<code>`) and a small client script for Claude tokens.

2.4 Hosts

- **Secretary host**: small, always on (on-prem or a small VM). Runs the secretary, broker, intake and web UI, and the admin's Claude Code session for the install. Managers usually run here or on one shared CPU VM.
- **GPU hosts**: cloud VMs (Nebius in this version), `power: on_demand` or `always_on`, stopped when idle.
- All hosts are on one **Tailscale tailnet**; services talk to each other only over it.

3 The big picture




Figure 1: Components and their main conversations. Between lab hosts, everything runs over the tailnet. Slack, Claude, GitHub and Nebius are reached over the internet by the services; sandboxed agent commands reach none of them, except GitHub for an agent with a bot (§11). Every agent calls Claude on a member's seat (dotted).

A typical piece of work:

1. A member DMs their manager: *"train the baseline on worker-a and show me the loss curve"*.
2. The manager submits a task to the worker over MCP, naming the member as the requester, and registers it with the broker.

3. The worker runs the task in its sandbox, reporting progress. If it needs something outside the sandbox (say, a dataset from the internet) it asks; the broker DMs *the requester* with buttons; the answer comes back to the worker.
4. The manager follows the task and posts progress, the plot and a summary in the member's thread. The secretary's web UI shows it all as it happens.

4 Identity, users and tokens

- **One Unix user per agent**: `lab-<agent id>` (a system user, no login shell, no SSH keys, home folder mode 700). Several agents on one host never share a user, so they can't read each other's files. Humans log in as themselves.
- Each agent runs as a **systemd service** under its user: `lab-worker@<id>`, `lab-manager@<id>`, `lab-secretary`; plus `lab-broker` and `lab-intake`.
- **Folders per agent user**:
  - `~/work`: its working folder (writable in its sandbox);
  - `~/.config/agentic-lab`: its service's secrets (Claude token, Slack tokens, lab tokens, GitHub token), *not readable* by its sandbox;
  - `~/.local/state/agentic-lab`: the service's state (task queue, memory, usage, event log), *not readable* by its sandbox.
- **Claude**: `human:` on an agent says whose Claude seat it runs on (a `claude setup-token` token, valid a year). The token reaches Claude Code as an environment variable that is stripped from sandboxed commands.
- **Lab tokens**: generated by `lab apply` and never shown; each pair of services that talk has its own (manager→worker, agent→broker, the secretary's *read-only* monitoring tokens). They live in `/etc/agentic-lab/private/tokens.yaml` (root) and in the services' secret folders.
- **Display names**: every agent has an id (`mgr-flash`) and a `display_name` (*Flash*), the name humans see. Names are the admin's choice; the framework and its guide never invent them.

5 The sandbox and permissions

5.1 Inside the sandbox: no questions

Every agent's Claude Code runs with the built-in sandbox (bubblewrap + seccomp), rendered per agent from `lab.yaml` (`lab settings <agent>` prints it):

- **Network**: only the lab's tailnet names (`*.<tailnet>`), plus hosts granted to it; strict allowlist (unknown hosts are refused, not prompted). Raw IPs are refused: lab resources are reached by their tailnet names.
- **Files**: writes only in the working folder, `/tmp` and granted paths; reads anywhere except `/run`, `/var/run` and its service's secret and state folders.
- **GPU**: workers see the GPU through a wrapper around bubblewrap (`bwrap-gpu`, set as `sandbox.bwrapPath` in Claude Code's managed settings) that binds the NVIDIA devices; Unix sockets are allowed for CUDA, and `/run` is hidden instead (closing a `systemd-run` escape).

- **Host setup** (`setup-sandbox.sh`): an AppArmor profile that lets bubblewrap create its namespaces on Ubuntu, the GPU wrapper, the managed settings.

Any Bash command that stays in the sandbox is allowed without asking. Caches (`XDG_CACHE_HOME`) point into the working folder. Managers auto-compact their context at 17% of the window (`compact_percent`); others at Claude's default.

5.2 Outside the sandbox: a human decides

When the sandbox refuses something, the agent sees why and may retry outside it. That retry is a permission request: the agent's service sends it to the broker, with the sandbox violations that explain it.

Who decides The human *the action is for*: a worker task's requester (as registered by the manager that submitted it, not as claimed by the worker); for a manager, the member whose message started the work. Never an agent.

How A DM from the *Lab Approvals* app with buttons: **Run once**, **Allow *X* for 1 hour**, **Allow *X* for this task**, **Deny**. A reply in the DM's thread denies, with the reply as the reason.

Timeout Unanswered requests are denied (default 120 s per human, `timeout_s`); a timeout never approves.

Grants "For a while" answers become *grants* that widen the sandbox (a domain, a writable path, or a tool) with an expiry; the agent's session restarts with the wider sandbox. *Standing* grants are written in `lab.yaml`. "Trust everything unsandboxed for an hour" does not exist.

Managers relay: they can show members what their tasks are waiting for and add context to a pending request; they cannot decide it.

6 Work: managers and workers

6.1 Workers

- An MCP server on the tailnet (`http://<host>:8770/mcp`), authenticated by bearer tokens: one per manager allowed to use it, plus the secretary's read-only one.
- Its tools:
  `submit_task`, `task_status`, `task_result`, `cancel_task`, `list_tasks`, `get_guardrails`, `read_file` and `write_file` (its working folder, up to 20 MB), `health_check` (queue, GPU and its processes, disk, usage), `check_usage`, and `recent_events` (its log: *the secretary's token only*).
- Tasks run one at a time, first come first served; a restart requeues a running task and resumes its Claude session. No fixed results contract: a result is a summary plus whatever artifacts fit (files, commits, links).

6.2 Managers

- **Slack**: Socket Mode (no public URL). A DM is one conversation; in channels a manager joins only threads where it's mentioned or already involved, reading the thread so far (up to 50 messages) on first mention. In such a thread it sees every message and may stay silent. Attachments (up to 50 MB) are downloaded into its working folder.

- Every message is checked against `lab.yaml`: only lab members, and only those who may use this manager.
- **Tools**: list workers, submit and follow tasks, pending approvals and notes on them, post files, fetch a worker's file into the conversation, send a file to a worker, `recall` and `remember`.
- **Memory**: durable notes about members and their work. A dedicated manager has one memory; a shared manager keeps one per member, separated by code (private conversations stay private).
- **Follow-up**: a background loop posts each task's progress and result in the conversation that started it, mentioning the requester.

6.3 Who may use what

`access`	Meaning
`dedicated`	Only the agent's own member (`human:`) may use it; a dedicated worker takes tasks only from its member's managers.
`shared`	Every member may use it; a shared manager keeps per-member memory.

7 The secretary

7.1 State and the web UI

Every 15 s the secretary collects the lab's state: workers (over MCP, with its read-only token), managers (their status endpoint), the broker (pending approvals, grants), local services (systemd) and machines (Nebius, every few rounds). It serves:

- **The web UI** (`http://<secretary host>:8774/`, tailnet only, refreshes every 20 s): Claude usage per account, workers and their tasks, approvals and grants, machines, agents, and which configuration and framework commits are deployed.
- **Agents' logs** (`/logs/<agent>`), **admins only**: the request's tailnet address must not be a lab host; `tailscale whois` must name a person (not a tagged device) whose login is an admin's in `lab.yaml`. Tailscale authenticates every packet with the device's key, so the address can't be forged.
- **A Slack Home tab**: a personal digest (your usage, your tasks, approvals waiting for you, machines) with a link to the web UI.

7.2 Claude usage

- Each agent records its tokens per run (new vs. cached) and its seat's limit readings. Readings are per account (a seat is shared by all its agents); the freshest wins, and every number shows *as of when* and *from which agent*.
- Percentages come from a **probe**: every API reply carries the seat's 5-hour and weekly utilization in headers, which Claude Code doesn't pass on. Each agent's service sends one tiny request (Haiku, 1 output token) every 10 minutes, only while its seat's 5-hour window is known to be open, so it never opens one.
- **Check now** on each account in the web UI asks one agent on that seat to probe at once (once a minute at most).

7.3 Machines

- **Power**: the secretary starts and stops Nebius VMs listed in `lab.yaml` (`kind: cloud`, `provider: nebius`, `instance`), with a service account that may only view, start and stop VMs. Never its own host.
- **Busy** means: a worker there has a task running, queued or awaiting approval; or any process on a GPU (anyone's, not only the lab's); or a GPU at 10% or more; or a manager runs there.
- **Idle stop**: an `on_demand` host with only workers is stopped after `idle_stop_min` minutes of not being busy.
- **Who may power**: any member may power a machine on, or off when idle; powering off a busy machine is for admins only, after confirming (`force_off`).

7.4 Notices

Daily, the secretary warns about credentials and GitHub bot tokens expiring within 14 days (from `lab.yaml`) and can post lab-wide notices to an `announcements` channel.

8 Configuration: lab.yaml and the config repository

8.1 lab.yaml

Section	Contents
`lab`, `tailnet`	The lab's name; the tailnet's DNS suffix.
`humans`	Members: `name`, `slack_user`, `channels` (permissions: Slack DM), `admin`, `tailscale_login`.
`agents`	Each agent: `role`, `human` (whose seat), `host`, `access`, `display_name`, `grants` (standing), `github` (its bot), `model`, `workdir`, `port`, `compact_percent`, `slack_app`.
`hosts`	`kind` (onprem/cloud), `provider`, `instance`, `power`, `idle_stop_min`, `tailnet_name`, `ssh_user`.
`github`	`accounts`: the bots, with their commit `email` and token `expires`.
`credentials`	Other expiring credentials to be reminded of.
`announcements`	A Slack channel for lab-wide notices.

`lab check` validates everything at once (unknown keys are errors) and warns about what is merely odd. Agent ids are lowercase (`[a-z][a-z0-9-]*`), since they become Unix user names.

8.2 Only reviewed configuration is deployed

- The lab's configuration lives in its own **private repository**: `lab.yaml` and `framework.lock`, which pins the framework to one commit. The framework repository is only read.
- `lab apply` fetches the config repository and deploys `lab.yaml` and `framework.lock` *as they are on* `origin/main`, never the working copy. It ships the framework only from a clean checkout at the pinned commit.
- Every change: a branch → `lab plan -working-tree` (preview) → a pull request (`lab pr-link`) → a human reviews and merges → `lab apply`. Upgrading the framework is the

same: `-update-framework` only rewrites `framework.lock`; the new pin goes through a pull request.

- Every host records what it runs in `/etc/agentic-lab/applied.yaml` (config and framework commits, when, by whom), shown by `lab doctor` and the web UI.
- **Break glass**: `lab apply -unreviewed` deploys the working copy; every host flags it as unreviewed until a reviewed deploy replaces it.

8.3 What lab apply does

From the secretary host, as root, for each host (locally, or over SSH as the admin with passwordless sudo): ship the framework to `/opt/agentic-lab` (and `lab` on the PATH), install `lab.yaml`, set up the sandbox, create the agents' users, install their secrets and generated tokens, install and (re)start their services. Services whose secrets haven't arrived yet are installed but held. Every step is idempotent: re-running is safe. `lab doctor` checks a host against `lab.yaml` and says how to fix each failure.

9 Administering the lab from Slack

After the install, admins work with the secretary in a DM; the console is for the install and emergencies. Admin-only tools, checked in code (the person's Slack identity must be an admin's in `lab.yaml`):

`propose_lab_change` writes the whole new `lab.yaml` on a branch of the secretary's own clone of the config repository, checks it, pushes it, and replies with the diff and the pull request link: *"here is the PR, review and merge it"*. It never touches `main`.

`offer_deploy` after the merge, posts a **Deploy** button listing what is merged but not deployed. Only an admin's click deploys; a button left behind by a newer `main` refuses. The result is posted back in the conversation.

`request_slack_app`, `request_github_token` post the steps (manifest, links, clicks) and a one-time link for a new manager's Slack app or a bot's token.

`check_slack_app`, `read_lab_config` check a Slack app's tokens; read the configuration on `main`.

The secretary's one root command is `lab apply-main`, allowed by a sudoers rule with no arguments: it deploys only the config repository's `main`, moving the framework checkout to the pinned commit, as its own systemd unit (so it survives the secretary's own restart). Even a misled secretary can only deploy what a human merged. Its deploy key (write: it pushes branches, never merges) and its clone live in folders its sandbox can't read.

Still at the console: the install itself; creating the first Slack apps; giving a new GPU VM SSH access; removing an agent's Unix user; `-unreviewed`; uninstalling (`docs/uninstall.md`).

10 Secrets

Secret	How it arrives
A member's Claude token	The secretary DMs them a one-time command. On their own computer it runs `claude setup-token` and sends the token straight to the intake over the tailnet; the intake checks it with Anthropic. Fallback: a hidden prompt.
A Slack app's tokens	A one-time web form (bot token `xoxb-`, app token `xapp-`); `lab slack-verify` checks them with Slack.
A GitHub bot's token	A one-time web form; the intake checks with GitHub that it is that bot's.
Nebius service account	`lab nebius connect` (key generated on the host), or a form.
Lab tokens	Generated by `lab apply`; never shown.

One-time codes expire after 24 h and are used once; failed attempts are rate-limited. Rules: no secret in any chat (Slack or Claude); agents can't read their service's secrets; an agent asked to recite a token refuses.

11 GitHub for agents

- A manager or worker may have **one GitHub identity**: a bot account (a GitHub machine user) named in `lab.yaml` (`github: <bot>` on the agent, the bot in `github.accounts`). Several agents may share one bot.
- The bot's token is in the agent's environment (`GH_TOKEN`) for all its work; git authenticates through a credential helper and commits carry the bot's name and email; `gh` is installed; `github.com` is reachable from its sandbox.
- The agent *can* read that token. What keeps this safe is GitHub: private repositories, a fine-grained token limited to the lab's repositories (contents, pull requests, issues), and **branch protection** on `main` (pull requests only, reviews by human code owners, no bypass for bots). Bots push branches and open pull requests, issues and comments; their approval never counts and they can't merge.

12 Observability

- **Event logs**: each agent's service writes its own log (messages, replies, tool calls, approvals, task events), one JSON-lines file per day, kept 14 days, in its state folder. The agent can't read it.
- **Reading logs**: the web UI (admins), `sudo lab logs <agent>` on its host. Workers hand their log only to the secretary's monitoring token; managers' status endpoint likewise.
- **Debugging**: `sudo lab debug <agent>` stops its service and opens its latest session in the classic Claude Code console, as its user with its sandbox; `lab manager ask` and `lab secretary ask` talk to them without Slack.

13 Security summary

Boundary	What enforces it
Agent vs. the internet and the host	Claude Code's sandbox (strict network allowlist, write allowlist, hidden secrets and `/run`); leaving it needs a human.
Agent vs. agent	One Unix user per agent; lab tokens per pair of services; a worker accepts only its allowed managers.
Who approves	The broker asks the human the action is for; timeouts deny; agents have no way to approve.
Who changes the lab	Merged pull requests on the config repository; `lab apply` and `apply-main` deploy only `main`; Slack admin tools check the admin in code.
Who reads logs	Tailscale identity matched to `admin: true`; lab hosts and tagged devices refused.
Secrets	Services' folders unreadable by sandboxes; one-time intake; no chat.
GitHub	Private repos, fine-grained tokens, branch protection.

Residual risks, by design: anyone with `sudo` on a lab host is effectively an admin there; an admin's device and Tailscale login are the keys to the logs; the web UI's main page is visible to the whole tailnet (restrict it with Tailscale ACLs); a GitHub bot's token is readable by its agents.

14 Conventions

- **Names**: agents' display names are chosen by the admin, never invented; ids derive from them (`Flash` → `mgr-flash`); Unix users are `lab-<id>`; services `lab-<role>@<id>`.
- **Ports** (tailnet only): worker MCP 8770, intake 8771, broker 8772, manager status 8773, secretary web UI 8774.
- **Paths**:
  - framework: `/opt/agentic-lab`; deploy logs: `/var/log/agentic-lab`;
  - configuration: `/etc/agentic-lab` (`lab.yaml`, `applied.yaml`, `private/`);
  - per agent: `~/work`, `~/.config/agentic-lab` (secrets), `~/.local/state/agentic-lab` (state).
- **Changes**: branch → pull request → human merge → deploy, for the lab's configuration and the framework alike.
- **Slack apps**: one per Slack-facing agent (each manager, the secretary) and one *Lab Approvals* app for the broker; manifests generated by `lab slack-manifest`; created one at a time, verified before the next.
- **Guidance**: the admin's own Claude Code session follows the repository's `lab-admin` skill and `docs/install.md`: explain before acting, ask rather than assume (names, ids), derive rather than ask (App IDs, tailnet names), never take a secret in the chat.

15 Command reference

Command	Purpose
`lab init`	Write the first `lab.yaml` (and `framework.lock`).
`lab check`	Validate `lab.yaml`.
`lab plan [-working-tree]`	What a deploy would do; missing secrets.
`lab apply [-update-framework] [-unreviewed]`	Deploy `main` (sudo).
`lab apply-main`	The secretary's deploy of `main` (sudoers).
`lab pr-link`	The link to open a pull request for the config branch.
`lab doctor`	Check this host; every failure says how to fix it.
`lab secret request`	A one-time code or link for a secret.
`lab slack-manifest`, `lab slack-verify`	A Slack app's manifest; check its tokens.
`lab nebius connect`	Set up VM power with one admin login.
`lab settings <agent>`	The agent's rendered sandbox settings.
`lab logs`, `lab debug`	An agent's log; its session in the console.
`lab manager ask`, `lab secretary ask`	Talk to them without Slack.

16 Not in this version

- Per-token (API) billing: agents run on members' Claude seats only.
- Permission channels other than Slack DM; approvals in the web UI (it monitors only).
- Several GitHub identities per agent, or switching identity per task.
- Cloud providers other than Nebius for VM power.
- An uninstall command (`docs/uninstall.md` describes the steps).
- Project tools such as experiment trackers: extensions a lab builds itself.