
## Example/How-To create calendar appointment using Exchange 03 Webday and PHP?

Asked 16 years, 3 months ago Modified 15 years, 3 months ago





6









I can provide examples of the XML I'm sending to WebDav but hoping someone out there has done this and has an example?



php

calendar

ms-office

exchange-server

webdav

## Share

Improve this question

Follow

edited Apr 2, 2009 at 15:09



warren

**33.4k** • 23 • 89 • 128

asked Sep 17, 2008 at 22:19



Charlie Davis





way I did it was to PUT a VCALENDAR document into the



folder. One quirk is that the VCALENDAR had to be enclosed within an RFC822 message. It's a bizarre combination of WebDAV, email, and iCAL/VCAL, but it worked at the time on Exchange 2003 hosted at Link2Exchange.

I did this in a Java program a few years back, and the



I'm sure there is an easier way, but this is what worked for me. Below I show a topdump packet trace of what happened. You should probably use ngrep/tcpdump on your own Outlook/Entourage client to see what it does.

Note that "Cal2" is the name of my test calendar folder. You'd use "Calendar" for the main calendar folder.

```
T 10.0.1.95:59741 -> 66.211.136.9:80 [AP]
PUT /exchange/yourname.domainname.com/Cal2/CC1.1163646
translate: f.
Content-Type: message/rfc822.
Pragma: no-cache.
Accept: */*.
Cache-Control: no-cache.
Authorization: Basic NOYOUCANTSEEMYPASSWORDYOUBASTARDS
User-Agent: Jakarta Commons-HttpClient/2.0final.
Host: e1.exmx.net.
Cookie: sessionid=29486b50-d398-4f76-9604-8421950c7dcd
Content-Length: 478.
Expect: 100-continue.
T 66.211.136.9:80 -> 10.0.1.95:59741 [AP]
HTTP/1.1 100 Continue.
```

```
T 10.0.1.95:59741 -> 66.211.136.9:80 [AP]
content-class: urn:content-classes:appointment.
Content-Type: text/calendar;.
.method=REQUEST; .
.charset="utf-8".
Content-Transfer-Encoding: 8bit.
BEGIN: VCALENDAR.
BEGIN: VEVENT.
UID: E1+1382+1014+495066799@I1+1382+1014+6+495066799.
SUMMARY: Voice Architecture Leads Meeting.
PRIORITY:5.
LOCATION: x44444 pc: 6879.
DTSTART: 20061122T193000Z.
DTEND: 20061122T203000Z.
DTSTAMP: 20061110T074856Z.
DESCRIPTION: this is a description.
SUMMARY: this is a summary.
END: VEVENT.
END: VCALENDAR.
T 66.211.136.9:80 -> 10.0.1.95:59741 [AP]
HTTP/1.1 201 Created.
Date: Thu, 16 Nov 2006 03:00:16 GMT.
Server: Microsoft-IIS/6.0.
X-Powered-By: ASP.NET.
MS-Exchange-Permanent-URL:
http://el.exmx.net/exchange/yourname.yourdomain.com/-
FlatUrlSpace-/122cda661de1da48936f9
44bda4dde6e-3af8a8/122cda661de1da48936f944bda4dde6e-3f
Location:
http://el.exmx.net/exchange/yourname.yourdomain.com/Ca
Repl-UID: <rid:122cda661de1da48936f944bda4dde6e00000003
Content-Type: text/html.
Content-Length: 110.
Allow: OPTIONS, TRACE, GET, HEAD, DELETE, PUT, COPY, M
SEARCH, SUBSCRIBE, UNSUBSCRIBE, PO
LL, BDELETE, BCOPY, BMOVE, BPROPPATCH, BPROPFIND, LOCK
```

ResourceTag:

```
<rt:122cda661de1da48936f944bda4dde6e0000003f3383122cda
GetETag: "122cda661de1da48936f944bda4dde6e00000003f4671
MS-WebStorage: 6.5.7638.
Cache-Control: no-cache.</pre>
```

T 66.211.136.9:80 -> 10.0.1.95:59741 [AP] <body><h1>/exchange/yourname.yourdomain.com/Cal2/CC1.1 created successfully</h1></body>.

You can verify that it worked using something like Cadaver to query the object's properties via WebDAV like so:

```
dav:/exchange/yourname@yourdomain.com/Cal2/> propget C
  Fetching properties for `CC1.1163646061548.0.eml':
 textdescription = this is a description
  contentclass = urn:content-classes:appointment
  supportedlock = <lockentry><locktype><transaction><g</pre>
</groupoperation></transaction></locktype><locks</pre>
  cope><local></lockscope></lockentry>
 permanenturl = http://e1.exmx.net/exchange/yourname@
FlatUrlSpace-/122cda661de1da48936f944bda4dde6e-
  3af8a8/122cda661de1da48936f944bda4dde6e-3f3383
  getcontenttype = message/rfc822
  id = AQEAAAAAOvioAQAAAAA/M4MAAAAA
 mid = -8992774761696198655
 uid = E1+1382+1014+495066799@I1+1382+1014+6+49506679
  isfolder = 0
  resourcetype =
 method = PUBLISH
  getetag = "122cda661de1da48936f944bda4dde6e00000003f4
  lockdiscovery =
  outlookmessageclass = IPM.Appointment
  creation date = 2006-11-16T03:00:16.549Z
  outlookmessageclass = IPM.Appointment
  creation date = 2006-11-16T03:00:16.549Z
```

```
ntsecuritydescriptor =
CAAEAAAAAABAC+MMAAAAEwAAAAAAAAAAAAIAHAABAAAAARAUAL
  nkePD6LEa8iIT/+gqDAAAAQUAAAAAAUVAAAAp5Hjw+ixGvIiE//
  dtstamp = 2006-11-10T07:48:56.000Z
  lastmodified = 2006-11-16T03:00:16.565Z
  dtstart = 2006-11-22T19:30:00.000Z
  location = x444444 pc:6879
  duration = 3600
 htmldescription = <!DOCTYPE HTML PUBLIC "-//W3C//DTD
 <HEAD>
  <META NAME="Generator" CONTENT="MS Exchange Server v</pre>
  <TITLE>this is a summary</TITLE>
 </HEAD>
 <BODY>
  <!-- Converted from text/plain format -->
  <P><FONT SIZE=2>this is a description</FONT>
 </P>
 </BODY>
 </HTML>
 ishidden = 0
  parentname = http://e1.exmx.net/exchange/yourname@yo
 meetingstatus = TENTATIVE
  subject = this is a summary
  getcontentlength = 631
  normalized subject = this is a summary
  isstructureddocument = 0
  repl-uid = rid:122cda661de1da48936f944bda4dde6e00000
  timezoneid = 0
  displayname = CC1.1163646061548.0.eml
 href =
http://el.exmx.net/exchange/yourname@yourdomain.com/Ca
 nomodifyexceptions = 1
 patternend = 2006-11-22T20:30:00.000Z
 isreadonly = 0
 instancetype = 0
 uid = AQEAAAAAPzODAAAAAAAAAAAAAA
  getlastmodified = 2006-11-16T03:00:16.565Z
  created = 2006-11-16T03:00:16.549Z
  sensitivity = 0
  dtend = 2006-11-22T20:30:00.000Z
```

```
hasattachment = 0
iscollection = 0
read = 1
resourcetag =
rt:122cda661de1da48936f944bda4dde6e00000003f3383122cda6
patternstart = 2006-11-22T19:30:00.000Z
priority = 0
sequence = 0
```

Share Improve this answer Follow

answered Sep 18, 2008 at 13:28





## have a look at this

http://golemlab.wordpress.com/2009/09/13/php-owa-



Share Improve this answer answered Sep 13, 2009 at 16:27 Follow





community wiki golemwashere