

elixir dynamic module call

Asked 7 years, 11 months ago Modified 7 years, 11 months ago

Viewed 2k times



How can I call function `func()` in a module called `App.Reporting.Name`

6

based on the string `"name"` which is not known until runtime



using `String.to_atom` or `to_existing_atom` does not work :



```
alias App.Reporting.Name
module = "name" |> String.capitalize |>
String.to_atom
apply(module, :func, [])
```

Without the alias, this does not work either

```
module = "App.Reporting.Name" |> String.to_atom
apply(module, :func, [])
```

I get an `(UndefinedFunctionError)` and `(module :\"App.Reporting.Name\" is not available)`

thanks

dynamic

module

elixir

Share

Improve this question

Follow

asked Dec 27, 2016 at 21:47



[user2725682](#)

139 ● 1 ● 10

2 Answers

Sorted by:

Highest score (default)



9



Your second approach is almost correct, you just need to prefix `Elixir.` because `App.Reporting.Name` is equal to `: "Elixir.App.Reporting.Name"`, not `: "App.Reporting.Name"` since Elixir prefixes all module names (names starting with an uppercase letter) with `Elixir.` before turning it into an atom:

```
iex(1)> App.Reporting.Name ==  
: "App.Reporting.Name"  
false  
iex(2)> App.Reporting.Name ==  
: "Elixir.App.Reporting.Name"  
true
```

So, this code should work:

```
module = "Elixir.App.Reporting.Name" |>  
String.to_atom  
apply(module, :func, [])
```

and so should this:

```
module = Module.concat(App.Reporting, "name" |>  
String.capitalize |> String.to_atom)  
apply(module, :func, [])
```

Share Improve this answer

answered Dec 28, 2016 at 4:37

Follow



Dogbert

222k ● 42 ● 417 ● 414



1



The reason yours isn't working is because the `String.to_atom` does just that, turns a string into an atom. Because there is no module called "App.Reporting.Name" it's most likely `App.Reporting.Name` it errors.



Not sure if this is the *best* way to do this, just one that sprang to mind. But you could do something like this:

```
iex(2)> module = "Casing"
"Casing"
iex(3)> Module.concat(String, "#{module}") |>
  apply(:upcase, ["test sentence"])
"TEST SENTENCE"
```

Another solution could be to create a macro that automatically does this process, however that is not something I am that great at so you will have to go through the docs [here](#) for that one.

Share Improve this answer

answered Dec 27, 2016 at 22:58

Follow



Harrison Lucas

2,951 ● 20 ● 25