

[Lesson 4]

Roi Yehoshua 2018

[What we learnt last time?]

- Learn what is CSS and how it works
- CSS syntax
- Margins and Paddings, difference between them
- Basics of working with git

[Our targets for today]

- Browser default styles
- What is reset.css and why do we need it
- CSS block model
- box-sizing property
- Block display modes

[Reset.css]

- Aside from styles set by user, browsers have their own default styles for many elements. They add by default margins and paddings.
- Reset.css can remove default margins and paddings and make styling more clear and obvious.
- There are many options of reset.css configuration - all of them may be easily found in the internet. One of them can be found here:


<https://meyerweb.com/eric/tools/css/reset/>

- Reset.css can be added as external style via link tag:

```
<link rel="stylesheet" href="css/reset.css">
```

[CSS Box Model]

- All HTML elements can be considered as boxes
- Each box consists of:
 - **Content** - The content of the box, where text and images appear
 - **Padding** - Clears an area around the content. The padding is transparent
 - **Border** - A border that goes around the padding and content
 - **Margin** - Clears an area outside the border. The margin is transparent




```
width:250px;  
padding:10px;  
border:5px solid gray;  
margin:10px;
```

Let's do the math:
250px (width)
+ 20px (left and right padding)
+ 10px (left and right border)
+ 20px (left and right margin)
= 300px

[CSS Box Model In Developer Tools]

- You can examine the box model of each individual element on the page by opening up the browser developer tools and clicking on the elements in the DOM inspector



[Borders]

- The CSS border properties allow you to specify the style, width, and color of an element's border
- The **border-style** property specifies what kind of border to display
 - This property is required for all the other border properties to take affect
 - It can have from one to four values (for the top/right/bottom/left borders)

```
p.solid { border-style: solid; } p.dotted {  
border-style: dotted; } p.dashed { border-style:  
dashed; } p.double { border-style: double; }  
p.groove { border-style: groove; } p.ridge {  
border-style: ridge; } p.inset { border-style:  
inset; } p.outset { border-style: outset; }  
p.mix { border-style: dotted dashed solid double;  
}
```

A solid border.

A dotted border.

A dashed border.

A double border.

A groove border.

A ridge border.

An inset border.


An outset border.

A mixed border.

[Border Width]

- The **border-width** property specifies the width of the four borders
- The width can be set as a specific size (in px, pt, cm, em, etc.) or by using one of the three pre-defined values: thin, medium, or thick
- The border-width property can have from one to four values (for the top/right/bottom/left borders)

```
p.one {  
  border-style: solid;  
  border-width: 5px;  
}  
p.two {  
  border-style: solid; border-width: medium;  
}  
p.three {  
  border-style: solid;  
  border-width: 2px 10px 4px 20px;  
}
```



[Border Color]

- The border-color property is used to set the color of the four borders
- The border-color property can have from one to four values (for the top/right/bottom/left borders)
- If border-color is not set, it inherits the color of the element

```
p.color_one {  
    border-style: solid; border-color:  
    red;  
}  
  
p.color_two {  
    border-style: solid;  
    border-color: red green blue yellow;  
}
```

A solid red border

A solid multicolor border

[Border – Individual Sides]

- There are also properties for specifying each of the borders (top, right, bottom, and left)
- If the **border-style** property has four values: **border-style: dotted solid double dashed;**
 - top border is dotted
 - right border is solid
 - bottom border is double
 - left border is dashed
- If the border-style property has two values: **border-style: dotted solid;**
 - top and bottom borders are dotted
 - right and left borders are solid
- If the border-style property has one value: **border-style: dotted;**
 - all four borders are dotted
- The same works with **border-width** and **border-color**

[Border – Individual Sides]

```
p.individual_sides {  
    border-top-style: dotted;  
    border-right-style: solid;  
    border-bottom-style: dotted;  
    border-left-style: solid;  
}  
  
/* The same as: */  
p.individual_sides {  
    border-style: dotted solid;  
}
```

Two different border styles.

[Border – Shorthand Property]

→ The **border** property is a shorthand property for the following individual border properties:

- border-width
- border-style (required)
- border-color

```
p.border {  
  border: 5px solid red;  
}
```

This property is a shorthand property for border-width, border-style, and border-color.

→ You can also specify all the individual border properties for just one side:

```
p.leftBorder {  
  border-left: 6px solid red;  
  background-color: lightgrey;  
}
```

This property is a shorthand property for border-left-width, border-left-style, and border-left-color.

[Rounded Borders]

- The **border-radius** property is used to add rounded borders to an element
 - This property is not supported in IE8 and earlier versions

```
p.normal {  
    border: 2px solid red;  
}  
p.round1 {  
    border: 2px solid red;  
    border-radius: 5px;  
}  
p.round2 {  
    border: 2px solid red;  
    border-radius: 8px;  
}  
p.round3 {  
    border: 2px solid red;  
    border-radius: 12px;  
}
```

Normal border

Round border


Rounder border

Roudest border

[Width and Height]

- The **width** and **height** properties are used to set the width and height of an element
- They can be specified by:
 - **auto** (default) - the browser calculates the width and height
 - length values, like px, cm, etc.
 - percent (%) of the containing block
- The width and height properties do not include padding, borders, or margins
 - They set the size of the area inside the element!

```
div {  
  width: 50%; height: 200px;  
  background-color: powderblue;  
}
```



[Box Sizing]

- The **box-sizing** property (CSS3) defines how the width and height of an element are calculated: should they include padding and borders, or not
- Possible values:
 - **content-box** (default) - The width and height properties (and min/max properties) includes only the content. Border and padding are not included.
 - **border-box** - The width and height properties (and min/max properties) includes content, padding and border
 - **inherit** - Inherits this property from its parent element

```
div.box {  
  box-sizing: border-box;  
  width: 50%;  
  border: 5px solid blue;  
  float: left;  
}
```

This div occupies the left half

This div occupies the right half

[CSS Layout – The display Property]

- The **display** property specifies if/how an element is displayed
- Every HTML element has a default display depending on what type of element it is
 - The default display value for most elements is **block** or **inline**
- A block-level element always starts on a new line and takes up the full width available (stretches out to the left and right as far as it can)
 - Examples of block-level elements: `<div>`, `<h1>` - `<h6>`, `<p>`, `<form>`, `<header>`, `<footer>`, `<section>`
- An inline element does not start on a new line and only takes up as much width as necessary
 - Examples of inline elements: ``, `<a>`, ``

[Override The Default Display Value]

- Changing an inline element to a block element, or vice versa, can be useful for making the page look a specific way, and still follow the web standards.
- A common example is making inline elements for horizontal menus:

```
li {  
    display: inline;  
}
```

Display a list of links as a horizontal menu:

[HTML](#) [CSS](#) [JavaScript](#)

- Setting the display property of an element only changes **how the element is displayed**, NOT what kind of element it is
 - e.g., an inline element with display: block; is not allowed to have other block elements inside it

[Inline-Block]

- **display: inline-block** allows to set a width and height on an inline element
- Also, the top and bottom margins/paddings are respected, in contrast to display:inline
- Compared to display: block, the major difference is that display: inline-block does not add a line-break after the element, so the element can sit next to other elements
- The following example shows the different behavior of display: inline, display: inline-block and display: block:

[Inline vs. Inline-Block vs. Block]

```
span.a {  
  display: inline; width: 70px;  
  height: 70px; padding: 15px;  
  border: 1px solid blue;  
  background-color: yellow;  
}  
span.b {  
  display: inline-block; width:  
    70px; height: 70px; padding: 15px;  
  border: 1px solid blue;  
  background-color: yellow;  
}  
span.c {  
  display: block; width: 70px;  
  height: 70px; padding: 15px;  
  border: 1px solid blue;  
  background-color: yellow;  
}
```

display: inline


Lorem ipsum dolor sit amet, consectetur adipiscing elit.



gravida nisl sit amet facilisis.

display: inline-block


Lorem ipsum dolor sit amet, consectetur adipiscing elit.



gravida nisl sit amet facilisis.

display: block

Lorem ipsum dolor sit amet, consectetur adipiscing elit.



gravida nisl sit amet facilisis.

[Hide an Element]

- Hiding an element can be done by setting the **display** property to **none**
 - The element will be hidden, and the page will be displayed as if the element is not there

```
h1.hidden {  
  display: none;  
}  
  
<h1>This is a visible heading</h1>  
<h1 class="hidden">This is a hidden  
heading</h1>
```

This is a visible heading

Notice that the h1 element with display: none; does not take up any space.

- **visibility:hidden**; also hides an element
 - However, the element will still take up the same space as before

```
h1.hidden2 {  
  visibility: hidden;  
}  
  
<h1>This is a visible heading</h1>  
<h1 class="hidden2">This is a hidden  
heading</h1>
```

This is a visible heading

Notice that the hidden heading still takes up space.

[Control questions]

1. Why do we need reset.css?
2. What is a block model?
3. How does inline, block and inline-block modes work?
4. What is the purpose of box-sizing property?

[Materials]

Core materials:

<https://habr.com/post/45296/>

<https://htmlacademy.ru/blog/64-about-normalize-css>

<https://dan-it.gitlab.io/fs-book/projects/landing/basic.html#element-types>

<https://learn.javascript.ru/display>

<https://getinstance.info/articles/css/display-inline-block/>

Additional materials:

<https://stackoverflow.com/questions/6867254/browsers-default-css-for-html-elements>

<http://dreamhelg.ru/2010/04/what-is-inline-block/>

Video materials:

<https://www.youtube.com/watch?v=-JFZ8mqmPJw>

<https://www.youtube.com/watch?v=krsV53STWkE>