PostgreSQL Buffers

Vik Fearing

PGDay.FR Toulouse 8 juin 2017

2ndQuadrant PostgreSQL

Vik Fearing Change "and and" to "and".

irc: xocolatl

Twitter: @pg_xocolatl


PostgreSQL Buffers


Backend




Data Directory

data_directory






Page
=
Block
=
Buffer



Shared Buffers

shared_buffers



Usage Count 1.. 5

ClockSweep




Write-Ahead Log (WAL)

pg_xlog


Write-Ahead Log (WAL)

pg_wal



WAL Buffers


wal_buffers





WAL Writer

wal_writer_delay




Background Writer


bgwriter_lru_multiplier
bgwriter_lru_maxpages
bgwriter_delay

Checkpoints

```
checkpoint_timeout
checkpoint_completion_target
min_wal_size • max_wal_size
```




Buffer Rings



Temporary Tables

```
temp_buffers
temp_tablespaces
temp_file_limit
```



View "public.pg_buffercache" Column Modifiers Type bufferid integer relfilenode oid reltablespace oid reldatabase oid relforknumber smallint relblocknumber bigint boolean isdirty smallint usagecount pinning_backends integer

View "pg_catalog.pg_stat_bgwriter" Modifiers Column Type checkpoints_timed bigint checkpoints_req bigint checkpoint_write_time double precision checkpoint_sync_time double precision buffers_checkpoint bigint buffers_clean bigint maxwritten_clean bigint buffers_backend bigint buffers_backend_fsync bigint buffers_alloc bigint timestamp with time zone stats_reset

SET track_io_timing = on;

EXPLAIN (ANALYZE, BUFFERS)

View "pg_catalog. pg_stat_database "			
Column	Type	Modifiers	
datid datname numbackends xact_commit xact_rollback blks_read blks_hit tup_returned tup_fetched tup_inserted tup_updated tup_deleted conflicts temp_files temp_bytes deadlocks blk_read_time blk_write_time	oid name integer bigint	MOUITIERS +	
stats_reset	timestamp with time zone	I	

```
View "pg_catalog.pg_statio_all_tables"
     Column
                              Modifiers
                     Type
 relid
                    oid
 schemaname
                    name
 relname
                    name
 heap_blks_read
                    bigint
 heap_blks_hit
                    bigint
 idx_blks_read
                    bigint
 idx_blks_hit
                    bigint
 toast_blks_read
                    bigint
 toast_blks_hit
                    bigint
 tidx blks read
                    bigint
 tidx_blks_hit
                    bigint
```

```
View "pg_catalog.pg_statio_all_indexes"
                         | Modifiers
    Column
                  Type
 relid
                  oid
 indexrelid
                  oid
 schemaname
                  name
 relname
                  name
 indexrelname
                  name
 idx_blks_read
                  bigint
 idx_blks_hit
                  bigint
```

View "public.pg_stat_statements"			
Column	Type	Modifiers	
userid	oid	+ 	
dbid	oid		
queryid	bigint		
query	text		
calls	bigint		
total_time	double precision		
min_time	double precision		
max_time	double precision		
mean_time	double precision		
stddev_time	double precision		
rows	bigint		
shared_blks_hit	bigint		
shared_blks_read	bigint		
shared_blks_dirtied	bigint		
shared_blks_written	bigint		
local_blks_hit	bigint		
local_blks_read	bigint		
<pre>local_blks_dirtied</pre>	bigint		
<pre>local_blks_written</pre>	bigint		
temp_blks_read	bigint		
temp_blks_written	bigint		
blk_read_time	double precision		
blk_write_time	double precision		

2ndQuadrant PostgreSQL

Vik Fearing Change "and and" to "and".

irc: xocolatl

Twitter: @pg_xocolatl