

a What is knowable, and when

Fixed at or before it

Arrival to acquisition minutes elapsed	Hour of day as an integer	Day of week ISO weekday
Month calendar month	Triage acuity as recorded, missing kept	ECG number in stay ordinal position
Prior ECG exists indicator	Days since prior ECG null if none	Prior ED visits count before arrival

9 pre-acquisition features. Every one carries an availability timestamp and a unit test that fails if that timestamp postdates the index time; the test passes on all 129,057 records and fails on each of the nine when it is deliberately poisoned.

time

the index acquisition

Resolves only after it

ECGs in first 90 min resolves after the index
Inter-ECG interval undefined on most records
Care unit at acquisition one level on the whole cohort
Cardiologist over-read declared, probed, not built

b Input blocks by arm, and the estimator each uses

A filled cell is a block the arm sees.

	Row 1	Row 2	Row 3	Row 3b	Row 4	Row 5	Row 6	Row 7	Row 8
Age, sex									
Acquisition context									
Index window									
Vitals, labs									
Waveform									
Estimator	gradient-boosted trees						the benchmark's published state-space model		

The waveform arms read the benchmark's committed configuration rather than its prose: 4 layers at model dimension 512, 2.5-second crops at 100 Hz, focal binary cross-entropy summed over all 15 targets. Row 5 passes through 463 columns unchanged.

Row 8 trains nothing. It is row 6 under a within-stratum statistic on 143 non-empty coarsened strata, so no compared pair differs in acquisition context.