3.8 Get mileage report

> 章节编号 3.8 为占位，接入 tracksolidprodocs 站点时按 Tracking Function 章实际顺序调整。

3.8.1 Description

Returns the mileage report data of the specified device(s) within a time range. The mileage is accumulated from GPS track data, and the value is consistent with the **Mileage Report** on the TrackSolid Pro web platform.

Notes:

- The query time range cannot exceed **3 months** (92 days).
- A maximum of **1000 IMEIs** per request.
- `begin_time` must be earlier than or equal to `end_time`.
- This interface returns mileage summary data only. To get trip details, use `jimi.device.track.mileage` or `jimi.open.platform.report.trips`.

3.8.2 Request URL

For the unique request URL, see Getting Started.

Method = jimi.open.platform.report.mileage

3.8.3 HTTP Request method

POST

3.8.4 Request parameters

(1) Common parameters: see Getting Started.

(2) Private parameters:

Parameter	Type	Required	Description
access_token	string	Yes	The access token obtained from `jimi.oauth.to`
imeis	string	Yes	Device IMEI list, separated by commas (,)
begin_time	string	Yes	Begin time of the query, format: yyyy-MM-dd
end_time	string	Yes	End time of the query, format: yyyy-MM-dd H
start_row	number	No	Row number of the result set
page_size	number	No	Number of records per page
filter_mileage	number	No	Whether to filter out devices without mileage devices are returned, and devices without mil the query time range as `startTime` / `endTime`; 1 data are returned

3.8.5 Response

Key	Type	Description
code	int	0: success; other values: see the error code list
message	string	Error message when code is not 0
data	Object	Mileage report data

data object:

Key	Type	Description
totalRows	int	Total number of records. When `filter_mileage` =1, it is the mileage data; when `filter_mileage` =0, it is the number of devices

Key	Type	Description
totalDistance	string	Total mileage of the current page, unit: km, 2 decimal place

Item of rows:

Key	Type	Description
imei	string	Device IMEI
deviceName	string	Device name
mcType	string	Device model
totalMileage	string	Total mileage within the query time range, unit: km, 2 decir up)
startTime	string	Time of the first GPS point within the range, in the account' yyyy-MM-dd HH:mm:ss
endTime	string	Time of the last GPS point within the range, in the account' yyyy-MM-dd HH:mm:ss

Correct response example:

json


```
{
  "code": 0,
  "message": "success",
  "result": null,
  "data": {
    "totalRows": 2,
    "totalDistance": "31.93",
    "rows": [
      {
        "imei": "860121060690446",
        "deviceName": "EM3065",
        "mcType": "GT800",
        "totalMileage": "24.27",
```

```
        "startTime": "2026-10-13 10:24:58",
        "endTime": "2026-10-13 17:28:55"
      },
      {
        "imei": "860121060690447",
        "deviceName": "EM3066",
        "mcType": "X3",
        "totalMileage": "7.66",
        "startTime": "2026-10-13 10:28:01",
        "endTime": "2026-10-14 13:43:01"
      }
    ]
  }
}
```


Error response example:


```json
{
  "code": 1001,
  "message": "param_error"
}
```


Common errors of this interface:

code	message	Scenario
1001	param_error	Missing required parameter / invalid time format / b time range exceeds 3 months / page_size out of ran invalid filter_mileage
1002	invalid_device_error	At least one IMEI does not belong to the app_key ac
1004	token_error	access_token is invalid or expired
1100	business_error	Internal query error (see message for details)