DATA SHEET

PAGE: Page 2

General	1	Tag Number	P&ID No.		
	2	Service	Pipe O. D. /I. D. inches		6.625" / 4.209
	3	Inlet Pipe No.	Inlet Pipe Class		6" ACK 4
	4	Inlet Pipe Mat'l	Inlet Pipe Insulation	316SS	
	5	Outlet Pipe No.	Outlet Pipe Class		2" ACK 4
	6	Outlet Pipe Mat'l	Outlet Pipe Insulation	316SS	
Process Conditions	7	Fluid	State	Oxygen	Liquid
	8	Design Press. Psig	Design Temp. Max/Min	8,500 psig	-320 F to 100 F
	9	Inlet Press. Psig	Inlet Temp. F	8,500 psig	-320 F
	10	Max. Shut-Off psig	Solid %	8,500 psig	
	11	Oper. Density kg/m3	Kin Visc(mm2/s)		
	12	Molecular Weight	Dyn Visc(mPa. s)	16	
	13	Allowable SPL dBA	Max. Flow		

Valve Body/Bonnet	14	Model		Actuator	52	Actuator Model	
	15	Body Type	Bolted		53	Actuator Type	Hydraulic
	16	Body Size	6"		54	Size	
	17	Allow. Oper. Temp. ℃			55	Action Mode	Double Acting
	18	Pressure Rating	8,500 psi		56	Spring Action	
	19	In/Out Conn.	6" RCon F08-061.208		57	Max Allow. P.	2800 psig
	20	Body/Bonnet Mat'l	Stainless Steel		58	Min Req. P	2200 psig
	21	Bonnet Type	Extention		59	Max./Min.	
	22	Flow Direction	Uni-directional		60	Actuator Orientation	
	23	Packing Type	Energized spring/seal		61	Handwheel Type	
	24	Packing Mat'l	PTFE/Elgiloy		62	Trip to Open/Close	Close
	25	Lubricator			63	Air Failure Valve	
	26	Isolated Valve			64	Set at MPa(g)	
	27	Predicted SPL dBA			65	Full Stroke Time	200ms
	28	Rated Cv			66	Gauge	
	29	Face to Face Dimension			67	Adj. Travel Limit	
Trim	30	Trim Type	Ball		68		
	31	Trim Size		Solenoid Valve	69	Model	
	32	Rated Travel	90º		70	Type	
	33	Plug/Ball/Disk Mat'l	A286		71	Single or Double Coil	
	34	Seat Mat'l	ENCAPSULATED PTFE		72	Operating Voltage	
	35	Stem/Shaft Mat'l	INCONEL 718		73	Body Material	
	36	Seal Type	Energized spring/seal		74	Trim Size	
	37	Seal Mat'l	PTFE/Elgiloy		75	Elec. Conn.	
	38	Seat Leakage Class			76	Explosion Proof	
	39	Firesafe			77	Enclosure Protection	
	40				78	Junction Box	
	41				79	Insulation Class	
Limit Switch	42	Model	Go Switch	Airset	80	Airset Mode	
	43	Switch Type			81	Pressure Set	
	44	Open Tag No.			82	Airset Mode	
	45	Close Tag No.		Accessories	83	Air Tank Capacity	
	46	Contact Form/Rating			84	Air Tank Vol.	
	47	Elec. Conn.			85	Air Tank Assembly	
	48	Explosion Proof			86	Pneu. Conn.	
	49	Enclosure Protection			87	Booster	
Clean/Test	50	Clean Level	400A	Misc.	88	Manufacturer	
	51	Clean Specification	RPT-STD 8070-0001		89	Requisition No.	
		Test Specification	See Note 3 Below				
		Spares Cleaned	No				

Note:
1) Manufacturer must supply any special tools needed for disassembly or reassembly of valve.
2) Manufacturer shall supply two (2) sets of repair soft goods with delivery of valve. A soft good set shall be defined as any and all non-metallic parts, recommended to be changed every time the valve is reassembled, and soft parts that experience severe wear. These shall include seats, packing, and body/bonnet seals and will be cleaned and bagged to match valve requirements
3) Special Testing: Testing per 54000-GT03, except do not cycle under differential pressure when conducting test in Section 8.
4) Delivery shall include one copy of the following for each valve: Detailed drawings, test procedures, material certifications (MTR's) for pressure containing parts, 54000-GM30 documentation if necessary, and all other pertinent documentation.
5) All welds must meet ASME Boiler and Pressure Vessel Code, Div. 1 sections II, V, VIII, IX. Welds must be backed with Argon only, no Nitrogen.
6) The Government reserves the right to inspect any or all component piece parts for cleanliness and workmanship prior to assembly with advanced two week notice.
7) All external ports such as bleed ports shall be medium pressure thread type.
8) Vendor drawings shall be approved by NASA personnel prior to manufacturing.
9) Valve shall be permanently marked in the following way.

Locator Number:	[redacted]
Manufacturer:	[redacted]
Model #:	[redacted]
Serial #:	[redacted]
Nominal Size:	[redacted]
MAWP:	[redacted]
Temperture Rating:	[redacted]
Max Cv:	[redacted]
Proof Test Type Date:	[redacted]
Weight:	[redacted]
Flow Direction arrow:	[redacted]

DATA SHEET

		PAGE:	Page 2

General	1	Tag Number	P&ID No.		
	2	Service	Pipe O. D. /I. D. inches		4.5" / 2.86"
	3	Inlet Pipe No.	Inlet Pipe Class		4" ACK 4
	4	Inlet Pipe Mat'l	Inlet Pipe Insulation	316SS	
	5	Outlet Pipe No.	Outlet Pipe Class		2" ACK 4
	6	Outlet Pipe Mat'l	Outlet Pipe Insulation	316SS	
Process Conditions	7	Fluid	State	Oxygen	Liquid
	8	Design Press. Psig	Design Temp. Max/Min	8,500 psig	-320 F to 100 F
	9	Inlet Press. Psig	Inlet Temp. F	8,500 psig	-320 F
	10	Max. Shut-Off psig	Solid %	8,500 psig	
	11	Oper. Density kg/m3	Kin Visc(mm2/s)		
	12	Molecular Weight	Dyn Visc(mPa. s)	16	
	13	Allowable SPL dBA	Max. Flow		

Valve Body/Bonnet	14	Model		Actuator	52	Actuator Model	
	15	Body Type	Bolted		53	Actuator Type	Hydraulic
	16	Body Size	4"		54	Size	
	17	Allow. Oper. Temp. ℃			55	Action Mode	Double Acting
	18	Pressure Rating	8,500 psi		56	Spring Action	
	19	In/Out Conn.	4" RCon F05-04.820		57	Max Allow. P.	2800 psig
	20	Body/Bonnet Mat'l	Stainless Steel		58	Min Req. P	2200 psig
	21	Bonnet Type	Extention		59	Max./Min.	
	22	Flow Direction	Uni-directional		60	Actuator Orientation	
	23	Packing Type	Energized spring/seal		61	Handwheel Type	
	24	Packing Mat'l	PTFE/Elgiloy		62	Trip to Open/Close	Close
	25	Lubricator			63	Air Failure Valve	
	26	Isolated Valve			64	Set at MPa(g)	
	27	Predicted SPL dBA			65	Full Stroke Time	200ms
	28	Rated Cv			66	Gauge	
	29	Face to Face Dimension			67	Adj. Travel Limit	
Trim	30	Trim Type	Ball		68		
	31	Trim Size		Solenoid Valve	69	Model	
	32	Rated Travel	90º		70	Type	
	33	Plug/Ball/Disk Mat'l	A286		71	Single or Double Coil	
	34	Seat Mat'l	ENCAPSULATED PTFE		72	Operating Voltage	
	35	Stem/Shaft Mat'l	INCONEL 718		73	Body Material	
	36	Seal Type	Energized spring/seal		74	Trim Size	
	37	Seal Mat'l	PTFE/Elgiloy		75	Elec. Conn.	
	38	Seat Leakage Class			76	Explosion Proof	
	39	Firesafe			77	Enclosure Protection	
	40				78	Junction Box	
	41				79	Insulation Class	
Limit Switch	42	Model	Go Switch	Airset	80	Airset Mode	
	43	Switch Type			81	Pressure Set	
	44	Open Tag No.			82	Airset Mode	
	45	Close Tag No.		Accessories	83	Air Tank Capacity	
	46	Contact Form/Rating			84	Air Tank Vol.	
	47	Elec. Conn.			85	Air Tank Assembly	
	48	Explosion Proof			86	Pneu. Conn.	
	49	Enclosure Protection			87	Booster	
Clean/Test	50	Clean Level	400A	Misc.	88	Manufacturer	
	51	Clean Specification	RPT-STD 8070-0001		89	Requisition No.	
		Test Specification	See Note 3 Below				
		Spares Cleaned	No				

Note:

1) Manufacturer must supply any special tools needed for disassembly or reassembly of valve.

2) Manufacturer shall supply two (2) sets of repair soft goods with delivery of valve. A soft good set shall be defined as any and all non-metallic parts, recommended to be changed every time the valve is reassembled, and soft parts that experience severe wear. These shall include seats, packing, and body/bonnet seals and will be cleaned and bagged to match valve requirements

3) Special Testing: Testing per 54000-GT03, except do not cycle under differential pressure when conducting test in Section 8.

4) Delivery shall include one copy of the following for each valve: Detailed drawings, test procedures, material certifications (MTR's) for pressure containing parts, 54000-GM30 documentation if necessary, and all other pertinent documentation.

5) All welds must meet ASME Boiler and Pressure Vessel Code, Div. 1 sections II, V, VIII, IX. Welds must be backed with Argon only, no Nitrogen.

6) The Government reserves the right to inspect any or all component piece parts for cleanliness and workmanship prior to assembly with advanced two week notice.

7) All external ports such as bleed ports shall be medium pressure thread type.

8) Vendor drawings shall be approved by NASA personnel prior to manufacturing.

9) Valve shall be permanently marked in the following way.

Locator Number:	[redacted]
Manufacturer:	[redacted]
Model #:	[redacted]
Serial #:	[redacted]
Nominal Size:	[redacted]
MAWP:	[redacted]
Temperture Rating:	[redacted]
Max Cv:	[redacted]
Proof Test Type Date:	[redacted]
Weight:	[redacted]
Flow Direction arrow:	[redacted]