25-0080 GEIGER QUAD G550 DOAS REPLACEMENT

MARINE CORPS BASE, CAMP LEJEUNE, N.C.

VICINITY MAP



LOCATION MAP



AREA MAP



GENERAL NOTES

1. THESE DRAWINGS INDICATES GENERAL CONDITIONS WITH INFORMATION COMPILED FROM FIELD OBSERVATION. CONSTRUCTION AND MATERIALS INDICATED ARE GENERAL IN NATURE AND ARE NOT INTENDED TO FULLY DESCRIBE THE EXISTING CONSTRUCTION PRESENT. THE CONTRACTOR IS RESPONSIBLE TO INSPECT ALL FACILITIES TO BE DEMOLISHED TO HIS OWN SATISFACTION AND INCLUDE ALL NECESSARY COSTS TO COMPLETELY REMOVE EACH FACILITY AS DESCRIBED. CONTRACTOR SHALL BE RESPONSIBLE FOR ACTUAL FIELD VERIFICATION PRIOR TO BIDDING, ORDERING MATERIALS AND DURING EVERY STEP OF CONSTRUCTION FOR EXISTING SURFACES, DIMENSIONS AND CONDITIONS. NUMBER OF ITEMS AND LOCATIONS SHOWN ARE APPROXIMATE, CONTRACTOR MUST VERIFY ALL CONDITIONS AND INCLUDE IN SCOPE OF WORK ACCORDINGLY.
2. PRIOR TO STARTING DEMOLITION ON ANY STRUCTURES OR UTILITIES, THE CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE EXISTING CONDITIONS OF ANY STRUCTURES AND UTILITIES. THE CONTRACTOR SHALL DEVELOP A PLAN OF DEMOLITION THAT ENSURES ALL ACTIVITIES ARE COMPLETED IN A SAFE MANNER. PROVIDE ANY TEMPORARY SHORING, SHEETING OR SUPPORT REQUIRED TO COMPLETE WORK IN A SAFE MANNER.
3. COMPLETELY REMOVE ALL STRUCTURE AND UTILITIES INDICATED, BOTH ABOVE GROUND AND BELOW GROUND.
4. WHERE ROADS, SIDEWALKS, ETC ARE INDICATED TO BE CUT AND PATCHED, EACH SHALL BE REMOVED AND REPLACED ALONG NEAT SAWCUT LINES, AND TO THE NEAREST JOINT WHERE IT EXISTS.
5. THIS AREA OF WORK IS LOCATED WITHIN RESTRICTED AREAS. ACCESS TO THIS AREA SHALL BE COORDINATED WITH THE CONTRACTING OFFICER.
6. REPAIR AND REFINISH AREAS DAMAGED OR DISTURBED BY NEW WORK TO BE PROVIDED UNDER THIS CONTRACT.
7. DIMENSIONS PROVIDED ON EXISTING ITEMS ARE PROVIDED TO AID THE CONTRACTOR UNDERSTAND THE SCOPE OF WORK. FIELD VERIFY ALL CONDITIONS. ALL THE DIMENSIONS SHOWN ARE APPROXIMATE ONLY.
8. METHOD OF REMOVAL OF ANY BUILDING COMPONENT SHALL BE APPROVED BY THE CO CONTRACTING REPRESENTATIVE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR ENSURING THAT REMOVAL OF EXISTING COMPONENTS DO NOT AFFECT ADJACENT OCCUPIED AREAS.
9. DEMOLITION OPERATIONS SHALL BE COMPLETED IN COMPLIANCE WITH ALL STATE AND FEDERAL REGULATIONS AND AS SPECIFIED.
10. ALL CONSTRUCTION ACTIVITIES SHALL BE IN ACCORDANCE WITH OSHA STANDARDS, AND GOVERNMENT REQUIREMENTS
11. THE NOTATION (TYP) INDICATES THAT THE CONDITION OCCURS IN MORE THAN ONE PLACE INCLUDING ALL SIMILAR CONDITIONS NOT INDIVIDUALLY NOTED.
12. COORDINATE STAGING AREA, SITE ACCESS, TOILET USE WITH THE CO CONTRACTING REPRESENTATIVE.
13. CONTRACTOR SHALL BE RESPONSIBLE FOR SITE SECURITY AND JOB SAFETY.
14. AREAS OUTSIDE THE LIMITS OF PROPOSED WORK DISTURBED BY THE CONTRACTOR'S OPERATIONS SHALL BE RESTORED BY THE CONTRACTOR TO THEIR ORIGINAL CONDITION AT THE CONTRACTOR'S EXPENSE AS SOON AS PRACTICABLE.
15. CONTRACTOR SHALL MINIMIZE DUST, SEDIMENT AND DEBRIS FROM EXITING THE CONSTRUCTION SITE AND SHALL BE RESPONSIBLE FOR CLEANUP, REPAIRS AND CORRECTIVE ACTION IF SUCH OCCURS. CONTRACTOR SHALL DISPOSE OF DEBRIS IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE, AND LOCAL REGULATIONS, ORDINANCE AND STATUTES.
16. BURNING WILL NOT BE ALLOWED ON THE PROJECT SITE UNLESS AUTHORIZED IN WRITING BY THE CONTRACTING OFFICER.
17. ADJACENT STRUCTURES AND UTILITIES MUST REMAIN IN OPERATION DURING DEMOLITION ACTIVITIES. EXISTING ROADS SHALL REMAIN OPEN AND ACCESSIBLE BY VEHICULAR AND PEDESTRIAN TRAFFIC. IF ROADWAY CLOSURE IS REQUIRED, APPROVAL SHALL BE SECURED FROM THE CONTRACTING OFFICER. THE CONTRACTOR SHALL PROVIDE BARRICADES, LIGHTS, SIGNAGE AND OTHER PROTECTIVE DEVICES IN ACCORDANCE
18. CONTRACTOR'S PERSONNEL MUST WEAR IDENTIFICATION AT ALL TIMES.
19. COORDINATE POWER OUTAGES WITH THE GOVERNMENT. MAINTAIN EXISTING ELECTRICAL SYSTEMS IN SERVICE. DISABLE SYSTEMS ONLY TO MAKE SWITCHOVERS AND CONNECTIONS. OBTAIN PERMISSION FROM THE CONTRACTING OFFICER AT LEAST 5 DAYS BEFORE PARTIALLY OR COMPLETELY DISABLING SYSTEM. MINIMIZE OUTAGE DURATION.

DRAWING INDEX

NAVFAC #	SHEET #	SHEET NAME
60042368	T001	TITLE SHEET, AREA MAPS
60042369	G001	GENERAL NOTES AND ABBREVIATIONS
60042370	M101	MECHANICAL SITE PLAN
60042371	M501	MECHANICAL DETAILS AND SCHEDULE
60042372	M801	MECHANICAL BARRACKS DOAS DDC DIAGRAM
60042373	M802	MECHANICAL BARRACKS DOAS DDC POINTS
60042374	M803	MECHANICAL ADMIN DOAS DDC DIAGRAM
60042374	M804	MECHANICAL ADMIN DOAS DDC POINTS

REVISIONS

SYM	REVISIONS	DATE	APPROVED
1			
2			
3			

CONSTRUCTION DOCUMENTS | T001

DEPARTMENT OF THE NAVY — NAVAL FACILITIES ENGINEERING SYSTEMS COMMAND

MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

GEIGER QUAD G550
DOAS REPLACEMENT

TITLE SHEET ABREVIATIONS, AREA MAPS LEGEND

DES.	C. HUSKEY
DR.	C. HUSKEY
CHK.	C. MAAS
SUBMITTED BY:	C. MAAS
DESIGN DIR.	C. MAAS
APPROVED: PWO OR OICC:	DATE:
SATISFACTORY TO:	DATE: 24 FEBUARY 2026

SIZE	CODE IDENT. NO	NAVFAC DRAWING NO.
E1	80091	60042368
		CONST. CONTR. NO.:

SCALE: NOTED | SPEC NO.: 25-0080 | SHEET: 1 OF 8

REVISIONS:

MECHANICAL GENERAL NOTES:

1. ALL MECHANICAL WORK MUST BE IN STRICT COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL CODES AND STANDARDS.
2. ALL DIMENSIONS AND ELEVATIONS FOR NEW EQUIPMENT, DUCTWORK, PIPING AND APPARATUS ARE APPROXIMATE AND ARE ONLY FOR CONTRACTOR'S GUIDANCE. CONTRACTOR MUST SUBMIT DIMENSIONS AND ELEVATIONS VERIFIED IN THE FIELD. DUCTWORK AND PIPING INDICATED ON THE DRAWINGS, SECTIONS AND PROSPECTIVE VIEWS ARE SHOWN DIAGRAMMATICALLY. DUCT AND PIPE ELEVATIONS IN EXACT LOCATIONS MUST BE DETERMINED BY THE INSTALLING CONTRACTOR AND DETAILED ON THE SHOP DRAWINGS.
3. ALL DUCT DIMENSIONS INDICATED ON PLAN ARE CLEAR INSIDE DIMENSIONS. CONTRACTOR MUST ACCOUNT FOR THE THICKNESS OF EXTERIOR INSULATION WHEN DETERMINING INSTALLATION CLEARANCES.
4. THE CONTRACTOR MUST TEMPORARILY COVER ALL EXPOSED DUCT AND PIPE OPENINGS WITH A NON-COMBUSTIBLE MATERIAL, AND SEAL THEM AIR TIGHT TO PREVENT CONTAMINATION OF THE RESPECTIVE SYSTEMS DURING CONSTRUCTION.
5. CONTRACTOR MUST REMOVE AND DISPOSE OF OFFSITE ALL DEMOLISHED WORK IN ACCEPTABLE AND SAFE MANNER AND MUST KEEP ALL NON-WORK AREAS CLEAN AND SAFE.
6. ALL EXISTING EQUIPMENT AND CONNECTIONS THAT NEED TO BE TEMPORARILY DEMOLISHED FOR RIGGING AND / OR INSTALLATION MUST BE REINSTALLED AND BROUGHT BACK TO ORIGINAL CONDITIONS PRIOR TO TEMPORARY REMOVAL.
7. INSTALL WORK SO AS TO BE READILY ACCESSIBLE FOR OPERATION, MAINTENANCE AND REPAIR. MINOR DEVIATIONS FROM DRAWINGS MAY BE MADE TO ACCOMPLISH THIS, BUT CHANGES WHICH INVOLVE EXTRA COST MUST NOT BE MADE WITHOUT APPROVAL.

MECHANICAL DEMOLITION NOTES:

1. THE CONTRACTOR MUST REVIEW THE DRAWINGS AND SPECIFICATIONS FOR DEMOLITION REQUIREMENTS AND LAYOUT HIS WORK IN A COMPATIBLE AND COMPLEMENTARY MANNER. REMOVE ALL EQUIPMENT, DUCTWORK, SUPPORTS, CONTROLS, ACCESSORIES, ETC..., AND MECHANICAL ITEMS MADE OBSOLETE BY THESE ALTERATIONS AS SHOWN IN THE MECHANICAL DRAWINGS. ALL ITEMS TO BE REMOVED OR MODIFIED MAY NOT BE SHOWN, HOWEVER, THIS CONTRACTOR MUST REMOVE ANY MECHANICAL WORK AS REQUIRED BY THE CONSTRUCTION OR AS DIRECTED BY THE GOVERNMENT CONTRACTING OFFICER. SURVEY THE AFFECTED AREAS BEFORE SUBMITTING A BID.
2. SCHEDULING OF DEMOLITION - COORDINATE SCHEDULING OF MECHANICAL DEMOLITION WORK WITH THE CONTRACTING OFFICER SO AS TO MINIMIZE DISRUPTION OF THE GOVERNMENT'S USE OF THE FACILITIES AND MAINTAIN THE CONSTRUCTION SEQUENCE. SEE DRAWINGS AND SPECIFICATIONS FOR ADDITIONAL INSTRUCTIONS CONCERNING PHASING AND SEQUENCE OF WORK.
3. DEMOLISHED MATERIALS - UNLESS SPECIFICALLY REQUESTED BY THE GOVERNMENT, ALL DEMOLISHED MECHANICAL MATERIALS MUST BECOME THE PROPERTY OF THE CONTRACTOR AND MUST BE REMOVED FROM THE SITE AND DISPOSED OF PROPERLY.
4. CUTTING AND PATCHING - PERFORM CUTTING AND PATCHING FOR MECHANICAL WORK SO AS TO MINIMIZE DAMAGE TO CEILINGS, FLOORS AND WALLS.
5. THESE DRAWINGS ARE COMPILED BY THE ENGINEER FROM THE GOVERNMENT'S AS-BUILT RECORD DRAWINGS AND LIMITED FIELD VERIFICATION OF EXISTING CONDITIONS FOR THE PURPOSE OF INDICATING THE WORK REQUIRED AND ARE BELIEVED TO BE CORRECT. NOTWITHSTANDING, THE CONTRACTOR MUST VERIFY ALL DUCTWORK, EQUIPMENT LOCATIONS, DIMENSIONS AND ALL FIELD CONDITIONS AFFECTING HIS WORK.
6. WHERE MECHANICAL SYSTEMS PASS THROUGH THE DEMOLITION AREAS TO SERVE OTHER PORTIONS OF THE PREMISES, THEY MUST REMAIN OR BE SUITABLY RELOCATED AND THE SYSTEM RESTORED TO NORMAL OPERATION. ADVISE THE CONTRACTING OFFICER IMMEDIATELY IF SUCH CONDITIONS ARE UNCOVERED BEFORE PROCEEDING WITH ADDITIONAL WORK.
7. PROTECT ALL EXISTING LIFE SAFETY SYSTEMS, FIRE ALARM AND PUBLIC ADDRESS SYSTEMS AND MAINTAIN THEM IN OPERATION THROUGHOUT THE PROGRESS OF THE WORK. NOTIFY THE CONTRACTING OFFICER IN WRITING IF SHUTDOWNS ARE REQUIRED PRIOR TO ANY OUTAGE OF SERVICE. WHERE THE DURATION OF A PROPOSED OUTAGE CANNOT BE TOLERATED BY THE GOVERNMENT, PROVIDE TEMPORARY CONNECTIONS AS REQUIRED MAINTAINING SERVICE.
8. SURVEY THE AFFECTED AREAS BEFORE STARTING DEMOLITION AS ALL EXISTING CONDITIONS CANNOT BE COMPLETELY DEPICTED ON THE DRAWINGS AND SOME UNUSUAL CONDITIONS EXIST.
9. IF ANY UNUSUAL STRUCTURAL OR ARCHITECTURAL CONDITIONS ARE ENCOUNTERED DURING DEMOLITION, CONTACT THE CONTRACTING OFFICER FOR ASSISTANCE.

DDC SYSTEM INTEGRATION NOTE:

THE ENERGY MANAGEMENT AND CONTROL SYSTEM (EMCS) AT CAMP LEJEUNE IS BY JOHNSON CONTROLS, INC. (JCI) METASYS. INCLUDE ALL CONTROL POINTS, SEQUENCES, PROGRAMMING, AND GRAPHIC UPDATES FOR NEW AND EXISTING HVAC EQUIPMENT MODIFIED UNDER THIS PROJECT TO MATCH THE BUILDING STANDARD FOR A COMPLETE AND OPERABLE SYSTEM.

MECHANICAL ABBREVIATIONS

ABBREVIATION	TERM
ADJ	ADJUSTABLE
AMCA	AIR MOVEMENT AND CONTROL ASSOCIATION
AMP	AMPERE (AMP, AMPS)
ASTM	AMERICAN SOCIETY OF TESTING AND MATERIALS
CFM	CUBIC FEET PER MINUTE
CIP	CAST IN PLACE
CMU	CONCRETE MASONRY UNIT
COP	COEFFICIENT OF PERFORMANCE
DB	DRY BULB
DEG OR º	DEGREE
EA	EXHAUST AIR
EG	EXHAUST GRILLE
EAT	ENTERING AIR TEMPERATURE
ECM	ELECTRONICALLY COMMUTATED MOTOR
EER	ENERGY EFFICIENCY RATIO
ESP	EXTERNAL STATIC PRESSURE
F	FAN
ºF	FAHRENHEIT
FLA	FULL LOAD AMPS
FT	FEET
HC	HOT WATER COIL
HGT OR H	HEIGHT
HP	HORSEPOWER
HR	HOUR(S)
IN.	INCH
IN.-WG	INCHES WATER GAUGE
KW	KILOWATT
LAT	LEAVING AIR TEMPERATURE
LBS	POUNDS
L	LOUVER
MAX	MAXIMUM
MBH	1000 BTUH
MCA	MINIMUM CIRCUIT AMPACITY
MCWB	MEAN COINCIDENT WET BULB
MIN.	MINIMUM
MOCP	MAXIMUM OVER CURRENT PROTECTION
NEMA	NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION
OZ	OUNCE
OA	OUTSIDE AIR
%	PERCENT
RA	RETURN AIR
RG	RETURN GRILLE
RPM	REVOLUTIONS PER MINUTE
RTU	ROOF TOP UNIT
SA	SUPPLY AIR
SF	SQUARE-FEET
SG	SUPPLY GRILLE
SQ	SQUARE
TG	TRANSFER GRILLE
TYP	TYPICAL
UH	UNIT HEATER
V/PH/HZ	VOLT/PHASE/HERTZ
VTR	VENT THROUGH ROOF
W	WIDTH
WB	WET BULB

NOTE: ALL ABBREVIATIONS MAY NOT BE USED IN PROJECT.

MECHANICAL LEGEND

	CEILING EXHAUST AIR GRILLE
	CEILING RETURN AIR / TRANSFER AIR GRILLE
	CEILING SUPPLY AIR DIFFUSER / GRILLE
AIR TYPE DESIGNATOR AIRFLOW, CFM	DIFFUSER / REGISTER / GRILLE TAG
	EXTENT OF DEMOLITION
H	HUMIDISTAT / HUMIDITY SENSOR
	INDICATES TO DEMOLISH
	MANUAL VOLUME DAMPER
M	MOTORIZED DAMPER
	POINT OF CONNECTION
	RETURN, EXHAUST OR TRANSFER AIR FLOW
	SUPPLY AIR FLOW
T	THERMOSTAT / TEMPERATURE SENSOR
TH	T-STAT / HUMIDISTAT OR TEMP/HUMIDITY SENSOR

NOTE: ALL ITEMS LISTED MAY NOT BE USED IN THIS PROJECT.

FINAL
02-24-2026

G001

DEPARTMENT OF THE NAVY NAVAL FACILITIES ENGINEERING COMMAND
MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

GEIGER QUAD G550
DOAS REPLACEMENT

GENERAL
NOTES AND ABREVIATIONS

DES.	CJH
DR.	CJH
CHK.	CJM
SUBMITTED BY:	CJM
DESIGN DIR.	C. Maas, PE
APPROVED: PWO OR OICC	DATE
SATISFACTORY TO:	DATE

SIZE	CODE IDENT. NO	NAVFAC DRAWING NO.
E1	80091	60042369
		CONST. CONTR. N40085-25-B-0080
SCALE: NOTED		SPEC. 05-25-0080

REVISIONS:

GENERAL NOTES:

1	EXISTING EQUIPMENT MAY NOT BE REMOVED FROM SERVICE UNTIL NEW EQUIPMENT IS ONSITE.
2	ONLY 1 DOAS UNIT MAY BE OUT OF SERVICE AT ANY GIVEN TIME. PROVIDE 14 DAYS NOTIFICATION PRIOR TO ANY OUTAGES.
3	EXCEPT FOR THE ADMIN BUILDING, OUTAGES MAY NOT EXTEND INTO WEEKENDS OR HOLIDAYS.
4	CONTRACTOR MUST FIELD VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS PRIOR TO ORDERING EQUIPMENT.
5	PROVIDE GOVERNMENT 14 DAYS NOTICE PRIOR TO DEMO. GOVERNMENT SHALL BE GIVEN OPPORTUNITY TO RECOVER PARTS FROM EXISTING DOAS.



1 MECHANICAL SITE PLAN
1" = 20'-0"

KEYNOTES:

1	DEMOLISH EXISTING DOAS UNIT COMPLETELY. PROTECT ALL OPENINGS TO BE REUSED. CLEAN AND REUSE EXISTING CONDENSATE DRAIN PIPE. INTEGRATE NEW UNIT INTO EXISTING DDC AND FIRE ALARM SYSTEM. REUSE EXISTING SMOKE DETECTOR. EXTEND EXISTING EQUIPMENT PAD AS REQUIRED FOR NEW UNIT. MODIFY, PROCURE, AND INSTALL ALL PARTS NECESSARY TO CONNECT NEW EQUIPMENT TO EXISTING COMPONENTS INCLUDING BUT NOT LIMITED TO GAS PIPE, DUCT, DRAIN PIPE, AND ELECTRICAL CONNECTIONS.
2	EXCEPT FOR DOAS INTAKE, ALL DUCT MUST BE PREFABRICATED, PREINSULATED PHENOLIC. SEE SPECIFICATIONS FOR DETAILS. DEMOLISH ALL EXISTING EXTERIOR DUCT. PROVIDE AND INSTALL NEW DUCT FROM DOAS TO EXISTING DUCT PENETRATION AT BUILDING.
3	REUSE AND INTEGRATE EXISTING DUCT HEATER.
4	PROVIDE AND INSTALL (3) 125 PINT PORTABLE DEHUMIDIFIERS WITH WHEELS IN SQUAD BAY BATHROOMS. PROVIDE AND INSTALL (3) 50 PINT PORTABLE DEHUMIDIFIERS WITH WHEELS IN DUTY BATHROOMS. PIPE TO FLOOR DRAIN OR SHOWER DRAIN WITH FLEXIBLE TUBE OR PIPE. DEHUMIDIFIERS TO BE INSTALLED PRIOR TO DOAS BEING DISCONNECTED. CONTRACTOR TO MAINTAIN DEHUMIDIFIERS DURING CONTRACT DURATION. DEHUMIDIFIERS TO BE TURNED OVER TO GOVERNMENT AFTER COMPLETION.

FINAL
02-24-2026

M101

DEPARTMENT OF THE NAVY NAVAL FACILITIES ENGINEERING COMMAND
MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

GEIGER QUAD G550
DOAS REPLACEMENT

MECHANICAL SITE PLAN

DES.	CJH
DR.	CJH
CHK.	CJM
SUBMITTED BY:	CJM
DESIGN DIR.	C. Maas, PE
APPROVED: PWO OR OICC	DATE
SATISFACTORY TO:	DATE

SIZE	CODE IDENT. NO	NAVFAC DRAWING NO.
E1	80091	60042370
		CONST. CONTR. N40085-25-B-0080
SCALE: NOTED	SPEC. 05-25-0080	SHEET 3 OF 8

REVISIONS:



1 **DOAS VERTICAL DUCT EXTENSION**

NOT TO SCALE



2 **EQUIPMENT MOUNTING DETAIL**

NOT TO SCALE

DEDICATED OUTSIDE AIR UNIT SCHEDULE

MARK	LOCATION	OUTDOOR AMBIENT		SUPPLY AIR (DB/WB °F)	RETURN AIR (DB/WB °F)	SUPPLY FAN DATA		EXHAUST FAN DATA		HEATING			ELECTRICAL			NOTES	ACCESSORIES
		SUMMER (DB/WB °F)	WINTER (DB °F)			OUTSIDE AIR (CFM)	ESP (IN WG)	EXHAUST AIR (CFM)	ESP (IN WG)	FUEL TYPE	EAT (°F)	INPUT (MBH)	VOLTS/PH/HZ	MCA	MOCP		
DOAS-1,2,3,4	G551, G551A, G551B, G551C	84/78.5	22	72.0/59.0	72.0/61.4	5,100	2.0	4,900	1.5	NATURAL GAS	40	200	460/3/60	64.1	80	1,2,4,5	A,B,C,D,E,F,G,H,I,J,K,L,M,N,O,P
DOAS-5	G550	84/78.5	22	72.0/59.0	-	770	0.5	-	-	HEAT PUMP	22	-	460/3/60	13.2	20	1,2,3,5	A,B,C,D,E,G,H,I,K,L,M,O,P

NOTES:
1) REFER TO SPECIFICATION SECTION 23 73 33 - HEATING, VENTILATION, AND COOLING SYSTEM FOR FURTHER REQUIREMENTS.
2) EFFICIENCY RATED IN ACCORDANCE WITH ANSI/AHRI STANDARD 340/360.
3) HOT GAS REHEAT AND HEAT PUMP HEATING IS INTEGRAL TO UNIT. UTILIZE EXISTING AUXILIARY ELECTRIC HEATING.
4) HEATING SHALL BE DONE VIA NATURAL GAS. DX SHALL ONLY BE USED FOR COOLING AND DEHUMIDIFICATION.
5) SETPOINTS SHALL BE ADJUSTABLE WITHOUT THE USE OF ANY ADDITIONAL ACCESSORIES NOT PERMANENTLY INSTALLED ON THE UNIT.

ACCESSORIES:
A) CONDENSER, EVAPORATOR AND REHEAT COILS TO BE COATED FOR EXPOSURE TO ASTM B117-90 3,000 HOUR SALT SPRAY RESISTANCE TEST WITH NO DEGRADATION.
B) SINGLE POINT ELECTRICAL CONNECTION WITH STAINLESS STEEL NEMA 4X DISCONNECT.
C) MODULATING HOT GAS REHEAT.
D) MERV 8 PRE-FILTER AND MERV 13 FILTER ON OUTDOOR AND RETURN AIR. PROVIDE 1 EXTRA COMPLETE SET OF FILTERS TO THE GOVERNMENT.
E) HAIL GUARD.
F) ERV FACE/BYPASS DAMPER WITH MODULATING ACTUATOR. ELECTRIC PREHEAT MAY BE PROVIDED AS AN ALTERNATE MEANS OF FROST CONTROL.
G) 120V GFCI CONVENIENCE OUTLET.
H) AIR COOLED VARIABLE SPEED HEAD PRESSURE CONTROL.
I) PHASE AND VOLTAGE MONITOR.
J) EXHAUST AIR GRAVITY DAMPER.
K) MANUFACTURER DDC CONTROLS WITH BACNET MS/TP INTERFACE.
L) OUTSIDE AIR DAMPER WITH 2-POSITION ACTUATOR. DAMPERS SHALL BE SEACOAST DESIGN AND LOW LEAKAGE WITH RUBBER EDGES.
M) 304 STAINLESS STEEL CONDENSATE DRAIN PAN.
N) PLATE HEAT EXCHANGER.
O) FULL 5 YEAR PARTS, LABOR, AND REFRIGERANT WARRANTY.
P) FACTORY STARTUP. REPORT TO BE PROVIDED TO THE GOVERNMENT 5 DAYS AFTER STARTUP.

FINAL
02-24-2026

M501

DEPARTMENT OF THE NAVY NAVAL FACILITIES ENGINEERING COMMAND
MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

DES. CJH
DR. CJH
CHK. CJM
SUBMITTED BY: CJM
DESIGN DIR. C. Maas, PE
APPROVED: PWO OR OICC DATE
SATISFACTORY TO: DATE

GEIGER QUAD G550
DOAS REPLACEMENT

MECHANICAL DETAILS AND SCHEDULE

SIZE E1
CODE IDENT. NO 80091
NAVFAC DRAWING NO. 60042371
CONST. CONTR. N40085-25-B-0080
SCALE: NOTED
SPEC. 05-25-0080

REVISIONS:



1 **BARRACKS DOAS DDC CONTROL DIAGRAM**

NOT TO SCALE

KEYNOTES:

1	ELECTRIC PREHEAT IS ACCEPTABLE IN LIEU OF FACE AND BYPASS DAMPER. IF ELECTRIC PREHEAT IS PROVIDED, PROVIDE COMMAND AND STATUS POINT. CONTRACTOR SHALL MAKE ALL NECESSARY MODIFICATIONS REQUIRED IF ELECTRICAL REQUIREMENTS EXCEED CURRENT INSTALLED CAPACITY.

FINAL
02-24-2026

M801

DEPARTMENT OF THE NAVY — NAVAL FACILITIES ENGINEERING COMMAND

MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

GEIGER QUAD G550
DOAS REPLACEMENT

MECHANICAL BARRACKS DOAS DDC DIAGRAM

DES.	CJH
DR.	CJH
CHK.	CJM
SUBMITTED BY:	CJM
DESIGN DIR.	C. Maas, PE
APPROVED: PWO OR OICC	DATE
SATISFACTORY TO:	DATE

SIZE	CODE IDENT. NO	NAVFAC DRAWING NO.
E1	80091	60042372
		CONST. CONTR. N40085-25-B-0080
SCALE: NOTED	SPEC. 05-25-0080	SHEET 5 OF 8

REVISIONS:

BARRACKS DOAS SEQUENCE OF OPERATIONS

A. GENERAL

1. PROGRAMS AND SEQUENCES INDICATED AND IMPLIED HEREIN SHALL BE PROVIDED.
2. PROVIDE ALL I/O POINTS INDICATED ON THE CONTROL DIAGRAM AND AS REQUIRED TO ACCOMPLISH THE SEQUENCE OF OPERATION.
3. THE VFD/MCC HOA SWITCH SHALL BE KEPT IN THE AUTO POSITION. HAND AND OFF POSITION SHALL BE UTILIZED FOR MAINTENANCE PURPOSES ONLY.
4. ALL POINTS SHALL BE ABLE TO INTEGRATE TO ALL TRENDS TOTALIZATIONS, GRAPHICS PAGES ETC., AS APPLICABLE.
5. ALL SETTINGS AND SETPOINTS SHALL BE USER ADJUSTABLE WITHOUT REQUIRING A MODIFICATION TO THE PROGRAMMING LOGIC CODE.
6. ALL ALARMS AS INDICATED ON THE DIAGRAMS IN THE SEQUENCE OF OPERATION SHALL BE GENERATED TO THE APPROPRIATE SERVER/WORKSTATIONS.

B. SETPOINTS:

1. SUPPLY AIR TEMPERATURE: 72.0°F
2. SUPPLY AIR DEWPOINT: 50.0°F

C. START/STOP/SCHEDULING:

1. THE DOAS OPERATES CONTINUOUSLY WITH REMOTE CAPABILITY FOR START/STOP/SCHEDULING FUNCTIONS.
   a. PROVIDE INDIVIDUAL, USER DEFINABLE SCHEDULES FOR OCCUPIED AND UNOCCUPIED TIME PERIODS.
   b. OCCUPANCY HOURS WILL BE CONTINUOUS.
2. WHEN AHU IS STARTED (MANUALLY OR AUTOMATICALLY):
   a. THE OUTSIDE AIR DAMPER (OAD) AND EXHAUST AIR DAMPERS (EAD) SHALL OPEN TO 100%. FANS SHALL BE ENERGIZED AFTER THEIR RESPECTIVE DAMPERS ARE PROVED OPEN.
3. WHEN DOAS IS STOPPED (EITHER MANUALLY, AUTOMATICALLY DURING UNOCCUPIED MODE, OR FROM SAFETY FUNCTION):
   a. THE SUPPLY AND EXHAUST FAN SHALL BE DE-ENERGIZED, OAD CLOSED, AND EAD CLOSED.

C. AIRFLOW CONTROL:

1. WHEN FAN STATUS INDICATES THE FAN HAS STARTED, THE FANS SHALL MODULATE TO MAINTAIN AIRFLOW SETPOINTS USING PID CONTROL LOOP.

D. TEMPERATURE AND HUMIDITY CONTROL:

1. HEATING:
   a. IF THE SUPPLY AIR TEMPERATURE IS LESS THAN THE SUPPLY AIR TEMPERATURE SETPOINT AND THE SUPPLY AIR DEWPOINT IS LESS THAN 50°F, THE UNIT WILL ENABLE THE NATURAL GAS HEATER AND MODULATE CAPACITY TO MAINTAIN THE SUPPLY AIR TEMPERATURE SETPOINT.
   b. DX HEATING OR DX COOLING WITH REHEAT SHALL NOT BE UTILIZED IN HEATING MODE.
2. DEHUMIDIFICATION:
   a. IF THE SUPPLY AIR DEWPOINT IS GREATER THAN 50°F, THE UNIT WILL ENABLE THE DX COOLING AND REHEAT AND MODULATE CAPACITY TO MAINTAIN THE SUPPLY AIR TEMPERATURE AND DEWPOINT SETPOINT.
3. COOLING:
   a. IF THE SUPPLY AIR TEMPERATURE IS GREATER THAN THE SUPPLY AIR TEMPERATURE SETPOINT AND THE SUPPLY AIR DEWPOINT IS LESS THAN 50°F, THE UNIT WILL ENABLE THE DX COOLING AND REHEAT AND MODULATE CAPACITY TO MAINTAIN THE SUPPLY AIR TEMPERATURE SETPOINT.
   b. NATURAL GAS HEATER SHALL BE ENABLED IF REHEAT CANNOT MAINTAIN THE SUPPLY AIR TEMPERATURE SETPOINT.

E. ALARMS:

1. IF AFTER 60 SECOND DELAY (ADJ.), THE SUPPLY OR EXHAUST FAN DOES NOT PROVIDE STATUS OF ON, THE FANS WILL BE SHUT DOWN, THE OAD WILL CLOSE, THE EAD WILL CLOSE, AND AN ALARM WILL BE GENERATED. THE SYSTEM WILL RESTART AUTOMATICALLY WHEN FAULT CONDITIONS HAVE CLEARED.
2. GENERATE AN ALARM AT THE BAS IF THE DISCHARGE AIR TEMPERATURE EXCEEDS ±5°F (ADJ.) FROM SETPOINT FOR MORE THAN 30 MINUTES (ADJ.).
3. GENERATE AN ALARM AT THE BAS IF THE SUPPLY OR EXHAUST AIRFLOW IS ±10% (ADJ.) FROM SETPOINT FOR MORE THAN 30 MINUTES (ADJ.).
4. GENERATE AN ALARM AT THE BAS IF THE SUPPLY AIR DEWPOINT EXCEEDS +5°F (ADJ.) FROM SETPOINT FOR MORE THAN 30 MINUTES (ADJ.).
5. GENERATE AN ALARM AT THE BAS IF A DAMPER STATUS DOES NOT MATCH THE COMMAND.
6. GENERATE AN ALARM AT THE BAS UPON RECEIVING A SMOKE DETECTOR SIGNAL.
7. GENERATE AN ALARM AT THE BAS IF A COMPRESSOR STATUS DOES NOT MATCH THE COMMAND.
8. GENERATE AN ALARM AT THE BAS IF THE UNIT IS IN HAND.

F. SAFETY INTERLOCKS

1. PROVIDE ANTI-TERRORISM FORCE PROTECTION (ATFP) EMERGENCY SHUTDOWN BOTH HARDWIRED IN THE EQUIPMENT SAFETY CIRCUIT AND IN SOFTWARE FROM THE BAS. THE SHUTDOWN ACTIVATION SHALL LATCH AND REQUIRE MANUAL RESET. UPON ACTIVATION, THE UNIT SHALL:
   a. OUTSIDE AIR DAMPER AND EXHAUST AIR DAMPER SHALL CLOSE WITHIN 30 SECONDS.
   b. EXHAUST FAN AND SUPPLY AIR FAN SHALL STOP.
2. HX BYPASS DAMPER SHALL MODULATE OPEN TO PREVENT THE ENTERING COIL TEMPERATURE FROM FALLING BELOW THE FROST THRESHOLD SETPOINT AS REQUIRED BY THE HX MANUFACTURER (26°F ADJ.)
3. INTEGRATE HARDWIRED SMOKE DETECTOR IN THE EQUIPMENT SAFETY CIRCUIT AND IN SOFTWARE FROM THE BAS. UPON ACTIVATION OF THE SMOKE DETECTOR, THE UNIT SHALL:
   a. OUTSIDE AIR DAMPER AND EXHAUST AIR DAMPER SHALL CLOSE.
   b. EXHAUST FAN AND SUPPLY AIR FAN SHALL STOP.

1 BARRACKS DOAS SEQUENCE OF OPERATION

NOT TO SCALE

BARRACKS DOAS UNIT POINTS LIST

	HARDWARE POINTS				SOFTWARE POINTS						SHOW ON GRAPHIC
POINT NAME	AI	AO	BI	BO	AV	BV	LOOP	SCHED	TREND	ALARM	
SUPPLY AIR FAN STATUS			X						X		X
SUPPLY AIR FAN START/STOP				X					X		X
SUPPLY AIR FAN VFD FREQUENCY		X							X		X
SUPPLY AIR FAN VFD FREQUENCY SETPOINT					X				X		X
SUPPLY AIR FAN VFD FAULT			X						X	X	X
SUPPLY AIR FAN FAULT CODE	X								X		X
HOA STATUS SWITCH			X						X		X
SUPPLY AIR SMOKE DETECTOR			X						X		X
SUPPLY AIR TEMPERATURE	X								X		X
SUPPLY AIR TEMPERATURE SETPOINT					X				X		X
SUPPLY AIR RH	X								X		X
SUPPLY AIR DEWPOINT					X				X		X
SUPPLY AIR DEWPOINT SETPOINT					X				X		X
SUPPLY AIRFLOW	X								X		X
SUPPLY AIRFLOW SETPOINT					X				X		X
HEATING STATUS			X						X		X
HEATING COMMAND				X					X		X
OUTSIDE AIR DAMPER		X							X		X
OUTSIDE AIR DAMPER POSITION	X								X		X
OUTSIDE AIR TEMPERATURE	X								X		X
OUTSIDE AIR RH	X								X		X
OUTSIDE AIR FILTER DIFFERENTIAL PRESSURE	X								X		X
HX BYPASS DAMPER		X							X		X
HX BYPASS DAMPER STATUS	X								X		X
RETURN AIR TEMPERATURE	X								X		X
RETURN AIR RH	X								X		X
RETURN AIRFLOW	X								X		X
RETURN AIR FILTER DIFFERENTIAL PRESSURE	X								X		X
ENTERING COIL AIR TEMPERATURE	X								X		X
ENTERING COIL RH	X								X		X
LEAVING COIL AIR TEMPERATURE	X								X		X
EXHAUST AIR TEMPERATURE	X								X		X
EXHAUST AIR RH	X								X		X
EXHAUST AIR DAMPER		X							X		X
EXHAUST AIR DAMPER STATUS	X								X		X

BARRACKS DOAS UNIT POINTS LIST

	HARDWARE POINTS				SOFTWARE POINTS						SHOW ON GRAPHIC
POINT NAME	AI	AO	BI	BO	AV	BV	LOOP	SCHED	TREND	ALARM	
UNIT ENABLE			X						X		X
EXHAUST AIR FAN STATUS			X						X		X
EXHAUST AIR FAN START/STOP				X					X		X
EXHAUST AIR FAN VFD FREQUENCY		X							X		X
EXHAUST AIR FAN FREQUENCY SETPOINT					X				X		X
EXHAUST AIR FAN VFD FAULT			X						X	X	X
EXHAUST AIR FAN FAULT CODE	X								X		X
COMPRESSOR 1 COMMAND		X							X		X
COMPRESSOR 1 STATUS	X								X		X
COMPRESSOR 2 COMMAND				X					X		X
COMPRESSOR 2 STATUS			X						X		X
HOT GAS REHEAT COMMAND		X							X		X
HOT GAS REHEAT STATUS	X								X		X
SUPPLY AIR FAN ALARM									X		X
EXHAUST AIR FAN ALARM									X		X
HIGH SUPPLY AIR TEMPERATURE									X	X	X
LOW SUPPLY AIR TEMPERATURE									X	X	X
HIGH SUPPLY AIR DEWPOINT									X	X	X
HIGH RETURN AIR TEMPERATURE									X	X	X
LOW RETURN AIR TEMPERATURE									X	X	X
HIGH RETURN AIR RH									X	X	X
COMPRESSOR 1 ALARM									X	X	X
COMPRESSOR 2 ALARM									X	X	X
OUTSIDE AIR DAMPER ALARM									X	X	X
EXHAUST AIR DAMPER ALARM									X	X	X
LOW SUPPLY AIRFLOW									X	X	X
HIGH SUPPLY AIRFLOW									X	X	X
LOW RETURN AIRFLOW									X	X	X
HIGH RETURN AIRFLOW									X	X	X
HIGH OA FILTER DIFFERENTIAL PRESSURE									X	X	X
HIGH RA FILTER DIFFERENTIAL PRESSURE									X	X	X
HX BYPASS DAMPER ALARM									X	X	X

2 BARRACKS DOAS POINTS LIST

NOT TO SCALE

FINAL
02-24-2026

M802

DEPARTMENT OF THE NAVY NAVAL FACILITIES ENGINEERING COMMAND
MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

DES. CJH
DR. CJH
CHK. CJM
SUBMITTED BY: CJM
DESIGN DIR. C. Maas, PE
APPROVED: PWO OR OICC DATE
SATISFACTORY TO: DATE

GEIGER QUAD G550
DOAS REPLACEMENT

MECHANICAL BARRACKS DOAS DDC POINTS

SIZE E1 | CODE IDENT. NO 80091 | NAVFAC DRAWING NO. 60042373
CONST. CONTR. N40085-25-B-0080
SCALE: NOTED | SPEC. 05-25-0080 | SHEET 6 OF 8

REVISIONS:



1 **ADMIN DOAS DDC CONTROL DIAGRAM**
NOT TO SCALE

FINAL
02-24-2026

M803

DEPARTMENT OF THE NAVY NAVAL FACILITIES ENGINEERING COMMAND
MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

DES.	CJH
DR.	CJH
CHK.	CJM
SUBMITTED BY:	CJM
DESIGN DIR.	C. Maas, PE
APPROVED: PWO OR OICC	DATE
SATISFACTORY TO:	DATE

GEIGER QUAD G550
DOAS REPLACEMENT

MECHANICAL ADMIN
DOAS DDC DIAGRAM

SIZE	CODE IDENT. NO	NAVFAC DRAWING NO.
E1	80091	60042374
		CONST. CONTR. N40085-25-B-0080
SCALE: NOTED	SPEC. 05-25-0080	SHEET 7 OF 8

REVISIONS:

ADMIN DOAS SEQUENCE OF OPERATIONS

A. GENERAL

1. PROGRAMS AND SEQUENCES INDICATED AND IMPLIED HEREIN SHALL BE PROVIDED.
2. PROVIDE ALL I/O POINTS INDICATED ON THE CONTROL DIAGRAM AND AS REQUIRED TO ACCOMPLISH THE SEQUENCE OF OPERATION.
3. THE VFD/MCC HOA SWITCH SHALL BE KEPT IN THE AUTO POSITION. HAND AND OFF POSITION SHALL BE UTILIZED FOR MAINTENANCE PURPOSES ONLY.
4. ALL POINTS SHALL BE ABLE TO INTEGRATE TO ALL TRENDS TOTALIZATIONS, GRAPHICS PAGES ETC., AS APPLICABLE.
5. ALL SETTINGS AND SETPOINTS SHALL BE USER ADJUSTABLE WITHOUT REQUIRING A MODIFICATION TO THE PROGRAMMING LOGIC CODE.
6. ALL ALARMS AS INDICATED ON THE DIAGRAMS IN THE SEQUENCE OF OPERATION SHALL BE GENERATED TO THE APPROPRIATE SERVER/WORKSTATIONS.

B. SETPOINTS:

1. SUPPLY AIR TEMPERATURE: 72.0°F
2. SUPPLY AIR DEWPOINT: 50.0°F

C. START/STOP/SCHEDULING:

1. THE DOAS OPERATES CONTINUOUSLY WITH REMOTE CAPABILITY FOR START/STOP/SCHEDULING FUNCTIONS.
   a. PROVIDE INDIVIDUAL, USER DEFINABLE SCHEDULES FOR OCCUPIED AND UNOCCUPIED TIME PERIODS.
   b. OCCUPANCY HOURS WILL BE 0600–1800.
2. WHEN AHU IS STARTED (MANUALLY OR AUTOMATICALLY):
   a. THE OUTSIDE AIR DAMPER (OAD) SHALL OPEN TO 100%. FAN SHALL BE ENERGIZED AFTER OAD IS PROVED OPEN.
3. WHEN DOAS IS STOPPED (EITHER MANUALLY, AUTOMATICALLY DURING UNOCCUPIED MODE, OR FROM SAFETY FUNCTION):
   a. THE SUPPLY FAN SHALL BE DE–ENERGIZED AND OAD CLOSED.

C. AIRFLOW CONTROL:

1. WHEN FAN STATUS INDICATES THE FAN HAS STARTED, THE FAN SHALL MODULATE TO MAINTAIN AIRFLOW SETPOINT USING PID CONTROL LOOP.

D. TEMPERATURE AND HUMIDITY CONTROL:

1. HEATING:
   a. IF THE SUPPLY AIR TEMPERATURE IS LESS THAN THE SUPPLY AIR TEMPERATURE SETPOINT AND THE SUPPLY AIR DEWPOINT IS LESS THAN 50°F, THE UNIT WILL ENABLE THE DX HEATING MODULATE CAPACITY TO MAINTAIN THE SUPPLY AIR TEMPERATURE SETPOINT.
   b. DURING DEFROST OR IF THE SUPPLY AIR SETPOINT CANNOT BE MAINTAINED, ENABLE THE EXISTING DUCT HEATER.
2. DEHUMIDIFICATION:
   a. IF THE SUPPLY AIR DEWPOINT IS GREATER THAN 50°F, THE UNIT WILL ENABLE THE DX COOLING AND REHEAT AND MODULATE CAPACITY TO MAINTAIN THE SUPPLY AIR TEMPERATURE AND DEWPOINT SETPOINT.
   b. IF THE SUPPLY AIR TEMPERATURE SETPOINT CANNOT BE MAINTAINED, ENABLE THE EXISTING DUCT HEATER.
3. COOLING:
   a. IF THE SUPPLY AIR TEMPERATURE IS GREATER THAN THE SUPPLY AIR TEMPERATURE SETPOINT AND THE SUPPLY AIR DEWPOINT IS LESS THAN 50°F, THE UNIT WILL ENABLE THE DX COOLING AND REHEAT AND MODULATE CAPACITY TO MAINTAIN THE SUPPLY AIR TEMPERATURE SETPOINT.
   b. IF THE SUPPLY AIR TEMPERATURE SETPOINT CANNOT BE MAINTAINED, ENABLE THE EXISTING DUCT HEATER.

E. ALARMS:

1. IF AFTER 60 SECOND DELAY (ADJ.), THE SUPPLY FAN DOES NOT PROVIDE STATUS OF ON, THE FAN WILL BE SHUT DOWN, THE OAD WILL CLOSE, AND AN ALARM WILL BE GENERATED. THE SYSTEM WILL RESTART AUTOMATICALLY WHEN FAULT CONDITIONS HAVE CLEARED.
2. GENERATE AN ALARM AT THE BAS IF THE DISCHARGE AIR TEMPERATURE EXCEEDS ±5°F (ADJ.) FROM SETPOINT FOR MORE THAN 30 MINUTES (ADJ.).
3. GENERATE AN ALARM AT THE BAS IF THE SUPPLY AIRFLOW IS ±10% (ADJ.) FROM SETPOINT FOR MORE THAN 30 MINUTES (ADJ.).
4. GENERATE AN ALARM AT THE BAS IF THE SUPPLY AIR DEWPOINT EXCEEDS +5°F (ADJ.) FROM SETPOINT FOR MORE THAN 30 MINUTES (ADJ.).
5. GENERATE AN ALARM AT THE BAS IF A DAMPER STATUS DOES NOT MATCH THE COMMAND.
6. GENERATE AN ALARM AT THE BAS UPON RECEIVING A SMOKE DETECTOR SIGNAL.
7. GENERATE AN ALARM AT THE BAS IF A COMPRESSOR STATUS DOES NOT MATCH THE COMMAND.
8. GENERATE AN ALARM AT THE BAS IF THE UNIT IS IN HAND.

F. SAFETY INTERLOCKS

1. PROVIDE ANTI–TERRORISM FORCE PROTECTION (ATFP) EMERGENCY SHUTDOWN BOTH HARDWIRED IN THE EQUIPMENT SAFETY CIRCUIT AND IN SOFTWARE FROM THE BAS. THE SHUTDOWN ACTIVATION SHALL LATCH AND REQUIRE MANUAL RESET. UPON ACTIVATION, THE UNIT SHALL:
   a. OUTSIDE AIR DAMPER SHALL CLOSE WITHIN 30 SECONDS.
   b. SUPPLY AIR FAN SHALL STOP.
2. INTEGRATE HARDWIRED SMOKE DETECTOR IN THE EQUIPMENT SAFETY CIRCUIT AND IN SOFTWARE FROM THE BAS. UPON ACTIVATION OF THE SMOKE DETECTOR, THE UNIT SHALL:
   a. OUTSIDE AIR DAMPER SHALL CLOSE.
   b. SUPPLY AIR FAN SHALL STOP.
   c. 3. INTERLOCK SUPPLY FAN WITH EXISTING DUCT HEATERS. DUCT HEATER MUST BE ENERGIZE UNLESS DESIGN SUPPLY AIRFLOW IS PROVEN.

1 **ADMIN DOAS SEQUENCE OF OPERATION**
NOT TO SCALE

ADMIN DOAS UNIT POINTS LIST

	HARDWARE POINTS				SOFTWARE POINTS						SHOW ON GRAPHIC
POINT NAME	AI	AO	BI	BO	AV	BV	LOOP	SCHED	TREND	ALARM	
SUPPLY AIR FAN STATUS			X						X		X
SUPPLY AIR FAN START/STOP				X					X		X
SUPPLY AIR FAN VFD FREQUENCY		X							X		X
SUPPLY AIR FAN VFD FREQUENCY SETPOINT					X				X		X
SUPPLY AIR FAN VFD FAULT			X						X	X	X
SUPPLY AIR FAN FAULT CODE	X								X		X
HOA STATUS SWITCH			X						X		X
SUPPLY AIR SMOKE DETECTOR			X						X		X
SUPPLY AIR TEMPERATURE	X								X		X
SUPPLY AIR TEMPERATURE SETPOINT					X				X		X
SUPPLY AIR RH	X								X		X
SUPPLY AIR DEWPOINT					X				X		X
SUPPLY AIR DEWPOINT SETPOINT					X				X		X
SUPPLY AIRFLOW	X								X		X
SUPPLY AIRFLOW SETPOINT					X				X		X
OUTSIDE AIR DAMPER		X							X		X
OUTSIDE AIR DAMPER POSITION	X								X		X
OUTSIDE AIR TEMPERATURE	X								X		X
OUTSIDE AIR RH	X								X		X
OUTSIDE AIR FILTER DIFFERENTIAL PRESSURE	X								X		X
LEAVING COIL AIR TEMPERATURE	X								X		X

ADMIN DOAS UNIT POINTS LIST

	HARDWARE POINTS				SOFTWARE POINTS						SHOW ON GRAPHIC
POINT NAME	AI	AO	BI	BO	AV	BV	LOOP	SCHED	TREND	ALARM	
UNIT ENABLE			X						X		X
COMPRESSOR 1 COMMAND		X							X		X
COMPRESSOR 1 STATUS	X								X		X
COMPRESSOR 2 COMMAND				X					X		X
COMPRESSOR 2 STATUS			X						X		X
HOT GAS REHEAT COMMAND		X							X		X
HOT GAS REHEAT STATUS	X								X		X
SUPPLY AIR FAN ALARM									X		X
HIGH SUPPLY AIR TEMPERATURE									X	X	X
LOW SUPPLY AIR TEMPERATURE									X	X	X
HIGH SUPPLY AIR DEWPOINT									X	X	X
COMPRESSOR 1 ALARM									X	X	X
COMPRESSOR 2 ALARM									X	X	X
OUTSIDE AIR DAMPER ALARM									X	X	X
LOW SUPPLY AIRFLOW									X	X	X
HIGH SUPPLY AIRFLOW									X	X	X
HIGH OA FILTER DIFFERENTIAL PRESSURE									X	X	X

2 **ADMIN DOAS POINTS LIST**
NOT TO SCALE

FINAL
02-24-2026

M804

DEPARTMENT OF THE NAVY NAVAL FACILITIES ENGINEERING COMMAND
MARINE CORPS BASE
CAMP LEJEUNE, NORTH CAROLINA

DES. CJH
DR. CJH
CHK. CJM
SUBMITTED BY: CJM
DESIGN DIR. C. Maas, PE
APPROVED: PWO OR OICC DATE
SATISFACTORY TO: DATE

GEIGER QUAD G550
DOAS REPLACEMENT

MECHANICAL ADMIN
DOAS DDC POINTS

SIZE E1
CODE IDENT. NO 80091
NAVFAC DRAWING NO. 60042375
CONST. CONTR. N40085-25-B-0080
SCALE: NOTED
SPEC. 05-25-0080