

38E9313601R

Ship/HULL NO. LSD-47	Ship/HULL NAME USS RUSHMORE	JON:	ICN: 38E9213601 38E9113601	Rev:	Key Op: A01
TITLE: Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace					

JOB SPECIFICATION

Anticipated Award Date: 8/13/2026	Production Completion Date: 2/12/2027	PREPARING ACTIVITY: SASEBO	
POP Start Date: 10/12/2026	POP End Date: 7/31/2027		
PREPARED BY: N.MATSUYA	CODE H MA	DATE 1/09/2024	
APPROVED BY: S.MURAKAMI	CODE S225		
CONCURRED BY: S.MOROOKA	CODE S231		
ASSIST PLANNER'S NAME:	CODE		
ASSIST PLANNER'S NAME:	CODE		
ASSIST PLANNER'S NAME:	CODE		
All pages of this documents will change ICN from 38E9213601 to 38E9313601 where written as shown on this cover sheet. All pages of this documents will change avail from 5C1 to 6G4 where written as shown on this cover sheet. 7C1 Y.M. 3/20/26 Y.Mori			
DESCRIPTION:			
JSN(S): OT01-0945		CASREP #	
S/F CONTACT: COUTUER CTT2 / OSC WARA		CWP #	CCNS #
S. JONES Project Manager, S320		6G4 7C1 Y.M. 3/20/26 Y.Mori	
Approved by S300/S900	Date: 1/11/24	Avl:	4J4
LWC:			
Work Completed			
S/Force:	Rate:	Date:	
Ship Supt:	Date:	SRF CONTROL NO.: 1301351810	
WORK CERTIFICATION SIGNATURES			
COMPLETION OF WORK REVIEW:	BADGE NO.:	SHOP/CODE:	PHONE: DATE:

Ship/HULL NO.	Ship/HULL NAME	JON:	ICN:	Rev:	Key Op:
LSD-47	USS RUSHMORE		38E9113601		A01

TITLE:

Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace

1. SCOPE:

1.1 Title: Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace

1.2 Location of Work:

- 1.2.1 Weather Deck 06 Level, Frames 32-59
- 1.2.2 Passage (05-29-0-L)
- 1.2.3 Passage (05-29-2-L)
- 1.2.4 Pressure Lock (05-30-2-L)
- 1.2.5 Pressure Lock (05-31-1-L)
- 1.2.6 Pressure Lock (05-31-2-L)
- 1.2.7 Passage (05-32-4-L)
- 1.2.8 Passage (05-35-1-L)
- 1.2.9 Passage (05-35-6-L)
- 1.2.10 Passage (05-39-6-L)
- 1.2.11 Passage (05-39-1-L)
- 1.2.12 Passage (05-39-4-L)
- 1.2.13 Passage (05-43-1-L)
- 1.2.14 Passage (05-43-2-L)
- 1.2.15 Passage (05-45-2-L)
- 1.2.16 Passage (05-48-1-L)
- 1.2.17 Passage (05-48-0-L)
- 1.2.18 Passage (05-52-3-L)
- 1.2.19 Passage (05-52-6-L)
- 1.2.20 Passage (05-56-4-L)
- 1.2.21 Light Trap (05-57-2-L)
- 1.2.22 Light Trap (05-57-3-L)
- 1.2.23 Senior Troop NCO Living Space (05-29-1-L)
- 1.2.24 CPO & Troop SH & Drying Area (05-34-1-L)
- 1.2.25 CG Locker (05-35-3-Q)

Ship/HULL NO.	Ship/HULL NAME	JON:	ICN:	Rev:	Key Op:
LSD-47	USS RUSHMORE		38E9113601		A01

TITLE:

Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace

- 1.2.26 CPO & Senior Troop NCO WR & WC (05-35-5-L)
- 1.2.27 CPO Living Space (05-38-1-L)
- 1.2.28 Crew Recreation RM & Lounge No.3 (05-48-3-L)
- 1.2.29 AMMO Elevator (2-48-1-T)
- 1.2.30 SCS UPS Room (05-50-1-Q)
- 1.2.31 Uptake (05-49-1-Q)
- 1.2.32 Troop Officer Bunk Room (05-29-2-L)
- 1.2.33 Troop Officer Bunk Room (05-32-2-L)
- 1.2.34 Troop Officer Bunk Room (05-32-6-L)
- 1.2.35 Troop Officer SH & Drying Area (05-35-10-L)
- 1.2.36 Troop Officer Bunk Room (05-35-8-L)
- 1.2.37 Troop Officer WR & WC (05-37-2-L)
- 1.2.38 Troop Officer Bunk Room (05-40-2-L)
- 1.2.39 Troop Officer Bunk Room (05-40-4-L)
- 1.2.40 Officer RCN Room (05-43-4-L)
- 1.2.41 Crew Library (05-43-6-Q)
- 1.2.42 Crew Living Space (05-49-4-L)
- 1.2.43 CIC (05-30-0-C)
- 1.2.44 Radar Room (05-35-0-C)
- 1.2.45 AN/SPS 49 MG Room (05-35-2-Q)
- 1.2.46 AN/SPS 49 CLG Equipment Room (05-35-4-Q)
- 1.2.47 Taclog Officer (05-39-0-Q)
- 1.2.48 Troop Admin Office (05-39-2-Q)
- 1.2.49 Crew Living Space (05-43-0-L)
- 1.2.50 Operations Dept Office (05-49-1-Q)
- 1.2.51 Line Locker (05-49-0-Q)
- 1.2.52 Secure Storage Room (05-50-0-A)
- 1.2.53 Fan Room (05-49-2-Q)
- 1.2.54 Electronic Shop (05-52-1-Q)
- 1.2.55 CG Locker (05-52-2-Q)

Ship/HULL NO.	Ship/HULL NAME	JON:	ICN: 38E9313601R	Rev:	Key Op:
LSD-47	USS RUSHMORE		38E9413601		A01

TITLE:

Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace

- 1.2.56 Crew SH & Drying Area (05-54-2-L)
- 1.2.57 Crew WR & WC (05-52-4-L)
- 1.2.58 Electronic Testing Equipment Storeroom (05-57-1-A)
- 1.2.59 Senior Troop NCO Living Space (05-56-2-L)
- 1.2.60 CPO/SNCO WC & SH (05-57-2-L)
- 1.2.61 CPO Living Space (05-57-4-L)
- 1.2.62 RAM Equipment Room (05-59-1-A)
- 1.2.63 RAM Handling Equipment Storeroom (05-59-0-A)
- 1.3 Identification:
 - 1.3.1 A Total of (5,841 SF) of Nonskid Deck Covering, Located in 1.2.1
 - 1.3.2 A Total of (1,525 SF) of Preservation on Deck Including Up to 24 Inch (Maximum Height) above Vertical Surface of Structure Member, Foundation, Deck Fitting, Deck Edge and Coaming, Located in 1.2.1
 - 1.3.3 A Total of (100 SF) of Deck Plate, Located in 1.2.1
 - 1.3.4 A Total of (25 LF) of Existing Seam and Butt, Located in 1.2.1
 - 1.3.5 A Total of (5 SF) of Pitted Surface, Located in 1.2.1

2. REFERENCES:

- FY25 27 Y.M. 3/20/26 Y.Mori
- 2.1 Standard Items (~~FY24~~)
- 2.2 139-6102538 Rev C, Unit 463 06 Deck FRS 31-42 S/S
- 2.3 139-6102536 Rev D, Unit 461 06 Deck FRS 42-53 S/S
- 2.4 635-6101907 Rev C, Insulation ARR Thermal & Acoustic 03 Level & Above
- 2.5 635-6101909 Rev D, Overhead Sheathing Layout
- 2.6 635-6101910 Rev B, Bulkhead and Overhead Sheathing DET
- 2.7 S9086-CH-STM-010/CH-074/V1/Rev 6, Welding and Allied Processes
- 2.8 S9086-DA-STM-010/CH-100/Rev 3, Hull Structures
- 2.9 T9074-AS-GIB-010/271 Rev-1, Requirements for Nondestructive Testing for Methods
- 2.10 S9086-VH-STM-010/CH-635/Rev 3, Thermal, Fire and Acoustic Insulation

Ship/HULL NO.	Ship/HULL NAME	JON:	ICN: 38E9113601	Rev:	Key Op: A01
LSD-47	USS RUSHMORE				

TITLE:

Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace

3. REQUIREMENTS:

(V) "REPORT"

3.1 Submit one legible copy of Marine Chemist certificate to SUPERVISOR including certified location.

3.2 Prior to commencement of any nonskid work, inspect each counter measure washdown nozzle and test each deck drain to ensure that each washdown nozzle and each drain is not clogged and damaged.

(V) "REPORT"

3.2.1 Submit one legible copy of a report listing results of the requirement of 3.2 to SUPERVISOR.

3.2.2 Remove each damaged and install (4) new counter measure washdown nozzles.

3.3 Remove each existing nonskid deck covering and coating from each area listed in 1.3.1 and 1.3.2 for visual inspection and UT thickness reading.

3.3.1 Accomplish a visual inspection of each exposed deck plating for deterioration, pitting, crack and damage of distortion for structural integrity to determine each repair area and repair recommendation, using Section 6 of 2.7, 100-2.8 of 2.8, and 2.2 through 2.6 for guidance.

(I) "UT THICKNESS READING"

3.3.1.1 Accomplish UT thickness reading of each expected reducing deck plating with ultrasonic thickness reading machine in accordance with Chapter 6 of 2.9 using 2.2 and 2.3 for guidance. **-Certified Contractor** (Estimated 450 points)

(V) "REPORT"

3.3.2 Submit one legible copy of a report listing the results of requirement of 3.3.1 and 3.3.1.1 to SUPERVISOR. This report must be submitted within the 20 percent of avail timeframe.

3.4 Accomplish the requirements for repair of each structure listed in 1.3.3 through 1.3.5 as follows determined by the visual inspection and UT thickness reading in 3.3.1 and 3.3.1.1 using Section 6 of 2.7, 100-2.8 of 2.8, and 2.2 through 2.6 for guidance.

3.4.1 Remove each damaged, fabricate and install each new deck plate listed in 1.3.3 out of each new 3/16 inch thick mild steel plate conforming to ASTM A36.

3.4.2 Vee out and weld each damaged welding seam and butt listed in 1.3.4.

3.4.3 Grind out and build up weld each pitted surface listed in 1.3.5.

Ship/HULL NO.	Ship/HULL NAME	JON:	ICN:	Rev:	Key Op:
LSD-47	USS RUSHMORE		38E9113604		A01

TITLE:

Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace

3.4.4 Accomplish the requirements of 009-12 of 2.1, including Table 2, Columns A and D Lines One through 7 for welding.

3.4.5 Accomplish the requirements of 009-25 of 2.1 for a local air hose test of each welded section of watertight boundary. Allowable leakage: None.

3.5 Accomplish the requirements of 009-32 of 2.1, including Table 2, Line 21, Columns A, B, C and E for each area listed in 1.3.1 and 1.3.2 using manufacturer's instructions for guidance.

3.5.1 Power tool clean each narrow area to SSPC-SP-11 where blast nozzle cannot reach.

3.5.1.1 Power tool clean each narrow area to SSPC-SP-3 where power tool in 3.5.1 cannot reach.

3.5.1.2 Hand tool clean each narrow area to SSPC-SP-2 where power tool in 3.5.1.1 cannot reach.

3.5.2 Apply each new marking on the nonskid surfaces using color topping.

3.6 Upon completion of the work, inspect each counter measure washdown nozzle and test each deck drain to ensure that each deck drain is not clogged.

3.7 Accomplish the requirements of 009-32 of 2.1 for cleaning and preservation of each new and disturbed surface to match surrounding areas.

3.7.1 A brush or spray may be used as a paint application for acoustic insulation in 635-7.2.4 of 2.10 as applicable.

4. NOTES:

4.1 Initial Condition - There are numerous cracks in nonskid located in 06 level weather deck (Between Frame 32 and 59).

4.2 SRF Tool room will issue pressure gauges, torque wrenches and depth gages when required.

5. GOVERNMENT FURNISHED MATERIAL (GFM) :

5.1 Government Furnished Materials.

MATERIAL LIST									
ITEM NO.	PC NO.	REF NO.	M / C	DESCRIPTION	STOCK NUMBER	HAZ MAT	DOC NO.	QTY /UNIT	Para No.
001			M	PLATE, METAL, 3/16" THK, 60IN X 20FT,	9B 9515 002375333	N	3362B001	2/PM	3.4

Ship/HULL NO.	Ship/HULL NAME	JON:	ICN: 38E9113601	Rev:	Key Op: A01
LSD-47	USS RUSHMORE				

TITLE:

Nonskid Deck Covering and Deck Plate at 06 Level Weather Deck; replace

MATERIAL LIST									
ITEM NO.	PC NO.	REF NO.	M / C	DESCRIPTION	STOCK NUMBER	HAZ MAT	DOC NO.	QTY /UNIT	Para No.
002			M	ELECTROD, WELDING, 7018M, 3/32"DIA X 14"L, MIL-E-22200/10, P/N: 255014102, 10LB/CN	9G 3439 SA4742861	N	4004E905	20/CN	3.4
003			M	ACOUSTIC BOARD, 2"THK, 2 FT X 3 FT, MIL-DTL-32585 TYPE II FORM 1, FACING C	9Q 5640 007565866	N	3362B002	6/BX	3.3 3.4
004			M	INSULATION BOARD, 2"THK, 2 FT X 3 FT, MIL-DTL-32585 TYPE I FORM 1, FACING B	9Q 5640 008096315	N	3362B003	4/BX	3.3 3.4
005			M	INSULATION BOARD, 1"THK, 2 FT X 3 FT, MIL-DTL-32585 TYPE I FORM 1, FACING B	9Q 5640 008096312	N	3362B004	6/BX	3.3 3.4
006			M	SNAP FASTENER, AL, CAP	9B 5325 007377648	N	3362B005	5/HD	3.3 3.4
007			M	TAPE, TEXTILE, 2"W X 50YD/RL, MIL-C-20079H TY-II	9B 8315 002671632	N	3362B006	20/RO	3.3 3.4
008			M	ADHESIVE, MIL-A-3316C, CL-1	9B 8040 002738708	Y	3361EX01	8/GL	3.3 3.4
009			M	PART KIT (CRES), COUNTERMEASURE WASHDOWN NOZZLE.	9B 4730 011717185	N	3362B009	10/EA	3.2 3.4