

Brand Name or Equal Worksheet (“Salient Characteristics”) v 2.0

593-26-102 Engineering Conf Rm High Performance Wall System

Brand Name or Equal Item: Faulkbuilt (High Performance Bldg System – Architectural Bldg System)

1) Essential/significant physical, functional, and/or performance characteristics.

2) Material – High Performance Bldg System

3) Building System General Requirements

- Building System shall be comprised of 16 ga steel split super stud equipped with 2 7/16” cavity width allowing for MEP components to be installed both horizontally and vertically inside cavity
- Building System shall be comprised of 16 ga steel split super stud with capability of 24’ wall height.
- Building System shall have the capability to extend to deck to achieve 1 hour fire rating
- Building System shall have the capability to extend into plenum space and incorporate drop ceiling mount to support ceiling grid and tiles to achieve superior acoustics
- Building System wall cavity shall accommodate and provide provisions for additional embedded elements (charting stations, way finding, security systems, touchless entry mechanism, millwork, plumbing fixtures, etc...)
- Building System shall have the capability to accept all door frame styles to include welded and knockdown
- Building System shall have the capability to achieve a solid wall STC rating of 53 or higher
- Building System shall provide a pre-engineered electrical system with hospital grade power for both critical and non-critical applications equipped with 25ft of HCF – MC power whip.
- Building System pre-engineered electrical system shall be UL listed.
- Building System shall come equipped with factory mounted rough in boxes for power, data, med gas and nurse call system.
- Building System shall provide factory cutouts in cladding to accommodate power, data, med gas and nurse call systems
- Building System wall cladding shall be 3/4” MDF with steel fastening system
- Building System shall have finished mitered wall ends and corners, eliminating the site of structural posts
- Building System wall cladding shall be finished with healthcare grade 3D laminate finish or UV cured finish process to ensure maximum durability for high traffic settings
- Building System wall cladding shall be resistant to staining, chipping and cracking omitting the need for additional wall protection
- Building System wall cladding shall be cleanable with healthcare grade disinfectants
- Building System shall provide a seamless installation designed to install up to 3 times faster than conventional construction
- Building System shall provide easy access to inside wall cavities for ease of MEP maintenance, adaptability, and a future proof facility

Brand Name or Equal Worksheet (“Salient Characteristics”) v 2.0

- Building System shall provide a clean installation process omitting the need to seal off areas from dust and debris
- Building System shall have the capability to contribute to LEED v4 - Building Design & Construction and Well v2 Preconditions and Optimizations
- Building System shall have a 3-week manufacturers lead time for standard components and materials
- Building System shall be designed utilizing cloud-based Revit software to allow seamless collaboration with the A+D community and real time visibility of complete workflow process.
- Building System shall be shipped as knock down components equipped with QR label for component visibility, project staging, installation and maintenance support throughout the life of the facility.
- Building System shall be shipped as knock-down components to ensure the most economical and sustainable shipping
- Building System shall have STC ratings at 44 for solid wall without insulation, and 53 with layer of insulation.
- Building System shall have limited 10-year warranty

4) Door

- Narrow Framed Glass Sliding Door with Soft Close/Soft
- Open mechanism with 3/8” tempered glass. Anodized aluminum finish. 24” brushed stainless non-locking bar pull.

5) Walls

- Height – 12’ 8” to 10’ -8”
 - Glass Wall 16 LF, 10’-0” High – Anodized finish, with ½” clear tempered glass and acoustic seals.
 - Solid Wall – 31 LF solid wall, 10’ – 0” – 12’ –6” H.
 - Total Linear Feet – 47’
 - Upper cladding to be scribed in field to match slope of existing ceiling.
 - Finish: 3D Laminate, Color to be coordinated with COR.
 - Each panel shall have integrated leveling devices with a base adjustability range of +/- 1/2 inch (13mm) and a head adjustability range of +/- 1 inch (25mm).
 - In general, solid panels shall provide an overall sound transmission class 53+ STC rating determined testing to ASTM E90 and classified in accordance with ASTM E413.
 - Framing, fixed glazed wall systems shall have a 36 STC rating. Minimum STC ratings will be evaluated on a project-by-project basis. Manufacturer shall be able to provide documentation regarding STC ratings for their products.
 - Walls to include all framing, blocking, wall base and finishes (cladding)
 - Walls shall include cutouts for power, data, light switches and thermostats.
 - Seismically braced to deck.
- 6) Sustainability: Product provided under this specification shall be at least 65% recyclable at the end of its useful life and be GREENGUARD, LEED + WELL certified as a low-emitting product that meets current indoor air quality standards.

Brand Name or Equal Worksheet (“Salient Characteristics”) v 2.0

7) The contractor shall perform all reconfiguration work at no additional cost to the owner using non-proprietary equipment and materials. The building system shall be designed for reconfiguration by the owner without additional cost or the need for licensed personnel. All systems and materials must allow for easy, industry-standard modifications. All materials and systems used must be non-proprietary, enabling easy modifications.

DRAFT