COST AND SOFTWARE DATA REPORTING PLAN

OMB No. 0704-0671

The public reporting burden for this collection of information is estimated to average 57 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Executive Services Directorate (0704-0671). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.
PLEASE DO NOT RETURN YOUR COMPLETED FORM TO THE ABOVE ORGANIZATION.

1a. PROGRAM NAME
KC-135 Center Console Refresh

1b. PHASE/MILESTONE *(check all that apply)*
- [ ] Pre-A
- [ ] A
- [X] B
- [ ] C-LRIP
- [ ] C-FRP
- [ ] O&S

1c. PRIME MISSION PRODUCT
KC-135 Center Console Refresh Development

1d. ACQUISITION CATEGORY (ACAT)
- [ ] Pre-ACAT
- [ ] ACAT I (MDAP)
- [ ] ACAT IA (MAIS)
- [X] ACAT II
- [ ] ACAT III
- [ ] Other

2. COMMODITY TYPE
Aircraft System

3. PLAN ITERATION TYPE
- [ ] INITIAL
- [X] REVISION

4. CURRENT SUBMISSION DATE *(YYYYMMDD)*
20251218

5. LAST APPROVED PLAN DATE *(YYYYMMDD)*
20230628

6a. GOVERNMENT PLAN POINT OF CONTACT (POC) NAME *(Last, First, M.)*
Shrader, Christopher, N.

6b. ADDRESS *(Include ZIP Code)*
3001 Staff Drive STE 2AE1-88G, Tinker AFB, OK 73145

6c. TELEPHONE NUMBER *(Include Area Code)*
256-285-0095

6d. E-MAIL ADDRESS
Christopher.shrader@us.af.mil

7. PLAN TYPE
- [ ] GOVERNMENT
- [X] CONTRACT (PRIME)
- [ ] CONTRACT (SUB)

8. PLAN GOVERNMENT PREPARING ORGANIZATION
AFLCMC/WLTMD

9a. CONTRACTOR NAME/ADDRESS
i. REPORTING ORGANIZATION NAME
TBD
ii. DIVISION NAME

iii. LOCATION

iv. CONTRACTOR BUSINESS DATA REPORT (CBDR 1921-3) REQUIREMENT:
- [X] CBDR REQUIRED FOR THIS ORGANIZATION

9b. CONTRACT NUMBER *(List all that apply, separated by commas)*
TBD - (AF-23-C1(R))

9c. APPROPRIATION *(check all that apply)*
- [X] RDT&E
- [X] PROCUREMENT
- [ ] O&M
- [ ] FMS
- [ ] WCF
- [ ] OTHER

10a. APPROVED PLAN NUMBER
AF-23-C1(R)

10b. APPROVED PLAN REVISION NUMBER
1

10c. APPROVED PLAN REQUIREMENTS
- [X] AT COMPLETION COSTS FOR STANDARD FUNCTIONAL CATEGORIES (FlexFile or Legacy)
- [X] AT COMPLETION COSTS FOR RECURRING/NONRECURRING (FlexFile only)
- [X] TECHNICAL DATA REQUIRED

10d. COST REPORT TYPE
- [X] FLEXFILE
- [ ] LEGACY DD 1921 SERIES

DRAFT

COST AND SOFTWARE DATA REPORTING PLAN

11. WORK BREAKDOWN STRUCTURE (WBS)			12. COST					13. TECHNICAL DATA			
								a. QUANTITY			
a. WBS CODE	b. WBS LEVEL	c. WBS ELEMENT NAME	a. ACTUALS TO DATE (ATD)	b. LEGACY 1921-1	c. LEGACY 1921-2	d. LEGACY 1921-3	e. EAC/FAC (See Item 15d)	i. QUANTITY DATA	ii. GFE QUANTITY	b. SRDR FORMAT8	c. MAINT. & REPAIR PARTS
1.0	1	KC-135 Center Console Refresh Development					X				
1.1	2	Aircraft System, Integration, Assembly, Test, and Checkout	X				X	X			
1.2	2	Air Vehicle					X	X			
1.2.1	3	Air Vehicle Integration, Assembly, Test, and Checkout					X	X			
1.2.1.1	4	Integration and Assembly	X				X	X			
1.2.1.2	4	Test and Checkout	X				X				
1.2.1.3	4	Rate Tooling	X				X				
1.2.2	3	Airframe					X	X			
1.2.2.1	4	Airframe Integration, Assembly, Test, and Checkout	X				X	X			
1.2.2.2	4	Fuselage					X	X			
1.2.2.2.1	5	Forward Fuselage	X				X	X			
1.2.2.2.2	5	Center Fuselage	X				X	X			
1.2.2.2.3	5	Aft Fuselage	X				X	X			
1.2.2.2.4	5	Other Fuselage (specify)	X				X	X			
1.2.2.3	4	Wing	X				X	X			
1.2.2.4	4	Empennage	X				X	X			
1.2.2.5	4	Nacelle	X				X	X			
1.2.2.6	4	Other Airframe Components 1..n (Specify)	X				X	X			
1.2.3	3	Propulsion	X				X	X			
1.2.4	3	Vehicle Subsystems					X	X			
1.2.4.1	4	Vehicle Subsystem Integration, Assembly, Test, and Checkout	X				X	X			
1.2.4.2	4	Flight Control Subsystem					X	X			
1.2.4.2.1	5	Flight Control Hardware Integration, Assembly, Test and Checkout	X				X	X			
1.2.4.2.2	5	Flight Control Hardware 1..n (Specify)	X				X	X			
1.2.4.2.3	5	Flight Control Software Release 1..n (Specify)	X				X				
1.2.4.3	4	Auxiliary Power Subsystem					X	X			
1.2.4.3.1	5	Auxiliary Power Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.4.3.2	5	Auxiliary Power Hardware 1..n (Specify)	X				X	X			
1.2.4.3.3	5	Auxiliary Power Software Release 1..n (Specify)	X				X				
1.2.4.4	4	Hydraulic Subsystem	X				X	X			
1.2.4.5	4	Electrical Subsystem					X	X			
1.2.4.5.1	5	Electrical Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.4.5.2	5	Electrical Hardware 1..n (Specify)	X				X	X			
1.2.4.5.3	5	Electrical Software Release 1..n (Specify)	X				X				
1.2.4.6	4	Crew Station Subsystem					X	X			
1.2.4.6.1	5	Crew Station Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.4.6.2	5	Canopy /Cockpit System	X				X	X			
1.2.4.6.3	5	Mechanical System	X				X	X			
1.2.4.6.4	5	Fire Protection System	X				X	X			
1.2.4.6.5	5	Crew Station Software Release 1..n (Specify)	X				X				
1.2.4.7	4	Environmental Control Subsystem	X				X	X			
1.2.4.8	4	Fuel Subsystem					X	X			
1.2.4.8.1	5	Fuel Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.4.8.2	5	Fuel Subsystem Hardware 1..n (Specify)	X				X	X			
1.2.4.8.3	5	Fuel Subsystem Software Release 1..n (Specify)	X				X				
1.2.4.9	4	Landing Gear	X				X	X			
1.2.4.10	4	Rotor Group	X				X	X			
1.2.4.11	4	Drive Group	X				X	X			
1.2.4.12	4	Vehicle Subsystem Software Release 1..n (Specify)	X				X				
1.2.4.13	4	Other Subsystems 1...n (Specify)					X	X			
1.2.4.13.1	5	Other Vehicle Subsystem Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.4.13.2	5	Other Vehicle Subsystem Hardware 1..n (Specify)	X				X	X			
1.2.4.13.3	5	Other Vehicle Subsystems Software Release 1..n (Specify)	X				X				
1.2.5	3	Avionics					X	X			
1.2.5.1	4	Avionics Integration, Assembly, Test And Checkout	X				X	X			
1.2.5.2	4	Communication/Identification					X	X			
1.2.5.2.1	5	Communication/Identification Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.5.2.2	5	Communication/Identification Hardware 1..n (Specify)	X				X	X			
1.2.5.2.3	5	Communication/Identification Software Release 1..n (Specify)	X				X				
1.2.5.3	4	Navigation/Guidance					X	X			
1.2.5.3.1	5	Navigation/Guidance Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.5.3.2	5	Navigation/Guidance Hardware 1..n (Specify)	X				X	X			
1.2.5.3.3	5	Navigation/Guidance Software Release 1..n (Specify)	X				X				
1.2.5.4	4	Mission Computer/Processing					X	X			
1.2.5.4.1	5	Mission Computer/Processing Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.5.4.2	5	Mission Computer/Processing Hardware 1..n (Specify)	X				X	X			
1.2.5.4.3	5	Mission Computer/Processing Software Release 1..n (Specify)	X				X				
1.2.5.5	4	Fire Control	X				X	X			
1.2.5.6	4	Data Display & Control					X	X			
1.2.5.6.1	5	Data Display and Control Hardware Integration, Assembly, Test And Checkout	X				X	X			
1.2.5.6.2	5	Data Display & Control Hardware 1..n (Specify)	X				X	X			
1.2.5.6.3	5	Data Display & Control Software Release 1..n (Specify)	X				X				
1.2.5.7	4	Survivability					X	X			
1.2.5.7.1	5	Survivability Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.5.7.2	5	Survivability Hardware 1..n (Specify)	X				X	X			
1.2.5.7.3	5	Survivability Software Release 1..n (Specify)	X				X				
1.2.5.8	4	Reconnaissance	X				X	X			
1.2.5.9	4	Electronic Warfare	X				X	X			
1.2.5.10	4	Automatic Flight Control					X	X			
1.2.5.10.1	5	Automatic Flight Control Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.5.10.2	5	Automatic Flight Control Hardware 1..n (Specify)	X				X	X			
1.2.5.10.3	5	Automatic Flight Control Software Release 1..n (Specify)	X				X				
1.2.5.11	4	Health Monitoring System	X				X	X			
1.2.5.11.1	5	Health Monitoring Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.5.11.2	5	Health Monitoring System Hardware 1..n (Specify)	X				X	X			
1.2.5.11.3	5	Health Monitoring System Software Release 1..n (Specify)	X				X				
1.2.5.12	4	Stores Management	X				X	X			
1.2.5.13	4	Avionics Software Release 1..n (Specify)	X				X				
1.2.5.14	4	Other Avionics Subsystems 1...n (Specify)					X	X			
1.2.5.14.1	5	Other Avionics Subsystem Hardware Integration, Assembly, Test, and Checkout	X				X	X			
1.2.5.14.2	5	Other Avionics Subsystem Hardware 1..n (Specify)	X				X	X			
1.2.5.14.3	5	Other Avionics Subsystem Software Release 1..n (Specify)	X				X				
1.2.6	3	Armament/Weapons Delivery	X				X	X			
1.2.7	3	Auxiliary Equipment	X				X	X			
1.2.8	3	Furnishings and Equipment	X				X	X			
1.2.9	3	Air Vehicle Software Release 1..n (Specify)	X				X				
1.2.10	3	Other Air Vehicle 1..n (Specify)	X				X	X			
1.3	2	Payload/Mission System	X				X	X			
1.4	2	Ground/Host Segment	X				X	X			
1.5	2	Aircraft System Software Release 1..n (Specify)	X				X				
1.6	2	Systems Engineering					X				
1.6.1	3	Software Systems Engineering	X				X				
1.6.2	3	Integrated Logistics Support (ILS) Systems Engineering	X				X				
1.6.3	3	Cybersecurity Systems Engineering	X				X				
1.6.4	3	Core Systems Engineering	X				X				
1.6.5	3	Other Systems Engineering 1...n (Specify)	X				X				
1.7	2	Program Management					X				
1.7.1	3	Software Program Management	X				X				
1.7.2	3	Integrated Logistics Support (ILS) Program Management	X				X				
1.7.3	3	Cybersecurity Management	X				X				
1.7.4	3	Core Program Management	X				X				
1.7.5	3	Other Program Management 1...n (Specify)	X				X				
1.8	2	System Test and Evaluation					X				
1.8.1	3	Development Test and Evaluation					X				
1.8.1.1	4	System Acceptance Test (SAT)	X				X				
1.8.1.2	4	Wind Tunnel	X				X				
1.8.1.3	4	Structural Test	X				X				
1.8.1.4	4	Flight Test	X				X				
1.8.1.5	4	Ground Test	X				X				
1.8.1.6	4	Cybersecurity Test and Evaluation					X				
1.8.1.6.1	5	Cybersecurity Developmental Test	X				X				
1.8.1.6.2	5	Cybersecurity Operational Test	X				X				
1.8.1.6.3	5	Cybersecurity Other (1...n)	X				X				
1.8.1.7	4	Service/Agency DT&E Tests 1...n (Specify) (GOV ONLY)	X				X				
1.8.1.8	4	Other DT&E Tests 1...n (Specify)	X				X				
1.8.2	3	Operational Test and Evaluation					X				
1.8.2.1	4	Limited User Evaluation (LUE/MALUFS/IE)	X				X				
1.8.2.2	4	Interoperability Testing (IOP/TIW/AVOTS)	X				X				
1.8.2.3	4	Flight Tests	X				X				
1.8.2.4	4	Ground Tests	X				X				
1.8.2.5	4	Cybersecurity Test and Evaluation					X				
1.8.2.5.1	5	Cybersecurity Developmental Test	X				X				
1.8.2.5.2	5	Cybersecurity Operational Test	X				X				
1.8.2.5.3	5	Cybersecurity Other (1...n)	X				X				
1.8.2.6	4	Other OT&E Tests 1...n (Specify)	X				X				
1.8.3	3	Live Fire Test and Evaluation	X				X				
1.8.4	3	Mock-ups/System Integration Labs (SILs)	X				X				
1.8.5	3	Test and Evaluation Support	X				X				
1.8.6	3	Test Facilities					X				
1.8.6.1	4	Commercial (GOV ONLY)	X				X				
1.8.6.2	4	Government (Pay-as-You-Go) (GOV ONLY)	X				X				
1.9	2	Training					X				
1.9.1	3	Equipment					X	X			
1.9.1.1	4	Operator Instructional Equipment	X				X	X			
1.9.1.2	4	Maintainer Instructional Equipment	X				X	X			
1.9.2	3	Services					X				
1.9.2.1	4	Operator Instructional Services					X				
1.9.2.1.1	5	Development of Training Materials	X				X				
1.9.2.1.2	5	Provide Training	X				X				
1.9.2.2	4	Maintainer Instructional Services					X				
1.9.2.2.1	5	Development of Training Materials	X				X				
1.9.2.2.2	5	Provide Training	X				X				
1.9.3	3	Facilities	X				X				
1.9.4	3	Training Software 1...n (Specify)	X				X				
1.10	2	Data					X				
1.10.1	3	Data Deliverables 1...n (Specify)	X				X				
1.10.2	3	Data Repository	X				X				
1.10.3	3	Data Rights 1...n (Specify)	X				X				
1.11	2	Peculiar Support Equipment					X	X			
1.11.1	3	Test and Measurement Equipment	X				X	X			
1.11.2	3	Support and Handling Equipment	X				X	X			
1.12	2	Common Support Equipment					X	X			
1.12.1	3	Test and Measurement Equipment	X				X	X			
1.12.2	3	Support and Handling Equipment	X				X	X			
1.13	2	Operational/Site Activation by Site 1...n (Specify)					X				
1.13.1	3	System Assembly, Installation and Checkout on Site					X				
1.13.1.1	4	Deployment Hardware and Software	X				X				
1.13.1.2	4	Site Activation	X				X				
1.13.2	3	Contractor Technical Support	X				X				
1.13.3	3	Site Construction	X				X				
1.13.4	3	Site/Ship/Vehicle Conversion	X				X				
1.13.5	3	Interim Contractor Support (ICS)	X				X				
1.14	2	Contractor Logistics Support (CLS)	X				X				
1.15	2	Industrial Facilities	X				X				
1.16	2	Initial Spares and Repair Parts					X	X			
1.16.1	3	PMP Spare and Repair 1...n (Specify)	X				X	X			
1.16.2	3	Support Equipment Spare and Repair Parts	X				X	X			
1.16.3	3	Training Equipment Spare and Repair Parts	X				X	X			
1.16.4	3	Packaging, Handling, Storage, and Transportation (PHS&T)	X				X	X			
1.16.4.1	4	Containers	X				X	X			
1.16.4.2	4	Transportation	X				X	X			
		Subtotal Cost	X				X				
		Reporting Contractor G&A	X				X				
		Reporting Contractor Undistributed Budget	X				X				
		Reporting Contractor Management Reserve	X				X				
		Reporting Contractor FCCM	X				X				
		Total Cost	X				X				
		Reporting Contractor Profit/Loss or Fee	X				X				
		Total Price	X				X				

COST AND SOFTWARE DATA REPORTING PLAN

14. CSDR SUBMISSION EVENTS

a. EVENT ID	b. DATA REPORT(S)	c. SUBMISSION EVENT NAME	d. REPORT CYCLE	e. AS OF DATE (YYYYMMDD)	f. DUE DATE (YYYYMMDD)
1	Cost and Hour Report (FlexFile), Quantity Data Report	Contract Award Cost Report	Initial	20271231	20280229
2	Technical Data Report	Contract Award Tech Report	Initial	20271231	20280229
3	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #1	Interim	20281231	20290228
4	Technical Data Report	Annual Tech Report #1	Interim	20281231	20290228
5	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #2	Interim	20291231	20300228
6	Technical Data Report	Annual Tech Report #2	Interim	20291231	20300228
7	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #3	Interim	20301231	20310228
8	Technical Data Report	Annual Tech Report #3	Interim	20301231	20310228
9	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #4	Interim	20311231	20320229
10	Technical Data Report	Annual Tech Report #4	Interim	20311231	20320229
11	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #5	Interim	20321231	20330228
12	Technical Data Report	Annual Tech Report #5	Interim	20321231	20330228
13	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #6	Interim	20331231	20340228
14	Technical Data Report	Annual Tech Report #6	Interim	20331231	20340228
15	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #7	Interim	20341231	20350228
16	Technical Data Report	Annual Tech Report #7	Interim	20341231	20350228
17	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #8	Interim	20351231	20360229
18	Technical Data Report	Annual Tech Report #8	Interim	20351231	20360229
19	Cost and Hour Report (FlexFile), Quantity Data Report	Annual Cost Report #9	Interim	20361231	20370228
20	Technical Data Report	Annual Tech Report #9	Interim	20361231	20370228
21	Cost and Hour Report (FlexFile), Quantity Data Report	Contract Completion (60 days before)	Final	20371231	20380228
22	Technical Data Report	Contract Completion (60 days before)	Final	20371231	20380228

DRAFT

COST AND SOFTWARE DATA REPORTING PLAN

15. REMARKS

A. In addition to the direction provided in the associated CSDR Data Item Descriptions (DIDs) and the CSDR Manual (DoDM 5000.04), the following instructions, requirements, and considerations found on this page/worksheet shall be utilized when collecting data and preparing CSDR submissions. This CSDR Contract plan is intended to capture costs associated with the contract number(s) listed in block 9.b, irrespective of contract type (e.g., firm-fixed price, cost-plus fixed fee) or CLIN structure, including Over and Above, Advance Procurement, Long Lead Materials, Multiyear Procurement, Inter-Division or Inter-Company Work Orders (IWOs), Foreign Military Sales (FMS), Warranty, etc.

B. CSDR PLAN REMARKS & PREPARATION INSTRUCTIONS

1. Costs reported against this CSDR plan shall be cumulative in nature (i.e., each submission shall report any and all costs incurred on and prior to the submission's "AS OF DATE" (block 14.e)).

i. WBS Element Names (block 11.c) Ending with "1...n (Contractor Shall Specify)": The contractor shall extend and specify (i.e., include additional WBS elements determined by the contractor) in order to provide additional insight into the contractor's technical approach or design. The additional WBS elements shall be developed in accordance with the WBS guidelines included in MIL-STD-881F (or latest version).

ii. The contractor may extend any WBS element in accordance with guidelines included in MIL-STD-881F (or latest version). Any changes to WBS, Order/Lot, End Item, and/or Period of Performance must be reported to the government prior to submission or immediately, with revised CSDR Plan, must be approved by the CSDR Plan approval authority.

C. SUBMISSION EVENTS & DATES

1. Deliverable Preparation Instructions by AS OF and DUE Dates: All CSDR deliverable "AS OF DATE[S]" and "DUE DATE[S]" listed in blocks 14.e and 14.f are identified for planning purposes only. Submission dates are subject to change and are determined in accordance with the event drivers as identified below:

i. All "DUE DATE" requirements are equal to the "AS OF DATE" plus 60 calendar days. If the calculated "DUE DATE" does not fall on a regular business day, the "DUE DATE" will be the next regular business day on the contractor's accounting calendar.

ii. "Final" Submission Events must meet both of the following two conditions: Condition 1: The final end item(s) has been delivered and accepted by the government (e.g., as evidenced by a completed DD-250) or higher tier contractor in the case of a subcontractor, and Condition 2: 95% or more of all ATD costs associated with the Subtotal, G&A and FCCOM have been incurred relative to all costs the reporting entity expects to incur for each and every Order/Lot (defined in Item 4 of Data Group B) associated with the contract Subtotal, G&A, FCCOM and UB.

iii. If the Contract period of performance is extended by more than six months, or if the scope of work is modified to include work not otherwise covered by the CSDR Plan, the government may modify the CSDR Plan to require additional submission events and add additional WBS elements in order to ensure the accurate and complete collection of cost data associated with the modified contract.

D. COST & HOUR REPORT (FLEXFILE)

1. The Reporting Entity is required to provide unit reporting for any given Order/Lot and End Item as outlined in block 18 of the DD Form 2794.

2. The checkmarks for EAC/FAC in column 12e at the WBS level shall be reported as "Forecast at Completion" (FAC). The Forecast At Completion (FAC) required here is not subject to the standards established in ANSI/EIA-748 guideline #27 (Estimate at Complete); therefore, the FAC does not need to be, but may be, derived from Industry Earned Value Management (EVM) processes.

3. WBS Definitions & Remarks (Data Group C) must match the technical content, cost content, and work content of each end item (see Block 17) for all WBS elements for each Cost and Hour (FlexFile) submission. The WBS Definitions & Remarks shall contain a disclosure statement detailing any differences between the CSDR reporting methodology and the reporting entity's Cost Accounting Standards. WBS Definitions & Remarks shall include a section detailing how parts are procured under this contract and any limitations of the parts procurement cost data or allocation of cost data for the WBS element.

4. The reporting entity must maintain and update WBS Definitions & Remarks throughout the life of the contract, IAW DI-FNCL-82162, if changes to the WBS occur, the reporting entity shall annotate and track changes by adding the "As of Date" of the submitted FlexFile report and indicate the changes to the WBS Definitions.

5. Order/Lot: Block 16 Orders/Lots is meant to capture the discrete Delivery Orders/Task Orders exercised on the contract. If a Delivery Order/Task Order is exercised on the contract and the CSDR plan has not been updated, it is the Reporting Entity's responsibility to still submit the dollars and hours in the FlexFile tagged to the appropriate Delivery Orders/Task Orders. The CSDR plan will be revised accordingly to include all exercised Delivery Orders/Task Orders.

6. End Items: Block 17 of this CSDR Plan is meant to capture the discrete hardware end items that are DD-250'ed, ordered, procured, or exercised (as applicable) on the contract. If an End Item is DD-250'ed, ordered, procured, or exercised (as applicable) on the contract but is not listed in block 17, the contractor shall submit the dollars and hours in the Cost and Hour Report (FlexFile) and the quantity information in the Quantity Report tagged using the name of the End Item utilized on the contract. The CSDR Plan will be updated to include the appropriate End Item name in block 17, after report submission, if required.

i. The "Common" end item tag shall be used to report costs and hours which are not incurred or directly attributable to an individual end item. For example, overarching program management costs and hours that are required, independent of the type or quantity of end items on contract would be tagged against the "Common" end item. Common hardware (i.e., identical/homogeneous part numbers) procured and integrated into multiple end items shall utilize the end item tag for the prime product they were integrated onto and shall not be tagged with the "Common" end item.

7. The contractor shall utilize and include the following mappings from its accounting system to the Actual Cost-Hour Data tags:

i. {To be determined during the CSDR Readiness Review based on contractor's accounting system} = Tag1

ii. {To be determined during the CSDR Readiness Review based on contractor's accounting system} = Tag2

iii. {To be determined during the CSDR Readiness Review based on contractor's accounting system} = Tag3

E. QUANTITY DATA REPORT

1. If the quantity for a given element differs from the quantity reported for the full system, provide a comment in the WBS Element Remarks section.

2. The Reporting Entity shall provide meaningful quantity information lower than the summary level in the remarks for hardware-related content across the following WBS elements: Peculiar Support Equipment, Common Support Equipment, and Initial Spares and Repair Parts, if applicable.

F. TECHNICAL DATA REPORT

1. Include only UNCLASSIFIED/CUI information in Technical Data Report deliverables submitted to CADE. Notify the Government if any values associated with the Technical Parameter Requirements are classified.

G. RESOURCE DISTRIBUTION TABLE (RDT)

1. Submissions of the Resource Distribution Table (RDT) are required under the following conditions:

i. An RDT shall be delivered no later than seven calendar days before the "CSDR Readiness Review". Prepare this submission of the RDT in accordance with the RDT Instructions on the CADE website at FAC/EAC value.This copy of the RDT will be used during the "CSDR Readiness Review" in order to identify which subcontractors will be required to provide CSDR reporting via electronic submission of deliverables directly to CADE and which subcontractors may qualify for a CSDR direct reporting subcontractor waiver.

ii. The contractor must notify the government program office immediately of the contractor identifying that a subcontractor who, at the time of initial subcontractor award, was not anticipated to qualify for direct subcontractor CSDR reporting via electronic submission of deliverables directly to CADE but is subsequently anticipated to meet the CSDR direct reporting subcontractor threshold value due to changes to scope of work, end-item design, subcontractor/supplier, or subcontract price changes since initial contract award (unless the newly identified subcontractor has already been issued a subcontractor reporting waiver associated with this contract).

H. CONTRACTOR BUSINESS DATA REPORT (1921-3)

1. The Contractor Business Data Report is prepared by and for the business entity (e.g., business unit, segment, or site) responsible for submitting the Forward Pricing Rate Proposal (FPRP) representing the basis for Forward Pricing Rate Agreement (FPRA) negotiations with the government.

2. Reports are submitted annually at the end of the contractor's fiscal year.

3. Data for Future Years should be reflective of the number of years contained in the most current document, i.e., the FPRP or the FPRA.If the document applies to more than three future years, attach additional future year sheets as required. In the absence of these documents, estimates should be provided for three future years.

I. RELATIONSHIP/USE OF COST ACCOUNTING STANDARDS (CAS) **DELETE if CAS is not applicable**

1. The contractor shall follow the accounting procedures specified in its latest approved CAS Disclosure Statement and with any clauses or requirements included in the contract. As part of the CSDR Readiness Review, the contractor shall identify any aspect(s) of its latest approved CAS Disclosure Statement which preclude or inhibit compliance with this CSDR Plan. The contractor shall identify any deviations from its CAS disclosure statement it intends to utilize to prepare CSDR submissions.

2. The contractor shall provide a description of significant accounting systems or CAS changes and how those changes effect the latest CSDR deliverable or the ability to compare CSDR deliverables provided before/after the accounting system/CAS revision. The contractor shall provide the description within the submission remarks of the FlexFile deliverable.

J. CSDR READINESS REVIEW

1. The contractor shall host a CSDR-RR with the Government's Cost Working Group Integrated Product Team (CWIPT) IAW DFARS 242.503-2(b) and DoD Manual 5000.04 (CSDR Manual). The purpose of the CSDR-RR is to review the contract's CSDR requirements and assess how the Contractor's accounting system satisfies the CSDR requirements found in DODM 5000.04 and this CSDR Plan. Reference the CADE website for instructions and additional information: https://cade.osd.mil/csdrreportingguidance/dd2794.html

2. The contractor and CWIPT will also review the initial submission of the "Resource Distribution Table (RDT)", in order to finalize which subcontractors will be required to provide CSDR reporting and electronic submission of deliverables directly to Cost Assessment Data Enterprise (CADE), and which subcontractors may qualify for a CSDR direct reporting subcontractor waiver.

3. The CSDR-RR shall be held within 60 days of contract award or the start of work meeting on a date mutually agreed to by the CWIPT and the contractor.

DRAFT

COST AND SOFTWARE DATA REPORTING PLAN

INTRA-CONTRACT SCOPE REPORTING DEFINITION

16. ORDERS/LOTS

a. ID	b. NAME	c. PHASE/MILESTONE
1	TBD Contract Number	B

17. END ITEMS

a. ID	b. NAME
1	Prototype 1 - A Kits
2	Prototype 1 - B Kits
3	Prototype 2 - A Kits
4	Prototype 2 - B Kits
5	Common

18. UNIT/SUBLOT REPORTING AND UNIT SEQUENCING REQUIREMENTS

a. ORDER/LOT ID	b. END ITEM ID	c. UNIT/SUBLOT REPORTING *(X if applicable)*	d. UNIT SEQUENCING *(X if applicable)*
1	1	X	X
1	2	X	X
1	3	X	X
1	4	X	X

DRAFT

COST AND SOFTWARE DATA REPORTING PLAN - TECHNICAL PARAMETER REQUIREMENTS								
TECHNICAL PARAMETER REQUIREMENTS								
29. WBS ELEMENT CODE	30. WBS ELEMENT NAME	31. ITEM TYPE	32. TECHNICAL PARAMETER					
			a. PARAMETER	b. UNIT OF MEASURE	c. UNIT OF MEASURE	d. REPEATABLE	e. DEFINITION	f. REMARKS
1.2.1	Air Vehicle Integration, Assembly, Test, and Checkout	Heritage	New Design	Percent			The extent of the item's design that is new on a 0-100% scale as follows: 0% - 10% Existing design. May include previously qualified units, build-to-print units, and units with minimal changes from a prior unit. TRL is expected to be high (e.g. TRL 9) in this range. 10% - 40% Minor design changes. May include minor design changes due to component swap out for obsolescence and minor enhancements for producibility - TRL is expected to be high (e.g. TRL 8-9) in this range. 40% - 60% Moderate design changes. Based on prior design. May include problematic parts obsolescence (e.g. forced design changes or new vendor) as well as downstream impacts. Unlikely to include any significant changes to form, fit, or function (see below). TRL is may be moderately high in this range (e.g. TRL 7-8). 60% - 90% Mostly new design or major redesign. This range suggests a significant design effort. More than 50% of the item by weight is modified and will typically undergo some form of qualification testing. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. Usually includes changes to form, Fit, or function. Parts obsolescence and downstream impacts may be more severe in this range. TRL may be in the 6-7 range. 90% - 100% Complete new design. Minimal design heritage. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. TRL may be 8 or lower. Other considerations include: General characteristics * Difficulty or complexity of requirements (e.g., uniqueness of program, stringency of specs, challenge
1.2.1	Air Vehicle Integration, Assembly, Test, and Checkout	Heritage	Predecessor	Descriptor			The year of the predecessor system
1.2.1	Air Vehicle Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.1	Air Vehicle Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.4	Vehicle Subsystems	Heritage	New Design	Percent			The extent of the item's design that is new on a 0-100% scale as follows: 0% - 10% Existing design. May include previously qualified units, build-to-print units, and units with minimal changes From a prior unit. TRL is expected to be high (e.g. TRL 9) in this range. 10% - 40% Minor design changes. May include minor design changes due to component swap out For obsolescence and minor enhancements for producibility - TRL is expected to be high (e.g. TRL 8-9) in this range. 40% - 60% Moderate design changes. Based on prior design. May include problematic parts obsolescence (e.g. forced design changes or new v endor) as well as downstream impacts. Unlikely to include any significant changes to form, Fit, or function (see below). TRL is may be moderately high in this range (e.g. TRL 7-8). 60% - 90% Mostly new design or major redesign. This range suggests a significant design effort. More than 50% of the item by weight is modified and will typically undergo some form of qualification testing. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. Usually includes changes to form, Fit, or function. Parts obsolescence and downstream impacts may be more severe in this range. TRL may be in the 6-7 range. 90% - 100% Complete new design. Minimal design heritage. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. TRL may be 8 or lower. Other considerations include: General characteristics * Difficulty or complexity of requirements (e.g., uniqueness of program, stringency of specs, challenge
1.2.4	Vehicle Subsystems	Heritage	Predecessor	Descriptor			The year of the predecessor system
1.2.4.1	Vehicle Subsystem Integration, Assembly, Test, and Checkout	Heritage	New Design	Percent			The extent of the item's design that is new on a 0-100% scale as follows: 0% - 10% Existing design. May include previously qualified units, build-to-print units, and units with minimal changes From a prior unit. TRL is expected to be high (e.g. TRL 9) in this range. 10% - 40% Minor design changes. May include minor design changes due to component swap out For obsolescence and minor enhancements for producibility - TRL is expected to be high (e.g. TRL 8-9) in this range. 40% - 60% Moderate design changes. Based on prior design. May include problematic parts obsolescence (e.g. forced design changes or new v endor) as well as downstream impacts. Unlikely to include any significant changes to form, Fit, or function (see below). TRL is may be moderately high in this range (e.g. TRL 7-8). 60% - 90% Mostly new design or major redesign. This range suggests a significant design effort. More than 50% of the item by weight is modified and will typically undergo some form of qualification testing. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. Usually includes changes to form, Fit, or function. Parts obsolescence and downstream impacts may be more severe in this range. TRL may be in the 6-7 range. 90% - 100% Complete new design. Minimal design heritage. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. TRL may be 8 or lower. Other considerations include: General characteristics * Difficulty or complexity of requirements (e.g., uniqueness of program, stringency of specs, challenge
1.2.4.1	Vehicle Subsystem Integration, Assembly, Test, and Checkout	Heritage	Predecessor	Descriptor			The year of the predecessor system
1.2.4.1	Vehicle Subsystem Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.4.1	Vehicle Subsystem Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.4.5.1	Electrical Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.4.5.1	Electrical Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Total Weight	Material Name	Y	List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
1.2.4.5.2	Electrical Hardware 1..n (Specify)	PhysicalStruc	Volume	Cubic Inches			Physical volume of the item.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	PhysicalStruc	Weight	Pounds			Physical weight of the item.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Power - Subsystem	Watts			The Primary Power's Power Subsystem Total Power.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Power - Subsystem	Watts			The Primary Power's Power Subsystem Peak Power.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Power - Supply Performance	Seconds			The Primary Power's Power Supply Performance Period.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Power - Supply Average	Volts			The Primary Power's Power Supply Average Voltage.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Volume of Electrical Power	Cubic Inches			The volume of the electrical power system in cubic inches
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Number of Power Supply Inputs - Alternating	Quantity	Inputs		The Primary Power's Number of AC Power Supply Inputs.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Number of Power Supply Inputs - Direct	Quantity	Inputs		The Primary Power's Number of DC Power Supply Inputs.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Number of Power Supply Outputs - Direct	Quantity	Outputs		The Primary Power's Number of DC Power Supply Outputs.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Type of Power	List			Choice List: (1) DC (2) AC
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Type of Battery	List			The Primary Power's Electrical Power And Networks Battery
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Power	Number of Stages Covered	Quantity	Stages		Number of Stages Covered (for missiles, ICBMs, and Launch Vehicles)
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Battery	Battery Capacity	Ampere Hours			Measure of the charge stored by the battery, and is determined by the mass of active material contained in the battery. The battery capacity represents the maximum amount of energy that can be extracted from the battery
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Battery	Output Voltage	Volts			The output voltage is the voltage released by a device. For batteries, use the nominal/reported/reference voltage.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Battery	Type of Battery	List			Type of battery used to power battery (e.g. Silver Zinc, Silver Oxide, Li-ion Polymer, etc.).
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Battery	Number of Battery Cells	Quantity			Number of cells per battery
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Computer	Simultaneous Multi-Mode Operation	List			Simultaneous mode operation refers to the concurrent processing and interleaving of multiple modes. Choice List: if system requires interleaving of multiple modes.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Computer	Processor Type	Descriptor			Description of the processor used in the server, including manufacturer, version number, etc.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	Computer	Computing Performance	Millions of Instructions per Second			The number of MIPS (million instructions per second) is a general measure of computing performance and, by implication, the amount of work a larger computer can do. For large servers or mainframes, MIPS is a way to measure the cost of computing: the more MIPS deliv-ered for the money,
1.2.4.5.2	Electrical Hardware 1..n (Specify)	ElecBox	Circuit Cards - Number of	Quantity			Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
1.2.4.5.2	Electrical Hardware 1..n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs		Number of Application Specific Integrated Circuit (ASIC) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.4.5.2	Electrical Hardware 1..n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs		Number of Field Programmable Gate Array (FPGA) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.4.6.1	Crew Station Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.4.6.1	Crew Station Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.4.6.2	Canopy /Cockpit System	PhysicalOther	Material Mix 1...n	Percent of Total Weight	Material Name	Y	List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
1.2.4.6.2	Canopy /Cockpit System	PhysicalStruc	Volume	Cubic Inches			Physical volume of the item.
1.2.4.6.2	Canopy /Cockpit System	PhysicalStruc	Weight	Pounds			Physical weight of the item.
1.2.4.8.1	Fuel Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.4.8.1	Fuel Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.4.8.2	Fuel Subsystem Hardware 1..n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Total Weight	Material Name	Y	List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
1.2.4.8.2	Fuel Subsystem Hardware 1..n (Specify)	PhysicalStruc	Volume	Cubic Inches			Physical volume of the item.
1.2.4.8.2	Fuel Subsystem Hardware 1..n (Specify)	PhysicalStruc	Weight	Pounds			Physical weight of the item.
1.2.4.8.2	Fuel Subsystem Hardware 1..n (Specify)	FuelSystem	Fuel Capacity	Gallons			The total amount of fuel that the vehicle is capable of carrying in its fuel tank/cell (not including any fuel the vehicle may be carrying for the sole purpose of
1.2.4.13.1	Other Vehicle Subsystem Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.4.13.1	Other Vehicle Subsystem Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Total Weight	Material Name	Y	List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	PhysicalStruc	Volume	Cubic Inches			Physical volume of the item.
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	PhysicalStruc	Weight	Pounds			Physical weight of the item.
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	Computer	Simultaneous Multi-Mode Operation	List			Simultaneous mode operation refers to the concurrent processing and interleaving of multiple modes. Choice List: if system requires interleaving of multiple modes.
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	Computer	Processor Type	Descriptor			Description of the processor used in the server, including manufacturer, version number, etc.
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	Computer	Computing Performance	Millions of Instructions per Second			The number of MIPS (million instructions per second) is a general measure of computing performance and, by implication, the amount of work a larger computer can do. For large servers or mainframes, MIPS is a way to measure the cost of computing: the more MIPS deliv-ered for the money,
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	ElecBox	Circuit Cards - Number of	Quantity			Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs		Number of Application Specific Integrated Circuit (ASIC) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.4.13.2	Other Vehicle Subsystem Hardware 1..n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs		Number of Field Programmable Gate Array (FPGA) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.5	Avionics	Heritage	New Design	Percent			The extent of the item's design that is new on a 0-100% scale as follows: 0% - 10% Existing design. May include previously qualified units, build-to-print units, and units with minimal changes from a prior unit. TRL is expected to be high (e.g. TRL 9) in this range. 10% - 40% Minor design changes. May include minor design changes due to component swap out for obsolescence and minor enhancements for producibility - TRL is expected to be high (e.g. TRL 8-9) in this range. 40% - 60% Moderate design changes. Based on prior design. May include problematic parts obsolescence (e.g. forced design changes or new vendor) as well as downstream impacts. Unlikely to include any significant changes to form, fit, or function (see below). TRL is may be moderately high in this range (e.g. TRL 7-8). 60% - 90% Mostly new design or major redesign. This range suggests a significant design effort. More than 50% of the item by weight is modified and will typically undergo some form of qualification testing. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. Usually includes changes to form, Fit, or function. Parts obsolescence and downstream impacts may be more severe in this range. TRL may be in the 6-7 range. 90% - 100% Complete new design. Minimal design heritage. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. TRL may be 8 or lower. Other considerations include: General characteristics * Difficulty or complexity of requirements (e.g. uniqueness of program, stringency of specs, challenge
1.2.5	Avionics	Heritage	Predecessor	Descriptor			The year of the predecessor system
1.2.5.1	Avionics Integration, Assembly, Test And Checkout	Heritage	New Design	Percent			The extent of the item's design that is new on a 0-100% scale as follows: 0% - 10% Existing design. May include previously qualified units, build-to-print units, and units with minimal changes from a prior unit. TRL is expected to be high (e.g. TRL 9) in this range. 10% - 40% Minor design changes. May include minor design changes due to component swap out for obsolescence and minor enhancements for producibility - TRL is expected to be high (e.g. TRL 8-9) in this range. 40% - 60% Moderate design changes. Based on prior design. May include problematic parts obsolescence (e.g. forced design changes or new v endor) as well as downstream impacts. Unlikely to include any significant changes to form, fit, or function (see below). TRL is may be moderately high in this range (e.g. TRL 7-8). 60% - 90% Mostly new design or major redesign. This range suggests a significant design effort. More than 50% of the item by weight is modified and will typically undergo some form of qualification testing. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. Usually includes changes to form, Fit, or function. Parts obsolescence and downstream impacts may be more severe in this range. TRL may be in the 6-7 range. 90% - 100% Complete new design. Minimal design heritage. Typically includes dev-elopment and testing of engineering, prototype, or qualification models. TRL may be 8 or lower. Other considerations include: General characteristics * Difficulty or complexity of requirements (e.g. uniqueness of program, stringency of specs, challenge
1.2.5.1	Avionics Integration, Assembly, Test And Checkout	Heritage	Predecessor	Descriptor			The year of the predecessor system
1.2.5.1	Avionics Integration, Assembly, Test And Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.5.1	Avionics Integration, Assembly, Test And Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.5.2.1	Communication/Identification Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.5.2.1	Communication/Identification Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Total Weight	Material Name	Y	List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	PhysicalStruc	Volume	Cubic Inches			Physical volume of the item.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	PhysicalStruc	Weight	Pounds			Physical weight of the item.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Computer	Simultaneous Multi-Mode Operation	List			Simultaneous mode operation refers to the concurrent processing and interleaving of multiple modes. Choice List: if system requires interleaving of multiple modes.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Computer	Processor Type	Descriptor			Description of the processor used in the server, including manufacturer, version number, etc.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Computer	Computing Performance	Millions of Instructions per Second			The number of MIPS (million instructions per second) is a general measure of computing performance and, by implication, the amount of work a larger computer can do. For large servers or mainframes, MIPS is a way to measure the cost of computing: the more MIPS deliv-ered for the money,
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	ElecBox	Circuit Cards - Number of	Quantity			Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs		Number of Application Specific Integrated Circuit (ASIC) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs		Number of Field Programmable Gate Array (FPGA) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	AmpliFier	Peak Output Power	Watts			The maximum instantaneous output power of which the amplifier is capable.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	AmpliFier	Av-erage Output Power	Watts			The av-erage (ov-er the complete wav-eform) output power of which the amplifier is capable.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	AmpliFier	Frequency - Maximum	Megahertz			The maximum operating Frequency .
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	AmpliFier	Frequency - Minimum	Megahertz			The minimum operating Frequency.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	AmpliFier	AmpliFier Efficiency	Percent			The amplifier efficiency percentage. Efficiency is a measure of how much of the power source is usefully applied to the
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Frequency Band	List			Denotes the band type. Band types include bands such as
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Frequency Range	Megahertz			Denotes the primary frequency range of the antenna. The frequency range of the RF, microwav-e or other radio signals that the antenna is designed to efficiently collect or radiate. Frequency is the number of cy-cles per second or hertz that the radio signals or electromagnetic wav-e oscillates at.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Aperture - Antenna	Inches			Denotes the aperture by it's diameter. The aperture is the antenna dross section.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Number of Sub Arrays	Quantity	Per Antenna Face		Denotes the Total Number of subarrays per Antenna Face. The antenna array consists of many radiating elements whose output RF energy is phase controlled to steer the RF output beam. It consists of a structural item that supports the elements, a feed system, output radiators, power supplies, and beam steering unit (processor). A Sub Array is
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Tunable Bandwidth	Gigahertz			A tunable bandwidth is the difference between the highest and lowest tunable frequency the antenna can support.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Type of Steering	List			Denotes if the Radar is: (1) Electronically Scanned Array or (2) Mechanically Scanned or (3) Other
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Pattern Type	List			List: 1) Omnidirectional Antenna is an antenna that has a radiation pattern that is nondirectional in azimuth; 2) A Directional Antenna is any antenna that is not
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Technology Type	Descriptor			Denotes the antenna type. Examples include Whip, Dipole, Slotted Waveguide, Horn, Dish/Reflector, Phased Array, etc.
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Operational Mode	List			Choice List: (1) Active (Transmit and Receiv-e) or (2) Passive (Receiv-e-only)
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	Antenna	Bandwidth	Gigahertz	Instantaneous		The instantaneous bandwidth is the baseband frequency extent for the widest transmitted wav-eform the antenna can
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	TransReceiv-R/F	Transmitter Power Output -	Watts			The Peak Transmitter Power Output
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	TransReceiv-R/F	Transmitter Power Output -	Watts			The Av-erage Transmitter Power Output
1.2.5.2.2	Communication/Identification Hardware 1..n (Specify)	TransReceiv-R/F	Bandwidth	Megahertz			The width of the band of frequencies occupied by the central lobe of the spectrum of an alternating current signal. Bandwidth is the difference between the upper and lower cut-
1.2.5.3.1	Navigation/Guidance Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.
1.2.5.3.1	Navigation/Guidance Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Mechanical Connections	Quantity	Mechanical Connections		The number of mating surfaces, fasteners, or other non-electrical attach points at the level of assembly.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Total Weight	Material Name	Y	List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	PhysicalStruc	Volume	Cubic Inches			Physical volume of the item.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	PhysicalStruc	Weight	Pounds			Physical weight of the item.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Computer	Simultaneous Multi-Mode Operation	List			Simultaneous mode operation refers to the concurrent processing and interleaving of multiple modes. Choice List: if system requires interleaving of multiple modes.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Computer	Processor Type	Descriptor			Description of the processor used in the server, including manufacturer, version number, etc.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Computer	Computing Performance	Millions of Instructions per Second			The number of MIPS (million instructions per second) is a general measure of computing performance and, by implication, the amount of work a larger computer can do. For large servers or mainframes, MIPS is a way to measure the cost of computing: the more MIPS deliv-ered for the money,
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	ElecBox	Circuit Cards - Number of	Quantity			Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs		Number of Application Specific Integrated Circuit (ASIC) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs		Number of Field Programmable Gate Array (FPGA) (unspecified type) designs required - See HW Tech Table - SRU.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	AmpliFier	Peak Output Power	Watts			The maximum instantaneous output power of which the amplifier is capable.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	AmpliFier	Av-erage Output Power	Watts			The av-erage (ov-er the complete wav-eform) output power of which the amplifier is capable.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	AmpliFier	Frequency - Maximum	Megahertz			The maximum operating Frequency .
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	AmpliFier	Frequency - Minimum	Megahertz			The minimum operating Frequency.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	AmpliFier	AmpliFier Efficiency	Percent			The amplifier efficiency percentage. Efficiency is a measure of how much of the power source is usefully applied to the
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Frequency Band	List			Denotes the band type. Band types include bands such as
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Frequency Range	Megahertz			Denotes the primary frequency range of the antenna. The frequency range of the RF, microwav-e or other radio signals that the antenna is designed to efficiently collect or radiate. Frequency is the number of cy-cles per second or hertz that the radio signals or electromagnetic wav-e oscillates at.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Aperture - Antenna	Inches			Denotes the aperture by it's diameter. The aperture is the antenna dross section.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Number of Sub Arrays	Quantity	Per Antenna Face		Denotes the Total Number of subarrays per Antenna Face. The antenna array consists of many radiating elements whose output RF energy is phase controlled to steer the RF output beam. It consists of a structural item that supports the elements, a feed system, output radiators, power supplies, and beam steering unit (processor). A Sub Array is
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Tunable Bandwidth	Gigahertz			A tunable bandwidth is the difference between the highest and lowest tunable frequency the antenna can support.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Type of Steering	List			Denotes if the Radar is: (1) Electronically Scanned Array or (2) Mechanically Scanned or (3) Other
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Pattern Type	List			List: 1) Omnidirectional Antenna is an antenna that has a radiation pattern that is nondirectional in azimuth; 2) A Directional Antenna is any antenna that is not
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Technology Type	Descriptor			Denotes the antenna type. Examples include Whip, Dipole, Slotted Waveguide, Horn, Dish/Reflector, Phased Array, etc.
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Operational Mode	List			Choice List: (1) Active (Transmit and Receiv-e) or (2) Passive (Receiv-e-only)
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	Antenna	Bandwidth	Gigahertz	Instantaneous		The instantaneous bandwidth is the baseband frequency extent for the widest transmitted wav-eform the antenna can
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	TransReceiv-R/F	Transmitter Power Output -	Watts			The Peak Transmitter Power Output
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	TransReceiv-R/F	Transmitter Power Output -	Watts			The Av-erage Transmitter Power Output
1.2.5.3.2	Navigation/Guidance Hardware 1..n (Specify)	TransReceiv-R/F	Bandwidth	Megahertz			The width of the band of frequencies occupied by the central lobe of the spectrum of an alternating current signal. Bandwidth is the difference between the upper and lower cut-
1.2.5.4.1	Mission Computer/Processing Hardware Integration, Assembly, Test, and Checkout	IAT&CO	Number of Electrical	Quantity	Electrical Connections		The number of electrical and electronic connections at this level of assembly.

DRAFT

I.2.5.4.1	Mission Computer/Processing Hardware Integration, Assembly, Test, and Checkout	IAT⅋CO	Number of Mechanical Connections	Quantity	Mechanical Connections			The number of mating surfaces, f asteners, or other non-electrical attach points at the lev el of assembly.
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Weight	Total Material Name	Y		List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	PhysicalStruc	Volume	Cubic Inches				Physical volume of the item.
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	PhysicalStruc	Weight	Pounds				Physical weight of the item.
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	Computer	Simultaneous Multi-Mode Operation	List				Simultaneous mode operation refers to the concurrent processing and interleaving of multiple modes. Choice List: if system requires interleaving of multiple modes.
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	Computer	Processor Type	Descriptor				Description of the processor used in the server, including manufacturer, version number, etc.
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	Computer	Computing Performance	Millions of Instructions per Second				The number of MIPS (million instructions per second) is a general measure of computing performance and, by implication, the amount of work a larger computer can do. For large servers or mainf rames, MIPS is a way to measure the cost of computing: the more MIPS deliv ered for the money,
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	ElecBox	Circuit Cards - Number of	Quantity				Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs			Number of Application Specific Integrated Circuit (ASIC) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.4.2	Mission Computer/Processing Hardware 1...n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs			Number of Field Programmable Gate Array (FPGA) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.6.1	Data Display and Control Hardware Integration, Assembly, Test And Checkout	IAT⅋CO	Number of Electrical	Quantity	Electrical Connections			The number of electrical and electronic connections at this lev el of assembly.
I.2.5.6.1	Data Display and Control Hardware Integration, Assembly, Test And Checkout	IAT⅋CO	Number of Mechanical Connections	Quantity	Mechanical Connections			The number of mating surfaces, f asteners, or other non-electrical attach points at the lev el of assembly.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Weight	Total Material Name	Y		List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	PhysicalStruc	Volume	Cubic Inches				Physical volume of the item.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	PhysicalStruc	Weight	Pounds				Physical weight of the item.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Computer	Simultaneous Multi-Mode Operation	List				Simultaneous mode operation refers to the concurrent processing and interleaving of multiple modes. Choice List: if system requires interleaving of multiple modes.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Computer	Processor Type	Descriptor				Description of the processor used in the server, including manufacturer, version number, etc.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Computer	Computing Performance	Millions of Instructions per Second				The number of MIPS (million instructions per second) is a general measure of computing performance and, by implication, the amount of work a larger computer can do. For large servers or mainf rames, MIPS is a way to measure the cost of computing: the more MIPS deliv ered for the money,
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	ElecBox	Circuit Cards - Number of	Quantity				Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs			Number of Application Specific Integrated Circuit (ASIC) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs			Number of Field Programmable Gate Array (FPGA) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Display	Type of Display	List				Type of display on data display and control equipment
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Display	Size of monitor (diagonal)	Inches				The size of the monitor diagonal. Physical size of the display
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Display	Height	Inches				The height of the item.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Display	Applicable TSOs	Descriptor				Specifies which sy stems the MFD interfaces with, such as Airborne Weather Radar, TrafFic Alert & Collision Av oidance, TrafFic Adv isory Sy stem, Flight Information Sy stem – Broadcast, Temperature Instruments, Air Data Computer.
I.2.5.6.2	Data Display & Control Hardware 1...n (Specify)	Display	Civil Airspace Access	List				Denotes if item willbe used to support civil airspace access functions
I.2.5.7.1	Surv iv ability Hardware Integration, Assembly, Test, and Checkout	IAT⅋CO	Number of Electrical	Quantity	Electrical Connections			The number of electrical and electronic connections at this lev el of assembly.
I.2.5.7.1	Surv iv ability Hardware Integration, Assembly, Test, and Checkout	IAT⅋CO	Number of Mechanical Connections	Quantity	Mechanical Connections			The number of mating surfaces, f asteners, or other non-electrical attach points at the lev el of assembly.
I.2.5.7.2	Surv iv ability Hardware 1...n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Weight	Total Material Name	Y		List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
I.2.5.7.2	Surv iv ability Hardware 1...n (Specify)	PhysicalStruc	Volume	Cubic Inches				Physical volume of the item.
I.2.5.7.2	Surv iv ability Hardware 1...n (Specify)	PhysicalStruc	Weight	Pounds				Physical weight of the item.
I.2.5.7.2	Surv iv ability Hardware 1...n (Specify)	ElecBox	Circuit Cards - Number of	Quantity				Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
I.2.5.7.2	Surv iv ability Hardware 1...n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs			Number of Application Specific Integrated Circuit (ASIC) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.7.2	Surv iv ability Hardware 1...n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs			Number of Field Programmable Gate Array (FPGA) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.7.2	Surv iv ability Hardware 1...n (Specify)	Countermeasure s	Range - Maximum	Kilometers				Maximum ground distance v ehicle, sitage, or deploy ed countermeasure is capable of trav eling. Note: The range of a missile is essentially determined by the v elocity it reaches when all its propellant has been used up (its burnout
I.2.5.11.1	Health Monitoring Hardware Integration, Assembly, Test, and Checkout	IAT⅋CO	Number of Electrical	Quantity	Electrical Connections			The number of electrical and electronic connections at this lev el of assembly.
I.2.5.11.1	Health Monitoring Hardware Integration, Assembly, Test, and Checkout	IAT⅋CO	Number of Mechanical Connections	Quantity	Mechanical Connections			The number of mating surfaces, f asteners, or other non-electrical attach points at the lev el of assembly.
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Weight	Total Material Name	Y		List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	PhysicalStruc	Volume	Cubic Inches				Physical volume of the item.
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	PhysicalStruc	Weight	Pounds				Physical weight of the item.
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	Computer	Simultaneous Multi-Mode Operation	List				Simultaneous mode operation refers to the concurrent processing and interleaving of multiple modes. Choice List: if system requires interleaving of multiple modes.
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	Computer	Processor Type	Descriptor				Description of the processor used in the server, including manufacturer, version number, etc.
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	Computer	Computing Performance	Millions of Instructions per Second				The number of MIPS (million instructions per second) is a general measure of computing performance and, by implication, the amount of work a larger computer can do. For large servers or mainf rames, MIPS is a way to measure the cost of computing: the more MIPS deliv ered for the money,
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	ElecBox	Circuit Cards - Number of	Quantity				Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs			Number of Application Specific Integrated Circuit (ASIC) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.11.2	Health Monitoring Sy stem Hardware 1...n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs			Number of Field Programmable Gate Array (FPGA) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.14.1	Other Av ionics Subsy stem Hardware Integration, Assembly, Test, and Checkout	IAT⅋CO	Number of Electrical	Quantity	Electrical Connections			The number of electrical and electronic connections at this lev el of assembly.
I.2.5.14.1	Other Av ionics Subsy stem Hardware Integration, Assembly, Test, and Checkout	IAT⅋CO	Number of Mechanical Connections	Quantity	Mechanical Connections			The number of mating surfaces, f asteners, or other non-electrical attach points at the lev el of assembly.
I.2.5.14.2	Other Av ionics Subsy stem Hardware 1...n (Specify)	PhysicalOther	Material Mix 1...n	Percent of Weight	Total Material Name	Y		List of primary materials comprising the item by percent of total weight. (Cite one or more materials as applicable)
I.2.5.14.2	Other Av ionics Subsy stem Hardware 1...n (Specify)	PhysicalStruc	Volume	Cubic Inches				Physical volume of the item.
I.2.5.14.2	Other Av ionics Subsy stem Hardware 1...n (Specify)	PhysicalStruc	Weight	Pounds				Physical weight of the item.
I.2.5.14.2	Other Av ionics Subsy stem Hardware 1...n (Specify)	ElecBox	Circuit Cards - Number of	Quantity				Also referred to as Printed circuit boards. The IPC preferred term for assembled boards is circuit card assembly (CCA). Total Number of printed circuit boards (PCBs) in item. This includes all boards designed, modified, purchased or provided
I.2.5.14.2	Other Av ionics Subsy stem Hardware 1...n (Specify)	ElecBox	Application Specific Integrated	Quantity	ASICs			Number of Application Specific Integrated Circuit (ASIC) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.5.14.2	Other Av ionics Subsy stem Hardware 1...n (Specify)	ElecBox	Field Programmable Gate Array	Quantity	FPGAs			Number of Field Programmable Gate Array (FPGA) (unspecified ty pe) designs required - See HW Tech Table - SRU.
I.2.10	Other Air Vehicle 1...n (Specify)	Heritage	New Design	Percent				The extent of the item's design that is new on a 0-100% scale as follows: 0% - 10% Existing design. May include previously qualified minor modifications. Typically, the item is drawn directly from a prior unit. TRL is expected to be high (e.g., TRL 9) in this range. 10% - 40% Minor design changes. May include minor design changes due to component sweep out for obsolescence and minor enhancements for producibility. TRL is expected to be high (e.g. TRL 8-9) in this range. 40% - 60% Moderate design changes. Based on prior design. May include problematic parts obsolescence (e.g. forced design changes or new v endor) as well as downstream impacts. Unlikely to include any significant changes to f orm, f it, or function (see below). TRL is may be moderately high in this range (e.g. TRL 7-8). 60% - 90% Mostly new design or major redesign. This range suggests a signif icant design effort. More than 50% of the item by weight is modified and will typically undergo some form of qualification testing. Typically includes dev elopment and testing of engineering, prototy pe, or qualification models. Usually includes changes to form, f it, or function (see below). Interfaces with other components may be more sev ere in this range. TRL may be in the 6-7 range. 90% - 100% Complete new design. Minimal design heritage. Typically includes dev elopment and testing of engineering, prototy pe, or qualification models. TRL may be 5 or lower. Other considerations include: General characteristics " Difficulty or complexity of requirements (e.g. uniqueness of program, stringency of specs, challenge
I.2.10	Other Air Vehicle 1...n (Specify)	Heritage	Predecessor	Descriptor				The y ear of the predecessor sy stem
I.6	Systems Engineering	SysEng	Number of Requirement Document -	Quantity	Shalls	YG		The number of requirements cited in the sy stem's requirements documents.
I.6	Systems Engineering	SysEng	Number of Platforms -	Quantity	Platforms			The number of platf orms (e.g. aircraf t) on which the sy stem will be qualified
I.7	Program Management	ProgMgmt	Frequency of Gov ernment Program	Quantity	Reviews per Year			The Frequency of Gov ernment Program Rev iews in the contract.
I.7	Program Management	ProgMgmt	Number of Contract Line Item Number	Quantity	CLINs			The number of Contract CLINs in the contract.
I.7	Program Management	ProgMgmt	Number of Subcontractors	Quantity	Subcontractors			The number of major subcontractors/suppliers in the program.
I.7	Program Management	ProgMgmt	Number of Customer Stakeholders	Quantity	Stakeholders			The number of customers and stakeholders that may require management accommodation. Stakeholders consist of any group or organization with a related or subsequent responsibility that is directly related to the outcome of an action or result. Generally speaking they can influance the outcome or are the recipient of the results. The range of personnel selected to participate as stakeholders is based on the complexity of the program. Typical "end user" stakeholders are : users or operators, acquisition community,
I.8.4	Mock-ups/Sy stem Integration Labs (SILs)	SIL	Modeling Type	List		YG		Describes the ty pes of modeling to be performed by the SIL
I.8.4	Mock-ups/Sy stem Integration Labs (SILs)	SIL	Mock-up / SIL - Square Feet	Square Feet	by Facility / Suite	YG		Facility area measured in square f eet.
I.8.4	Mock-ups/Sy stem Integration Labs (SILs)	SIL	Mock-up / SIL - Primary Function	List		YG		Describes the SIL's primary purpose.
I.9.1.1	Operator Instructional Equipment	TrainDevice	Training Device Name	Descriptor	Training Device Name	YG		Training equipment name.
I.9.1.1	Operator Instructional Equipment	TrainDevice	Training Device Quantity	Quantity	Devices	YG		Training equipment quantity. Note: Describe Annual Quantity by Location in Time Phased Quantity Table
I.9.1.1	Operator Instructional Equipment	TrainDevice	Training Device Description	Descriptor		YG		Description of training devices
I.9.1.2	Maintainer Instructional Equipment	TrainDevice	Training Device Name	Descriptor	Training Device Name	YG		Training equipment name.
I.9.1.2	Maintainer Instructional Equipment	TrainDevice	Training Device Quantity	Quantity	Devices	YG		Training equipment quantity. Note: Describe Annual Quantity by Location in Time Phased Quantity Table
I.9.1.2	Maintainer Instructional Equipment	TrainDevice	Training Device Description	Descriptor		YG		Description of training devices
I.9.3	Facilities	ConstrConv	Facility Name	Descriptor				The Facility name.
I.9.3	Facilities	ConstrConv	Facility Description	Descriptor				Describes each facility and quantify to the extent possible in terms of square f eet, number of installations, power, etc.
I.9.3	Facilities	ConstrConv	New product alteration square footage	Feet				New product alteration square f ootage
I.10.1	Data Deliv erables 1...n (Specify)	Data	Data Rights Category	List				Category of Data Rights Purchased
I.10.2	Data Repository	DataDepository	Storage	Square Feet	Data storage size			The area required for data storage.
I.10.3	Data Rights 1...n (Specify)	Data	Data Rights Category	List				Category of Data Rights Purchased
I.11.1	Test and Measurement Equipment	SupportEquipme nt	Quantity of Support	Quantity	Support Equipment			Total number of support equipment used on the program
I.11.1	Test and Measurement Equipment	SupportEquipme nt	Number of Support Equipment	Quantity	Locations			Number of locations support equipment is utilized
I.11.1	Test and Measurement Equipment	SupportEquipme nt	Support Equipment	Descriptor				List of all locations support equipment is utilized.
I.11.1	Test and Measurement Equipment	SupportEquipme nt	Support and Handling Device Name	Descriptor	Support and Handling Device Name	YG		Support and Handling Dev ice equipment name.
I.11.1	Test and Measurement Equipment	SupportEquipme nt	Support and Handling Device Description	Descriptor	Devices	YG		Describes the Support and Handling Dev ice equipment
I.11.2	Support and Handling Equipment	SupportEquipme nt	Quantity of Support	Quantity	Support Equipment			Total number of support equipment used on the program
I.11.2	Support and Handling Equipment	SupportEquipme nt	Number of Support Equipment	Quantity	Locations			Number of locations support equipment is utilized
I.11.2	Support and Handling Equipment	SupportEquipme nt	Support Equipment	Descriptor				List of all locations support equipment is utilized.
I.11.2	Support and Handling Equipment	SupportEquipme nt	Support and Handling Device Name	Descriptor	Support and Handling Device Name	YG		Support and Handling Dev ice equipment name.
I.11.2	Support and Handling Equipment	SupportEquipme nt	Support and Handling Device Description	Descriptor	Devices	YG		Describes the Support and Handling Dev ice equipment
I.12.1	Test and Measurement Equipment	SupportEquipme nt	Quantity of Support	Quantity	Support Equipment			Total number of support equipment used on the program
I.12.1	Test and Measurement Equipment	SupportEquipme nt	Number of Support Equipment	Quantity	Locations			Number of locations support equipment is utilized
I.12.1	Test and Measurement Equipment	SupportEquipme nt	Support Equipment	Descriptor				List of all locations support equipment is utilized.
I.12.1	Test and Measurement Equipment	SupportEquipme nt	Support and Handling Device Name	Descriptor	Support and Handling Device Name	YG		Support and Handling Dev ice equipment name.
I.12.1	Test and Measurement Equipment	SupportEquipme nt	Support and Handling Device Description	Descriptor	Devices	YG		Describes the Support and Handling Dev ice equipment
I.12.2	Support and Handling Equipment	SupportEquipme nt	Quantity of Support	Quantity	Support Equipment			Total number of support equipment used on the program
I.12.2	Support and Handling Equipment	SupportEquipme nt	Number of Support Equipment	Quantity	Locations			Number of locations support equipment is utilized
I.12.2	Support and Handling Equipment	SupportEquipme nt	Support Equipment	Descriptor				List of all locations support equipment is utilized.
I.12.2	Support and Handling Equipment	SupportEquipme nt	Support and Handling Device Name	Descriptor	Support and Handling Device Name	YG		Support and Handling Dev ice equipment name.
I.12.2	Support and Handling Equipment	SupportEquipme nt	Support and Handling Device Description	Descriptor	Devices	YG		Describes the Support and Handling Dev ice equipment

DRAFT

COST AND SOFTWARE DATA REPORTING PLAN - TECHNICAL PARAMETER REQUIREMENTS		
33. TECHNICAL PARAMETER REQUIREMENTS (LIST ITEMS)		
a. ITEM TYPE	b. PARAMETER NAME	c. LIST ITEMS
Antenna	Frequency Band	L band (1 to 2 GHz)
Antenna	Frequency Band	S band (2 to 4 GHz)
Antenna	Frequency Band	C band (4 to 8 GHz)
Antenna	Frequency Band	X band (8 to 12 GHz)
Antenna	Frequency Band	Ku band (12 to 18 GHz)
Antenna	Frequency Band	K band (18 to 27 GHz)
Antenna	Frequency Band	Ka band (27 to 40 GHz)
Antenna	Frequency Band	V band (40 to 75 GHz)
Antenna	Frequency Band	W band (75 to 110 GHz)
Antenna	Frequency Band	Other
Antenna	Type of Steering	Electronically Scanned
Antenna	Type of Steering	Mechanically Scanned
Antenna	Type of Steering	Other
Antenna	Pattern Type	Omnidirectional
Antenna	Pattern Type	Not Omnidirectional
Antenna	Pattern Type	Other
Antenna	Operational Mode	Active
Antenna	Operational Mode	Passive
Battery	Type of Battery	Nickel-Cadmium (NiCd)
Battery	Type of Battery	Lithium-Ion (Li-ion)
Battery	Type of Battery	Nickel-Hydrogen (NiH2)
Battery	Type of Battery	Silver Zinc
Battery	Type of Battery	Silver Oxide
Battery	Type of Battery	Li-Ion Polymer
Battery	Type of Battery	Other
Computer	Simultaneous Multi-Mode Operation	Yes
Computer	Simultaneous Multi-Mode Operation	No
Data	Data Rights Category	Unlimited Rights
Data	Data Rights Category	Government Purpose Rights
Data	Data Rights Category	Limited Rights
Data	Data Rights Category	Restricted Rights
Data	Data Rights Category	Negotiated License Rights
Data	Data Rights Category	SBIR Data Rights
Data	Data Rights Category	Commercial Technical Data License Rights
Data	Data Rights Category	Commercial Computer Software Licenses
Display	Civil Airspace Access Functions	Yes
Display	Civil Airspace Access Functions	No
Guidance/Ctrl/Avionics	Type of Battery	Nickel-Cadmium (NiCd)
Guidance/Ctrl/Avionics	Type of Battery	Lithium-Ion (Li-ion)
Guidance/Ctrl/Avionics	Type of Battery	Nickel-Hydrogen (NiH2)
Guidance/Ctrl/Avionics	Type of Battery	Silver Zinc
Guidance/Ctrl/Avionics	Type of Battery	Silver Oxide
Guidance/Ctrl/Avionics	Type of Battery	Li-Ion Polymer
Guidance/Ctrl/Avionics	Type of Battery	Other
Power	Type of Battery	Nickel-Cadmium (NiCd)
Power	Type of Battery	Lithium-Ion (Li-ion)
Power	Type of Battery	Nickel-Hydrogen (NiH2)
Power	Type of Battery	Silver Zinc
Power	Type of Battery	Silver Oxide
Power	Type of Battery	Li-Ion Polymer
Power	Type of Battery	Other
Power	Type of Power	DC
Power	Type of Power	AC
Power	Type of Power	Other
Radar	Frequency Band	L
Radar	Frequency Band	S
Radar	Frequency Band	C
Radar	Frequency Band	X
Radar	Frequency Band	Ku
Radar	Frequency Band	K
Radar	Frequency Band	Ka
Radar	Frequency Band	Other
SIL	Modeling Type	3-DOF
SIL	Modeling Type	6-DOF
SIL	Modeling Type	Hardware in the loop
SIL	Modeling Type	Other
SIL	Mock-up / SIL - Primary Purpose	V&V
SIL	Mock-up / SIL - Primary Purpose	Prototyping
SIL	Mock-up / SIL - Primary Purpose	Sys-item Qualification
SIL	Mock-up / SIL - Primary Purpose	Other
Tx/Rx/Modules/Radar	Frequency Band	L band (1 to 2 GHz)
Tx/Rx/Modules/Radar	Frequency Band	S band (2 to 4 GHz)
Tx/Rx/Modules/Radar	Frequency Band	C band (4 to 8 GHz)
Tx/Rx/Modules/Radar	Frequency Band	X band (8 to 12 GHz)
Tx/Rx/Modules/Radar	Frequency Band	Ku band (12 to 18 GHz)
Tx/Rx/Modules/Radar	Frequency Band	K band (18 to 27 GHz)
Tx/Rx/Modules/Radar	Frequency Band	Ka band (27 to 40 GHz)
Tx/Rx/Modules/Radar	Frequency Band	V band (40 to 75 GHz)
Tx/Rx/Modules/Radar	Frequency Band	W band (75 to 110 GHz)
Tx/Rx/Modules/Radar	Frequency Band	Other

DRAFT

DRAFT

DRAFT