

Appendix BB

Pelletized Asphalt, Supersack

- 1. Introduction.** Under the ADR Modernization Program, Pelletized asphalt in 2,000-lb supersacks is procured standalone or as a component of the pelletized asphalt package. Pelletized asphalt is used as a capping material for crater repair. The material is packaged in 2,000-lb supersacks for use in an asphalt recycler.
- 2. Pelletized asphalt, supersacks.**
 - 2.1. Pelletized asphalt shall be packaged in supersacks meeting criteria in Appendix Q.
 - 2.2. For clarity and to avoid misidentification with other repair materials stored in supersacks, the pelletized asphalt supersacks shall be stenciled with PA. The stenciled lettering shall be a minimum of 6-in in height. The color of the lettering shall be forest green as shown in below example. The lettering shall be stenciled on the supersacks a minimum of two opposing sides.
 - 2.3. Pelletized asphalt unit of issue for this IDIQ shall be one (1) each.
 - 2.4. The pelletized asphalt capping material shall meet specifications in Appendix Z.
 - 2.5. If the pelletized asphalt supersacks are procured standalone and not as a pelletized asphalt package (Appendix CC), the contractor shall deliver the pelletized asphalt supersack on a wood pallet.
 - 2.6. Pallets shall be shrink wrapped with plastic. Plastic wrap shall be a minimum of 6-mil.

