

SALIENT CHARACTERISTICS

E0945 – Cart, Computer, Mobile

- a) Must include Central control panel for drawer access, power system controls, battery fuel gauge with visual and audible alerts, height adjustments, and light controls.
- b) Must consist of Power Max 150 with 50 ah class Lithium Iron Phosphate power system
- c) Shall have LCD VESA monitor mount with motorized height adjustment (5.25' range)
- d) Must have large work surface area (17'W x 14.3'D) with translucent protective cover
- e) Shall have Large, fan cooled, Electronic Locking PC compartment (dimensions: 17.1'W x 12.5'D x 3.2'H)
- f) Shall have (4) 5' premium casters with 2 locking casters on front
- g) Shall have Electronic Steer Assist Technology
- h) Must have adjustable push handles
- i) Must have Slide-out keyboard tray with positive and negative tilt feature and integral wrist rest
- j) Shall have Mouse surface and mouse pouch
- k) Shall have LED lights for keyboard, work surface and med drawer
- l) Must have Integral AC power distribution with 6 AC receptacles for powering customer equipment
- m) Shall have Universal accessory mounting locations on rear of cart and on monitor mount
- n) Shall have cable management area
- o) Includes 8ft three-coiled sections power cord with hospital-grade AC plug, dual integrated hooks
- p) Must have footrests on front legs to help reduce fatigue
- q) Shall have Tool-less, snap on, battery cover
- r) Shall have Standard gray and white color scheme
- s) Shall have In-Factory Standard Integration
- t) Dimensions: Cart overall size 21.4'W x 23.3'D, Base foot print 19' W x 20' D
- u) Must Include the Following:
 - a. HI-Care E Two-Tier Electronic Locking Storage Cabinet
 - b. SOFTWARE: Med Manager & Med Display
 - c. 24 inch monitor 1920x1080 resolution
 - d. Dell Pro Micro QCM1250 with intel core i7 PC
 - e. DELL Optiplex Antenna Mount
 - f. Keyboard, Mouse, Integration Kit
 - g. 7 port USB Hub
 - h. Smart Card Reader
- v) Quantity: 2