

Wisconsin Motors Canada
Everything For WISCONSIN Engines

Quick Reference Specifications

ENGINE MODEL	V465D
Current engine model ?	still in production as of April 2007
# of cylinders	4
Cylinder configuration	V-4
Head / valve style	overhead valve
Standard Bore Size	3.749" - 3.748" (95 mm), if worn .005" over standard size, re-bore, hone and fit with oversize pistons and rings
Stroke	4.00" (102 mm)
Displacement	177 cubic inches (2901 cc)
Maximum Horsepower @ RPM	65.9 @ 3000
Horsepower @ 2400 RPM	60
Horsepower @ 2000 RPM	52
Weight - lbs. (kg)	530 lbs. (241 kg)
Maximum Ft. lbs, Torques @ RPM	139 @ 1800
Dimensions - Lx W x H	34" x 28" x 36"
Maintenance Information	
Air cleaner, check and clean or replace	oil bath, every 4-8 hours depending on working environment, dry type change only when restriction indicator advises you to
Oil level, check	every 4 - 8 hours
Oil Change	every 50 hours
Oil type, must meet or exceed API Service specification SE / CC	-20oF to +32oF use 5w20, 5w30 or 10w, or 0oF to 95oF use 10w30, 10w40, 15w40, 15w50, or 60oF to 120oF use 20w40, 20w50, 40w
Gasoline	regular grade gasoline only, (87 octane minimum)
Clearance & Tolerances	
Piston skirt to bore clearance	.0025 - .003 cam ground piston
Crankpin diameter	2.1233 - 2.1238
Connecting rod to crankpin clearance	.0005 - .0018 shell bearing to crankpin clearance, vertical
Center bearing Shell (V465D only)	.0013 - .0038
Valve tappet clearance - cold - inlet	.008
Valve tappet clearance - cold - exhaust	.014

Valve face and valve seat angle	45o
Valve stem to guide clearance	.002" - .004", when clearance becomes over .002" over the high limit replace the guide(s)
Piston pin to piston	.0000" - .0008" tight
Piston pin to connecting rod	.0005" - .001"
Crankshaft end play	.002" - .005" cold
Bolt Torques - Foot lbs.	
Connecting rod	28 - 32
Cylinder block / center main to crankcase	center bearing hanger 74 - 76, prior to ser # 6089642 is 60, cap 32 - 35
Cylinder head	alternate in three steps, 8 - 10, 18 - 20, 27 - 30
Engine base	8 - 11
Gear Cover	16 - 18
Manifold	Upper to lower 13 - 15, to cylinder head 23 - 25
Main bearing plate	28 - 32
Spark plug	20 - 22
Flywheel	95 - 110
Rope pulley	not applicable
Miscellaneous	
Crankcase oil capacity	6 quarts plus 1 additional quart if replacing the filter
Running spark advance	23o, run engine to 2000 rpm or higher
Breaker point gap	distributor 020", magneto .015"
Spark plug gap	.030" gasoline, .018" LPG
Maximum operating rpm	3000