

BAGGAGE X-RAY MACHINE SALIENT CHARACTERISTICS

1. Purpose

The X-ray Machine are specifically designed to function in the same capacity to what Transportation Security Administration is currently using at commercial airport security screening check points. The 325th LRS/LGRD ATF office will utilize this equipment to properly conduct security screening of passengers and their carry-on items and checked baggage ensuring that no unauthorized items are carried or loaded onto aircraft.

The Air Force requires passenger baggage X-Ray machines to ensure passenger service agents are not required to hand search all hand-carried and checked baggage to meet United States Transportation Command (USTRANSCOM) and Air Mobility Command (AMC) passenger baggage screening requirements. Additionally, X-Ray screening technology provides a second level of screening to ensure safety of flight. The machines must be on the approved Air Cargo Screening Technology List (ACSTL) (Attached) as qualified TSA approved security programs. Devices purchased cannot be on the Conditionally Approved or the Grandfathered list.

2. Requirements

Desired outcome: Semi Portable (capable of being maneuvered within same building by no more than two people) passenger baggage visual image inspection device that displays digitized transmission radiographic images of an object under inspection following an interrogation and capable of enabling visual differentiation between types of materials detected, e.g., nylon vs explosives vs PVS under steel. Device must be capable of displaying images scanned from at least two perspectives.

3. Characteristics:

Length: Not greater than 115 in

Width: Not greater than 60 in

Height: Not greater than 75 in

Weight: Not greater than 2300 lbs.

Tunnel Size: Not less than 40 in x 40 in

Tunnel Height from Ground: Not greater than 30

Duty Cycle: 100%, No Warm-Up Procedure Required

Number of views: Classification dual view, and or multi view.

Operating/storage temperature: 32-104 degree Fahrenheit/0-120 degree Fahrenheit

Power supply standard: 110-120 volt

Threat Image Projection

Automatic Liquids Detection

Dual color monitors- able to support two computer monitors.

Conveyor load-485 pounds

High Resolution sensor technology

Image Enhancement

Low density image enhancement

Duty Cycle: 100%, No Warm-Up Procedure Required

Training program included in purchase.

Set-up/installation included in purchase.

"Medium Aperture" visual image device capacity Can accommodate screening of air cargo with at item size of at least 80 cm (31.5 in) wide by 60 cm (23.6 in) high by 120 cm (47.2 in) long and 100 kg (220.5 lbs.) in weight and up to 122 cm (48 in) wide by 153 cm (60.2 in) high by 122 cm (48 in) long and 1,000 kg (2,205 lbs.) in weight. (See ACSTL).

Needs to have the addition of entry/exit roller tables.

Extended Entry/Exit Roller Tables for the machine meet minimum of 20in on both tables and not exceeding 36in per table. Any size between the minimum and maximum are acceptable.

Entry/Exit tunnels that protect personnel/prevent them from reaching into the scanner while in operation.

Semi-Portable with roller castors

4. Warranty

Twelve-month warranty after installation of the machines

One year, parts and Labor.

Vendor will promptly expedite warranted parts to 325th Logistics Readiness Squadron

The warranty start date will commence upon completed delivery.

5. Installation and Delivery Address

Set-up/installation included in purchase.

Training program included in purchase.

Address

Tyndall AFB

Beacon Beach Road, BLDG 995,

Panama City , FL 32403 United States