

SONOBUOY LOT ACCEPTANCE TESTING (SLAT)

N0042126RXXXX

ATTACHMENT 1; PERFORMANCE WORK STATEMENT (PWS)

Naval Air Systems Command (NAVAIR)
Program Manager, Adversary and Specialized Aircraft (PMA-226)
Contracted Air Services (CAS)

18 February 2026

Controlled by: PMA-226
CUI Category: CTI
Distribution Statement: D
POC: Michael ORourke, michael.j.orourke1.civ@us.navy.mil

Distribution Statement D: Distribution authorized to the Department of Defense and U.S. DoD contractors only (CTI) (09 February 2026). Other requests for this document must be referred to PMA-226.

Table of Contents

1.0	SCOPE	5
2.0	APPLICABLE DOCUMENTS.....	5
2.1.	General Documents	5
2.2.	Aeronautical Regulations	6
3.0	GENERAL MISSION REQUIREMENTS.....	6
3.1.	SLAT Aircraft Capability, Configuration, and Performance Requirements	6
3.2.	Missions.....	8
3.3.	Shipment and Handling of Equipment	10
3.4.	Aircrew and Maintenance Communication	10
3.5.	Long Term Scheduled Maintenance Requirements	10
4.0	CAPABILITY STAND UP	11
4.1.	Integrated Master Schedule (IMS)	11
4.2.	Contractor Representative (CR) Designation	12
4.3.	Contractor Airworthiness Representative (AR) Designation	12
4.4.	Contractor Personnel Roster	13
4.5.	Aircraft Modification.....	13
4.6.	Airworthiness Substantiation and Certification.....	14
4.7.	Physical Configuration Audit (PCA), Functional Configuration Audit (FCA), and Launch System Demonstration	14
4.8.	Public Aircraft Operations (PAO) and Civil Aircraft Operations (CAO) Documentation and Certification	15
4.9.	Aircraft Basing and Positioning Plan	16
4.10.	Initial Training.....	16
4.11.	Civil Aircraft Landing Permits (CALPs).....	17
4.12.	Common Access Card (CAC) Issuance and Access Authorization	17
4.13.	Fuel Card Training and Onboarding.....	17
4.14.	System Readiness Review	17
4.15.	Initial GFR Inspection	17
4.16.	Safe-for-Flight (SFF) Inspection	18
5.0	FLIGHT AND GROUND OPERATIONS	18
5.1.	Aircraft Certification and Maintenance	18
5.2.	Aircraft Maintenance Program	18
5.3.	FAA Airworthiness Certification	18
5.4.	Civil Aircraft Operations (CAO) Requirements.....	18
5.5.	Safety and Survival Equipment Requirements	19
5.6.	Interim Flight Clearance (IFC)	19

5.7.	Safe-for-Flight (SFF) / Configuration Approval Requirements	19
5.8.	Notification of Proposed Aircraft Changes	20
5.9.	PAO Policy and Procedures	20
5.10.	Fuel	27
6.0	PERSONNEL QUALIFICATIONS.....	29
6.1.	Training Requirements	29
6.2.	Aircrew Training and Currency	29
6.3.	Public Aircraft Operations (PAO) Flight Familiarization	30
6.4.	Pilot Qualifications, Experience, and Proficiency	30
6.5.	Sonobuoy Operator Requirements.....	32
6.6.	Other Mission Support Personnel.....	33
6.7.	Maintenance Personnel Training	33
7.0	PERFORMANCE METRICS	34
7.1.	Mission Success Rate (MSR)	34
7.2.	Sonobuoy Launch Compliance Rate	35
7.3.	Aircraft Availability Rate	35
7.4.	Aircrew Qualification Currency	36
7.5.	CDRL Deliverable Timeliness	37
7.6.	Fuel Consumption Reporting Accuracy	37
7.7.	GFR Safety Inspection Results.....	39
8.0	CONTRACT STATUS REPORTING.....	39
8.1.	Monthly Progress, Status and Management Report	40
8.2.	Operational Coordination and Daily Comms	40
8.3.	Meetings and Communications	41
9.0	OTHER PERFORMANCE REQUIREMENTS.....	42
9.1.	Physical, Personnel, and Information Security Controls.....	42
9.2.	Contractor Facility Basing Requirements.....	43
9.3.	Access to U.S. Government Installations	43
9.4.	Controlled Unclassified Information (CUI).....	46
9.5.	Cybersecurity and Cybersecurity Maturity Model Certification (CMMC).....	46
9.6.	Technical Assistance Agreements (TAA) and Export Control	47
9.7.	Records Retention and Data Rights.....	48
9.8.	Government Provisions	48
9.9.	Government Furnished Material (GFM)	48
9.10.	Subcontractor Management.....	48
9.11.	Contract Closeout Requirements	49

10.0 DATA DELIVERABLES.....	49
APPENDIX A - APPLICABLE DOCUMENTS	51
APPENDIX B - DEFINITIONS AND GLOSSARY	53
APPENDIX C - ACRONYM LIST.....	54
APPENDIX D – CAPABILITY STAND-UP CHECKLIST.....	57
APPENDIX E – MISSION AIRCRAFT CONFIGURATION CHECKLIST	58

TABLES AND FIGURES

Table 1: Required GOPS procedures to conduct PAO / State Operations.....	25
Table 2: Minimum Pilot Qualifications	30
Table 3: Pilot Currency, Experience, and Proficiency Requirements.....	31
Table 4: Data Deliverables.....	49

1.0 SCOPE

The Naval Air Systems Command (NAVAIR) Program Manager, Adversary and Specialized Aircraft (PMA-226) program provides Contractor Owned Contractor Operated (COCO) aircraft to the Department of the Navy (DON) Fleet and Test customers. This Performance Work Statement (PWS) defines the requirement for COCO aircraft services in support of Sonobuoy Lot Acceptance Testing (SLAT). The SLAT mission provides aerial deployment of production and pre-production sonobuoys in support of the Navy's Sonobuoy Quality Assurance Program (SQAP), ensuring compliance with performance and reliability specifications prior to fleet delivery. The contractor shall provide aircraft equipped with a pneumatic launch system capable of deploying NATO 'A' size sonobuoys. The aircraft shall support overwater flight profiles for a minimum of five hours on station, flying within an altitude envelope of 500 to 8,000 feet Mean Sea Level (MSL), and maintain stable airspeeds suitable for sonobuoy launch spacing and accuracy. Each SLAT mission shall be executed using a single flight sortie, during which all scheduled sonobuoys must be deployed. The use of multiple aircraft and/or sorties to complete a mission is not permitted.

This contract requires that all operational SLAT missions be performed under Public Aircraft Operations (PAO) authority in accordance with 49 U.S.C. § 40125, FAA AC 00-1.1B, DCMA INST 8210.1D, and NAVAIRINST 13034.1G. Civil Aircraft Operations (CAO) will be required for all repositioning/ferry flights, maintenance/functional check flights, pilot training and currency flights conducted in the aircraft, and all other flight activities where PAO authorization is not authorized. The contractor must clearly identify in the aircraft logbook, prior to flight, if a flight will be conducted in a CAO or PAO status and ensure all certifications, documentation, conformity inspections, and procedures align with the applicable contractual, regulatory and statutory framework. All PAO flights require advanced coordination with, and written approval from the Government Flight Representative (GFR).

The primary performance location for mission events will be in the vicinity of San Clemente Island (SCI), California. Aircraft operations shall originate from a contractor base of operations located within 50 nautical miles of Naval Air Station North Island in San Diego, CA.

2.0 APPLICABLE DOCUMENTS

2.1. General Documents

The Contractor shall utilize and adhere to the documents listed in Appendix A (Applicable Documents), and updates or revisions to them, in satisfying the performance requirements of this Performance Work Statement (PWS). For clarity, all references to the Federal Aviation Regulations in this PWS will be by reference to Title 14, Code of Federal Regulations (CFR) and abbreviated with the acronym "14 CFR". All references to the Federal Acquisition Regulation will be abbreviated with the acronym "FAR". When the requirements of this PWS exceed the minimum requirements of 14 CFR, this PWS takes precedence. Definitions contained in 14 CFR Part 1, which are derived from 14 CFR and Defense Contract Management Agency Instruction (DCMA INST) 8210-1D, apply to all situations and conditions relating to flight operations, aircraft maintenance, and flight crew certifications and qualifications.

2.2. Aeronautical Regulations

The contractor shall operate aircraft in accordance with the most restrictive applicable regulation or directive, to include but not limited to:

- 14 CFR §§ 61, 91, and 135 (if applicable)
- U.S. Navy and U.S. Marine Corps aviation directives
- Local military flying instructions
- Applicable DoD guidance (e.g., DCMA INST 8210.1D, NAVAIRINST 13034.1 (series), CNAF M-3710.7)
- International Civil Aviation Organization (ICAO) Standards
- Any civil aviation regulations of the country of intended operation

In cases of conflict between guidance sources, the most restrictive shall apply. The contractor shall distinguish between PAO and CAO flight types and ensure compliance with the most applicable and restrictive regulations for each. CAO flights shall be conducted fully in accordance with 14 CFR and FAA-approved airworthiness standards.

3.0 GENERAL MISSION REQUIREMENTS

The Contractor shall provide a FAA certificated aircraft and personnel capable of providing the services outlined in the PWS. The Contractor shall ensure all aircraft are equipped with the communication and navigation capability necessary to operate under both visual and instrument conditions IAW CFR §§ 61 and 91 in the United States National Airspace (NAS) and in international airspace.

SLAT missions under this contract are to be executed in a single presentation and completed within a single flight event (sortie). The contractor shall not substitute aircraft or split sonobuoy deployment across multiple sorties for any given mission. The aircraft provided must have sufficient range, endurance, payload capacity, and reliability to support this operational requirement.

3.1. SLAT Aircraft Capability, Configuration, and Performance Requirements

The contractor shall provide an aircraft capable of meeting or exceeding the following minimum performance requirements in support of Sonobuoy Lot Acceptance Testing (SLAT) missions:

- Endurance: Minimum of 5.0 hours on-station time with transit to/from Contractor base of operations
- Range: Minimum 700 Nautical Miles (NM) unrefueled under visual meteorological conditions (VMC)
- Altitude Envelope: Capable of operating from 500 feet to at least 8,000 feet Mean Sea Level (MSL)
- Airspeed Envelope: Maintain stable, controllable airspeeds below 250 Knots Indicated Airspeed (KIAS) during straight-and-level flight for launch operations
- Overwater Capability: Aircraft must be capable of overwater operations up to 100 NM from nearest land

- Maneuverability: Due to the tight airspace limitations around the drop area, the Contractor aircraft shall possess the flight characteristics necessary to execute precise and repeatable flight patterns required for sonobuoy deployment in a maritime environment. The aircraft must be able to transition efficiently from transit flight to on-station patterns.
- Cabin pressurization: Launches will be performed from altitudes not requiring a pressurized cabin

3.1.1. Launch System Requirements

- Pneumatic system, capable of launching NATO 'A' size sonobuoys
- Ability to execute sonobuoy drops that provide 100-yard spacing between 4 sonobuoys during a single pass
- Aircraft must be prepared for another drop pass within six (6) minutes
- High speed camera (40 fps minimum) and video system must be installed on aircraft and/or launcher to capture & record sonobuoy launch separation

3.1.2. Payload Capacity

- Accommodate carriage and in-flight deployment of a minimum of 32 and up to 52 NATO 'A' size sonobuoys in launch containers, weighing up to 45 lbs. each
- Aircraft shall be able to load the minimum number of sonobuoys required for the daily mission to complete mission in a single sortie (e.g. no mid-mission landing requirements for refueling or aircraft substitution)
- Provide adequate stowage, loading/unloading access, and environmental control (as required) to support safe handling and deployment of lithium battery-equipped sonobuoys. Storage system must be installed per 14 CFR § 43 requirements

3.1.3. Communications & Navigation

- Equipped with FAA-compliant navigation and communications systems (e.g., GPS, UHF, VHF)
- Aircraft shall be equipped with an intercom system to allow the flight deck crewmembers to communicate with the non-crewmembers via headset in the cabin of the aircraft while at their designated duty positions and allow an instructor to communicate from the flight deck or cabin of the aircraft
 - Minimum of four (4) operational intercom connections for Pilot in Command (PIC), Second in Command (SIC), Sonobuoy Operator, and additional personnel (as required)
- Equipped with additional UHF radio for mission coordination (total of two (2) UHF radios required on aircraft)
- Equipped with operable Radar Altimeter (RADALT)
- Aircraft shall be equipped with ADSB-In/Out

3.1.4. Hazardous Material Compliance

- Capable of safely carrying Class 2.2 and Class 9 hazardous materials, including lithium

battery-equipped sonobuoys. If carriage is conducted in CAO flight, the contractor must have a DOT/FAA approved HAZMAT program to carry such materials.

3.2. Missions

The contractor shall provide air support for sonobuoy lot acceptance testing flights as directed by the Government. Flight operations will occur over open-ocean test ranges in the vicinity of San Clemente Island, CA (SCI), and shall be coordinated with a Government-operated surface vessel. The contractor shall plan and execute all missions in accordance with established profiles and within the performance parameters specified in this PWS.

3.2.1. Typical Profiles

The contractor shall be capable of supporting the following typical mission profiles:

- Conducting overwater flight operations up to 100 NM offshore
- Maintain stable, controllable airspeeds below 250 Knots Indicated Airspeed (KIAS) during straight-and-level flight for launch operations
- Operating at altitudes ranging from 500 feet AGL to 8,000 feet MSL
- Sustaining an on-station presence for up to five (5) continuous hours per mission
- Launching a minimum of 32 and up to 52 A-size sonobuoys from designated test altitudes and speeds
- Conducting multi-drop passes per sortie with no less than six (6) minutes between passes
- Recovering to a designated base within FAA-compliant crew duty limits and with appropriate fuel reserves
- The Contractor aircraft must be capable of operating within current SCI airspace constraints including operations on weekends when SCI NALF (KNUC) tower is closed

3.2.2. Typical Missions

SLAT mission types may include, but are not limited to:

- Sonobuoy Lot Acceptance Testing: Launching production sonobuoys from specified altitudes and speeds into a predefined pattern to validate factory performance
- Engineering Test Drops: Deploying prototype or pre-production buoys to support development and qualification
- Pattern Accuracy Testing: Precision placement of multiple buoys with specific spacing (e.g., 100 yards) for acoustic testing by a nearby surface vessel
- Mammal Mitigation & Range Clearance: Assisting with pre-drop aerial surveys for marine mammal presence in coordination with Navy range control, when requested
- Training and Rehearsal Sorties: Supporting Government familiarization flights, sonobuoy operator training, or operational rehearsals when required

The contractor shall maintain flexibility to support mission-specific changes within the approved flight envelope and notify the Government promptly of any operational limitations or deviations. Each SLAT mission shall be executed in a single continuous flight event. The contractor shall ensure sufficient aircraft endurance and reliability to complete all scheduled sonobuoy drops in

one sortie.

3.2.3. Mission coordination

Mission coordination shall be maintained with:

- PMA-264 test team personnel
- Range control and Naval Base air traffic authorities
- The project support vessel via VHF/UHF as required

3.2.4. Mission Planning

The contractor shall conduct thorough mission planning for all SLAT flights. At a minimum, mission planning shall address:

- Route selection and airspace deconfliction
- Flight profiles consistent with the sonobuoy launch envelope
- Weather evaluation and risk mitigation
- Launch system configuration and sequencing
- Sonobuoy handling and loading plan
- Marine species mitigation procedures (in accordance with awareness training)
- Coordination with range authorities and support vessel
- Aircrew shall coordinate with the surface vessel to ensure all drops are conducted downwind and outside of $\frac{1}{4}$ NM of visible marine mammals
- Drop patterns may be clockwise or counterclockwise based on real-time wind conditions and will require re-marking the vessel location if repositioned
- Mission planning shall be conducted in coordination with PMA-264 test team personnel.
- Mission briefings shall be conducted prior to each flight to ensure all aircrew, sonobuoy operators, and support personnel are aligned on objectives and contingencies
- Sonobuoy deployments shall occur no less than 500 ft AGL at least 1 NM offshore, and in alignment with a predefined heading as determined by Range Control. Drop spacing shall place the final buoy abeam the support vessel, with total drop range between 100–500 yards. A dry run is recommended before live drops
- Ensure the flight plan, aircraft configuration, fuel load, and mission duration allow for the full sonobuoy load to be launched in a single sortie, with no requirement for mid-mission refueling or aircraft substitution

3.2.5. Scheduling and Mission Notification

The contractor shall maintain availability to support monthly SLAT missions. PMA-264 will provide a forecasted mission schedule with at least 30 days' notice, subject to change based on range and vessel availability. The contractor shall:

- Provide confirmation of aircraft and crew availability no later than 10 business days prior to the first mission day scheduled. Aircraft availability and mission readiness shall be sufficient to complete each scheduled mission in one sortie using the designated aircraft

- Notify the Government of any issues that may impact availability or readiness within 24 hours of discovery
- Submit daily mission status reports during test periods, including aircraft status, flight hours, sonobuoy drop counts, and any anomalies or aborted missions (See PWS Section 8.2.1. for submission requirements)

3.3. Shipment and Handling of Equipment

The contractor shall be responsible for the safe and secure handling of government equipment, material, and test equipment required for SLAT missions. This includes:

- Receipt, inspection, inventory, and storage of sonobuoys and support hardware
- Transport of equipment to and from the aircraft and/or aircraft launch locations
- Return of unused or failed test items to the Government as directed
- Coordination of Safety Data Sheets (SDS) for lithium battery-equipped sonobuoys and Class 2.2/9 HAZMAT handling procedures
- The contractor shall comply with all applicable HAZMAT and shipping regulations and ensure sonobuoy storage and handling areas meet safety and environmental compliance standards

3.4. Aircrew and Maintenance Communication

The contractor shall maintain a process for continuous communication between flight crew, qualified non-crewmembers, and maintenance personnel. Pre-flight and post-flight coordination shall include:

- Review of maintenance status and discrepancies
- Aircraft configuration confirmation
- Feedback on system or performance issues
- Transfer of aircraft servicing and re-arming duties

3.5. Long Term Scheduled Maintenance Requirements

The Contractor shall coordinate with PMA-264 test team personnel no less than once per month to discuss long-term maintenance planning (typically looking 12 to 24 months into the future) and identify aircraft scheduled maintenance. No special scheduling arrangements or considerations will be made to meet the Contractor's maintenance requirements.

The contractor shall sustain the full operational capability of aircraft, crew, and mission systems throughout the period of performance. Sustainment efforts shall ensure no degradation in safety, availability, or performance of SLAT operations.

The contractor shall develop and maintain a scheduled maintenance and inspection program in accordance with 14 CFR §§ 43 and 91, OEM recommendations, and DCMA INST 8210.1D. The maintenance program shall include:

- The contractor shall ensure long-term inspections (e.g., phase/letter checks, overhauls)

- are forecasted and coordinated such that SLAT mission availability is not impacted
- Downtime for depot-level maintenance or major inspections shall be communicated to the COR and PMA-264 test team personnel via e-mail at least 60 calendar days in advance
- Maintenance plans and component time-tracking systems must be auditable and kept current
- Aircraft shall not operate beyond published time limits for life-limited components or scheduled inspections

4.0 CAPABILITY STAND UP

The contractor shall complete all required preparations necessary to achieve full operational capability within twelve (12) months of contract award. No SLAT missions shall be conducted until the contractor has successfully completed all elements of the stand-up phase and received Government concurrence. At the time of contract award, the Contractor shall possess (own or lease) at least one (1) FAA registered and certified aircraft, capable of meeting SLAT Aircraft Capability, Configuration, and Performance Requirements as identified in PWS Section 3.1 and PWS Appendix E, when modified.

The contractor's completion of Milestone A and Milestone B, as detailed in Appendix D, serves as the contractual prerequisite for the release of funding for specific Contract Line-Item Numbers (CLINs).

- Milestone A (Pre-Operational Readiness Gate): This milestone shall be deemed complete only upon the Government's formal written acceptance of all plans, documentation, and data submitted by the contractor as required under the "Milestone A" category in Appendix D. The Contracting Officer's Representative (COR) will provide a singular, formal notification to the Contracting Officer and the contractor upon successful verification of all Milestone A requirements. The obligation of funds for CLIN 0002 is contingent upon this notification.
- Milestone B (Full Operational Capability Readiness Gate): This milestone shall be deemed complete only after the successful completion of all "Milestone A" requirements AND the successful completion of all Government on-site inspections, evaluations, and final flight clearances as required under the "Milestone B" category in Appendix D. The COR will provide formal notification upon successful verification. The use of CLINs 0003, 0004, and 0005 is contingent upon this notification.

4.1 Integrated Master Schedule (IMS)

The contractor shall submit an Integrated Master Schedule (IMS) IAW Contract Exhibit A, CDRL A001. The IMS shall include all activities, milestones, and dependencies required to achieve mission-ready status. At a minimum, the IMS shall include:

- Aircraft modification or configuration timeline
- Launch system design, procurement, modification, and/or certification (as required)
- Launch system integration, and test schedule (PCA/FCA)

- Flight Operations Procedures & Ground Operations Procedures (FOPs/GOPs) manual development and Government approval timeline
 - Government approved FOPs/GOPs are required at least 30 days prior to the start of pilot training, aircraft maintainer training, and PAO flight operations
- Maintenance organization setup (facilities, tools, etc.)
- Pilot hiring, onboarding, training, and qualification schedule
- Sonobuoy operator hiring, onboarding, training, and qualification schedule
- Maintenance personnel hiring, onboarding, training, and qualification schedule
- Contractor personnel background check and Common Access Card (CAC) application processes
- Airworthiness certification and documentation milestones
- Public Aircraft Operations (PAO) coordination timeline
- Government Fuel Card and Civil Aircraft Landing Permit (CALP) application processes
- Facilities and range coordination steps

4.2. Contractor Representative (CR) Designation

The Contractor shall designate a Contractor Representative (CR) as a single point of contact for mission coordination. This individual shall be responsible for:

- Liaison with the COR, GFR, and PMA-264 test team personnel
- Coordinating daily operations and issue resolutions
- Maintaining a clear audit trail of flight operations, logs, and communications
- Ensuring timely submission of required deliverables, including CDRLs
- Overseeing and ensuring all designated personnel obtain the necessary access to the NAVAIR Acquisition Management System (AMS) CDRL Tool. This responsibility includes:
 - Tracking the application for and maintenance of Department of Defense Public Key Infrastructure (DoD PKI) certificates, Common Access Cards (CACs), or other required digital certificates
 - Verifying the completion of any required system training or user registration processes
 - Coordinating with the COR to ensure system access is active and tested prior to the first submission
 - Failure to obtain the required certificates or access to AMS does not relieve the Contractor of the responsibility to meet the delivery schedule specified in the contract

4.3. Contractor Airworthiness Representative (AR) Designation

The contractor shall appoint and maintain a designated Airworthiness Representative (AR) responsible for ensuring compliance with airworthiness, configuration, and certification requirements under PAO. The AR shall:

- Act as the primary interface to the Government for all flight- and ground-operational compliance matters

- Ensure timely development, submission, and updates of required Flight and Ground Operating Procedures (FOPs/GOPs)
- Ensure accuracy of configuration data, maintenance status, and substantiation packages for aircraft and installed systems (e.g., sonobuoy launcher)
- Participate in reviews and briefings required for SFF release or Interim Flight Clearance (IFC) determinations

4.4. Contractor Personnel Roster

The Contractor shall submit a comprehensive roster of all personnel supporting this effort. This roster shall include both prime and subcontractor personnel assigned to the contract and shall be submitted to the Government by the deadlines established in Contract Exhibit A, CDRL A007. All updates shall be submitted to the Government by the deadlines established in Contract Exhibit A, CDRL A007.

The submission shall include the following information:

- Full Name (first, middle initial, last)
- Employer (Prime/Subcontractor, including company name)
- Position / Job Title
- Specific Qualifications (PIC, SIC, SO, SFF, etc.)
- Full-time/Part-time status
- Common Access Card (CAC) Requested? (Yes/No)
- CAC Justification (if applicable)
- Access to CUI Requested? (Yes/No)
- CUI Access Justification (if applicable)
- Federal Background Check / Security Clearance Type (if known)
- Federal Background Check Completion Date (if known)

The following information shall NOT be included in the submission:

- Social Security Numbers (SSNs)
- Date of Birth (DOB)
- Place of Birth (POB)

The roster shall be submitted IAW Contract Exhibit A, CDRL A007 and shall be kept current throughout the period of performance. Personnel who do not meet the background check requirement shall not be permitted to access Controlled Unclassified Information (CUI) or receive a Common Access Card (CAC).

4.5. Aircraft Modification

If required to meet mission performance requirements defined in Appendix E, the Contractor shall complete all modifications necessary to enable Sonobuoy Lot Acceptance Testing (SLAT) operations. At a minimum, the Contractor shall:

- Modification and Integration. Modify aircraft to incorporate a pneumatic sonobuoy

launch system, communications/navigation equipment, safety and survival equipment, and any other mission systems required to comply with Appendix E. Modifications must be designed, installed, and documented in accordance with applicable FAA regulations, OEM data, and DCMA INST 8210.1D

- Substantiation. Provide structural, electrical, and systems substantiation data sufficient to support NAVAIR Interim Flight Clearance (IFC) and Safe-for-Flight (SFF) determinations. Data shall be delivered in accordance with IAW Contract Exhibit A, CDRL A002 and the PAO Airworthiness Checklist (Section J, Attachment 2)
- Substantiation shall include, as applicable:
 - FAA Form 8110-3, Statement of Compliance with Airworthiness Standards
 - FAA Form 337, Major Repair and Alteration
 - Approved engineering drawings, data packages, or other FAA-accepted substantiating data
- Certification. Ensure all modifications receive FAA or equivalent certification (Standard or Special Airworthiness Certificate, as applicable) and Government approval under PAO authority prior to commencement of SLAT operations
- Configuration Control. Maintain configuration documentation for all modifications and provide timely notification of changes in accordance with PWS Section 5.8 (Notification of Proposed Aircraft Changes)

4.6. Airworthiness Substantiation and Certification

The contractor shall provide all substantiation data necessary for Government review of airworthiness under Public Aircraft Operations (PAO). Documentation shall support a Safe for Flight (SFF) release and comply with DCMA INST 8210.1D and NAVAIRINST 13034.1G. The contractor shall submit all required substantiation documentation in accordance with Contract Exhibit A, CDRL A002 and Contract Section J, Attachment 2 (Public Aircraft Operation (PAO) Airworthiness Checklist).

4.7. Physical Configuration Audit (PCA), Functional Configuration Audit (FCA), and Launch System Demonstration

4.7.1. PCA/FCA

The Contractor shall support a Government lead PCA and FCA to support a NAVAIR Airworthiness evaluation prior to NAVAIR IFC issuance. The purpose of these audits is to formally examine the ready-to-operate aircraft and verify the accuracy of the aircraft's configuration as described by the documentation provided in support of the aircraft's IFC. The PCA and FCA provide confirmation that the contractor is meeting the requirements as defined by the PWS. The Government will conduct an onsite aircraft assessment for each T/M/S that is fully configured to meet the performance requirements of the PWS.

4.7.2. Launch System Demonstration

The contractor shall demonstrate the functional performance of the sonobuoy launch system prior to commencing flight operations. The demonstration shall include:

- Successful static test (ground-based) of pneumatic launch at specified exit velocities
- Loading/unloading procedures for A-size sonobuoys
- Safety and hazard mitigation systems, including venting and jettison procedures for lithium battery-equipped buoys

4.8. Public Aircraft Operations (PAO) and Civil Aircraft Operations (CAO) Documentation and Certification

All flights performed under PAO status shall follow the documentation and certification process outlined herein and DCMA INST 8210.1D. For flights conducted under CAO (e.g., pilot training, ferry/positioning flights, maintenance flights), the contractor shall maintain and submit FAA airworthiness documentation, maintenance procedures, and crew certifications required by 14 CFR and contract terms. The contractor shall maintain a clear record of each flight's status in the aircraft logbook (PAO vs CAO) and in the flight schedule for audit and oversight purposes. To support PAO status and enable the Government to issue a Safe for Flight (SFF) determination, the contractor shall submit the following documentation for Government review within 30 calendar days of contract award, unless otherwise directed by the Government. GFR approved FOPs/GOPs are required at least 30 days prior to the start of pilot training, aircraft maintainer training, and PAO flight operations. All PAO required documentation shall be submitted IAW Contract Exhibit A, CDRL A003.

4.8.1. Required PAO Documentation

- Ground Operating Procedures (GOPs) developed in accordance with the contract, DCMA INST 8210.1D, and applicable service guidance for sonobuoy operations
- Flight Operating Procedures (FOPs) developed in accordance with the contract, DCMA INST 8210.1D, and applicable service guidance for sonobuoy operations
- Flight schedule template that contains all information listed on DD Form 3062
- Training Plans
 - Aircrew Training Plan: as required by DCMA INST 8210.1D. Additionally, it describes initial and recurrent pilot and sonobuoy operator training, including simulator use (if one exists for the type aircraft used), safety training, and marine mammal mitigation awareness
 - Maintenance Training Plan: Describes initial qualification and sustainment training for all personnel performing aircraft and launch system maintenance
 - Training Records as required by DCMA INST 8210.1D
- The contractor shall submit a Management Plan (MP) that is a comprehensive description of how the contractor manages quality, compliance, and safety under PAO status.
 - The MP shall identify responsible personnel, processes for internal audits, and corrective action protocols
- Approved Civil Aircraft Landing Permits (CALP)
- Safety and Survival Equipment
 - The contractor shall ensure each aircraft is equipped with the safety and survival gear required in 14CFR § 91. At a minimum, the contractor shall demonstrate that:
 - All required crewmember and qualified non-crewmember survival

- equipment complies with 14 CFR § 91 and aircraft OEM specifications
- Life vests, rafts, ELTs, and portable oxygen (if applicable) are available, serviceable, and documented
- All crew have been trained in the location and use of equipment within the past 12 months

4.9. Aircraft Basing and Positioning Plan

The contractor shall provide a detailed aircraft basing and positioning plan that confirms the aircraft will be located and supported within 50 nautical miles of Naval Air Station North Island in San Diego, CA. The plan shall be incorporated into the Contractor's Ground Operating Procedures (GOPs) and submitted IAW Contract Exhibit A, CDRL A003. The plan shall include:

- Hangar or tie-down location
- Access to fueling, servicing, and Ground Service Equipment (GSE) support
- Security measures and facility points of contact
- Contingency plans for repositioning or maintenance away from home base

4.10. Initial Training

The Contractor shall complete initial training for all flight crew and sonobuoy operators during the Capability Stand-Up phase. Training shall be conducted in two parts:

4.10.1. Ground Training

The Contractor shall provide formal ground training for pilots, sonobuoy operators, and maintenance personnel. Ground training shall include, at a minimum: aircraft systems familiarization; Public Aircraft Operations (PAO) responsibilities; safety and emergency procedures; sonobuoy handling and deployment procedures; hazardous material awareness; and marine mammal mitigation procedures. Ground training shall be conducted in accordance with Government Flight Representative (GFR)-approved Ground Operating Procedures (GOPs), Flight Operating Procedures (FOPs), and Training Plans. Training records shall be documented and submitted to the Government IAW Contract Exhibit A, CDRL A003.

4.10.2. Initial Flight/Simulator Training

Prior to commencement of PAO operations, the Contractor shall conduct initial proficiency training and familiarization events under Civil Aircraft Operations (CAO) authority or in approved flight simulators. Such training may include simulated sonobuoy deployment profiles, overwater familiarization, emergency procedures, and mission coordination tasks. All initial flight and simulator training shall be performed in accordance with GFR-approved GOPs, FOPs, and Training Plans, and documented in the Contractor's Training Plan.

4.10.3. Training Records

The Contractor shall maintain complete training records for all pilots and sonobuoy operators.

Training records shall include dates, instructor/evaluator names, course syllabi, and proficiency check results. These records shall be submitted as part of the airworthiness substantiation package to support Interim Flight Clearance (IFC) and Safe-for-Flight (SFF) determinations.

4.10.4. Transition to PAO

No PAO missions may be conducted until IFC and SFF approvals have been granted. Upon approval, all subsequent flight training and mission operations shall be conducted under PAO authority, in compliance with GFR-approved Flight Operating Procedures (FOPs) and Ground Operating Procedures (GOPs).

4.11. Civil Aircraft Landing Permits (CALPs)

The contractor shall submit the following to the appropriate military service (e.g., USN/USMC/USAF):

- DD Form 2400 – Civil Aircraft Certificate of Insurance
- DD Form 2401 – Civil Aircraft Landing Permit
- DD Form 2402 – Civil Aircraft Hold Harmless Agreement

Signed copies of the above DD Forms must be sent IAW Contract Exhibit A, CDRL A002. Approved CALPs must be sent to the Government IAW Contract Exhibit A, CDRL A003 prior to the end of the capability standup period.

4.12. Common Access Card (CAC) Issuance and Access Authorization

The contractor shall identify all personnel requiring Common Access Cards (CACs) for access to DoD installations (e.g. pilots, aircrew, operations personnel, etc.). During the capability standup period, the contractor shall submit a complete list of CAC-required personnel to the COR with justification for each role via the contractor roster submitted IAW Contract Exhibit A, CDRL. See PWS Section 9.3.1 for further information regarding the CAC Issuance process.

4.13. Fuel Card Training and Onboarding

Contractor personnel who will use Government-issued AIR cards must complete initial training through the DoN Consolidated Card Program Management Division (CCPMD) system. All training must be completed prior to the end of the capability standup period. See PWS Section 5.10 for fuel card training and onboarding requirements.

4.14. System Readiness Review

Upon completion of stand-up activities, the contractor shall support a System Readiness Review (SRR) with the Government. The SRR will confirm readiness to commence flight operations and validate that all required documentation, equipment, training, and risk mitigations are in place.

4.15. Initial GFR Inspection

An initial GFR inspection conducted IAW DCMA INST 8210.1D is required to be successfully

completed prior to receiving a final NAVAIR Safe-for-Flight inspection

4.16. Safe-for-Flight (SFF) Inspection

Conducted IAW NAVAIR INST 3700.4B. See PWS Section 5.9.13

5.0 FLIGHT AND GROUND OPERATIONS

5.1. Aircraft Certification and Maintenance

The contractor shall certify, maintain, and operate aircraft in accordance with this contract, GFR approved FOPs/GOPs, applicable FAA regulations, DoD airworthiness policy, and public aircraft operation (PAO) guidance to ensure safe, compliant, and mission-ready performance throughout the contract period of performance.

5.2. Aircraft Maintenance Program

The Contractor shall maintain aircraft used in the performance of this contract IAW 14 CFR § 43 and 91, GFR approved FOPs/GOPs, and the NAVAIR IFC(s). The Contractor shall conduct scheduled maintenance at a 14 CFR § 145 certificated repair station or IAW their GFR and FAA approved maintenance and inspection program.

5.3. FAA Airworthiness Certification

All aircraft shall hold valid FAA airworthiness documentation. The contractor shall:

- Maintain and comply with an FAA issued Standard or Special (Restricted or Experimental) Airworthiness Certificate for any aircraft operated in a civil configuration under FAA Part 91 or Part 135 (if applicable)
- If the aircraft is operated in an experimental, restricted, or other non-standard category, during civil flight operations, provide documentation showing the aircraft will be maintained IAW with its FAA approved maintenance and inspection program
- Maintain current aircraft registration and ensure no conflicting operational restrictions exist that would preclude use under PAO

5.4. Civil Aircraft Operations (CAO) Requirements

Ferry, repositioning, maintenance, functional test flights, and pilot training & currency flights shall be conducted in a civil status IAW 14 CFR. All flights performing SLAT mission execution shall be conducted in a PAO status. CAO operations shall:

- Be conducted in full compliance with 14 CFR §§ 61 and 91 (as applicable)
- Be supported by a valid FAA airworthiness certificate and current aircraft registration
- Include documentation in the aircraft flight log clearly identifying the flight as CAO
- GFR coordination is not required for CAO flight operations. Flight schedules submitted to the GFR shall only contain PAO mission flights
- The Contractor shall not use contracted flight operations to conduct flight training unless such training cannot otherwise be accomplished in a simulator or the aircraft under civil

rules and at no time without written GFR authorization

5.5. Safety and Survival Equipment Requirements

The contractor shall ensure that each aircraft is equipped with crew safety and survival equipment appropriate for the number of personnel onboard and the mission profile.

Responsibilities include:

- The type and quantity of equipment shall comply with 14 CFR § 91 and be maintained to applicable OEM documentation
- At a minimum, equipment shall include that referenced in 14 CFR § 91, to include, but not limited to, personal flotation devices (PFDs), life rafts, emergency oxygen, fire extinguishers, and emergency locator transmitters (ELTs) as applicable
- All crew members and qualified non-crewmembers shall receive annual hands-on training in the location and use of survival equipment

Equipment configurations will be reviewed during the NAVAIR Interim Flight Clearance (IFC) and Safe-for-Flight (SFF) processes; however, the contractor is solely responsible for ensuring operational compliance.

5.6. Interim Flight Clearance (IFC)

The contractor shall support the issuance of an Interim Flight Clearance by the appropriate NAVAIR Airworthiness Authority in accordance with NAVAIRINST 13034.1 (series). The contractor shall:

- Submit all substantiation documentation identified in Contract Section J, Attachment 2 – PAO Airworthiness Checklist IAW Contract Exhibit A, CDRL A002
- Provide supporting data for any aircraft modifications or mission equipment installations, including structural substantiation, electromagnetic compatibility, and safety-of-flight risk analysis
- Coordinate with the COR, CAS Class Desk, and GFR to ensure all technical data is suitable for IFC review
- If aircraft have a civil airworthiness certificate and FAA approved master minimum equipment list (MMEL), the contractor shall obtain FAA approval to use the MMEL as their minimum equipment list (MEL) or approval to create an aircraft or fleet specific MEL. If the FAA has not published an MMEL for the type of aircraft used for PAO operations, the contractor shall develop a deferred maintenance program (like a FAA MMEL) to be submitted and approved by the USN Class Desk and incorporated by reference in the IFC and FOPs/GOPs, prior to deferring any maintenance, inspections, or repairs

5.7. Safe-for-Flight (SFF) / Configuration Approval Requirements

Prior to conducting any PAO flight operations, the contractor shall satisfactorily complete an initial GFR inspection and pass a NAVAIR Safe-for-Flight (SFF) inspection. The contractor shall:

- Support the GFR and the NAVAIR Certification Authority with all requested documentation
- Maintain accurate configuration tracking through Pre-Configuration Approval (PCA) and Final Configuration Approval (FCA) processes, if applicable
- Ensure no aircraft is operated on contracted PAO operations until configuration has been reviewed and determined acceptable for SFF release

5.8. Notification of Proposed Aircraft Changes

The contractor shall notify the CAS Class Desk and GFR in writing of all proposed changes to the aircraft, associated systems, or configuration that may affect airworthiness or safety-of-flight prior to implementation. Notifications shall include:

- Description of the proposed change and justification
- Analysis of impacts to airworthiness, performance, or mission suitability
- Proposed timeline for implementation and documentation updates
- Updated substantiation if required by the IFC or SFF process
- Changes shall not be implemented without Government concurrence and, if applicable, update to the airworthiness baseline or SFF release

5.9. PAO Policy and Procedures

5.9.1. Public Aircraft Operations (PAO) Compliance

SLAT operations under this contract shall be conducted under PAO in accordance with 49 U.S.C. § 40125 and FAA AC 00-1.1B. The contractor shall:

- Provide a copy of the PAO Declaration letter to the FSDO having geographic oversight of the public aircraft missions and where the aircraft will be routinely maintained and operated.
- Adhere to 14 CFR maintenance and operational standards unless deviations are specifically authorized under PAO status

5.9.2. Government Flight Representative (GFR), Public Aircraft Operations (PAO), and Safe-for-Flight (SFF) Oversight

The contractor shall conduct all flight and ground operations in accordance with this contract, and DCMA Instruction 8210.1D

5.9.3. GFR Oversight and Authority

The Government will appoint a designated GFR and/or Alternate GFR to provide contract oversight. The GFR shall:

- Review and approve the contractor's Flight Operating Procedures (FOPs) and Ground Operating Procedures (GOPs)

- Approve all PAO flights
- Conduct initial and recurring facility, records, and operational inspections to ensure compliance with the contract and DCMA INST 8210.1D
- Serve as the primary point of contact for waivers, aircraft configuration changes, and operational authorizations

The contractor shall provide the GFR with unrestricted access to aircraft, flight records, maintenance documentation, training files, and related systems upon request during normal duty hours or as required to support safety-of-flight concerns.

5.9.4. Public and Civil Aircraft Operations (PAO and CAO) Compliance

All SLAT mission flights under this contract shall be conducted as Public Aircraft Operations (PAO). The contractor shall implement procedures to differentiate PAO and CAO flights and maintain documentation supporting the designation of each flight. PAO flights require:

- Government authorization (e.g., DD Form 3062)
- GFR approved GOPs and FOPs
- Use of qualified personnel in accordance with DCMA INST 8210.1D and GFR approved FOPs/GOPs

The Contractor shall be responsible for ensuring aircraft missions remain within the PAO scope and for coordinating documentation and notifications as required by the FAA and contract terms. The Contractor shall coordinate with the GFR to identify which missions are to be performed under PAO. For any CAO flights, the Contractor must ensure compliance with FAA certification, maintenance, and operating limitations applicable to the aircraft's airworthiness certificate type (e.g., standard or special airworthiness).

5.9.5. Safe-for-Flight (SFF) Determination

No flight operations shall be conducted until the contractor has received either a Safe-for-Flight (SFF) or Conditionally Safe-for-Flight determination from NAVAIR. The contractor shall:

- Submit all required substantiation data as outlined in Contract Section J, Attachment 2 – PAO Airworthiness Checklist IAW Contract Exhibit A, CDRL A002
- Submit all required PAO documentation IAW Contract Exhibit A, CDRL A003. GFR approved FOPs/GOPs are required at least 30 days prior to the start of pilot training, aircraft maintainer training, and PAO flight operations
- Support the GFR and NAVAIR SFF team with documentation, briefings, and facility access during inspections
- Address any deficiencies identified during the GFR and SFF inspection within 30 calendar days, or as directed by the GFR

5.9.6. GFR Notification Requirements

The contractor shall notify the GFR in advance of the following events:

- Any change to aircraft configuration, mission systems, or modifications that affect airworthiness or PAO eligibility
- Any relocation of aircraft operations to a new facility or base not previously surveyed under SFF criteria
- The introduction of a new aircraft type, mission profile, or subcontractor supporting flight operations

Changes may not be implemented until the Government concurs and, if applicable, updates are reflected in the current SFF documentation.

5.9.7. Waiver Requests

The contractor shall comply with all requirements in DCMA INST 8210.1D and this contract. If deviations are necessary, the contractor shall submit written waiver requests to the GFR with the following:

- Justification for the waiver
- Impact and risk assessment
- Risk mitigation strategy
- Duration and scope of the waiver

Waivers affecting aircraft operations, safety of flight, or configuration shall not be implemented until approved by the GFR and, where required, by the designated waiver authority (e.g., NAVAIRSYSCOM).

5.9.8. Ground and Flight Operating Procedures (GOPs / FOPs)

The contractor shall develop, implement, and maintain standard Flight Operating Procedures (FOPs) and Ground Operating Procedures (GOPs) to govern all aviation operations conducted under this contract. These procedures shall be developed in accordance with DCMA INST 8210.1D, NAVAIRINST 13034.1G, and other applicable civil and military guidance.

5.9.9. FOP/GOP Development and Approval

The contractor shall submit FOPs and GOPs to the GFR for review within 30 calendar days after contract award, IAW Contract Exhibit A, CDRL A003. All procedures must be current, comprehensive, and aligned with the specific scope of work for Sonobuoy Lot Acceptance Testing (SLAT) operations. GFR approved FOPs/GOPs are required at least 30 days prior to the start of pilot and maintainer training, aircraft modifications, and PAO flight operations. Revisions to FOPs or GOPs shall not be implemented without prior GFR review and written approval. Procedures must address all relevant operational, safety, and mission requirements including, but not limited to:

- Aircrew qualifications and rest limitations
- Aircraft servicing and fueling
- Preflight, inflight, and postflight checklists
- Launch system operations and safety measures

- FOD prevention, towing, marshalling, and ramp operations
- Emergency procedures and mishap response

5.9.10. Applicability to Subcontractors

The contractor shall ensure that any subcontractors conducting flight or ground operations under this contract operate in full compliance with the prime contractor's GFR-approved FOPs and GOPs. The contractor remains fully responsible for monitoring and enforcing compliance among subcontractors.

5.9.11. Documentation and Distribution

Approved FOPs and GOPs shall be readily available to all flight and ground personnel at the point of execution. The contractor shall maintain records of the most current GFR-approved versions and track all revisions and approvals. Electronic or hard-copy distribution systems shall be established and maintained to ensure consistent access to current procedures across all operational locations.

5.9.12. Government Flight Representative (GFR) Inspections

In accordance with DCMA INST 8210.1D and applicable Navy guidance, the GFR shall conduct recurring oversight of the contractor's flight and ground operations. This includes reviews of the contractor's Flight Operating Procedures (FOPs), Ground Operating Procedures (GOPs), and related facilities and records to ensure safe, compliant execution under Public Aircraft Operations (PAO) authority.

Prior to the start of any contracted flight operations, the designated PMA-226 GFR will perform an initial survey. The survey results will be forwarded to the NAVAIR Safe-for-Flight (SFF) team for review and consideration during the contractor's SFF evaluation. Upon receipt of an SFF or Conditionally-SFF determination, the contractor may commence PAO flight and ground operations.

Once operational, the GFR will conduct recurring surveys in accordance with DCMA INST 8210.1D. Each survey will assess the contractor's adherence to its approved FOPs, GOPs, contract terms, and applicable service guidance. Survey results and any observations or discrepancies will be submitted to the Contracting Officer (CO) for endorsement and subsequent delivery to the contractor.

The contractor shall correct all deficiencies within 30 calendar days of receipt of the final survey report, unless otherwise directed by the GFR. Revised FOPs and GOPs incorporating corrective actions must be submitted for GFR approval within the same timeframe.

5.9.13. NAVAIR Safe-for-Flight (SFF) Inspections

The contractor shall support a Safe-for-Flight (SFF) inspection by the NAVAIR SFF team prior to commencement of flight operations under this contract. The GFR will notify the SFF team when the contractor is ready for assessment. Flight operations may not begin until an SFF determination is formally issued.

Subsequent SFF inspections are required if any of the following conditions occur during the contract period of performance:

- The contractor relocates to a new facility, airport, or operational location not previously evaluated by the SFF team, where operations will occur for more than 30 days in a fiscal year
- A new aircraft type or T/M/S (as defined by the FAA) is being introduced to support the contracted mission

Any findings of non-compliance shall be resolved by the contractor. Revisions to procedures must be submitted IAW Contract Exhibit A, CDRL A003, within 30 days of receiving the final inspection results.

5.9.14. Management Plan (MP) and Procedures

The contractor shall develop, implement, and maintain a comprehensive Management Plan (MP) in accordance with DCMA INST 8210.1D. The MP shall be submitted in accordance with Contract Exhibit A, CDRL A003, and must describe the contractor's approach to managing all aspects of PAO flight and ground operations under this contract.

The contractor is responsible for identifying and correcting all deficiencies noted by the GFR, and for ensuring the effectiveness of its internal safety, quality control, and compliance systems. Procedures must address both prime and subcontractor operations and be continuously maintained to reflect the scope and nature of ongoing operations.

If the contractor holds a valid FAA 14 CFR § 121 or 14 CFR § 135 certificate, applicable FAA-approved procedures may be used to satisfy relevant portions of the required FOPs/GOPs, subject to GFR review and approval.

Referenced or supporting documents (e.g., SOPs, technical instructions, QA manuals) must be made available for review and become part of the GFR approval baseline.

5.9.15. NAVAIR Aviation Maintenance Management Team (AMMT) Inspections

The NAVAIR AMMT shall inspect the contractor's aircraft, maintenance facilities, records, and GOPs within 12 to 24 months after contract performance begins, and at similar intervals thereafter. These inspections will occur at each location where maintenance is performed on aircraft operating under a NAVAIR-issued Interim Flight Clearance (IFC).

The contractor will receive a report of each AMMT inspection and shall implement corrective actions in accordance with AMMT direction. The contractor must maintain full cooperation with AMMT personnel and provide access to all facilities, documentation, and systems required to support the inspection.

5.9.16. Flight and Ground Operating Procedures (FOPs and GOPs)

The contractor shall establish and maintain standard Flight Operating Procedures (FOPs) and Ground Operating Procedures (GOPs) in accordance with DCMA INST 8210.1D and all

applicable civil and military aviation regulations. FOPs and GOPs shall be submitted to the GFR for review IAW Contract Exhibit A, CDRL A003, and are required to be GFR-approved at least 30 days prior to the start of any training or flight operations. Revisions must also be submitted to the GFR for approval before implementation. The contractor is responsible for the flow-down of and compliance with these procedures for all subcontractors.

As this is a Contractor-Owned, Contractor-Operated (COCO) contract, procedures shall be developed in accordance with DCMA INST 8210.1D, Appendix 9A. Per the instructions within Appendix 9A, the contractor shall use Appendix 3A (Standard Procedures) as the foundational baseline and then apply the specific modifications and lesser requirements outlined in Appendix 9A to create a comprehensive set of procedures tailored to the COCO environment.

While the contractor is responsible for developing a comprehensive set of procedures derived from this process, the Government has identified specific procedures that are critical to mission safety and risk management. Therefore, the contractor's final submitted GOP manual must, at a minimum, contain distinct, approved procedures for every topic listed in Table 1.

Table 1: Required GOPS procedures to conduct PAO / State Operations	
Section 5	Description
5.4.3	Testing
5.4.4	Recurring Training
5.7	Engine/APU/GTC Qualification Program
5.9	Vehicle and Powered Equipment Operation
5.10	Aircraft Servicing
5.11	Aircraft Ground Handling
5.12	Aircraft/equipment hydraulic fluid analysis program
5.13	Weight and Balance
5.18	Hangaring of Aircraft
Section 6	Description
6.3.3	Severe Weather
6.4.2	Aircraft Damage Reporting Procedures

5.9.17. Authorization of PAO Flight Operations

All SLAT operations shall be conducted under Public Aircraft Operations (PAO) as governed by FAA AC 00-1.1B, DCMA INST 8210.1D, and NAVAIRINST 13034.1G. Flight operations may not commence until the contractor receives an SFF or Conditionally-SFF determination from NAVAIR. All SLAT missions shall be conducted during daylight hours under Visual Meteorological Conditions (VMC) as coordinated through PMA-264 test team personnel and range authorities. Use of CAO status for any portion of a SLAT test mission is not authorized under this contract. Any exceptions must be pre-coordinated with and approved in writing by the GFR.

5.9.18. PAO Flight Approval

The Contractor shall obtain written approval from the GFR prior to conducting any PAO flight operations. All PAO flight operations shall be planned and executed in accordance with DCMA INST 8210.1D. The Government assumes no risk under the Ground and Flight Risk Clause (GFRC) for flights not previously approved in writing by the GFR. The Contractor shall coordinate with the COR and GFR to ensure that all contract flight operations are executed safely, with full compliance to approved procedures and government direction.

5.9.19. Mishap Prevention and Reporting

The contractor shall develop, implement, and maintain a proactive mishap prevention program in accordance with DCMA INST 8210.1D, Section 6 (Aviation Safety Management System), and applicable Service and FAA guidance.

5.9.20. Mishap Prevention Program

The contractor shall establish and maintain an Aviation Safety and Mishap Prevention Program IAW DCMA INST 8210-1D and implement a Safety Management System (SMS) that includes hazard identification, risk mitigation, safety assurance, and safety promotion. The contractor shall support GFR reviews and participate in Government-led safety assessments or Program Management Reviews (PMRs) addressing mishap trends or leading indicators. All flight and maintenance personnel shall be briefed on SMS elements and emergency procedures prior to beginning work on this contract.

5.9.21. Mishap Response Plan (MRP)

The Contractor shall establish and execute a Government-approved MRP (submitted IAW Exhibit A, CDRL A002) and shall establish policies, responsibilities, and actions to be initiated if any aircraft becomes overdue, involved in an accident, incident, mishap, experiences a near miss, unexpected proximity or runway incursion incident. Reporting requirements of this section would include (not an inclusive list) aircraft passing each other with vertical or horizontal separation of less than 1000', or when the proximity between aircraft is unexpected (is less than mission parameters). At a minimum, this plan shall also include procedures that conform to USC Title 49 § 830 National Transportation Safety Board (NTSB).

5.9.22. Mishap Reporting Requirements

Reporting shall be conducted in accordance with DCMA INST 8210.1D and applicable Navy/NAVAIR mishap classification and investigation guidance. The contractor shall cooperate fully with all Government mishap investigations and root cause analyses.

Reporting the requirements of this section would include the items below, but this is not an all-inclusive list. The contractor shall immediately notify the GFR, COR, and PMA-264 test team personnel in the event of any accident, incident, mishap, near-miss, or hazardous occurrence involving:

- Aircraft damage or abnormal inflight conditions
- System or equipment failure affecting safety of flight

- Ground handling incidents involving launch systems, GSE, or sonobuoys
- Personnel injury or loss of mission capability
- Aircraft passing each other with vertical or horizontal separation of less than 1000'
- Proximity between aircraft is unexpected (less than any pre-briefed mission parameters)

The Contractor shall immediately report all aircraft accidents and incidents IAW its MRP, GOPs and FOPs.

- After contacting the local base Commanding Officer, Safety Officer and Operations Officer (when applicable), the Contractor shall immediately contact the COR and the GFR
- The Contractor shall make continuous attempts to contact the COR and GFR until successful; leaving a voicemail alone is not sufficient

Within 7-calendar days following any accident, incident, or occurrence where aircraft damage has occurred (this may include damage to other than Contractor aircraft where the Contractor aircraft is in the vicinity of an incident and the personnel on board are able to provide witness accounts), or any 14 CFR regulation was violated, the Contractor shall submit a detailed written report to the COR and GFR outlining:

- Flight event number (per published schedule)
- Name and crew position for each person that was onboard the aircraft
- Any crew statements
- Results of any drug and/or alcohol testing (if required by the Contractor's drug and alcohol testing program)
- Logbook entries
- All other evidence that helps substantiate the event details
- Any lessons learned from the event, and any procedural updates resulting from the event.

Should new information be learned after the 7-calendar day reporting period, such new information as well as any new corrective procedural changes shall be forwarded to the COR and GFR within 7-calendar days from when the new information is identified.

5.10. Fuel

5.10.1. Fuel Purchases

This is a dry contract; fuel is not purchased under the contract. The Government will provide access to fuel at United States Government (USG) installations and civil airports via the Defense Logistics Agency (DLA) Energy Into-Plane Contract and Fixed Base of Operations (FBO) networks. The Government will issue Aviation Into-Plane Reimbursement (AIR) cards for each of the contractor's aircraft. Fuel procurement shall follow this priority in order:

- USG military airfields (when available)
- DLA-contracted "into-plane" merchants
- Non-contract commercial merchants (by exception only)

5.10.2. Fueling Locations

Per NAVSUP Instruction 4200.97A, the contractor shall use DLA-contracted fuel providers at commercial locations whenever military facilities are unavailable. When fuel is purchased at non-DLA “into-plane” civilian airports, the contractor shall record the circumstances and provide justification for the purchase. Fuel from non-contract commercial vendors shall only be used with prior approval from the COR. Fuel reimbursement is required for any fuel purchased using the AIR Card that is later consumed during:

- Maintenance flights or ferry flights
- Ground turns for maintenance
- Training flights
- Any operation outside the scope or tasking of this contract (e.g., non-exclusive use)

Reimbursement shall occur within 60 calendar days of the fuel being expended.

5.10.3. Fuel Tracking:

The contractor shall track all fuel consumption and provide supporting documentation IAW Contract Exhibit A, CDRL A004, including:

- Signed, legible fuel receipts
- Government provided fuel consumption tracker

5.10.4. Fuel / AIR Card Training

The Contractor shall ensure all personnel authorized to use the Government AIR Card complete all required training. All AIR Card users shall complete initial training at least 30 days prior to the first contracted flight and complete refresher training every two years thereafter. Training shall be conducted in accordance with the Department of the Navy (DoN) Consolidated Card Program Management Division (CCPMD) training curriculum.

The Contractor can utilize the following methods for training completion:

- Standard Method (Local Delivery): The COR shall provide the Contractor with the most current official CCPMD training package (e.g., Microsoft PowerPoint slides). The Contractor shall use this package to conduct and document local training for all card users
- Alternate Method (CAC Holders): If a card user holds a valid CAC, they may complete the requirement by using the online CCPMD training portal (https://my.navsup.navy.mil/webcenter/portal/ccpmd_ac/Training) and providing the system-generated certificate

Following the completion of either initial or refresher training, the Contractor shall:

- Ensure each user signs a Card User Statement of Understanding (SOU)

- Submit electronic copies of the training certificates and the signed SOUs to the Government IAW Contract Exhibit A, CDRL A005

5.10.5. Landing Fees

The Contractor's aircraft operating under this contract are not subject to landing fees at DoD-controlled airfields. However, landing fees incurred at commercial airfields, while operating on this contract, must be applied to the Government fuel card.

6.0 PERSONNEL QUALIFICATIONS

The contractor shall plan, coordinate, and execute Sonobuoy Lot Acceptance Testing (SLAT) flight operations in accordance with Government tasking, approved procedures, and all applicable regulatory and operational directives. Operations shall be conducted in a safe, efficient, and coordinated manner that supports the timely evaluation of production and pre-production sonobuoys.

6.1. Training Requirements

The Contractor shall establish and maintain GFR-approved training programs to ensure all personnel are qualified for their assigned duties. All training shall be conducted in accordance with DCMA INST 8210.1D, this PWS, and the specific governing standards identified below for each functional role. Pilot training and qualifications shall be governed by the Federal Aviation Regulations, primarily 14 CFR Parts 61 and 91, as supplemented by the requirements of this PWS. Training for maintenance and ground support personnel shall be governed by the applicable FARs (e.g., 14 CFR Part 43), Original Equipment Manufacturer (OEM) requirements, and other industry-standard practices.

6.2. Aircrew Training and Currency

The Contractor's training programs shall address initial qualification and annual recurrent training. No flight training may be conducted during contracted flight operations. The GFR-approved programs shall include, at a minimum, the following topics for each role:

6.2.1. Aircrew Training and Currency

Flight Crew Training Topics. The Flight Crew Training Program shall ensure pilots are proficient in:

- Aircraft systems, performance, and limitations
- Emergency procedures, command authority, and safety of flight decision-making
- Public Aircraft Operations (PAO) responsibilities and risk management
- Crew Resource Management (CRM)
- Oceanic and Remote Airspace Procedures
- Sonobuoy mission flight profiles, including airspace and timing coordination
- Marine Mammal Mitigation Awareness and procedures
- All other applicable requirements of 14 CFR Parts 61 and 91 necessary to maintain

qualifications and currency

6.2.2. Mission Specialist Training Topics

The Mission Specialist Training Program shall ensure Sonobuoy Operators are proficient in:

- Sonobuoy system operation, including handling, loading, and deployment procedures.
- Mission-specific procedures, including drop pattern execution and verification
- Mission system emergency procedures, including hung stores, jettison, and lithium battery fire response
- Duties and responsibilities during all aircraft emergencies

The Contractor shall maintain training records and submit certification documentation to the GFR upon request or IAW Contract Exhibit A, CDRL A003.

6.3. Public Aircraft Operations (PAO) Flight Familiarization

The Contractor shall ensure all personnel involved in flight operations are briefed on the nature of Public Aircraft Operations. All pilots shall receive in-depth training on PAO authority, limitations, and responsibilities in accordance with FAA AC 00-1.1B and DCMA INST 8210.1D. The contractor shall document and retain pilot qualifications, PAO authorizations, and assignment history for Government review upon request.

6.4. Pilot Qualifications, Experience, and Proficiency

All contractor pilots assigned to support SLAT operations shall meet the minimum qualifications and experience/proficiency requirements specified in this section. Unless waived in writing by the GFR, the contractor shall comply with the most restrictive applicable provisions from:

- 14 CFR §§ 61 and 91
- DCMA INST 8210.1D
- This Performance Work Statement (PWS)

All contracted flights shall be crewed with a Pilot in Command (PIC) and Second in Command (SIC). For safety assurance, no single-pilot operations are permitted under this contract regardless of aircraft certification basis.

6.4.1. Minimum Qualifications

All Contractor pilots shall obtain and maintain the following qualifications:

Table 2: Minimum Pilot Qualifications		
Category	PIC	SIC
Pilot Certification (Contractor aircraft class & category)	Commercial Pilot Certificate	Commercial Pilot Certificate
Instrument Rating	Required	Required

Table 2: Minimum Pilot Qualifications		
Category	PIC	SIC
Valid FAA Second Class Medical Certificate	Required	Required
FAA Aircraft Type Rating (Contractor aircraft class & category)	As Required per 14 CFR § 61.31	As Required per 14 CFR § 61.31

6.4.2. Pilot Experience and Proficiency Requirements

The minimum experience and currency requirements are outlined in Table 3.

Table 3: Pilot Currency, Experience, and Proficiency Requirements		
Category	PIC	SIC
Total Flight Time ¹	>1,500 hours ²	>750 hours ³
Instrument Flight Time ⁴	>75 hours	>75 hours
Instrument Currency	Maintained per 14 CFR § 61.57	Maintain Currency to PIC Standards (per 14 CFR § 61.57)
Annual Proficiency Check	Per 14 CFR § 61.58	Annual Competency Check per GFR Approved Training Program

Notes:

1. A maximum of 50 hours in a qualified flight simulator may be credited
2. 900 hours if a former military pilot
3. 450 hours if a former military pilot
4. A minimum of 50 hours must be in actual instrument conditions

6.4.3. Contractor Instructor Pilot (IP) Requirements

The contractor shall designate qualified Instructor Pilots (IPs) to conduct all pilot training and proficiency checks required by the GFR-approved Training Program.

- Designation: IPs shall be designated in writing by the contractor's Chief Pilot. The GFR shall be provided a copy of the designation letter for all authorized IPs
- Minimum Criteria: At a minimum, all designated IPs must:
 - Meet or exceed the minimum experience thresholds for Pilot in Command (PIC) as defined in this PWS
 - Have at least 100 hours of flight time as PIC in the make and model of aircraft used for instruction

6.4.4. Recurrent Qualification and Experience

To maintain qualification, pilots shall complete annual checks as follows. The loss of any required currency or certification shall disqualify a pilot from SLAT flight operations until the deficiency is rectified and documented.

- Mission-Specific Tasks: All annual checks for both PIC and SIC must evaluate, at a minimum, proficiency in:
 - Aircraft emergency and abnormal procedures
 - Sonobuoy mission planning and flight profiles
 - Crew Resource Management (CRM) and human factors
- Pilot in Command (PIC): The PIC shall complete an annual proficiency check that satisfies all requirements of 14 CFR § 61.58 in addition to the mission-specific tasks
- Second in Command (SIC): The SIC shall complete an annual competency check as defined in the GFR-Approved Training Program, which must include all mission-specific tasks

Loss of currency or certification shall disqualify a pilot from participating in SLAT flight operations until rectified and documented.

6.5. Sonobuoy Operator Requirements

The Contractor shall provide a qualified Sonobuoy Operator for each SLAT mission. The qualifications for this position are governed by the requirements of DCMA INST 8210-1D and the GFR-approved training program detailed herein.

6.5.1. Role and Responsibilities

- Separation of duties: A pilot serving as a required flight crewmember (PIC or SIC) shall not perform Sonobuoy Operator duties on the same flight. Likewise, an operator shall not perform any flight crew duties
- Government Operations: If a Government representative is performing sonobuoy operations, a Contractor-qualified Sonobuoy Operator shall remain on board to provide safety oversight

6.5.2. Operator Qualifications

- Medical Requirement: All Sonobuoy Operators shall obtain and maintain, at a minimum, a valid FAA Second-Class Medical Certificate. This is a mandatory requirement.
- Training and Proficiency: Operator qualification shall be based on the successful completion of a comprehensive, GFR-approved Mission Qualification Training Program as defined in section 6.5.3. The purpose of this program is to ensure each operator possesses the required proficiency for all specified duties, in accordance with the governing principles of DCMA INST 8210-1D.

6.5.3. Mission Qualification Training

The Contractor shall establish and maintain a GFR-approved Sonobuoy Operator Training Program. The program shall cover initial and annual recurrent training, and all operators must demonstrate proficiency in:

- Sonobuoy handling, loading, and launcher safety procedures
- Aircraft emergency egress procedures
- Execution of all SLAT mission profiles as defined in this PWS
- Use of installed aircraft communication equipment

6.5.4. Mission Operational Requirements

- Briefings: The Sonobuoy Operator shall be included in all mission briefings and debriefings. Prior to each flight, the operator must be fully briefed on the mission's drop pattern, aircraft limitations relevant to the mission, and abort criteria
- In-Flight Duties: During flight operations, the operator shall:
 - Maintain positive communication with the flight crew
 - Load, arm, and deploy sonobuoys in accordance with the mission profile
 - Observe system performance and immediately report any anomalies to the PIC
 - Comply with all range safety and marine mammal mitigation procedures

6.6. Other Mission Support Personnel

With prior written approval from the GFR, the Contractor may carry additional military, Government civilian, or other contractor personnel on board to support the mission through testing, training, or observation. These individuals are classified as qualified non-crewmembers and are not considered passengers. No specific training is required for these personnel under this PWS; however, they shall receive an appropriate safety briefing prior to flight.

6.7. Maintenance Personnel Training

The Contractor is responsible for ensuring the continued airworthiness of the aircraft and its mission systems. To this end, the Contractor shall establish and maintain a GFR-approved Maintenance Training Program.

6.7.1. Technician Qualifications

All maintenance, preventative maintenance, and alterations shall be performed or supervised by technicians holding a valid Mechanic Certificate with Airframe and Powerplant (A&P) ratings, in accordance with 14 CFR Part 65.

6.7.2. Training Program Topics

The GFR-approved Maintenance Training Program shall ensure all technicians are proficient in:

- Aircraft systems and required inspection procedures
- Sonobuoy launch system integration, handling, and maintenance
- Ground Support Equipment (GSE) operation and safety
- Hazardous materials (HAZMAT) handling and disposal
- Foreign Object Damage (FOD) prevention and tool control programs

The contractor shall maintain training records and submit certification documentation to the GFR upon request or IAW Contract Exhibit A, CDRL A003.

7.0 PERFORMANCE METRICS

The Government will evaluate contractor performance using the metrics defined in this section. These metrics provide objective, measurable criteria for assessing the contractor's ability to meet the performance requirements set forth in this PWS. Each metric will be tracked and assessed on a recurring basis; however, performance will be formally evaluated on an annual basis aligned with the Contractor Performance Assessment Reporting System (CPARS) reporting cycle. The metrics will not be averaged over the full period of performance but will reflect contractor performance during each distinct CPARS reporting period. These evaluations will inform CPARS entries, quality assurance assessments, and may support corrective actions or future award determinations. Contractor performance will be assessed in accordance with the Government's Quality Assurance Surveillance Plan (QASP), provided under Contract Section J, Attachment 3.

7.1. Mission Success Rate (MSR)

The Mission Success Rate (MSR) is calculated monthly as the number of successful missions executed divided by the number of missions scheduled, excluding missions canceled due to adverse weather or by Government direction (e.g., vessel unavailability, range restrictions, or scheduling changes). This metric is the primary measure of mission performance and reliability. The Contractor shall report the MSR as part of their monthly Progress, Status and Management Report IAW Contract Exhibit A, CDRL A006. The Government will use this metric to evaluate ongoing performance and support CPARS evaluations.

Successful Mission:

- A mission is considered successful when the aircraft launches, transits, and performs its assigned SLAT mission in the designated operating area. A mission is still considered successful if terminated early at Government direction (e.g., early completion or sensor failure unrelated to the contractor)
- All sonobuoys scheduled for deployment are successfully launched during a single, continuous sortie without aircraft substitution or additional flight events

Aborted Mission:

- A mission is considered aborted when it fails to launch or complete due to contractor equipment failure, personnel error, or noncompliance with pre-mission requirements
- Any mission requiring more than one flight event to deploy the planned sonobuoy load

will be considered aborted, unless explicitly authorized by the Government due to safety-of-flight conditions

The formula for computing MSR will be:

$$MSR (\%) = \left(\frac{\text{Number of Successful Missions}}{\text{Scheduled Missions} - \text{Gov't or Weather Cancellations}} \right) \times 100$$

Performance Rating Scale:

Mission Success Rate (%)	Performance Rating
99.0 - 100.0%	Exceptional
97.0 - 98.9%	Very Good
95.0 - 96.9%	Satisfactory
90.0 - 94.9%	Marginal
< 90.0%	Unsatisfactory

7.2. Sonobuoy Launch Compliance Rate

The Contractor will ensure that a minimum number of sonobuoys, as specified by the Government for each mission, are successfully launched. Percentage of SLAT missions in which the contractor meets or exceeds the Government-specified minimum number of sonobuoy launches (typically 32 per mission but may vary by test requirement).

The formula for computing MSR will be:

$$\text{Compliance Rate } (\%) = \left(\frac{\text{Number of Compliant Missions}}{\text{Total Missions Executed}} \right) \times 100$$

Performance Rating Scale:

Compliance Rating (%)	Performance Rating
99.0 - 100.0%	Exceptional
97.0 - 98.9%	Very Good
95.0 - 96.9%	Satisfactory
90.0 - 94.9%	Marginal
< 90.0%	Unsatisfactory

Data sources will include, but are not limited to, Progress, Status and Management Reports (CDRL A006), Government Range Data / Vessel Correlation, Flight Video / Launch Log. Mission-specific sonobuoy minimums will be identified in the pre-mission brief by the Government. Compliance data shall reflect that all scheduled sonobuoy launches were completed within a single flight event.

7.3. Aircraft Availability Rate

The Aircraft Availability Rate measures the contractor's ability to provide at least one fully

mission-capable aircraft on each scheduled mission day. This metric supports evaluation of fleet readiness, pre-mission maintenance effectiveness, and contract capacity to meet operational demand. The Contractor shall report aircraft availability as part of their monthly Progress, Status and Management Report IAW Contract Exhibit A, CDRL A006.

Available Aircraft:

- An aircraft is considered available if it is fully mission-capable at the designated mission crew brief time.

Exclusions:

- Pre-coordinated depot-level maintenance periods or Government-directed stand-downs do not count against availability.

The formula for computer Aircraft Availability will be:

$$\text{Availability (\%)} = \left(\frac{\text{Days with Aircraft Available}}{\text{Scheduled Mission Days}} \right) \times 100$$

Performance Rating Scale:

Availability (%)	Performance Rating
99.0 - 100.0%	Exceptional
97.0 - 98.9%	Very Good
95.0 - 96.9%	Satisfactory
90.0 - 94.9%	Marginal
< 90.0%	Unsatisfactory

7.4. Aircrew Qualification Currency

The Aircrew Qualification Currency metric evaluates the contractor's ability to maintain a fully staffed and qualified aircrew capable of executing scheduled missions without delay or cancellation. This metric is specifically based on the number of missions canceled, delayed beyond acceptable crew duty limits, or not executed due to the contractor's failure to provide qualified and current flight crew in accordance with DCMA INST 8210.1D, the contractor's Flight Operations Procedures (FOPs), and this PWS.

Qualified Aircrew:

- A crew member is considered qualified if they possess current medical clearance, regulatory flight currency, and mission-specific training necessary for their role at the time-of-flight execution.

Cancellation Criteria:

- Any missions not launched or significantly delayed (beyond duty day limits or into

noncompliance with flight scheduling) due to:

- Unavailability of minimum required flight crew
- Lapsed qualifications or training
- Medical disqualification
- Improper scheduling or rest period management

The formula for computer Aircrew Qualification Currency will be:

$$\text{Aircrew Qualification Rate (\%)} = \left(\frac{\text{Scheduled Missions} - \text{Crew Related Cancellations}}{\text{Scheduled Missions}} \right) \times 100$$

Performance Rating Scale:

Qualification Impact Rate (%)	Performance Rating
99.0 - 100.0%	Exceptional
97.0 - 98.9%	Very Good
95.0 - 96.9%	Satisfactory
90.0 - 94.9%	Marginal
< 90.0%	Unsatisfactory

7.5. CDRL Deliverable Timeliness

This metric tracks the Contract Data Requirements List (CDRL) Deliverable Timeliness, which reflects the contractor's ability to meet contractual reporting deadlines. Timely deliverables are critical to mission oversight, planning, and regulatory compliance. The Contractor shall report deliverables as part of their monthly Progress, Status and Management Report (CDRL A006).

On-Time Submission:

- A deliverable is considered on time if submitted by the contractual due date or within an officially granted extension.

Performance Rating Scale:

On-Time Submissions (%)	Performance Rating
99.0 - 100.0%	Exceptional
97.0 - 98.9%	Very Good
95.0 - 96.9%	Satisfactory
90.0 - 94.9%	Marginal
< 90.0%	Unsatisfactory

7.6. Fuel Consumption Reporting Accuracy

The Fuel Consumption Reporting Accuracy metric evaluates the contractor's ability to

accurately track, document, and report aircraft fuel consumption using their internal tracking tools and submitted documentation. This metric is based on the reconciliation of contractor-submitted data against official Government AIR Card transaction records. All variances must be annotated and justified in the CDRL A004 submission. This metric will be reviewed monthly by the COR and considered during performance reviews and CPARS reporting.

Reporting Requirements:

- The contractor shall submit a monthly fuel report IAW Contract Exhibit A, CDRL A004 using the standardized format provided by the Government. The Contracting Officer's Representative (COR) and the CAS Fuel Manager will provide the contractor with a reporting template that includes all required data fields. The template will identify mandatory elements such as fueling date, location, gallons dispensed, aircraft tail number, flight event number, receipt verification, and reconciliation of any applicable ancillary charges (e.g., ramp fees, additives, taxes).

Validation Criteria:

- Each entry is considered accurate when the contractor-submitted tracker and receipts:
 - Match the official AIR Card transaction record on date, gallons, location, and aircraft/event
 - Include signed fuel receipts
 - Reflect the ancillary charges present in the actual billing (if applicable)

Discrepancies include:

- Mismatched dates, gallons, or locations
- Omission of flight event or tail number
- Unsigned receipts
- Missing or undocumented ancillary charges
- Transactions found in AIR Card records that are not reported in the contractor's tracker

Assessment Basis:

- The number of accurate, reconciled transactions divided by the total number of actual fuel transactions performed during the month. The formula for computer Aircraft Availability will be:

$$\text{Fuel Reporting Accuracy (\%)} = \left(\frac{\text{Number of Reconciled Transactions}}{\text{Total Fuel Transactions}} \right) \times 100$$

Performance Rating Scale:

Accuracy Rate (%)	Performance Rating
99.0 - 100.0%	Exceptional
97.0 - 98.9%	Very Good

95.0 - 96.9%	Satisfactory
90.0 - 94.9%	Marginal
< 90.0%	Unsatisfactory

7.7. GFR Safety Inspection Results

The Government will evaluate contractor performance based on the contractor's adherence to its approved procedures and the effective resolution of any identified non-compliances. All contractual non-compliances will be documented via the Naval Aviation Enterprise (NAE) Corrective Action Request (CAR) process, with finding levels (Level I, II, III, or IV) defined in accordance with governing command guidance.

Performance Evaluation Ratings:

- **Exceptional:** The contractor demonstrates a mature, proactive safety culture that identifies and resolves potential issues before they become findings. The contractor receives no Level III or IV CARs during the rating period. Any minor findings are resolved with highly effective corrective actions that prevent recurrence.
- **Very Good:** For any Level II or III CARs received, the contractor's response is swift and effective. They provide robust Root Cause Analysis (RCA) and implement effective Corrective Action Plans (CAPs) that benefit the Government by restoring confidence and improving processes. No repeat findings occur for the same deficiency within the rating period.
- **Satisfactory:** The contractor adequately manages the CAR process. For any Level II or III CARs received, the contractor submits an acceptable and timely CAP and implements the required corrective actions.
- **Marginal:** The contractor's performance reflects a problem for which corrective actions have not been fully effective. This may be evidenced by untimely CAP submissions, repeat Level II findings for the same deficiency, or a failure to adequately address the root cause of a Level III finding.
- **Unsatisfactory:** An "Unsatisfactory" rating will be assigned if the contractor's corrective actions are ineffective, as evidenced by one or more of the following:
 - Receiving a Level IV CAR
 - A repeat Level III CAR for a previously addressed deficiency
 - An accumulation of CARs that demonstrates a systemic failure of the contractor's safety or quality management systems

8.0 CONTRACT STATUS REPORTING

The contractor shall provide routine and event-driven status reporting to ensure contract execution is transparent, measurable, and aligned with Government oversight needs. Reports

shall be submitted in accordance with the Contract Data Requirements List (CDRLs) and may be supplemented with verbal updates as directed by the COR.

8.1. Monthly Progress, Status and Management Report

The contractor shall submit a monthly Progress, Status and Management Report IAW Contract Exhibit A, CDRL A006. The report shall include the requirements of the DD Form 1423-1 and include:

- Summary of flight operations conducted (dates, flight hours, sortie counts)
- Aircraft availability and down-time
- Maintenance events and discrepancies of note
- Fuel reimbursement status
- Pilot and sonobuoy operator training completions and expirations
- Outstanding action items (e.g., waivers, inspections, documentation)
- Sonobuoy reconciliation: A summary accounting for all sonobuoys received, expended, and returned during the reporting period.
- Summary of any mission cancellations, delays, or safety events
- Post-Mission Data:
 - Mission success rate and flight hour utilization
 - Number and types of sonobuoys launched
 - Drop execution metrics and launch system performance
 - Observed safety or operational lessons learned
 - Suggestions for process improvement or future coordination

8.2. Operational Coordination and Daily Comms

During scheduled SLAT mission periods, the contractor shall establish daily operational coordination with PMA-264 test team personnel or their designated scheduling authority. This may include:

- Pre-mission coordination calls to review weather, objectives, aircraft status, and mission setup
- Daily reporting of aircraft status, crew availability, and drop execution results
- Immediate notification of mission aborts, delays, or safety-related events

The contractor shall identify a primary and alternate point of contact for all flight support coordination and ensure they are available during the mission period. Daily updates may be transmitted via email or other means as directed by the Government.

8.2.1. Daily Mission Reporting (During SLAT Events)

For scheduled SLAT mission periods, the contractor shall provide a Daily Status Report to PMA-264 test team personnel. Reports shall be submitted via email or secure means and include:

- Aircraft tail number and status
- Flight crew assigned and their qualifications.

- Sonobuoys loaded and launched
- Mission start/end times and remarks
- Any aborted drops, anomalies, or delays

Daily reports are due to the COR and PMA-264 test team personnel within 2 hours of mission completion.

8.2.2. Ad Hoc Notifications

The contractor shall notify the COR, GFR, and PMA-264 test team personnel within 24 hours of any of the following:

- Loss or significant damage to an aircraft
- Unexpected grounding of an aircraft beyond 48 hours
- Personnel unavailability affecting mission capability
- Missed deliverables or IMS milestone slips
- Requests for waivers or deviations
- Any event that may impact contract performance or safety of flight

8.3. Meetings and Communications

The contractor shall maintain regular communication with the Government throughout the period of performance to ensure alignment on mission readiness, contract deliverables, compliance, and operational status. The following meetings and communication protocols are required:

8.3.1. Post-Award Conference (PAC)

Pursuant to FAR 42.5, Contractor personnel, to include contracting and management personnel, shall attend a PAC with the Government no later than 30 days after contract award at Marine Corps Air Station (MCAS) Cherry Point, North Carolina (NC) or other location (meeting may occur virtually) as determined by the Government. The purpose of the PAC is to establish mutual understanding of the contract requirements, schedules, roles, and expectations.

The conference shall be coordinated by the Contracting Officer (PCO) and should include:

- Government representatives: PCO, COR, GFR, Program Office, PMA-264 test team personnel, and technical team
- Contractor representatives: Program Manager, Operations Lead, Chief Pilot, Maintenance Lead, and Quality/Airworthiness Representative

The contractor shall, at a minimum, present their proposed meeting agenda, introductions of key personnel, organizational structure, communication plan, understanding of contract and PWS requirements, Capability Stand Up Integrated Master Schedule (IMS), major risk areas, and timeline for PAO readiness. The contractor shall submit a copy of their PAC briefing materials IAW Contract Exhibit A, CDRL A008. Meeting minutes and action items shall be documented and distributed IAW Contract Exhibit A, CDRL A00A.

8.3.2. Program Management Reviews (PMR)

The Government will schedule and conduct PMRs on a semi-annual basis at NAVAIRSYSCOM PMA-226, Cherry Point, NC, the Contractor's facility, or other locations as directed by the COR (meetings may occur virtually). The Contractor shall attend all PMRs, however no more than two (2) Contractor personnel may attend unless prior approval for more personnel is obtained from the COR. Program Management Reviews (PMRs) shall be conducted to assess performance, address risks, and review milestones. PMRs shall include a review of:

- Contract execution status
- Flight hour utilization and mission success rates
- Aircraft readiness and maintenance performance
- Open actions from GFR inspections, SFF findings, or AMMT reviews
- Safety events, lessons learned, and mishap prevention initiatives
- Current and projected staffing, training, and subcontractor status
- CDRL deliverable compliance

The Contractor shall make a presentation consisting of the following:

- Overview of the work accomplished to date or since last review, the projected plan of action for completion of contract effort, and handout material documenting presentations
- Identification and discussion of problems encountered, if any, and action taken to resolve the problems
- Identification and discussion of problems anticipated and the Contractor's plan of action for mitigation
- Feedback on CAS missions. Specifically discuss the Contractor's experience working as part of a team with other CAS Contractors (when applicable) and the Government, identifying successes and improvement areas

The contractor shall provide a copy of their PMR briefing package IAW Contract Exhibit A, CDRL A009. Meeting minutes and action items shall be documented and distributed IAW Contract Exhibit A, CDRL A00A.

9.0 OTHER PERFORMANCE REQUIREMENTS

9.1. Physical, Personnel, and Information Security Controls

The contractor shall ensure proper physical, personnel, and information security controls are in place to support execution of all contract requirements. Operations under this contract may take place on U.S. military installations, Federal ranges, and at contractor-owned facilities. The contractor shall comply with all applicable base regulations, DoD directives, and Government-furnished guidance regarding access and security.

9.1.1. Operational Security (OPSEC) Requirements

This contract involves access to and the generation of Controlled Unclassified Information (CUI). The contractor shall develop, implement, and maintain an OPSEC program to protect this

information and all mission-related activities from adversary collection and exploitation. The program shall comply with the requirements of DoDI 5205.02 (DoD OPSEC Program) and DoDI 5200.48 (Controlled Unclassified Information). The contractor's OPSEC program shall include the following:

- The development and submission of a formal OPSEC Plan IAW Contract Exhibit A, CDRL A00E. This plan must detail the procedures and controls used to protect Government-furnished data, sonobuoy configurations, test profiles, and operational schedules.
- An annual OPSEC briefing for all contractor personnel assigned to the contract.
- A process for reviewing and clearing all official and public-facing information related to this contract prior to release, which requires prior written approval from the Government.

9.2. Contractor Facility Basing Requirements

The contractor's base of operations shall be located within 50 nautical miles of Naval Air Station North Island in San Diego, CA, to support recurring flight operations. If the facility the Contractor selects does not have a Defense Logistics Agency (DLA) Government fuels contract, the Contractor shall be reimbursed for fuel only up to the Government contract fuel rate published by DLA.

The facility shall have appropriate infrastructure to support:

- Aircraft parking and servicing
- Sonobuoy storage and staging
- Ground Support Equipment (GSE) operations
- Secure documentation storage and aircrew briefing rooms
- Physical protection of government owned property and contractor-furnished mission systems

Any proposed relocation of the base of operations must be submitted in writing to the Contracting Officer and approved prior to execution. A new Safe-for-Flight (SFF) inspection may be required if relocation occurs.

9.2.1. Protection of Government Property

The contractor shall ensure the proper storage, handling, and safeguarding of Government Furnished Property (GFP), including sonobuoys, test equipment, launch system components, and data. Loss, damage, or compromise of Government property or data shall be reported to the COR within 24 hours, with a written follow-up submitted within 5 business days.

9.3. Access to U.S. Government Installations

Contractor personnel shall comply with all base access procedures and identification requirements for DoD installations (e.g., Common Access Card (CAC), DBIDS). The contractor is responsible for submitting all required base access requests and coordinating badges, background checks, and escort requirements in advance. Foreign nationals are not authorized access to U.S. military installations or participation in this contract unless specifically approved

in writing by the Government and processed through official Foreign Disclosure channels.

9.3.1. Common Access Cards (CAC) Eligibility

Contractor personnel requiring access to DoD networks, AIR Card training systems, or base facilities shall be eligible for and issued a CAC. The contractor shall coordinate with the COR to submit and manage CAC issuance and renewal requests. Common Access Cards (CACs) will only be issued to contractor personnel that:

- Have a valid, contract-related need,
- Are authorized by the COR,
- Meet Homeland Security Presidential Directive 12 (HSPD-12) criteria, and
- Have successfully passed a federal background investigation (See PWS Section 9.3.2).

The contractor shall notify the COR within 24 hours of any personnel changes involving CAC issuance or classified access. The contractor shall immediately confiscate CACs upon contract separation or revocation of access and return them by mail to the COR listed in Section G, Clause 5252.201-9501. The Contractor shall not destroy CACs under any circumstances. CACs are U.S. Government property and shall only be issued where access is clearly required to perform contract responsibilities. CACs are not to be issued for convenience.

9.3.2. Federal Background Investigations

Performance of work under this contract will require access to sensitive (unclassified and controlled unclassified) information, systems and/or equipment. Contractor personnel must be eligible to perform Non-Critical Sensitive work as defined by SECNAVINST 5510.30C via the Non-National Industrial Security Program (Non-NISP). The Government's Non-NISP requires personnel to receive and maintain (e.g. self-reporting, foreign travel) a favorably vetted and adjudicated Tier-3 investigation by the Government Security Office and ultimately the Defense Counterintelligence and Security Agency (DCSA) Adjudication Vetting Services (AVS). The Government Security Office shall initiate the Contractor's electronic investigation questionnaire application (eAPP) and do a preliminary screening of the Contractor's eAPP and fingerprints for suitability and derogatory information prior to performance. The Contractor employee shall provide all requested information pursuant to the Privacy Act of 1974. Fingerprinting requirements for contractors located outside of the government security office's local area shall be the responsibility of the Contractor.

The Contractor shall coordinate and ensure the provision of security badges required to allow Contractor personnel access to designated workspaces and materials; the Contractor shall comply with all applicable security requirements, abide by direction given by Military Police or other security personnel, and adhere to installation traffic laws.

Positions that require access to military installations, sensitive unclassified information, and/or system access only are as follows:

LABOR CATEGORY	DOD SECURITY ACCESS REQUIREMENT	NOTES
Operations: Aircraft Crewmembers and Qualified Non-Crewmembers	Favorable Local Access	• CAC Required • Access to CUI required • Non-NISP investigation through Government Security Office
Operations: Contractor Representatives (CR)	Favorable Local Access	
Operations: Airworthiness Representatives (AR)	Favorable Local Access	

9.3.3. Anti-Terrorism Training for Contractors

Contractor personnel requiring routine physical access to DoD installations, facilities, or Government-furnished spaces in the performance of this contract shall complete Level I Anti-Terrorism (AT) Awareness Training in accordance with DoDI 2000.16 and applicable installation security protocols.

Training requirements for all personnel requesting a Common Access Card (CAC) are as follows:

- All affected contractor personnel must complete initial Level I AT Training within 30 calendar days of contract award or prior to initial base access, whichever is earlier
- Annual refresher training is required for continued access during the contract period of performance. Training may be completed online through the Joint Knowledge Online (JKO) portal: <https://jkodirect.jten.mil>
- All training records shall be submitted IAW Contract Exhibit A, CDRL A00B

Contractor Responsibilities:

- Maintain documentation of all completed AT training and submit certificates of completion to the COR/ACOR
- Ensure subcontractors and vendor personnel performing on base or at secure DoD facilities also complete and certify compliance with these requirements
- Coordinate with the Government for any additional site-specific AT orientation required by base security

Access Denial:

- Failure to complete AT training may result in denial of base access and will not constitute an excusable delay or valid justification for non-performance.

9.3.4. Combating Trafficking in Persons

In accordance with FAR 52.222-50, Combating Trafficking in Persons, and applicable DoD policies, the contractor shall take proactive measures to prevent, identify, and report trafficking-related activities throughout the period of performance. The contractor shall:

- Develop and implement a basic CTIP training and awareness program that informs personnel of the Government's zero-tolerance policy and the prohibited conduct outlined in FAR 52.222-50.
- Ensure the training:
 - Emphasizes awareness of forced labor, child labor, and commercial sex acts.
 - Explains contractor obligations and prohibited activities
 - Includes reporting mechanisms (e.g., DoD IG Hotline, National Human Trafficking Hotline)
 - Is accessible to both U.S. and foreign national employees, as applicable
- Training Requirements:
 - All contractor personnel working under this contract shall complete CTIP awareness training annually
 - Initial training must be completed 30 days after contract award or within 30 days of onboarding for new hires
 - Training content may be developed by the contractor or based on DoD CTIP materials (e.g., <https://ctip.defense.gov/Training>)
- Documentation and Reporting:
 - The contractor shall maintain records of CTIP training completion for all assigned personnel
 - All documentation to include the Contractor's training and awareness program IAW Contract Exhibit A, CDRL A00C
 - Contractor initial & annual training records shall be submitted IAW Contract Exhibit A, CDRL A00D

9.3.5. Transient Military Aircraft

Aircraft provided under this contract are considered transient military aircraft for purposes of DoD airfield support. No landing fees will be charged at U.S. Government-controlled airfields. If landing at commercial facilities, associated fees may be applied to the Government fuel card in accordance with Naval Supply Systems Command (NAVSUP) Instruction 4200.97 (series).

9.4. Controlled Unclassified Information (CUI)

This contract is unclassified but will involve handling Controlled Unclassified Information (CUI). Contractor personnel shall handle, store, and transmit CUI in accordance with DoDI 5200.48 and SECNAV M-5510.30C. All access to sensitive information shall be limited to personnel with valid need-to-know and proper training.

9.5. Cybersecurity and Cybersecurity Maturity Model Certification (CMMC)

9.5.1. General

The contractor shall protect all Government data, including Controlled Unclassified Information (CUI), in accordance with Federal law, DoD instructions, and the terms of this contract. The work performed under this PWS involves handling CUI.

9.5.2. CMMC Level 2 Compliance

The contractor shall establish, maintain, and advance a cybersecurity program that meets or exceeds the requirements of CMMC Level 2 for the entire period of performance. The contractor's compliance is a material requirement of this contract.

9.5.3. System Security Plan and POA&M Review

Upon request by the Government, but not more than annually, the contractor shall provide its current System Security Plan (SSP) and any associated Plans of Action and Milestones (POA&Ms) for the covered information systems for Government review. This is to provide insight into the contractor's security posture and does not constitute a formal approval of the plan by the Government.

9.5.4. Subcontractor Flow-Down

The contractor is responsible for ensuring that all subcontractors that create, receive, or possess CUI on their behalf comply with the CMMC Level 2 requirement. The contractor shall include DFARS clause 252.204-7021 and this requirement in all applicable subcontracts.

9.5.5. Annual Affirmation and Audits

The contractor shall achieve and maintain CMMC Level 2 compliance for all covered information systems. For the purposes of this contract, compliance shall be demonstrated through an annual self-assessment and a corresponding affirmation posted to the Supplier Performance Risk System (SPRS). The contractor shall comply with any future changes to DoD CMMC assessment requirements as they become applicable during the period of performance.

9.5.6. Cyber Incident Reporting

The contractor shall report any cyber incidents in accordance with DFARS Clause 252.204-7012, Safeguarding Covered Defense Information and Cyber Incident Reporting.

9.6. Technical Assistance Agreements (TAA) and Export Control

The contractor shall comply with all applicable U.S. export control laws and regulations, including the International Traffic in Arms Regulations (ITAR) (22 CFR §§ 120–130) and the Export Administration Regulations (EAR) (15 CFR §§ 730–774). If any work under this contract involves the transfer of technical data or defense articles to foreign persons (including employees), the contractor shall obtain the required Technical Assistance Agreements (TAA) and/or licenses from the U.S. Department of State or Commerce prior to disclosure. The contractor shall provide documentation of any required export control authorizations to the Contracting Officer (CO) upon request. The contractor shall be responsible for ensuring that all subcontractors or partners also comply with export control obligations under this contract.

9.7. Records Retention and Data Rights

The contractor shall maintain all technical records, maintenance logs, training documentation, fuel reports, and operational data for a minimum of three (3) years from the date of generation, or longer if required by law or regulation. The Government shall have unlimited rights to all deliverables defined in Exhibit A including data related to flight operations, airworthiness substantiation, and system integration.

9.8. Government Provisions

The Government may provide the following services and resources in support of this contract:

9.8.1. Directives and Operational Schedules

The Government may furnish unclassified website links or distribution portals to access relevant regulations, subordinate directives, and long-range operational planning tools.

9.8.2. Temporary Government Facility Use

If use of U.S. Government airfields or facilities is authorized, the Government will provide the following on a space-available and non-interference basis:

- Local radio clearances
- Customs services in accordance with DoD military aircraft policy
- Access to Base Operations Flight Planning services

9.9. Government Furnished Material (GFM)

Government Furnished Material (GFM), specifically sonobuoys, will be provided to the Contractor on a temporary basis for the execution of mission events.

9.9.1. Accountability and Reconciliation

The Contractor is responsible for the stewardship of all GFM from the point of receipt from the Government until each item is either expended during a mission event or returned to the Government post-event. In accordance with FAR Clause 52.245-1, the Contractor shall have a system of internal controls to manage and account for all GFM in its possession, however brief.

For all GFM received, the Contractor shall track the issuance, expenditure, and return of each item. The Contractor shall provide a monthly reconciliation report IAW Contract Exhibit A, CDRL A006.

The Contractor shall investigate and report to the Government all incidents of GFM loss (e.g., items that are unaccounted for and were neither expended nor returned) as soon as the facts become known, in accordance with the procedures outlined by the Contracting Officer's Representative (COR).

9.10. Subcontractor Management

The contractor shall be responsible for ensuring that all subcontractors performing under this contract comply with the same safety, quality, airworthiness, training, and operational requirements as the prime. Subcontractor procedures, training, and operations shall be covered under the prime contractor's GFR-approved FOPs/GOPs.

9.11. Contract Closeout Requirements

At the conclusion of contract performance, the contractor shall:

- Submit final fuel reconciliation and reimbursement statements
- Return all Government-furnished property, to include Common Access Cards (CACs) and document disposition
- Archive and provide access to records and deliverables for Government audit

10.0 DATA DELIVERABLES

The Contractor shall provide all data deliverables as required by this PWS, Contract Exhibit A - Contract Data Requirements List (CDRL), and any supplementary PWS documents.

All deliverables identified in Exhibit A shall be prepared, submitted, and tracked electronically via the NAVAIR Acquisition Management System (AMS) CDRL Tool in accordance with the schedules specified in the applicable CDRLs. Submissions made outside of the AMS CDRL Tool will not be considered valid unless specifically authorized in writing by the COR or ACOR or specifically listed in Block 16 of the DD Form 1423-1. The specific requirements and contractor responsibilities for obtaining and maintaining system access are detailed in Section 4.2 of this PWS. Failure to obtain the required certificates or access to AMS does not relieve the Contractor of the responsibility to meet the delivery schedule.

Table 4 of this PWS identifies the minimum data deliverables expected under this contract. The COR may direct compliance with specific industry or commercial standards, allow Contractor-preferred formats, or authorize the use of existing Contractor data where appropriate.

Table 4: Data Deliverables		
CDRL Number	PWS Reference	Title
A001	4.1	Capability Standup Schedule Integrated Master Schedule (IMS)
A002	4.5, 4.6, 4.11, 5.6, 5.9.5, 5.9.21	Public Aircraft Operation (PAO) Airworthiness Checklist Documentation
		Includes: All documents required by Contract Section J, Attachment 2 (Public Aircraft Operation (PAO) Airworthiness Checklist)
A003	4.8, 4.9, 4.10.1, 4.11, 5.9.5, 5.9.9, 5.9.13, 5.9.14, 5.9.16, 6.2, 6.6	Government Flight Representative (GFR) Supporting Documentation
		Includes: Management Plan (MP) Approved Civil Aircraft Landing Permits (CALPs) Ground Operating Procedures (GOPs)

Table 4: Data Deliverables		
CDRL Number	PWS Reference	Title
		Flight Operating Procedures (FOPs) Aircrew Training and Currency Records Maintenance Personnel Training Training Manuals
A004	5.10.3, 7.6	Fuel Consumption Tracking
A005	5.10.4	AIR Card Statement of Understanding (SOU) and Training
		Includes: Fuel Card Training Certificates Fuel Card Statement of Understanding (SOU)
A006	7.1, 7.2, 7.3, 7.5, 8.1, 9.9.1	Contractor's Progress, Status And Management Report
A007	4.4	Contractor Roster
A008	8.3.1	Post-Award Conference (PAC) Briefing Material
A009	8.3.2	Program Management Review (PMR) Briefing Material
A00A	8.3.1, 8.3.2	Post-Award Conference / Program Management Meeting Minutes
A00B	9.3.3	Anti-Terrorism Training for Contractors
A00C	9.3.4	Combating Trafficking in Persons Training (CTIP) Program Plan
A00D	9.3.4	Combating Trafficking in Persons (CTIP)
A00E	9.1.1	Operations Security (OPSEC) Plan

APPENDIX A - APPLICABLE DOCUMENTS

Document	Title
49 USC § 40125	Qualifications for Public Aircraft Status
Air Force Instruction (AFI) 10-1001	Civil Aircraft Landing Permits
AFI 10-1002	Joint Use Agreements for Military and Civilian Flying Facilities
CFR, Title 14	Aeronautics and Space
CFR, Title 14 Part 25 Subpart H	Electrical Wiring Interconnection System (EWIS)
CFR, Title 14 Part 43	Maintenance, Preventive Maintenance, Rebuilding and Alteration
CFR, Title 14 Part 61	Certification: Pilots, Flight Instructors, and Ground Instructors
CFR, Title 14 Part 91	General Operating and Flight Rules
CFR, Title 14 Part 121.1111	EWIS Maintenance Program
CFR, Title 32, Part 766	Use of Department of the Navy Aviation Facilities by Civil Aircraft
CFR, Title 49	Transportation
Commander Naval Air Forces (CNAF) M-3710.7	Naval Air Training and Operating Procedures Standardization (NATOPS) General Flight and Operating Instructions Manual
DCMA INST 8210-1 (series)	Contractor's Flight and Ground Operations
Department of Defense Directive (DoDD) 5030.61	DoD Airworthiness Policy
DoD 5500.07 (series)	Joint Ethics Regulation (JER)
DoDD 8140.01	Cyberspace Workforce Management
Department of Defense Instruction (DoDI) 4500.53	DoD Commercial Air Transportation Quality and Safety Review Program
DoDI 5200.48	Controlled Unclassified Information (CUI)
Department of Defense Manual (DoDM) 4140.25, Volume 3	DoD Management of Energy Commodities: Fuel Cards
DoDM 5220.22 (series)	National Industrial Security Program Operating Manual (NISPOM)
DoDM 8140.03	Cyberspace Workforce Qualification and Management Program
Federal Aviation Administration (FAA) Advisory Circular (AC) 00-1.1B	Public Aircraft Operations— Manned and Unmanned
FAA AC 43-210A	Standardized Procedures for Obtaining Approval of Data Used in the Performance of Major Repairs and Major Alterations
FAA AC 91-70C	Oceanic and Remote Continental Airspace Operations
FAA AC 91-91	Maintaining Public Aircraft
FAA Order 8300.16 (series)	Major Repair and Alteration Data Approval

Document	Title
HSPD-12	Homeland Security Presidential Directive-12
International Civil Aviation Organization (ICAO)	Annexes 1-18
ICAO, Annex 19	Safety Management
Military Handbook (MIL-HDBK)-516 (series)	DoD Handbook Airworthiness Certification Criteria
National Security Decision Directive (NSDD)	298 Operations Security (OPSEC) Program
NAVAIR Instruction (NAVAIRINST) 13034.1 (series)	Airworthiness Policy
Naval Supply Systems Command (NAVSUP) Instruction 4200.97 (series)	Policies and Procedures for the Operation and Management of the Aviation Into-Plane Reimbursement (AIR) Card Program
Naval Operations Instruction (OPNAVINST) 3432.1A	Operational Security
Secretary of the Navy (SECNAV) Instruction M-5510.30 (series)	DON Personnel Security Program

APPENDIX B - DEFINITIONS AND GLOSSARY

Aircraft Accident: An aviation accident is defined as an occurrence associated with the operation of an aircraft that takes place between the time any person boards the aircraft with the intention of flight and all such persons have disembarked, and in which any person suffers death or injury, or in which the aircraft receives damage, or in which GFP is damaged, or in which Government property is damaged by aircraft operations.

Aircraft Incident: An incident is an occurrence other than an accident that affects or could affect the safety of operations, or in which no intent for flight exists, but damage to aircraft, personal injury sustained, damage to GFP, or damage to Government property occurred.

Contractor Facility: The location where the aircraft will be while in a non-operational status without a crew assigned. Any costs to position the aircraft while in a non-operational status away from home base are the responsibility of the Contractor.

Crew Day: The crew duty period begins when an individual reports for work (either flight or administrative duties) and ends when the engines are stopped at the end of an event, mission, or series of missions.

Government Flight Representative (GFR): GFR is a rated U.S. military officer, or Government civilian in an aviation position, to whom Commander, Naval Air Systems Command (COMNAVAIRSYSCOM) has delegated the responsibility of approval of Contractor flights, procedures, crewmembers, and ensuring Contractor compliance with the applicable provisions of DCMA INST 8210-1D.

Mission Flight Time: The mission flight time is defined as from time of take-off (weight off wheels) to landing (weight on wheels).

Standard Day: Conditions at sea level, altimeter 29.92 in/Hg at 15 °C/59 °F. Sea level static conditions for a standard day are: Density - 0.00237 slug/ft.³, Pressure - 14.7 lb./in.², Temperature - 59 °F, Viscosity (μ) - 3.62×10^{-7} lb.-s/ft.².

Standard Mission Support Personnel: Standard Mission Support Personnel for SLAT operations will be defined by the applicable operations and flight manuals of the Type/Model/Series (T/M/S) aircraft being utilized but shall, at a minimum, consist of one PIC, one SIC, and one Sonobuoy Operator.

APPENDIX C - ACRONYM LIST

AC	Advisory Circular
AD	Airworthiness Directives
AFB	Air Force Base
AFI	Air Force Instruction
AGL	Above Ground Level
AIP	Aeronautical Information Publications
AIR	Aviation Into-plane Reimbursement
BLOS	Beyond Line of Sight
CA	California
CAC	Common Access Card
CALP	Civil Aircraft Landing Permit
CAO	Civil Aircraft Operations
CAS	Contracted Air Services
CCPMD	Consolidated Card Program Management Division
CDI	Covered Defense Information
CDRL	Contract Data Requirements List
CFR	Code of Federal Regulations
CLIN	Contract Line-Item Number
COCO	Contractor Owned Contractor Operated
COMNAVAIRSYSCOM	Commander, Naval Air Systems Command
COMSEC	Communications Security
CONUS	Continental United States
COR	Contracting Officer's Representative
CR	Contractor Representative
CUI	Controlled Unclassified Information
DCMA INST	Defense Contract Management Agency Instruction
DFARS	Defense Federal Acquisition Regulation Supplement
DLA	Defense Logistics Agency
DoD	Department of Defense
DoDD	Department of Defense Directive
DoDI	Department of Defense Instruction
DoDM	Department of Defense Manual
DoN	Department of the Navy
DSN	Defense Switched Network
EAR	Export Administration Regulations
FAA	Federal Aviation Administration
FACSFAC	Fleet Area Control Surveillance Facility
FAR	Federal Acquisition Regulation
FBO	Fixed Bases of Operations
FOP	Flight Operating Procedures
FSDO	Flight Standards District Office
FTS	Federal Telephone System

GFP	Government Furnished Property
GFR	Government Flight Representative
GOP	Ground Operating Procedures
GPS	Global Positioning System
HSPD-12	Homeland Security Presidential Directive-12
IAW	In Accordance With
ICA	Instructions for Continued Airworthiness
ICAO	International Civil Aviation Organization
IFC	Interim Flight Clearance
IFR	Instrument Flight Rule
IMS	Integrated Master Schedule
IPT	Integrated Product Team
ITAR	International Traffic in Arms Regulations
JER	Joint Ethics Regulation
KIAS	Knots Indicated Airspeed
LOS	Line of Sight
MCAS	Marine Corps Air Station
MIL-HDBK	Military Handbook
MIL-STD	Military Standard
MP	Management Plan
MRP	Mishap Response Plan
MS	Microsoft
MSL	Mean Sea Level
NAS	Naval Air Station
NATOPS	Naval Air Training and Operating Procedures Standardization
NAVAIR	Naval Air Systems Command
NAVAIRINST	NAVAIR Instruction
NAVAIRSYSCOM	Naval Air Systems Command
NAVSUP	Naval Supply Systems Command
NC	North Carolina
NISPOM	National Industrial Security Program Operation Manual
NM	Nautical Mile
NSDD	National Security Decision Directive
NTSB	National Transportation Safety Board
OCONUS	Outside Continental United States
OEM	Original Equipment Manufacturer
OPNAVINST	Naval Operations Instruction
OPSEC	Operations Security
PAC	Post-Award Conference
PAO	Public Aircraft Operations
PCO	Procurement Contracting Officer
PIC	Pilot in Command
PL	Program Letter
PMA	Program Manager Air
PMR	Program Management Review
PWS	Performance Work Statement

QASP	Quality Assurance Surveillance
RTB	Return to Base
SECNAV	Secretary of the Navy
SFF	Safe for Flight
SIC	Second in Command
SOU	Statement of Understanding
TAA	Technical Assistance Agreements
T/M/S	Type/Model/Series
TO	Task Order
U.S.	United States
USC	United States Code
USG	United States Government
USMC	United States Marine Corps
USN	United States Navy
VMC	Visual Meteorological Conditions
VHF	Very High Frequency

APPENDIX D – CAPABILITY STAND-UP CHECKLIST

Area	Requirement	Milestone	Reference
Documentation	IMS Submitted (CDRL A001)	A	Sec 4.1
Admin	Initial Personnel Hiring (Aircraft Maintenance & Modification Personnel) and Contractor Personnel Roster Submitted (CDRL A007)	A	Sec 4.1, Sec 4.4
Admin	Contractor Airworthiness (AR) and Contractor Representative (CR) Designations Completed	A	Sec 4.2, Sec 4.3
Aircraft	Aircraft Modifications	A	Sec 4.5
Documentation	Submission of all required FAA Form's 8110 and 337 for Major Repairs and Alterations	A	Sec 4.5
Documentation	PAO Airworthiness Checklist Substantiation Package Approved (CDRL A002)	A	Sec 4.5, Sec 4.6
Aircraft	Physical and Functional Configuration Audits (PCA/FCA)	A	Sec 4.7
Aircraft	Static Launch System Demonstration Complete	A	Sec 4.7
Procedures	GOPs / FOPs Approved (CDRL A003)	A	Sec 4.8
Procedures	Management Plan Approved (CDRL A003)	A	Sec 4.8
Safety	Mishap Response Plan Approved (CDRL A002)	A	Sec 4.8
Admin	Final Personnel Hiring (Pilots, Sonobuoy Operators, Maintenance Personnel and Contractor Personnel Submitted (CDRL A007)	B	Sec 4.1, Sec 4.4
Admin	Contractor Facility Standup per Aircraft Basing and Positioning Plan	B	Sec 4.9
Training	Pilots, Sonobuoy Operators, and Maintenance Personnel Trained and Training Documentation Submitted (CDRL A003)	B	Sec 4.10
Admin	CALPs Approved (CDRL A003)	B	Sec 4.11
Admin	CACs Requested and Issued (as required)	B	Sec 4.12
Admin	Fuel/AIR Card Training Complete + SOUs Submitted (CDRL A005)	B	Sec 4.13 Sec 5.10
Inspection	System Readiness Review (SRR) Conducted	B	Sec 4.14
Inspection	Government Flight Representative (GFR) Inspection Passed	B	Sec 4.15
Inspection	Safe-for-Flight (SFF) Inspection Passed	B	Sec 4.16

APPENDIX E – MISSION AIRCRAFT CONFIGURATION CHECKLIST

System / Capability	PWS Requirement Reference
Endurance	Sec 3.1
Range	Sec 3.1
Altitude Envelope	Sec 3.1
Airspeed Envelope	Sec 3.1
Overwater Operations	Sec 3.1
Launch System	Sec 3.1.1
Payload Capacity	Sec 3.1.2
Storage System	Sec 3.1.2
Communications	Sec 3.1.3
Navigation	Sec 3.1.3
HAZMAT Compliance	Sec 3.1.4
Safety Equipment	Sec 5.5
Airworthiness Certificates	Sec 5.3, Sec 5.6