

TECH DATA PGC00338
NSN 8415016922233

April 7, 2021

SOCKS, ATHLETIC

RP001: DLA PACKAGING REQUIREMENTS FOR PROCUREMENT

RA001: THIS DOCUMENT INCORPORATES TECHNICAL AND/OR QUALITY REQUIREMENTS (IDENTIFIED BY AN 'R' OR AN 'I' NUMBER) SET FORTH IN FULL TEXT IN THE DLA MASTER LIST OF TECHNICAL AND QUALITY REQUIREMENTS FOUND ON THE WEB AT:

<http://www.dla.mil/HQ/Acquisition/Offers/eProcurement.aspx>

FOR SIMPLIFIED ACQUISITIONS, THE REVISION OF THE MASTER IN EFFECT ON THE SOLICITATION ISSUE DATE OR THE AWARD DATE CONTROLS. FOR LARGE ACQUISITIONS, THE REVISION OF THE MASTER IN EFFECT ON THE RFP ISSUE DATE APPLIES UNLESS A SOLICITATION AMENDMENT INCORPORATES A FOLLOW-ON REVISION, IN WHICH CASE THE AMENDMENT DATE CONTROLS.

**SOCKS, ATHLETIC, CLASS 2 BLACK
GL-PD 20-07 DATED OCTOBER 28 2020**

MIL-STD-129R w/CHANGE 2 - DEPARTMENT OF DEFENSE STANDARD PRACTICE
MILITARY MARKING FOR SHIPMENT AND STORAGE
DATED: 27 SEPTEMBER 2019

INTERIM CHANGES:

OMISSION OF MARKINGS ON EXTERIOR SHIPPING CONTAINERS OF ITEMS
IN THE DLA TROOP SUPPORT CLOTHING AND TEXTILE (C&T) DIRECTORATE:

THE NOMENCLATURE AND MANUFACTURER'S NAME (WHEN THE NAME IDENTIFIES THE MATERIAL) SHALL BE OMITTED FROM ALL EXTERIOR SHIPPING CONTAINERS OF DLA TROOP SUPPORT C&T ITEMS, REGARDLESS OF MODE OF SHIPMENT.

IF THE MANUFACTURER'S NAME DOES NOT IDENTIFY THE MATERIAL AS BEING CLOTHING, IT MAY REMAIN. NSNS SHALL BE SHOWN ON ALL SHIPPING CONTAINERS OF C&T ITEMS, THE PACKING LIST SHALL BE PLACED INSIDE THE LAST CONTAINER TO BE LOADED FOR EACH SHIPMENT. THE WORDS "PACKING LIST HERE" SHALL BE STENCILED, NOT HAND LETTERED, ON THE CONTAINER.

MIL-STD-147E w/CHANGE 2
27 JUNE 2019

DEPARTMENT OF DEFENSE
STANDARD PRACTICE
PALLETIZED UNIT LOADS

THE GOVERNMENT ASSIGNED UNIVERSAL PRODUCT
CODE (UPC) MUST BE PLACED ON ALL SHIPPING
CARTONS ON WHICH THE NSN APPEARS".
DELETE CURRENT "BARCODE LABEL/TAG" REQUIREMENTS AND SUBSTITUTE THE
FOLLOWING:

LABEL TAG: EACH ITEM SHALL BE INDIVIDUALLY BAR-CODED WITH A PAPER TAG FOR PERSONAL CLOTHING ITEMS. THE PAPER USED FOR THE TAGS SHALL BE STANDARD BLEACHED SULFATE HAVING A BASIS WEIGHT OF 100 POUNDS WITH A SMOOTH FINISH TO ACCEPT THERMAL TRANSFER AND DIRECT PRINTING. THE TAGS SHALL HAVE A HOLE AND SHALL BE ATTACHED TO EACH ITEM BY A FASTENER, CLEARLY LEGIBLE AND READABLE BY SCANNER. THE BAR CODING ELEMENT SHALL BE A 13 DIGIT

NATIONAL STOCK NUMBER (NSN). THERE SHALL BE A 12 DIGIT UNIVERSAL PRODUCT CODE (UPC) ASSIGNED FOR ALL NSNS BY THE GOVERNMENT. THE INITIAL "UPC" MUST APPEAR BENEATH THE CODE. THE BAR CODES FOR NSN AND UPC SHALL BE A MEDIUM TO HIGH DENSITY AND SHALL BE LOCATED SO THAT THEY ARE COMPLETELY VISIBLE ON THE ITEM WHEN IT IS FOLDED AND PACKAGED AS SPECIFIED. THE LABEL'S LOCATION SHALL CAUSE NO DAMAGE TO THE ITEM.

NOTE: UNIVERSAL PRODUCT CODE INFORMATION THE GOVERNMENT ASSIGNED UNIVERSAL PRODUCT CODE (UPC) MUST BE PLACED ON ALL SHIPPING CARTONS ON WHICH THE NSN APPEARS.

THE FOLLOWING DEFECTS APPLY FOR BARCODE LABELS/TAGS:

BAR CODE OMITTED OR NOT READABLE BY SCANNER

HUMAN-READABLE INTERPRETATION (HRI) OMITTED OR ILLEGIBLE

NOT VISIBLE ON FOLDED, PACKAGED ITEM CAUSES DAMAGE TO THE ITEM

NOTE: IF THE END ITEM IS PLACED IN A PLASTIC BAG - USE TYPE VII (PRESSURE SENSITIVE LABEL) OF MIL-DTL-32075.

PRES/PACK C/C TO ASTM-D-3951

3 PAIR SOCKS PER PACK

SHIPPING CONTAINER:48 PACKAGES

MARKING SHALL BE IN ACCORDANCE

WITH MIL-STD-129.

MARKING SHALL BE IN ACCORDANCE WITH

MIL-STD-129

RFID HANGTAG:

An RFID inlay shall be added to the barcode paper hang tag attached to each item. Where the use of self-adhesive bar-code labels are authorized, the RFID inlay may be added to the self-adhesive label in lieu of a paper hang tag. All other contract barcode and hang tag requirements still apply.

The RFID inlay should be passive Gen2 with a frequency range between 860 and 960 MHz. The RFID antenna should be Avery/Dennis AD222 or comparable with ISO/IEC 18000-C EPCglobal C1G2 Protocol and an EPC memory allocation containing a 96 bit EPC Number. The data linking the EPC number to the NSN and quantity unit pack must be exportable to VIM/ASAP. The bar code of the EPC Number must be printed at the bottom of the tag along with the human readable version below the bar code.

In addition to defects applicable to the paper tag and barcoding element, the RFID tag shall be examined for the defects listed below:

RFID Inlay omitted

RFID Inlay not secure

RFID Inlay not laying flat when packaged

RFID Inlay not readable with RFID scanner

RFID Inlay or configuration not as specified

The manual "Item-Level Passive RFID Technology Manufacturer's Information Guide" provides guidance on RFID implementation and is available from the contracting officer.

252.211-7006 - RADIO FREQUENCY IDENTIFICATION (RFID) Required
(ref. T8379; Nov. 08, 2006)

SIGNIFICANT NOTE - "PALLETIZATION IS REQUIRED FOR THESE SUPPLIES".

NOTE: THE FOLLOWING APPLIES TO ALL NON-MANUFACTURED WOOD PACKAGING MATERIALS:

"All Wood Packaging Material (WPM) acquired by DOD must meet requirements of International Standards for Phytosanitary Measures (ISPM) 15, "Guidelines for Regulating Wood Packaging Materials in International Trade." DOD shipments inside and outside of the United States must meet ISPM 15 whenever WPM is used to ship DOD cargo, or when wood is being acquired by DLA for future use as packaging material. WPM is defined as wood pallets, skids, load boards, pallet collars, wooden boxes, reels, dunnage, crates, frame and cleats. Packaging materials exempt from the requirements are materials that have undergone a manufacturing process, such as corrugated fiberboard, plywood, particleboard, veneer, and oriented strand board (OSD). All WPM shall comply with one of the following official quality control programs:

Heat Treatment (HT) or Kiln Dried Heat Treatment (KD HT) in accordance with American Lumber Standard Committee, Incorporated (ALSC) Wood Packaging Material Program and WPM Enforcement Regulations (see <http://www.alsc.org/>; or

All WPM shall include certification/quality markings in accordance with the ALSC or NWPCA standards, as applicable. Markings shall be placed in an unobstructed area that will be readily visible to inspectors. Pallet markings shall be applied to the stringer or block on diagonally opposite sides of the pallet and be contrasting and clearly visible.

All containers shall be marked on a side other than the top or bottom, contrasting and clearly visible. All dunnage used in configuring and/or securing the load shall also comply with ISPM 15 and be marked with an ASLC approved DUNNAGE stamp. Failure to comply with the requirements of this restriction may result in refusal, destruction, or treatment of materials at the point of entry. The Agency reserves the right to recoup from the Contractor any remediation costs incurred by the Government."

PALLET SHALL BE 4 WAY ENTRY, WINGED TYPE. PALLETIZED LOAD DIMENSIONS SHALL NOT EXCEED 43 INCHES IN LENGTH, 52 INCHES IN WIDTH, AND 54 INCHES IN HEIGHT (INCLUDING THE PALLET).

THE PALLETIZED LOAD SHALL BE BONDED USING APPROVED COMMERCIAL BONDING MATERIALS. THE USE OF METAL BANDING, IN SECURING BOXES TO PALLETS, IS DISCOURAGED. PALLET LOADS SHALL CONTAIN THE SAME NUMBER OF CARTONS, OF IDENTICAL QUANTITIES, OF ONE NSN, TO THE MAXIMUM EXTENT POSSIBLE.

PALLET LOADS CONTAINING MORE THAN ONE NSN SHALL BE CLEARLY MARKED TO LIST ALL THE NSN'S CONTAINED IN THE LOAD. NO CARTON SHALL HAVE MORE THAN ONE NSN. AT THE END OF A SIZE RUN, NO MORE THAN ONE CARTON PER NSN MAY BE SHORT OR OVER THE SPECIFIED QUANTITY. SAID CARTON SHALL BE CLEARLY MARKED "SHORT" OR "OVER".

MIL-STD-147 IS REFERENCED FOR PALLETIZED LOADS.

IN ADDITION TO REQUIREMENTS SPECIFIED ABOVE THE FOLLOWING CLAUSE ALSO APPLIES:

52.247-9012 - REQUIREMENTS FOR TREATMENT OF WOOD PACKAGING MATERIALS (WPM) - (JULY 2006)

TGI DATA:

INCLUDE T0043 OBJECT TEXT ID ST

52.246-2, Inspection of Supplies - Firm-Fixed Price

52.209-4, Alt. I, First Article Approval - Government Testing

INCLUDE T0029 OBJECT TEXT ID ST

INSPECTION AND ACCEPTANCE AT DESTINATION.

INCLUDE T6855 OBJECT TEXT ID ST

52.246-15 CERTIFICATE OF CONFORMANCE

ADDITIONAL INFORMATION FOR COMMERCIAL AQL'S:

AQL'S FOR COMMERCIAL ITEM DESCRIPTIONS (CID'S):

VISUAL - GENERAL INSPECTION LEVEL II, AQL - 1.0

DIMENSIONAL - SPECIAL INSPECTION LEVEL S-2, AQL - 2.5

ACCEPTABILITY OF LOTS WILL BE DETERMINED BY THE USE

OF "SAMPLING PROCEDURES AND TABLES FOR INSPECTION BY ATTRIBUTES",

ANSI/ASQC Z1.4