

1 EA Large scale slope mower for rough terrain and steep hills including attachments.

SLOPE MOVER

hydrostatic drive and all-wheel drive

Diesel Engine:

min. 2615 cm³, turbo diesel, 4 cylinders, 4-stroke, water-cooled, power min. 53 kW (72 hp) at 2700 rpm, diesel particle filter, Stage V, min. torque 232 Nm at 1500 rpm, torque increase 24%, maintenance interval 500 h

Drive system - Engine

Engine type:	Diesel
Number of cylinders:	4
Exhaust emission:	min. Stage V
Min. Displacement:	2,615 cm ³
Min Power:	53 kW (72 HP) @ 2,700 1/min
Min. torque at speed:	225 Nm @ 1,600 1/min
Torque rise:	min. 24 %
Min. Diesel tank capacity:	70 l
Min. Hydraulic output:	40 l/min

Chassis and tires

Differential lock, front/rear axle

Selectable Front steering, All-wheel steering, Rear steering, or Crab steering

Max. Turning circle: 3,000 mm

Electrics

Electrical system:	12 V, 130 A
Battery capacity:	100 Ah

Lifting gears

Front lifting frame with side shift

Min. Side shift left	200 mm
Min. Side shift right:	200 mm
Min. Lifting capacity front:	1,300 kg
Min. Lifting capacity rear:	1,200 kg
Relief and vibration damping front	

Dimensions

Max. Length incl. lifting gears:	3,550 mm
Max. Width with single tires:	1,890 mm
Max. Height:	2,090 mm

Weights

Max. Empty weight:	1,900 kg
Max. Total weight:	3,500 kg
Min. permissible front axle load:	1,900 kg
Min. permissible rear axle load:	1,900 kg

Electrical system:

12 V, alternator 130 A, high-performance cold-start battery 100 Ah, battery disconnection switch

Clutch:

1-plate dry clutch for independent PTO drive

Transmission:

Infinitely variable hydrostatic and power shift able for travel drive at two speed levels

Speed:

slow range: 0-12 km/h

fast range: 0-40 km/h

the entire speed range must be without power transmission interruption forwards and backwards selectable with the multifunctional driving lever

PTO:

standard profile 1 3/8", 6 splines, rear and front under load Switchable, speeds: front approx. 570 rpm, rear approx. 590 rpm, direction of rotation right (looking at cones)

Final drive:

All-wheel drive with differential in both axles, front axle electro-hydraulically switchable, front axle pivoting, differential rear and front locks electrohydraulically. switchable, 100% blocking effect

Steering:

Hydrostatic all-wheel steering with Load sensing system, front steering must be preselectedable at the push of a button, changing the steering type any with automatic detection and synchronization of the wheel position via inductive sensors also while driving

Turning circle:

max. radius 3.0 m

Tires:

Equal or Terra profile or AS profile 31x15.50-15

Brakes:

Hydraulic 2-circuit servo foot brake acting on all wheels, additional hydrostatic driving brake, hand brake: mechanical servo brake acting on rear wheels, parking lock, hill holder

Cabin:

LED lighting (driving lights) front and rear, anti-vibration cushioned operator's platform, OECD-tested safety frame, curved windscreen, side window on the right, hinged rear window, plastic roof with integrated LED work lights, comfort seat with air suspension and electrical swivel device with safety belt, radio preparation, dashboard with round instruments with analogue displays and color display, longitudinal and adjustable steering column, indicator lever with automatic reset, Bottle holder, universal box, document compartment, holder for mobile telephone, 12 V socket

Hydraulic:

proportional valves, approx. 40 l/min at 190 bar, oil supply approx. 12 l, oil quantity proportionally adjustable, 2 plug-in connections at the front and rear for double acting cylinder with floating position and seat valves (additional hydraulics 4DWAS-), actuation via external control possible, for 6 plug-in clutches rear and front

Front hydraulics:

3-point Cat I, max. lifting capacity 1300 kg, hydraulically on the side Can be moved approx. 200 mm to the left or right, with quick connection catch pockets and upper link, adjustable lowering throttle, outer serves the functions lifting and lowering, self-regulating relief, Floating position and vibration damping for road travel

Rear hydraulics:

3-point cat. I + II, lifting capacity 1200 kg, stabilization chains, quick-change couplings and top links, adjustable lowering throttle, external controls for lifting and lowering functions, lifting rods with crank adjustment (adjustment range 100 mm), option: self-adjusting end

Additional Requirements:

- Relief and vibration damping for road travel
- Trailer coupling, diameter 26 mm, 27 cm above the ground, load unbraked 900 kg, braked 3500 kg
- Vehicle registration papers, TUEV approval
- Direction of rotation of PTO shaft, right when looking at PTO shaft
- Full-view cabin with heating, air conditioning and defroster system, including dust filter,
- Air suspension seat, suspension travel 80 mm, weight position, lumbar support and backrest angle adjustment, seat belt, electronically controlled swivel
- Radio DAB+/BLUETOOTH/USB
- Rotating beacon, yellow LED
- front lights, brake lights, blinkers according to StVZO
- Auxiliary hydraulics 10, front/rear, 1x da with float position and seat valves
- Unpressurized hydraulic tank return line, front
- Rear and crab steering (switchover at the push of a button),
- Reversible fan
- Lashing eye attachment tie down points, min. 4 ea.
- LED lighting for headlights front and rear
- LED work lights in front 2 ea.
- Rear working light, LED 1 ea.
- Trailer hitch with quick-release fastener, towing capacity unbraked 600 Kg, towing capacity braked (overrun brake system) 3.500 Kg

Flail mower

type Vario, wear insert, 2nd oil circuit in the gearbox, working width 200 cm, special attachment bock cat. 1 front, made of fine-grain steel, gear with freewheel, side skids, Hammer fails for optimal shredding with self-sharpening cutting surface, built-in, bolted shark fin short chopping unit, self-cleaning support roller for height adjustment, Parking support, weight min. 555 kg, The mower must have the new, improved stone chip protection according to ISO/WD 17101-2. front PTO shaft.

Snow Blade

V-Type snow blade, heavy duty, the two hydraulic folding wings of the snowplow must be adjustable individually and can be used in V- or Y-shape or in straight position.

Blade width 220 cm, blade height 74 cm, working width at the largest Inclination approx. 190 cm, with 2 da hydraulic cylinders, 4 hydraulic hoses, 4 hydraulic couplings and 1 pressure less return. With Vulkollan scraper bars, 2 support feet, 1 spiral scraper bar, approx. 25° level positively adjustable scrapers (despite positively employed Scraper strips do not leave a central strip), 4 spring flaps with oil-damped gas pressure springs. (To protect the hydraulic cylinders and the vehicle.) The snowplow must be hydraulically swiveling with 2 hydraulic cylinders. With overpressure device and Vulkollan knife kit 220 cm, warning flags 2 ea., light kit, linkage mounting plate CAT 1.

Salt Spreader

min. 560 liters with PTO drive, Slide open/close hydraulically EW, with electric remote control for joint adjustment of the spreading width limitation on the left and right, container cover on the top
Litter apron 120 cm
lighting
Agitator for sand and wet salt

Warranty:

min. 12 month

Documentation

Manual, registration paper, spare parts list

Training:

Training and instruction of equipment on day of delivery or upon appointment in German language

Delivery:

USAG Ansbach DPW Katterbach Kaserne 91522 Ansbach