

**Statement of Work (SOW)
Procure Waterjet Cleaning Tools, X41**

1. General

a. The contractor shall provide waterjet cleaning tools (hereinafter referred to as “the equipment”) to X-41 Boiler Shop at Bldg. 1922, Ship Repair Facility and Japan Regional Maintenance Center (SRF-JRMC), US Naval Base Yokosuka.

b. The equipment shall be one of the manufacturer's current production models which, on the date this solicitation is issued, has been designed, engineered, and sold, or is being offered for sale through advertisements or manufacturer's published catalogs or brochures. Products such as a prototype unit, reproduction model, or experimental units do not qualify as meeting these requirements. And all material used in the construction shall be new.

c. Unless otherwise specified herein, the contractor shall furnish all labor, materials, equipment, and transportation.

2. Reference

(a) 29 CFR 1910 - Occupational Safety and Health Standards

3. Enclosure

(1) Concept Sketch

4. Minimum requirements

a. Unless otherwise specified, stated values represent the minimum.

b. List of items to be provided

Paragraph	Nomenclature	Qty
4-1	High pressure hose	8 ea
4-2	Control gun	2 ea
4-3	Cartridge	5 ea
4-4	Foot pedal	2 ea
4-5	Quick connect coupling, Female NPT x Male quick	15 ea
4-6	Quick connect coupling, Female NPT x Female quick	15 ea
4-7	Hex nipple	10 ea
4-8	Nipple	5 ea
4-9	Socket	5 ea
4-10	Fire extinguisher	1 ea
4-11	Fire extinguisher wall mount bracket	1 ea

4-1. High pressure hose

- a. Maximum working pressure: 15,000 psig
- b. Burst pressure: 35,000 psig
- c. Length: 50 feet
- d. Inside diameter: 0.5 inches

- e. Bend radius: 6 inches or smaller
- f. Connection of both ends: 1/2"-14 NPT male
- g. Proposal model: 28524-0501212 (Mfr: Jetstream) or equivalent

4-2. Control gun

- a. Control gun shall be a hand-held gun to control the intensity of the waterjet.
- b. Allowable pressure: 15,000 psig
- c. Nominal pipe size: 1/2 inches
- d. The control gun shall have a single trigger, 1/2"-14 NPT inlet port, 1/2"-14 NPT outlet port, and drain port.
- e. When the trigger is not pulled, fluid supplied into the inlet port shall flow out from the drain port.
- f. When the trigger is pulled, fluid shall gradually begin to flow out from the outlet port. When the trigger is fully pulled, all the fluid shall flow out from the outlet port.
- g. Proposal model: 65739 (Mfr: Jetstream) or equivalent

4-3. Cartridge

- a. Spare cartridge for the control gun listed in Paragraph 4.2
- b. Proposal model: 50902 (Mfr: Jetstream) or equivalent

4-4. Foot pedal

- a. Foot pedal shall be provided to control the intensity of the waterjet.
- b. Allowable pressure: 15,000 psig
- c. Nominal pipe size: 1/2 inches
- d. The foot pedal shall have 1/2"-14 NPT inlet port, 1/2"-14 NPT outlet port, and drain port.
- e. When the pedal is not pressed, fluid supplied into the inlet port shall flow out from the drain port.
- f. When the pedal is pressed, fluid shall gradually begin to flow out from the outlet port. When the pedal is fully pressed, all the fluid shall flow out from the outlet port.
- g. Proposal model: 55435 (Mfr: Jetstream) or equivalent

4-5. Quick connect coupling, Female NPT x Male quick

- a. Allowable pressure: 15,000 psig
- b. First end connection: 1/2"-14 NPT female
- c. Second end connection: Hand-tightening quick connection (Male)
- d. Proposal model: 50990 (Mfr: Jetstream) or equivalent

4-6. Quick connect coupling, Female NPT x Female quick

- a. Allowable pressure: 15,000 psig
- b. First end connection: 1/2"-14 NPT female
- c. Second end connection: Hand-tightening quick connection (Female) that is corresponding to a male connector listed in Paragraph 4-5.
- d. Proposal model: 52684 (Mfr: Jetstream) or equivalent

4-7. Hex nipple

- a. Allowable pressure: 15,000 psig

- b. Connection: 1/2"-14 NPT male both ends
- c. Body type: Hexagonal
- d. Proposal model: 50488 (Mfr: Jetstream) or equivalent

4-8. Nipple

- a. Allowable pressure: 15,000 psig
- b. Connection: 1/2"-14 NPT male both ends
- c. Overall length: 3±0.2 inches
- d. Proposal model: 55450-2 (Mfr: Jetstream) or equivalent

4-9. Socket

- a. Allowable pressure: 15,000 psig
- b. Connection: 1/2"-14 NPT female both ends
- c. Proposal model: 26056 (Mfr: Jetstream) or equivalent

4-10. Fire extinguisher

- a. Type: For Class ABC fire
- b. Capacity: 10 lbs
- c. Proposal model: B456 (Mfr: Amerex Corporation) or equivalent

4-11. Fire extinguisher wall mount bracket

- a. Applicable for a fire extinguisher listed in Paragraph 4-10.
- b. Proposal model: 809 (Mfr: Amerex Corporation) or equivalent

5. Delivery

- a. The contractor shall deliver the equipment to X-41 Boiler Shop, Bldg. 1922, SRF-JRMC Yokosuka.

6. Document submission

Unless otherwise specified, documents shall be written in the Japanese or the English language.

a. Pre-ordering document

The contractor shall submit the following documents to Technical Point of Contact (TPOC) for review and approval within thirty (30) working days after contract award, prior to placing orders of the equipment from manufacturers or distributors. Technical review by the Government will be completed and returned with comments within ten (10) working days after receiving.

- (1) Item list (Manufacturer, model, specification, quantity)
- (2) Catalog of each product
- (3) Delivery schedule

b. Completion documents

The contractor shall submit the following documents before delivery.

- (1) Packing list
- (2) Technical instructions, if any

- (3) Pre-shipping inspection sheet, if any
- (4) SDS (Safety Data Sheets) for the fire extinguisher
- (5) Warranty sheet for one year

7. TPOC

To Be Determined (TBD)