

SALIENT CHARACTERISTICS

For

Industrial Vacuum Sealer

1.0. SCOPE OF EQUIPMENT:

All proposed products must meet or exceed the specifications outlined in this Salient Characteristics document. The products must be designed, manufactured, and tested to ensure compliance with all applicable requirements, including performance, safety, and environmental standards.

All items shall be delivered to the 309th Aerospace Maintenance and Regeneration Group (AMARG) at the designated location, with the seller responsible for all costs and risks associated with transportation. The delivery terms are FOB (Free on Board) DESTINATION, which means that the seller is responsible for delivering the products to the AMARG facility, with the buyer taking possession of the products at the destination.

1.1. PRODUCT PERFORMANCE SPECIFICATION:

SPECIFICATIONS	
Industrial Vacuum Sealer Specifications:	• Seal Length: 36 Inches. • Seal Width: 5/16 Inch • Vacuum Sealer Must Have an Onboard Air Compressor That Provides 100 PSI for Operation ○ Air Compressor Must Be 115v
Industrial Vacuum Sealing Standard Features:	• Digital Interface ○ Nine (9) Programable Storage with Multiple Stages • Motorized Adjustable Frame Allowing Adjustment Up To 12 Inches • Top And Bottom Heated Seal Bars for Thick Material • Bag Stretcher • Pneumatically Operated Seal Jaws • Temperature Controller: Up To 350°F • Independent Timers (Various Timers for The Below) ○ Vacuum ○ Seal ○ Cool • Pressure-Evening System • Must Be Foot Pedal Cycle Activation • Vacuum Level Sensor • Individual Vacuum Controls • Must Have a Work Shelf and Bag Support

Manufacture/Safety Specs:	• Country Of Manufacture Must Be United States • Locking Control Box Cover • Emergency Stop Button • Low Pressure Jaw Closing System • Automatic Jaw Interference Release • Locking Swivel Castors
Warranty	• Manufacture Warranty for 1-year minimum • Owner's Manual • Parts Manual