

STATEMENT OF WORK

1. Objective/Requirements

The information listed below is required to complete this purchase.

2. Characteristics, Scope, and Specs

LINE	PART NO.	DESCRIPTION	QTY.
1	VPT-24UHD-MIL-C53	23.8" Ruggedized Color Display, 3840 x 2160 Ultra HD [4K] Resolution, LED Backlighting System, Video Inputs: (1) DisplayPort with Retaining Mechanism, 28 VDC Input Power, Enhanced Brightness: 650 NITS, Contrast Ratio 1200:1, Ultra Wide Viewing Angle: 88°/ 88°/ 88°/ 88°, MIL-SPEC Barrel Style Connector for Power, Industrial Grade Connectors for Video Inputs, MIL-STD-810G Operational Environment, Operating Temperature Range: 0° C to +50° C, Circular Polarizer with Protective Front Glass and Anti-Reflective Coating, Illuminated User Control Buttons with Tactile Feedback, Remote Nightmode Toggle, Daymode Startup, Front Four Corner Mounting Configuration, 2 Year Workmanship and Material Warranty.	3
2	VPT-24UHD-MIL-C54	23.8" Ruggedized Color Display, 3840 x 2160 Ultra HD [4K] Resolution, LED Backlighting System, Video Inputs: (1) DisplayPort with Retaining Mechanism, 28 VDC Input Power, Enhanced Brightness: 1000 NITS, Contrast Ratio 1200:1, Ultra Wide Viewing Angle: 88°/ 88°/ 88°/ 88°, MIL-SPEC Barrel Style Connector for Power, Industrial Grade Connectors for Video Inputs, MIL-STD-810G Operational Environment, Operating Temperature Range: 0° C to +50° C, Protective Front Glass and Anti-Reflective Coating, Illuminated User Control Buttons with Tactile Feedback, Remote Nightmode Toggle, Daymode Startup, Front Four Corner Mounting Configuration, 2 Year Workmanship and Material Warranty.	3
3	NRE	Engineering and design effort to develop a custom drop-in replacement.	1

3. Place of Performance

NASA Langley Research Center

4. Period of Performance

30 days ARO