



US Army Corps
Of Engineers®
Nashville District

Solicitation No. XXXXXXXXXXXXX

EMERGENCY GATE LIFTING MACHINERY INSPECTION

**Barkley Lock and Dam
Cumberland River
Lyon County, Kentucky**

**Technical Specifications
RTA**

January 2026

THIS PAGE INTENTIONALLY LEFT BLANK

FOR DUPLEX PRINTING

PROJECT TABLE OF CONTENTS

DIVISION 01 - GENERAL REQUIREMENTS

01 11 00	SUMMARY OF WORK
01 35 50	PROJECT SITE SECURITY AND AT/OPSEC PROCEDURES

-- End of Project Table of Contents --

THIS PAGE INTENTIONALLY LEFT BLANK

SECTION TABLE OF CONTENTS

DIVISION 01 - GENERAL REQUIREMENTS

SECTION 01 11 00

SUMMARY OF WORK

PART 1 GENERAL

- 1.1 BASE SCOPE OF WORK (SOW)
 - 1.1.1 Removal of Concrete Access Covers
 - 1.1.2 Primary reducers- MK 31/4-5 QTY: 2
 - 1.1.3 Secondary reducers- MK 31/4-4 QTY: 2
 - 1.1.4 Flexible couplings- MK 31/4-9 and MK 31/4-10 QTY: 4 Plus Spare
 - 1.1.5 Bull gears- MK 31/2-2 QTY: 2; Bull Gear Guards
 - 1.1.6 Bull Gear Pinion Shaft- MK 31/4-2 QTY: 2
 - 1.1.7 Intermediate gears - MK 31/4-1 QTY: 2
 - 1.1.8 Gear Mounting Assemblies
 - 1.1.8.1 Bearing Pedestals- MK 31/3-1 QTY: 2
 - 1.1.8.2 Bearing Pedestals- MK 31/3-2 QTY: 2
 - 1.1.8.3 Bearing Pedestals- MK 31/3-3 QTY: 2
 - 1.1.8.4 Bearing Pedestals- MK 31/3-4 QTY: 2
 - 1.1.8.5 Bearing Caps- MK 31/3-5 QTY: 4
 - 1.1.8.6 Bearing Caps- MK 31/3-6 QTY: 4
 - 1.1.8.7 Bearing Caps- MK 31/3-7 QTY: 2
 - 1.1.9 Sheave Assemblies
 - 1.1.9.1 Sheaves- MK 31/7-1 QTY: 2
 - 1.1.9.2 Sheave Shafts- MK 31/7-2 QTY: 2
 - 1.1.9.3 Bearing Pedestals- MK 31/7-3, QTY: 4
 - 1.1.9.4 Bearing Caps- MK 31/7-6, QTY: 4
 - 1.1.10 Wire Rope Drum Assembly and Inspection of Wire Rope
 - 1.1.10.1 Stainless Steel Wire Rope
 - 1.1.10.2 Wire Rope Spacers- MK 31/13-3 QTY: 16
 - 1.1.10.3 End Drum Plates- MK 31/2-3 QTY: 2R/2L
 - 1.1.10.4 Intermediate Drum Plates- MK 31/2-4 QTY: 14
 - 1.1.10.5 Drum Rope Spacers- MK 31/2-5 QTY: 16
 - 1.1.10.6 Bull Gear and Drum Shafts- MK 31/2-11 QTY: 2
 - 1.1.11 Brakes
 - 1.1.12 Motors MK 31/4-3 QTY:)
 - 1.1.13 Miscellaneous Control Equipment, QTY: 2
- 1.2 OTHER SCOPE OF WORK
 - 1.2.1 Contact Pattern
 - 1.2.2 Repairs
 - 1.2.3 Option 1 - Bull Gear Painting and NDT, MK 31/2-2, QTY: 2
 - 1.2.4 Option 2 - Intermediate Gear Painting and NDT, MK 31/4-1, QTY: 2
- 1.3 NON-DESTRUCTIVE TESTING (NDT)
- 1.4 REPAIRS
- 1.5 INSPECTION REPORTS
- 1.6 QUALITY CONTROL
 - 1.6.1 Quality Control Plan (QCP)
 - 1.6.2 Testing and Certifications
 - 1.6.3 Shop and Field Tests

- 1.7 REFERENCES
- 1.8 APPLICABLE DRAWINGS
- 1.9 SAFETY
- 1.10 SECURITY
- 1.11 EXISTING WORK
- 1.12 GOVERNMENT-FURNISHED MATERIAL AND EQUIPMENT
 - 1.12.1 Delivery Schedule
 - 1.12.2 Delivery Location
 - 1.12.3 Site Work
- 1.13 SUBMITTAL DESCRIPTIONS
- 1.14 SUBMITTALS
- 1.15 REPAIR DRAWINGS

PART 2 PRODUCTS

- 2.1 KEYS AND KEYSEATS
- 2.2 BOLTS, NUTS, AND WASHERS
- 2.3 COUPLINGS

PART 3 EXECUTION

- 3.1 OPEN GEARS
- 3.2 ENCLOSED GEARS
- 3.3 CLEANING AND PAINTING
 - 3.3.1 Cleaning
 - 3.3.2 Painting
 - 3.3.3 Parts or Surfaces Not Painted
- 3.4 MISCELLANEOUS ITEMS
- 3.5 APPENDICES

-- End of Section Table of Contents --

SECTION 01 11 00

SUMMARY OF WORK

PART 1 GENERAL

1.1 BASE SCOPE OF WORK (SOW)

Contractor shall provide all labor, material, and equipment necessary to clean, disassemble/reassemble, and inspect all lifting machinery for the Barkley Lock Emergency Lift Gate, including but not limited to the limit switch assemblies, motors, enclosed gears, open gears, gear mounting assemblies, drums, sheaves, wire rope, brakes, shaft bearings, couplings, and control equipment. Provide the initial inspection reports with pictures of the equipment that show any deficiencies found during the inspection. Provide touch-up painting for all exterior surfaces of items in the scope of work after inspection except as otherwise noted. If a contract option is exercised, paint the respective components (except as otherwise noted) after the work in the contract option is completed. After completion, provide as-built reports that show as-built fits, backlashes, contact patterns and end floats. Initial inspection reports and as-built reports shall be required for all open gears, limit switch assemblies, and enclosed gears. Mark-up of the PDF for as-builts are acceptable. No CAD drawings shall be required for the as-builts. Provide new oil, grease, filters, fasteners, keys, and others as needed to get the Emergency Gate (E-Gate) machinery ready for operation.

Test Reports: The contractor will provide inspection reports detailing their findings after inspection of each component.

Provide four (4) flexible couplings and two (2) spare ones.

1.1.1 Removal of Concrete Access Covers

Provide all labor and equipment as required to remove and re-install six (6) concrete access covers (3 on the landside and 3 on the riverside) for the removal of the E-gate machinery as needed. Install new lifting points on all access covers. Provide rail around pit for protection. Rails must meet requirements of EM 385-1-1. Submit details of rails for approval. Rails and anchor bolts must be removed after the completion of the project. Cover all holes of removed anchor bolts with proper materials (concrete, epoxy, grout, etc.). It is also acceptable to cut the anchor rods to be flushed with the concrete surface. Reinstall access covers at the completion of work.

Weights for covers are as follows:

MK 20/63-3F: 7290 lbs (two total)
MK 20/63-1C: 4330 lbs (two total)
MK 20/63-2F: 2660 lbs (two total)

1.1.2 Primary reducers- MK 31/4-5 QTY: 2

1. Inspect reducer internals: Check for conditions of bearings, seals, pinions, gears, couplings, hardware, backlash, float, tooth contact, fits and clearance, keyway.

2. Perform NDT for all gear teeth.
3. Inspect gear teeth contact pattern.
4. Replace seals and gasket.
5. Replace filter (desiccant breather).
6. Replace oil.

Reducer housing: Clean reducer housing. No new painting or NDT is required for reducer housing.

1.1.3 Secondary reducers- MK 31/4-4 QTY: 2

1. Inspect reducer internals: Check for conditions of bearings, seals, pinions, gears, couplings, hardware, backlash, float, tooth contact, fits and clearance, keyway.
2. Perform NDT for all gear teeth.
3. Inspect gear teeth contact pattern.
4. Replace seals and gasket.
5. Replace filter (desiccant breather).
6. Replace oil.

Reducer housing: Clean reducer housing. No new painting or NDT is required for reducer housing.

1.1.4 Flexible couplings- MK 31/4-9 and MK 31/4-10 QTY: 4 Plus Spare

1. MK 31/4-9: required 2 and a spare (total of 3).
2. MK 31/4-10: required 2 and a spare (total of 3).

1.1.5 Bull gears- MK 31/2-2 QTY: 2; Bull Gear Guards

1. Check for conditions of bearings, gear teeth, gear body, bearing surface, etc..
2. Perform NDT for all gear teeth.
3. Inspect gear teeth contact pattern.
4. Remove the bull gear guards in order to access the bull gears for inspection and reinstall thereafter.
4. Modify the bull gear guards (MK 31/4-8, QTY: 2) to make them into two smaller sections for ease of removal. Smaller sections shall be reassembled with bolted connections. Connections shall not be made via weldment. Provide shop drawings for the modified bull gear guards for approval.

NDT shall not be performed for area of bull gear with existing painting. See paragraph "Option 1 - Bull Gear Painting and NDT" for additional scope of work.

1.1.6 Bull Gear Pinion Shaft- MK 31/4-2 QTY: 2

1. Check for conditions of bearings, gear teeth, gear body, bearing surface, etc..
2. Perform NDT for all gear teeth.
3. Inspect gear teeth contact pattern.

1.1.7 Intermediate gears - MK 31/4-1 QTY: 2

1. Check for conditions of bearings, gear teeth, gear body, bearing surface, etc..
2. Perform NDT for all gear teeth.
3. Inspect gear teeth contact pattern.

4. Remove the intermediate gear guards in order to access the intermediate gears for inspection and reinstall thereafter.

1.1.8 Gear Mounting Assemblies

Gear mounting assemblies shall be painted / coated as specified in paragraph "CLEANING AND PAINTING".

1.1.8.1 Bearing Pedestals- MK 31/3-1 QTY: 2

1. Clean and NDT bearing bases. Work shall be done at the project site since the bearing bases can't be removed.

1.1.8.2 Bearing Pedestals- MK 31/3-2 QTY: 2

1. Clean and NDT bearing bases. Work shall be done at the project site since the bearing bases can't be removed.

1.1.8.3 Bearing Pedestals- MK 31/3-3 QTY: 2

1. Clean and NDT bearing bases. Work shall be done at the project site since the bearing bases can't be removed.

1.1.8.4 Bearing Pedestals- MK 31/3-4 QTY: 2

1. Clean and NDT bearing bases. Work shall be done at the project site since the bearing bases can't be removed.

1.1.8.5 Bearing Caps- MK 31/3-5 QTY: 4

1. Clean and NDT bearing caps.

1.1.8.6 Bearing Caps- MK 31/3-6 QTY: 4

1. Clean and NDT bearing caps.

1.1.8.7 Bearing Caps- MK 31/3-7 QTY: 2

1. Clean and NDT bearing caps.

1.1.9 Sheave Assemblies

Sheave assemblies shall be painted / coated as specified in paragraph "CLEANING AND PAINTING".

1.1.9.1 Sheaves- MK 31/7-1 QTY: 2

1. Clean and NDT sheave body, bushings, and wire rope groove
2. Do NOT remove bushing from sheaves but inspect for unusual wear or eccentric bushings.
3. Apply rust inhibitor to the sheave assemblies.

1.1.9.2 Sheave Shafts- MK 31/7-2 QTY: 2

1. Clean and NDT sheave shaft.

1.1.9.3 Bearing Pedestals- MK 31/7-3, QTY: 4

1. Clean and NDT bearing bases. Work shall be done at the project

site since the bearing bases can't be removed.

1.1.9.4 Bearing Caps- MK 31/7-6, QTY: 4

1. Clean and NDT bearing caps.

1.1.10 Wire Rope Drum Assembly and Inspection of Wire Rope

1.1.10.1 Stainless Steel Wire Rope

1. Stainless steel wire ropes 1 1/2" dia. type 304 shall be inspected for but not limited to abrasion, corrosion, breaks, crushing, and diameter reduction. Reference ASME B30.30 for inspection of wire rope guidelines.

1.1.10.2 Wire Rope Spacers- MK 31/13-3 QTY: 16

1. Inspect for damage, signs of corrosion, and NDT any welds.

1.1.10.3 End Drum Plates- MK 31/2-3 QTY: 2R/2L

1. Clean and inspect for any surface defects that could cause rope damage, including but not limited to side-pulling, imprinting, and cracking.

1.1.10.4 Intermediate Drum Plates- MK 31/2-4 QTY: 14

1. Clean and inspect for any surface defects that could cause rope damage, including but not limited to side-pulling, imprinting, and cracking.

1.1.10.5 Drum Rope Spacers- MK 31/2-5 QTY: 16

1. Clean and inspect for any surface defects that could cause rope damage, including but not limited to side-pulling, imprinting, and cracking.

1.1.10.6 Bull Gear and Drum Shafts- MK 31/2-11 QTY: 2

1. Clean and visually inspect for surface defects, if a suspected area is identified the use of MT or PT shall be used to detail the defect. Cost for the MT or PT shall be covered in the contract modification.

1.1.11 Brakes

1. Clean and inspect for excessive wear and improper clearances. Replace oil and apply new grease as applicable.

1.1.12 Motors MK 31/4-3 QTY:)

1. Clean and inspect.
2. Check winding resistance.
3. Check winding insulation.

1.1.13 Miscellaneous Control Equipment, QTY: 2

Clean and inspect the miscellaneous control equipment that include, but not limited to the following items:

1. Driven gear - Limit Switch (MK 31/10-1, Qty: 2)
2. Driven gear - gear box (MK 31/10-2, Qty: 2)
3. Driven Gear - limit switch (MK 31/10-3, Qty: 2)
4. Driving gear - gear box (MK 31/10-4, Qty: 2)
5. Gear box - 1 to 1 ratio (MK 31/10-5, Qty: 2)
6. Shaft flange & stem (MK 31/10-6, Qty: 2)
7. Rear worm drive counter 1 to 10 ratio (Durant MOD.3SM-1193), Qty: 2
8. Others: couplings

NDT shall be included for all inspection of gear / reducer.

1.2 OTHER SCOPE OF WORK

1.2.1 Contact Pattern

Contractor shall provide the inspection report of the contact pattern. The report shall clearly indicate the percentage contact pattern for each gear. Pictures shall be included in the report to show the percentage of contact pattern.

1.2.2 Repairs

Repairs shall not be covered in this scope of work. However, Contractor shall develop a list of items recommended to be repaired. The cost to perform the inspection, develop the inspection report, and develop the list of items recommended to be repaired is covered in the base contract.

1.2.3 Option 1 - Bull Gear Painting and NDT, MK 31/2-2, QTY: 2

For area of bull gear with the existing paint, Contractor shall remove paint, perform NDT, and repaint the bull gear. Provide the NDT report.

1.2.4 Option 2 - Intermediate Gear Painting and NDT, MK 31/4-1, QTY: 2

For area of intermediate gear with the existing paint, Contractor shall remove paint, perform NDT, and repaint the bull gear. Provide the NDT report.

1.3 NON-DESTRUCTIVE TESTING (NDT)

All NDT performed shall be in the form of visual testing (VT) as well as dye-penetrant testing (PT) and/or magnetic particle testing (MT).

1.4 REPAIRS

Contractor shall not purchase any new material or components without prior submittal to the Government for approval. Contractor shall not repair or modify any existing government property without prior submittal to the Government for approval. Unless otherwise noted, Contractor shall submit the costs and schedule for the repairs as required from the initial inspection for approval.

1.5 INSPECTION REPORTS

Inspection reports shall include the initial inspection reports and final inspection reports (after repairs are done).

1.6 QUALITY CONTROL

1.6.1 Quality Control Plan (QCP)

The Contractor shall establish and maintain a quality control system to assure compliance with the requirements of these specifications and shall maintain records of quality control of all operations covered by these specifications. The contractor shall submit for review the quality control plan (QCP) for the work to be performed. The contents (at minimum) of the QCP shall be as follows:

- a. Table of contents.
- b. Pre inspection process indicating method of NDT and manufacture/product data of replacement seals.
- c. Work plan.
- d. Method of removal of bull gear guard.
- e. Post inspection repairs.

1.6.2 Testing and Certifications

Any testing shall be submitted as part of the QCP. All testing equipment shall be calibrated, and calibration certifications submitted as part of the QCP. All site testing results shall be submitted to the Government.

1.6.3 Shop and Field Tests

Shop and field testing of the equipment to be repaired shall be carried out in strict accordance with applicable specifications and standards. The contractor shall submit testing procedures for government approval.

1.7 REFERENCES

The publications listed below form a part of this section to the extent referenced. The publications are referred to within the text by the basic designation only.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

- | | |
|-------------|----------------------------------|
| ASME B17.1 | (1967; R 2017) Keys and Keyseats |
| ASME B30.30 | (2019) Ropes |

ASTM INTERNATIONAL (ASTM)

- | | |
|-------------------|---|
| ASTM F3125/F3125M | (2019) Standard Specification for High Strength Structural Bolts and Assemblies, Steel and Alloy Steel, Heat Treated, Inch Dimensions 120 ksi and 150 ksi Minimum Tensile Strength, and Metric Dimensions 830 MPa and 1040 MPa Minimum Tensile Strength |
|-------------------|---|

SOCIETY FOR PROTECTIVE COATINGS (SSPC)

- | | |
|------------------|---|
| SSPC 7/NACE No.4 | (2007) Brush-Off Blast Cleaning |
| SSPC QP 1 | (2019) Standard Procedure for Evaluating the Qualifications of Industrial/Marine Painting Contractors (Field Application to |

Complex Industrial Steel Structures and
Other Metal Components)

SSPC SP 2 (2024) Hand Tool Cleaning

SSPC SP 3 (2024) Power Tool Cleaning

U.S. ARMY CORPS OF ENGINEERS (USACE)

EM 385-1-1 (2024) Safety -- Safety and Occupational
Health (SOH) Requirements

1.8 APPLICABLE DRAWINGS

See Appendix B for details.

Q9-20/63.1 Misc. Metals, Armor, Recess, Frames and Covers
Q9-31/1.4 Upstream Emergency Gate Hoist - Assembly
Q9-31/2.3 Upstream Emergency Gate Hoist - Drum Assembly and Details
Q9-31/3.3 Upstream Emergency Gate Hoist - Bearings and Bushings
Q9-31/4.3 Upstream Emergency Gate Hoist - Gears, Pinion Shafts &
Equipment Details
Q9-31/5.3 Upstream Emergency Gate Hoist - Machinery Base
Q9-31/6.3 Upstream Emergency Gate Hoist - Machinery Base Support
Q9-31/7.3 Upstream Emergency Gate Hoist - Idler Sheave and Details
Q9-31/10.3 Upstream Emergency Gate Hoist - Misc. Control Equipment
and Details
Q9-31/11.2 Upstream Emergency Gate Hoist - Machinery Supports
Q9-31/13 Upstream Emergency Gate Hoist - Wire Rope Assembly
Replacement

1.9 SAFETY

The contractor must adhere to safety requirements in EM 385-1-1. The contractor shall closely coordinate with the lock master to conduct the work safely in accordance with LRN Operations safe work procedures.

1.10 SECURITY

See Section 01 35 50 PROJECT SITE SECURITY AND AT/OPSEC PROCEDURES for details.

1.11 EXISTING WORK

Remove or alter existing work in such a manner as to prevent injury or damage to any portions of the existing work which remain. Cover all MCCs and other exposed electrical equipment with waterproof tarp to prevent water intrusion for the duration of work.

Repair or replace portions of existing work which have been altered during construction operations to match existing or adjoining work, as approved by the Contracting Officer. At the completion of operations, existing work must be in a condition equal to or better than that which existed before new work started.

1.12 GOVERNMENT-FURNISHED MATERIAL AND EQUIPMENT

Unless otherwise noted, Contractor shall provide all labor and equipment to perform the required scope of work. Assistance with loading and

unloading of machinery components shall be requested and coordinated with the Lock Master 10 days in advance.

1.12.1 Delivery Schedule

Notify the Contracting Officer in writing at least 7 calendar days in advance of the date on which the materials and equipment are required.

Materials and equipment will be available on or after 10 calendar days after the award of contract.

1.12.2 Delivery Location

Barkley Lock
758 Barkley Dam Road
Grand Rivers, KY, 42045

PoC: Jeff Neely, jeffrey.o.neely@usace.army.mil, 270-362-4222

1.12.3 Site Work

While working on Government equipment contractor will adhere to safety standards EM 385-1-1. All coordination while on site shall be conducted through the lock master and his staff. Working hours shall be Monday-Thursday from 0600hrs-1600hrs except federal holidays. Any work outside these hours shall be submitted for approval.

1.13 SUBMITTAL DESCRIPTIONS

Submittal requirements are specified in the technical paragraphs. Examples and descriptions of submittals identified by the Submittal Description (SD) numbers and titles follow:

SD-01 Preconstruction Submittals

Government approved preconstruction submittals that are required prior to or commencing with the start of work must be submitted within 30 calendar days of contract award unless specified elsewhere in the specifications. Contractor approved submittals that are required prior to or commencing with the start of work must be submitted within 45 calendar days of contract award unless specified elsewhere in the specifications.

Preconstruction Submittals include schedules and a tabular list of locations, features, and other pertinent information regarding products, materials, equipment, or components to be used in the work.

List Of Proposed Products

Submittal Register

Quality Control (QC) plan

SD-03 Product Data

Catalog cuts, illustrations, schedules, diagrams, performance charts, instructions and brochures illustrating size, physical appearance and other characteristics of materials, systems or equipment for some portion of the work.

Samples of warranty language when the contract requires extended product warranties.

SD-06 Test Reports

Report signed by authorized official of testing laboratory that a material, product or system identical to the material, product or system to be provided has been tested in accord with specified requirements. Unless specified in another section, testing must have been within three years of date of contract award for the project.

Report that includes findings of a test required to be performed on an actual portion of the work or prototype prepared for the project before shipment to job site.

Report that includes finding of a test made at the job site or on sample taken from the job site, on portion of work during or after installation.

Investigation reports

Final acceptance test and operational test procedure

SD-11 Closeout Submittals

Documentation to record compliance with technical or administrative requirements or to establish an administrative mechanism.

Submittals required for Guiding Principle Validation (GPV) or Third Party Certification (TPC).

Special requirements necessary to properly close out a construction contract. For example, Record Drawings and as-built drawings. Also, submittal requirements necessary to properly close out a major phase of construction on a multi-phase contract.

1.14 SUBMITTALS

Government approval is required for submittals with a "G". Submittals not having a "G" are for information only. When used, a code following the "G" classification identifies the office that will review the submittal for the Government.

Submittals Requiring Approval: Submittals requiring approval shall be submitted per the following procedure: Each submission by the Contractor shall be accompanied by a letter of transmittal containing a list of the items submitted, giving titles and numbers as applicable. Transmittals shall be addressed to the person designated by the Contracting Officer. All submittals shall be provided via email unless otherwise requested or approved. Decisions on these submittals, either approval or disapproval, will be given by the Government's Representative within 15 calendar days (30 calendar days for shop drawings). Each item submitted with "Approved," "Approved Except as Noted," or "Returned for Correction." The notations "Approved" and "Approved Except as Noted" authorize the Contractor to proceed with the fabrication of the equipment and/or repair covered by such drawings, subject to the corrections, if any, indicated thereon or described in the letter of transmittal. When the submittal has been "Returned for Correction", the Contractor shall make the necessary

revisions and shall resubmit for approval in the same routine as before. Every revision made during the life of the contract shall be shown by the number, date, and subject in a revision block and a notation shall be made in the drawing margin to permit rapid location of the revision. The time consumed by the Contractor in submitting and obtaining approval of submittals shall be included in the time allowed for completion of the contract.

Submittals for Information Only: Submittals not requiring government approval shall be submitted for information only.

SD-01 Preconstruction Submittals

Qualifications; G

A statement certifying that the contractor possesses the capability to inspect items of similar scope and quality shall be submitted with the contractor's quote. The statement shall include examples of similar work performed within the past 36 months. List of qualification shall be submitted with the contractor's bid prior to award.

Schedule; G

The Contractor shall submit for approval a schedule of all work to be performed. The schedule shall detail time required for submittals, approvals, material purchases, NDT, and repair.

Materials List; G

The Contractor shall submit a detailed bill of materials for items used in installation of new lifting points, replacement of seals, or repairs post Government approval.

Quality Control Plan ; G

Removal Of Concrete Access Covers; G

SD-02 Shop Drawings

Bull Gear Guards; G

Rails; G

SD-03 Product Data

Flexible Couplings; G

SD-06 Test Reports

Letter of Certification and Technical Data; G

Letters of certification shall be provided for all materials to be used. Certified test reports for all required materials shall show that materials comply with applicable specifications. These reports shall note specific standards followed in the performance of tests. All materials to be used shall be products milled and /or manufactured within the borders of the United States of America.

Primary reducers; G

Secondary reducers; G

Bull Gears; G

Intermediate Gears; G

Sheave Assemblies; G

Miscellaneous Control Equipment; G

Repairs; G

Wire Rope Drum Assembly And Inspection Of Wire Rope; G

Inspection Reports; G

Brakes; G

Gear Mounting Assemblies; G

Bull Gear Pinion Shaft; G

Motors; G

Bull Gear Painting And Ndt; G

Intermediate Gear Painting And Ndt; G

SD-11 Closeout Submittals

Repair Drawings; G

1.15 REPAIR DRAWINGS

Repair drawings for the work herein shall be submitted for approval. Drawings shall include testing and repair details, along with type, grade, and class of materials as appropriate. Elements of fabricated items inadvertently omitted on contract drawings shall be detailed by the fabricator and indicated on the shop drawings. All work performed and all materials ordered prior to Government approval of the repair drawings are subject to refusal by the Government.

PART 2 PRODUCTS

2.1 KEYS AND KEYSEATS

New keys shall be in accordance with ASME B17.1 Class II for all machinery and connecting components. The keyway dimensions shall match contract drawings.

2.2 BOLTS, NUTS, AND WASHERS

Provide bolts, nuts, and washers of the material, grade, type, class, style, and finish indicated or best suited for intended use. All hardware shall be galvanized. Bolts shall be of Gr. 8 ASTM F3125/F3125M, Gr 490.

2.3 COUPLINGS

Provide flexible couplings as shown in drawings. Couplings shall be of equal rating to the existing couplings. Flexible couplings are double

engagement shaft standard type size 2. In determining the flexible couplings capacity, the manufacturer's published rating shall be divided by a service factor of 1.5 or factor recommended by manufacturer, whichever is greater. Flexible couplings shall be forged steel and shall transmit torque by means of external gears on hubs engaging in internal gears on the flexible coupling sleeves. Sleeves shall be fastened so that they cannot work or slip off. Flexible couplings with sleeves held in place or retained by snap rings will not be permitted. Flexible couplings shall be enclosed and sealed to retain the lubricant and shall be oil tight under both static and operating conditions.

PART 3 EXECUTION

3.1 OPEN GEARS

Pinions and bull gears for the hoists shall be cleaned and inspected. Inspect for excessive gear tooth wear, cracking, pitting, indentions, backlash, and missing gear teeth. Provide both visual testing (VT) and magnetic particle testing (MT). Provide new grease for pinions and gears as applicable. The gear guards shall be removed, cleaned and painted for all interior and exterior surfaces. Submit initial inspection reports and as-built reports that includes visual inspection of all teeth for approval. Alignment shall be checked at no load with bluing compound. Alignment of the gears shall be modified, where required, to obtain a minimum of 70% contact pattern across the face of the gear and pinion.

All limit switch assemblies shall also be reconditioned. Reconditioning procedures shall be the same as for other pinions and gears.

3.2 ENCLOSED GEARS

All components of the gear reducers shall be completely cleaned and inspected. Oil shall be drained and discarded. Provide new oil for helical gear reducers. All debris and sludge inside the gear reducer shall be removed and the gear reducer interior shall be wiped clean. New seals and filters shall be installed.

Unless otherwise noted, the following steps shall be required for reconditioning / rebuilding of the enclosed gears.

1. Record as received shaft end floats.
2. Record as received gear contact patterns.
3. Remove the gears from the housing and reassemble the housing to:
 - a. Measure housing bores for proper fit and roundness.
 - b. CMM (Coordinate Measuring Machines) the housing to assure proper bore alignment and look for any twist in the housing.
 - c. Measure the foot flatness relative to the bores.
4. Gears shall be cleaned and NDT for cracks.
5. Housing and all other exterior surfaces shall be cleaned and repainted per contract specifications.
6. Rolling element bearing shall be removed and inspected; the shafts shall be inspected for proper fit.
7. Submit the initial inspection report. Government personnel shall conduct the shop inspection after receiving the initial inspection report.
8. All rotating assemblies shall be dynamically balanced for the appropriate speeds.
9. Install all new bearings and seals.
10. Install new desiccant breathers.

11. Conduct leak test on gear boxes.
12. Test run for a minimum of 2 hours.
13. Provide as-built reports that include as-built fits, backlashes, contact patterns and end floats.

3.3 CLEANING AND PAINTING

3.3.1 Cleaning

All surfaces shall receive cleaning in accordance with SSPC QP 1. Remove all loose rust, dirt, moisture, grease or other contaminants from surface. When touch-up paint or new paint is required, provide additional cleaning in accordance with SSPC SP 3 and/or SSPC SP 2. For more severe environments, dry abrasive blast in accordance with SSPC 7/NACE No.4. Water blasting is also acceptable.

3.3.2 Painting

Touch-up paint shall be applied to surfaces that have scratches, chips, peeling paint, flaking paint, blistering, paint, rust, corrosion, etc. New paint shall be applied to repaired, modified, or new items.

After cleaning, surfaces shall be painted before formation of moisture on or contamination of the surfaces. All exterior surfaces shall be painted with one coat of primer and two coats of Amerlock 400 Aluminum color. Painting shall not be performed prior to inspection by Government unless waived in writing. Machined-finished surfaces of metals which are exposed after installation shall also be painted in the shop by the contractor, except components whose operation, assembly, or disassembly would be affected by paint application.

3.3.3 Parts or Surfaces Not Painted

Paint shall not be applied on nameplates, adjusting screws, corrosion resisting steel, running surfaces, mating surfaces, or other components whose operation, assembly, or disassembly would be affected by paint application.

Thoroughly clean foreign matter off machined surfaces. All finished surfaces shall be protected by suitable means. Oil and wrap unassembled pins and bolts with moisture resistant paper or protect them by other approved means. Wash finished surfaces of ferrous metals to be in bolted contact, with an approved rust inhibitor and coat them with an approved rust resisting compound for temporary protection during fabrication, shipping and storage periods.

All unpainted machine-finished surfaces shall be protected by Houghton-Vaughan Co.'s "Rust Veto No. 342" for shipping and storage protection.

3.4 MISCELLANEOUS ITEMS

Miscellaneous items such as bolts and screws for replaced and reconditioned components, keys, shim plates, grease fittings, grease line tubing, spiral pins, snap rings, seals, gaskets, grease, oil, etc. shall be replaced with new during rebuilding/reassembling of components.

3.5 APPENDICES

Appendix A: Submittal Register

Appendix B: Applicable Drawings / Reference Drawings

-- End of Section --

SECTION TABLE OF CONTENTS

DIVISION 01 - GENERAL REQUIREMENTS

SECTION 01 35 50

PROJECT SITE SECURITY AND AT/OPSEC PROCEDURES

PART 1 GENERAL

- 1.1 GENERAL
- 1.2 REFERENCES
- 1.3 SUBMITTALS
- 1.4 EMPLOYEE IDENTIFICATION AND CONTROL PROCEDURE
- 1.5 PRE-SCREENING CONTRACTOR'S ON-SITE EMPLOYEES USING E-VERIFY
- 1.6 GENERAL SECURITY REQUIREMENTS AND GUIDANCE
- 1.7 PHYSICAL SECURITY AND ACCESS CONTROL REQUIREMENTS
- 1.8 REQUIRED TRAINING
 - 1.8.1 AT Level 1 Training
 - 1.8.2 Suspicious Activity Reporting Training
 - 1.8.3 Operations Security (OPSEC) Training
- 1.9 CONVICT LABOR
- 1.10 ESCORTS
- 1.11 PRE-PROPOSAL MEETING IN CONTROLLED AREA
 - 1.11.1 U.S. Citizens
 - 1.11.2 Foreign Nationals (FNs)
- 1.12 ELECTRONIC MEDIA PROVIDED BY THE CONTRACTOR
- 1.13 CONDUCT OF CONTRACTOR EMPLOYEES
- 1.14 VEHICLES
 - 1.14.1 Parking of Vehicles
 - 1.14.2 Identification of Vehicles
- 1.15 RELEASE OF INFORMATION
- 1.16 DAMAGE OR LOSS OF CONTRACTOR'S SUPPLIES AND PROPERTY

PART 2 PRODUCTS

PART 3 EXECUTION

-- End of Section Table of Contents --

THIS PAGE INTENTIONALLY LEFT BLANK

SECTION 01 35 50

PROJECT SITE SECURITY AND AT/OPSEC PROCEDURES

PART 1 GENERAL

1.1 GENERAL

The entire Project area is not open to the public. Depending upon the level of security threat, some Project areas may or may not be open to the Contractor and Contractor employees. Guidance and forms for project site security requirements are available on the Nashville District Public Website:
<https://www.lrn.usace.army.mil/Business-With-Us/Contract-Security-Requirements/>

1.2 REFERENCES

The publications listed below form a part of this specification to the extent referenced. The publications are referred to within the text by the basic designation only.

U.S. ARMY (DA)

Army Directive 2014-05	(2014) Policy and Implementation Procedures for Common Access Card Credentialing and Installation Access for Uncleared Contractors
------------------------	---

DA AR 190-13	(2019) The Army Physical Security Program
--------------	---

U.S. ARMY CORPS OF ENGINEERS (USACE)

EM 385-1-1	(2024) Safety -- Safety and Occupational Health (SOH) Requirements
------------	---

1.3 SUBMITTALS

Government approval is required for submittals with a "G" designation; submittals not having a "G" designation are for information only. When used, a designation following the "G" designation identifies the office that will review the submittal for the Government.

SD-01 Preconstruction Submittals

Verified/Eligible Employee Candidates

Employee Identification and Control Procedure; G

Investigation Package

Foreign Nationals

SD-07 Certificates

At Level 1 Training

Suspicious Activity Reporting Training

Operations Security (OPSEC) Training

1.4 EMPLOYEE IDENTIFICATION AND CONTROL PROCEDURE

An employee identification and control procedure shall be submitted for approval for identification and control of employees entering or leaving the project site. Contract personnel shall comply with all personal identity verification requirements specified in facility policies and procedures. Contractor workforce must comply with all personal identity verification requirements (FAR Clause 52.204-9 PERSONAL IDENTITY VERIFICATION OF CONTRACTOR PERSONNEL) as directed by DOD, HQDA and/or local policy. It is expected that this will include a unique photo identification card for each contractor and subcontractor employees working at the project site.

1.5 PRE-SCREENING CONTRACTOR'S ON-SITE EMPLOYEES USING E-VERIFY

Contractors must comply with the requirements set forth in FAR clause 52.222-54 Employment Eligibility Verification and FAR Subpart 22.18 in using the E-Verify Program at (<https://www.e-verify.gov/>) (website subject to change) to meet the contract employment eligibility requirements. Contractors are encouraged to cooperate with Federal and State agencies responsible for enforcing labor requirements to include eligibility for employment under United States immigration laws in accordance with FAR 22.102-1(i). An initial list of verified/eligible candidates must be provided to the Contract Officer's Representative (COR) no later than three business days after the initial contract award. When contracts are with individuals, the individuals will be required to complete a Form I-9, Employment Eligibility Verification, and submit it to the Contracting Officer to become part of the official contract file.

1.6 GENERAL SECURITY REQUIREMENTS AND GUIDANCE

The security requirements described within apply to all contract personnel (including employees of the prime Contractor ("Contractor") and all subcontractor employees) supporting the performance requirements of this contract. The Contractor is responsible for compliance with these security requirements. Questions regarding security matters shall be addressed to the designated Government representative (e.g., Contracting Officer Representative (COR), Requiring Activity (RA) representative, or Contracting Officer (if a COR or other RA representative is not appointed)). Contractor personnel and vehicles are subject to search when entering Federal installations. Additionally, all contract personnel shall comply with Force Protection Condition (FPCON) measures, Random Antiterrorism Measures (commonly referred to as "RAMs"), and Health Protection Condition (HPCON) measures. The Contractor is responsible for meeting performance requirements during elevated FPCON and/or HPCON levels in accordance with applicable RA plans and procedures-this includes identifying mission essential and non-mission essential personnel. In addition to the changes otherwise authorized by the changes clause of this contract, should the FPCON or HPCON levels at any individual facility or installation change, the Government may implement security changes that effect contract personnel. All contract personnel must comply with Force Protection Condition (FPCON) measures, Random Antiterrorism Measures (commonly referred to as "RAMs"), and Health Protection Condition (HPCON) measures. Contract personnel and vehicles are subject to search when

entering Federal installations. Contractor must ensure all contract personnel are aware of their security responsibilities, including any site-specific requirements identified in local policies or procedures.

Contract personnel are critical to the overall security and safety of US Army Corps of Engineers (USACE) installations, facilities and activities, and security awareness training contributes to those efforts. The Department of Defense (DoD) and Army security training requirements specified below, if applicable, are performance requirements; all applicable contract personnel shall complete initial training within 30 days of contract award or the date new contract personnel begin performance on the contract. Within five business days from the completion of training, the Contractor shall provide written documentation (e.g., e-mail or memorandum) to the Government representative. The documentation shall include the names of contract personnel trained and which training they completed; the Contractor shall maintain training records as part of their contract files and be prepared to provide copies of training certificates to the Government representative.

1.7 PHYSICAL SECURITY AND ACCESS CONTROL REQUIREMENTS

All contractors and all associated sub-contractors shall comply with applicable District and local security policies and procedures (provided by the Government representative). The contractor shall provide the District Security Office with any/all requested information which may be required for background screenings, checks and/or investigations to meet installation/facility access requirements. Contractor workforce must comply with all personal identity verification requirements as directed by DOD, HQDA and/or local policy. In addition to the changes otherwise authorized by the changes clause of this contract, should the Force Protection Condition (FPCON) at any installation or facility change, the Government may require changes in contractor security matters or processes.

Contractor and all associated sub-contractors employees shall comply with adjudication standards and procedures using the National Crime Information Center Interstate Identification Index (NCIC-III) and Terrorist Screening Database (TSDB) (Army Directive 2014-05 / DA AR 190-13), applicable installation, facility and area commander installation/facility access and local security policies and procedures (provided by government representative, as NCIC and TSDB are available), or, at OCONUS locations, in accordance with status of forces agreements and other theater regulations.

Guidance and forms for the background investigation requirements are available on the Nashville District Public Website:
(<https://www.lrn.usace.army.mil/Business-With-Us/Contract-Security-Requirements/>)

Background investigations for U.S. Citizens who will work (a) within a control area, (b) on a government information system and/or (c) have access to government funds will be submitted in accordance with the appropriate level in Category B.

The background investigation requirements for those U.S. Citizens who will not work (a) within a control area, (b) on a government information system and/or (c) have access to government funds is provided in Category A.

Foreign National Contractors: Follow the guidance on the website specified in Category C - Foreign National Contractors

Since the work is being done within a controlled area and is expected to last more than six months, the investigation requirements fall under Category B3 for US Citizens and Category C for Foreign National Contractors. Guidance and forms for the requirements are available on the Nashville District Public Website:

<https://www.lrn.usace.army.mil/Business-With-Us/Contract-Security-Requirements/>.

Contractor employees are not authorized to begin work on the contract until investigation requirements have been completed and notification has been made by the COR or the District Security Office.

Background investigations for U.S. Citizens who will work (a) within a controlled area, (b) on a government information system and/or (c) have access to Government funds will be submitted in accordance with the appropriate level in Category B.

The Background investigation requirements for those U.S. Citizens who will not work (a) within a controlled area, (b) on a Government information system and/or (c) have access to Government funds is provided in Category A.

1.8 REQUIRED TRAINING

1.8.1 AT Level 1 Training

All contractor and subcontractor employees, requiring access to Army installations, facilities, controlled access areas, or require network access, shall complete AT Level I Awareness Training within 30 calendar days after contract start date or effective date of incorporation of this requirement into the contract, whichever is applicable. Upon request, the contractor shall submit certificates of completion for each applicable contract employee and subcontractor employee, to the COR or to the Contracting Officer (if a COR is not assigned), within 5 calendar days after completion of training by all contract personnel. AT Level I Awareness Training is available at the following website:

<https://jko.jten.mil/courses/AT-level1/launch.html>

Each contract employee must take the training individually to receive a training certificate.

1.8.2 Suspicious Activity Reporting Training

All Contractor personnel shall receive initial and annual refresher training from the RA representative on the local suspicious activity reporting program. This locally developed training provides contract personnel with general information on suspicious behavior, and guidance on reporting suspicious activity to the project manager, security representative or law enforcement entity. The Contractor and all associated sub-contractors shall receive training on the local Suspicious Activity Reporting Program. This training identifies behavioral indicators and provides guidance reporting suspicious activity. This training shall be completed within 30 calendar days of contract award and within 30 calendar days of new employees commencing performance with the results reported to the COR NLT 5 calendar days after the completion of the training. The iWatch training for contractors is available on the Nashville District Public Website::

<https://www.lrn.usace.army.mil/Business-With-Us/Contract-Security-Requirements/>

Additional Optional Information Regarding Suspicious Activity Reporting:

- a. iWatch Army is available at
<https://www.army.mil/standto/archive/2018/07/25/>;
- b. CorpsWatch (Property Protection Program to Deter Crime) is available at
<https://corpslakes.erdc.dren.mil/visitors/corpswatch.cfm>
- c. Homeland Security "See Something Say Something"
<https://www.dhs.gov/see-something-say-something>.
- d. Eye On Kentucky program (report anonymously suspicious criminal or terrorist activity):
<https://homelandsecurity.ky.gov/Pages/Report-Suspicious-Activity.aspx>
- e. Tennessee Suspicious Activity Report:
<https://www.tn.gov/safety/homeland-security/report-suspicious-activity.html>
- f. Alabama Suspicious Activity Report
<https://app.alea.gov/SAR/>

1.8.3 Operations Security (OPSEC) Training

All contract personnel with working in sensitive area for more than 180 days, have access to government networks, are working with or have access to CUI information, shall complete initial and annual refresher OPSEC Level I Awareness training, which is available at:
<https://securityawareness.usalearning.gov/opsec/index.htm> Contractor employees will complete Level 1 OPSEC Training within 30 calendar days of their reporting for duty. The contractor shall submit certificates of completion for each affected contractor and subcontractor employee, to the COR or to the Contracting Officer.

1.9 CONVICT LABOR

Because the work is being performed in a restricted area, there are restrictions on use of persons either imprisoned or previously convicted of a felony. The Contractor must not employ in the performance of this contract any person undergoing a sentence of imprisonment imposed by any court of a State, the District of Columbia, Puerto Rico, the Northern Mariana Islands, American Samoa, Guam, or the U.S. Virgin Islands, or the US Federal Government. The Contractor shall not employ in the performance of this contract any person who has been convicted of a felony imposed by any court of a State, the District of Columbia, Puerto Rico, the Northern Mariana Islands, American Samoa, Guam, the U.S. Virgin Islands, or the US Federal Government.

1.10 ESCORTS

In accordance with applicable regulations, all contract personnel who do not possess the appropriate security clearance or access privileges will be escorted in areas where they may be exposed to classified information

or operations, sensitive information or activities, or restricted areas. Escorts must be USACE employees and never other contractors.

Note: Escort Requirement will no longer be required once the Contract Officer's Representative has been notified a favorable long-term investigation (Category B3) has been completed. B3 not required for extremely short maintenance or repair contracts in which the contractor will be escorted throughout project completion (under 30 days).

1.11 PRE-PROPOSAL MEETING IN CONTROLLED AREA

Contractors and/or potential contractors wishing to attend a pre-bid meeting held at or in LRN restricted/controlled areas (such as a Power Plant or Navigation Lock) shall submit a Nashville District (LRN) Security Access Form to the Nashville District Point of Contact (LRN POC) five (5) days prior to the site visit or meeting. If submitting the document in less than five days, the Offeror/Bidder may not receive approval for participation. The LRN POC will notify the Contractor if the request is approval or denied. Any pre-bid meeting which will cover anything other than public domain information shall be limited to US Citizens, except under unique circumstances. The Security Access Form and guidance is available at:
<https://www.lrn.usace.army.mil/Business-With-Us/Contract-Security-Requirements/>

Any pre-bid meeting which will cover anything other than public domain information shall be limited to US Citizens, except under unique circumstances.

1.11.1 U.S. Citizens

The Offeror and/or Contractor shall submit a Nashville District (LRN) Security Access Form to the Nashville District Point of Contact (LRN POC) five (5) days prior to the site visit or any meeting held at or in LRN restricted/controlled areas (such as a Power Plant or Navigation Lock). If submitting the document in less than five days, the Offeror/Bidder may not receive approval for participation. The LRN POC will notify the individual(s) if the request is approved or denied.

The "Security Access Form - U.S. Citizens" with guidance is available at:

<https://www.lrn.usace.army.mil/Portals/49/docs/Security/US%20Citizen%20Pre-Bid%20or%20>

1.11.2 Foreign Nationals (FNs)

FNs wishing to attend a pre-proposal meeting or site visit shall submit a completed LRN FN Security Form and legible color copies of two of the following documents: Passport (unexpired or expired), Certificate of U.S. Citizenship (INS Form N-560 04 N-561), Certificate of Naturalization (INS Form N-550 or N-570), unexpired foreign Passport with I-551 stamp or attached INS Form I-94 indicating unexpired employment authorization, an Alien Registration Receipt Card with photo (INS Form I-151 or I-551), unexpired Temporary Resident Card (INS Form I-688), unexpired Employment Authorization Card (INS Form I-688A), unexpired Reentry Permit (INS Form I-327), unexpired Refugee Travel Document (INS- Form I-571), or unexpired Employment Authorization Documentation issued by the INS which contains a photograph (INS Form I-688B) to the LRN POC to be forwarded to LRN-SM for approval. These documents must be submitted 14 calendar days prior to the meeting or site visit. Exceptions will be considered on a case by case basis but will be limited.

The "Foreign National Security Access Form" and "Foreign National Pre-Bid Meeting Request Form" with guidance are available at:

<https://www.lrn.usace.army.mil/Portals/49/docs/Security/FN%20Site%20Visit%20Request%20>

1.12 ELECTRONIC MEDIA PROVIDED BY THE CONTRACTOR

If the Contractor provides any data, electronic media, electronic files, or documents etc., to the Government the Contractor must ensure it is free of any viruses, e.g. Trojan horses, botnet, worms, spyware, adware, rootkits, or any other malicious software that could be harmful or of a destructive nature to Government computer systems.

1.13 CONDUCT OF CONTRACTOR EMPLOYEES

Meet the requirements of EM 385-1-1, Section 01.C Physical Qualifications of Employees, in providing on-site employees. All Contractor employees and subcontractors shall conduct themselves in a proper manner at all times. No alcoholic or intoxicating beverages or substances or illegal drugs or controlled substances not prescribed by a physician shall be possessed, consumed, and no contractor employee shall be under the influence of any such unauthorized substance while on Government property.

The Contractor shall remove from the site any individual whose continued employment is deemed by the appointed receiving agent to be contrary to the public interest or inconsistent with the best interests of the U.S. Army Corps of Engineers.

The Contracting Officer or the appointed receiving agent will require the Contractor to immediately remove from the work site anyone who is incompetent or who endangers persons or property or whose physical or mental condition is such that it would impair the employee's ability to satisfactorily perform the work. Notification to the Contractor will be made in writing if time and circumstances permit. Otherwise, notification will be verbal and will be confirmed in writing as soon as possible. No such removal, however, will reduce the Contractor's obligation to perform all work required under this contract and immediate replacement shall be made as required.

1.14 VEHICLES

1.14.1 Parking of Vehicles

Parking of private and Contractor vehicles shall be restricted to the areas designated by the Government. Vehicles shall be parked no closer than 30 feet from occupied buildings.

1.14.2 Identification of Vehicles

The Contractor shall supply the Government with an up-to-date vehicle list that identifies contractor vehicles by license plate number, make and model of vehicle.

1.15 RELEASE OF INFORMATION

The Contractor shall not make available to the news media or publicly disclose any data generated or reviewed under this contract. Any inquiry received by the Contractor for information concerning work performed under this contract shall be referred to the Government for evaluation under the Freedom of Information Act of 1975, Public Law 93-502, 5 U.S.C., Section

552. The determination of whether records will be released will remain with the Government. The Contractor shall assist the COR in compiling information or records for submission upon request by the Government. Reports and data generated under this contract shall become property of the Government and distribution to any other source by the Contractor, unless authorized is prohibited.

1.16 DAMAGE OR LOSS OF CONTRACTOR'S SUPPLIES AND PROPERTY

The Contractor is responsible for taking the action necessary to protect Contractor supplies, materials and equipment, and the personal property of Contractor employees from loss, damage or theft. The Government assumes no responsibility for theft, damage, etc., of the above. All incidents of theft (or suspected theft) of contractor materials, supplies, or equipment from project lands shall be reported to the COR.

PART 2 PRODUCTS

Not Used.

PART 3 EXECUTION

Not Used.

-- End of Section --

SUBMITTAL REGISTER

CONTRACT NO.

TITLE AND LOCATION

BAR Egate Machinery Inspection

CONTRACTOR

ACTIVITY NO	TRANSMITTAL NO	SPEC SECT	DESCRIPTION ITEM SUBMITTED	PARAGRAPH	GOVT CLASS SIF CATION OR A/E REVIEW WR	CONTRACTOR: SCHEDULE DATES			CONTRACTOR ACTION		DATE FWD TO APPR AUTH/ DATE RCD FROM CONTR	APPROVING AUTHORITY				MAILED TO CONTR/ DATE RCD FRM APPR AUTH	REMARKS
						SUBMIT	APPROVAL NEEDED BY	MATERIAL NEEDED BY	ACTION CODE	DATE OF ACTION		DATE FWD TO OTHER REVIEWER	DATE RCD FROM OTH REVIEWER	ACTION CODE	DATE OF ACTION		
(a)	(b)	(c)	(d)	(e)	(f)	(g)	(h)	(i)	(j)	(k)	(l)	(m)	(n)	(o)	(p)	(q)	(r)
		01 11 00	SD-01 Preconstruction Submittals														
			Qualifications		G												
			Schedule		G												
			Materials List		G												
			Quality Control Plan	1.6.1	G												
			Removal Of Concrete Access	1.1.1	G												
			Covers														
			SD-02 Shop Drawings														
			Bull Gear Guards	1.1.5	G												
			Rails	1.1.1	G												
			SD-03 Product Data														
			Flexible Couplings	2.3	G												
			SD-06 Test Reports														
			Letter of Certification and		G												
			Technical Data														
			Primary reducers	1.1.2	G												
			Secondary reducers	1.1.3	G												
			Bull Gears	1.1.5	G												
			Intermediate Gears	1.1.7	G												
			Sheave Assemblies	1.1.9	G												
			Miscellaneous Control Equipment	1.1.13	G												
			Repairs	1.4	G												
			Wire Rope Drum Assembly And	1.1.10	G												
			Inspection Of Wire Rope														
			Inspection Reports	1.5	G												
			Brakes	1.1.11	G												

CONTRACT NO.

CONTRACTOR

[illegible]

TRANSMITTAL OF SHOP DRAWINGS, EQUIPMENT DATA, MATERIAL SAMPLES, OR MANUFACTURER'S CERTIFICATES OF COMPLIANCE <i>(Read instructions on the reverse side prior to initiating this form)</i>					DATE		TRANSMITTAL NO.			
SECTION I - REQUEST FOR APPROVAL OF THE FOLLOWING ITEMS <i>(This section will be initiated by the contractor)</i>										
TO:		FROM:			CONTRACT NO.		CHECK ONE: ☐ THIS IS A NEW TRANSMITTAL ☐ THIS IS A RESUBMITTAL OF TRANSMITTAL _____			
SPECIFICATION SEC. NO. <i>(Cover only one section with each transmittal)</i>		PROJECT TITLE AND LOCATION					CHECK ONE: THIS TRANSMITTAL IS FOR ☐ FID ☐ GOV'T. APPROVAL			
ITEM NO.	DESCRIPTION OF ITEM SUBMITTED <i>(Type size, model number/etc.)</i>			MFG OR CONTR. CAT., CURVE DRAWING OR BROCHURE NO. <i>(See instruction no. 8)</i>	NO. OF COPIES	CONTRACT REFERENCE DOCUMENT		FOR CONTRACTOR USE CODE	VARIATION <i>(See instruction No. 6)</i>	FOR CE USE CODE
a.	b.			c.	d.	SPEC. PARA. NO. e.	DRAWING SHEET NO. f.	g.	h.	i.
REMARKS						I certify that the above submitted items have been reviewed in detail and are correct and in strict conformance with the contract drawings and specifications except as other wise stated. _____ NAME AND SIGNATURE OF CONTRACTOR				

SECTION II - APPROVAL ACTION		
ENCLOSURES RETURNED <i>(List by Item No.)</i>	NAME, TITLE AND SIGNATURE OF APPROVING AUTHORITY	DATE

INSTRUCTIONS

1. Section I will be initiated by the Contractor in the required number of copies.
2. Each transmittal shall be numbered consecutively in the space provided for "Transmittal No.". This number, in addition to the contract number, will form a serial number for identifying each submittal. For new submittals or resubmittals mark the appropriate box; on resubmittals, insert transmittal number of last submission as well as the new submittal number.
3. The "Item No." will be the same "Item No." as indicated on ENG FORM 4288-R for each entry on this form.
4. Submittals requiring expeditious handling will be submitted on a separate form.
5. Separate transmittal form will be used for submittals under separate sections of the specifications.
6. A check shall be placed in the "Variation" column when a submittal is not in accordance with the plans and specifications--also, a written statement to that effect shall be included in the space provided for "Remarks".
7. Form is self-transmittal, letter of transmittal is not required.
8. When a sample of material or Manufacturer's Certificate of Compliance is transmitted, indicate "Sample" or "Certificate" in column c, Section I.
9. U.S. Army Corps of Engineers approving authority will assign action codes as indicated below in space provided in Section I, column i to each item submitted. In addition they will ensure enclosures are indicated and attached to the form prior to return to the contractor. The Contractor will assign action codes as indicated below in Section I, column g, to each item submitted.

THE FOLLOWING ACTION CODES ARE GIVEN TO ITEMS SUBMITTED

- | | |
|---|---|
| A -- Approved as submitted. | E -- Disapproved (See attached). |
| B -- Approved, except as noted on drawings. | F -- Receipt acknowledged. |
| C -- Approved, except as noted on drawings.
Refer to attached sheet resubmission required. | FX -- Receipt acknowledged, does not comply
as noted with contract requirements. |
| D -- Will be returned by separate correspondence. | G -- Other (<i>Specify</i>) |

10. Approval of items does not relieve the contractor from complying with all the requirements of the contract plans and specifications.