

ORDERING DATA SHEET – GENERAL

NOUN NAME: HOSE ASSEMBLY

DESCRIPTION:

1-1/2-INCH ID
SMOOTH RUBBER OUTER COVER; COLOR: WHITE
TEFLON BORE
150 PSI MINIMUM PRESSURE RATED
220°F MINIMUM TEMPERATURE RATED
300 SERIES STAINLESS STEEL CRIMP STYLE FEMALE CAM AND GROOVE SWIVEL COUPLERS, INSTALLED
ON BOTH ENDS WITH EPDM GASKETS
LENGTH: 36 FEET

MATERIAL: SAINT-GOBAIN CHEMFLUOR HOSE (WTLCT), 300 SERIES STAINLESS STEEL SWIVEL
COUPLERS

MANUFACTURER/VENDOR P/N: SAINT GOBAIN P/N: 24 WTLCT 16 16 S 6 - 36'

QUANTITY: 6 EA

ADDITIONAL NOTES:

- LENGTH IS MEASURED AS DISTANCE BETWEEN THE GASKET SEALING SURFACES.
- LENGTH TOLERANCE ± 1 OF HOSE LENGTH%.
- HYDROSTATIC TEST OF HOSE ASSEMBLY TO SPECIFICATIONS LISTED WITHIN THE SOW IS REQUIRED.

CERTIFICATE OF COMPLIANCE REQUIRED

SAINT GOBAIN P/N: 24 WTLCT 16 16 S 6 - 36' HAS BEEN FOUND TO BE TECHNICALLY ACCEPTABLE FOR THE GOVERNMENT. REQUEST
DATE OF MANUFACTURE BE MARKED ON THE MATERIAL. A MINIMUM OF 85% SHELF-LIFE SHALL REMAIN FROM THE DATE OF
MANUFACTURE UPON RECEIPT.

Changes to specification or other technical requirements are not allowed without Shipyard approval via the Administrative
Contracting Officer (ACO).

JOB ORDER 88MSMSHP91	KEY OP S01	KO ITEM 075	REV -	IDN 5344-7990	IDN REV 3	PAGE 1 OF 1
-------------------------	---------------	----------------	----------	------------------	--------------	-------------