

**TECHNICAL SPECIFICATION
MCNARY LOCK AND DAM
Diesel-Powered Mobile Air Compressors**

1.0 INTENT

This specification is for the purchase and delivery of two new Diesel-Powered Mobile Air Compressors for use by McNary Lock and Dam personnel.

2.0 SCOPE

The Contractor shall be required to fulfill the Diesel-Powered Mobile Air Compressors contract at McNary Dam by the date shown in the Shipment and Delivery Section below and shall provide documentation and other items, as stated in the specification. All materials shall conform to the "Buy American Act". All applicable National Electric Code (NEC) and American Society of Mechanical Engineers (ASME) standards shall be met or exceeded by the supplied equipment. The make and model of air compressor provided by the contractor shall be the most recent up-to-date version offered by the manufacturer.

3.0 PRODUCT CHARACTERISTICS

The Contractor shall provide two complete and identical Diesel-Powered Mobile Air Compressors with the associated, complete operation and maintenance manuals. These air compressors shall be integrated with their own trailers and fully rated and approved for highway transport. These air compressors shall be commercially available, standard offerings, and regularly produced by a manufacturer that makes mobile trailer-mounted air compressors. These air compressors must be the latest model available and not a prior year model. The Diesel-Powered Mobile Air Compressors shall have the following salient characteristics:

- 1) Single stage rotary screw air compressor.
- 2) 150 psi normal effective working pressure.
- 3) 400 cfm free air delivery.
- 4) Liquid-cooled 4 cylinder turbo-charged Diesel engine.
- 5) Meets T4F emissions regulations without regeneration / diesel particulate filter.
- 6) Double-walled fuel tank or integrated enclosure/frame containment that allows for 110% volume containment of fuel to prevent spills to the ground.
- 7) Integrated control system with screen which allows for operator view of compressor parameters such as pressure settings, engine codes, service timers, all system temperatures and pressures, and fuel level.
- 8) Cold weather package with integrated block heater and use of synthetic oils to allow for reliable cold weather operation down to at least -13 degrees Fahrenheit.
- 9) Integrated hose reel.
- 10) Battery disconnect switch built in.
- 11) Aftercooler, air/water separator, and filter assembly built in.
- 12) Full weather and UV resistant enclosure with sound dampening
- 13) Maximum sound pressure level at 23 feet at normal working speed and pressure: 80 dB.
- 14) Trailer mounted with heavy duty single axle trailer with 15" wheels.

- 15) Integrated forklift slots or lifting points for convenient lifting/placement.
- 16) Maximum allowable wet weight (ready-to-operate), including trailer: 6000 lb
- 17) Maximum allowable overall outside dimensions, including trailer (inches): 175 long x 75 wide x 85 high.

4.0 SUBMITTALS

All quotes are to be submitted with manufacturer's product data sheets. Quotes that are absent product data sheets will not be considered valid quotes. All documentation shall be provided to the Government for technical evaluation.

5.0 OPERATION AND MAINTENANCE MANUALS

Provide two complete hard copies of the Operation and Maintenance (O&M) Manual and one electronic copy in PDF format. The O&M Manuals shall include, at a minimum, the following:

- 1) Product data/technical specification cutsheets for the specific model(s) of equipment provided.
- 2) As-built drawings showing the actual equipment provided and listing all system components and part numbers.
- 3) Instructions on the installation, operation, maintenance, repair, troubleshooting, material certifications, replacement parts lists and warranty of the specific model(s) of equipment provided.
- 4) Any information applicable to other models of equipment not provided under this contract shall be crossed out or redacted and the information on these pages that is applicable to the actual equipment provided shall be highlighted to bring attention to it.

6.0 WARRANTY

Each Diesel-Powered Mobile Air Compressors shall be covered by a minimum one-year warranty on all parts, labor, and workmanship from factory defects. Any other warranties offered by the manufacturer that are regularly included with this product shall also apply.

7.0 SHIPMENT & DELIVERY

The Contractor shall:

- Deliver FOB Destination all components/materials no later than six months after award of contract.
- Be responsible for packing and shipping of all components/materials in a manner that ensures their complete and undamaged arrival at McNary Lock & Dam.
- Only perform partial shipments with Government consent.
- Ensure shipments are delivered during normal business hours (Monday – Thursday 7:00 AM to 4:00 PM)
- Ensure no deliveries are attempted on Federal holidays.
- Deliver all shipments to:
McNary Lock and Dam
82790 Devore Rd.
Umatilla, OR 97882