

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

XJO

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS**

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE 12268550-1 (19207) TRACK T-154		2. CODE IDENT 19207		3. SPI NO. AK13469233	
4. NATIONAL STOCK NUMBER 2530-01-346-9233		5. DATE OF DRAWING 10-16-2023		6. REVISION F	
7. QUP SEE NOTE B & D	8. ICQ NONE	9. UNIT PACK WT. (LB) EST. 500.0		10. UNIT PACK CU (CU FT) EST. 6.576	
11. UNIT PACK SIZE (INCHES) EST. 50.5 x 25.0 x 9.0					
12. MILITARY PRESERVATION (METHOD) MIL-STD-2073-1E, METHOD 20		18. STEPS 1-B	19. REQ'D A/R	20. DESCRIPTION PRESERVATIVE: MIL-PRF-16173, GRADE 1	
13. CLEANING MIL-STD-2073-1E		2	A/R	BLOCKING: SEE SHEET 2	
14. DRYING MIL-STD-2073-1E		3	A/R	STRAPPING: SEE SHEET 2	
15. PACKING					
A. LEVEL A MIL-STD-2073-1E AND NOTE D					
B. LEVEL B NOTE APPLICABLE					
16. MARKING MIL-STD-129 AND NOTE C					

17. NOTES / DRAWING

A. PRESERVATION AND PACKING SHALL BE INSPECTED IN ACCORDANCE WITH MIL-STD-2073-1E.

B. ASSEMBLE SHOES INTO (8) SHOE SECTIONS. PRESERVATIVE SHALL BE APPLIED TO EXPOSED METAL SURFACES. PRESERVATIVE ON RUBBER COMPONENTS IS PERMISSABLE. APPLICATION OF PRESERVATIVE MAY BE ACCOMPLISHED BY DIPPING, SPRAYING OR BRUSHING.

C. EACH TRACK SHOE ASSEMBLY SHALL BE MARKED PER MIL-PRF-11891. NO OTHER UNIT PACK MARKING IS REQUIRED. EXTERIOR IDENTIFICATION, CONTRACT DATA MARKING AND BAR CODING IS REQUIRED ON THE SHIPPING CONTAINER, SEE NOTE D AND MIL-STD-129.

D. PACKING SHALL CONSIST OF FOUR (4) TRACK SHOE SECTIONS (32 SHOE ASSEMBLES) AND BUNDLED IN ACCORDANCE WITH THE REQUIERMENTS ON SHEET 2. BUNDLED LOAD SHALL SERVE AS THE SHIPPING CONTAINER.

SPECIAL PACKAGING INSTRUCTION

Form Approved
OMB No. 0704-0188

XJO

The public reporting burden for this collection of information is estimated to average 30 days per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. **PLEASE DO NOT RETURN YOUR FORM TO THIS ADDRESS**

1. PART OR DRAWING NO. (CAGE) NOMENCLATURE 12268550-1 (19207) TRACK T-154	2. CODE IDENT 19207	3. SPI NO. AK13469233
4. NATIONAL STOCK NUMBER 2530-01-346-9233	5. DATE OF DRAWING 10-16-2023	6. REVISION F

17. NOTES / DRAWING

ITEM	DESCRIPTION	QTY.	NOTE
1.	2 X 6 NOM X 48	2	1
2.	2 X 6 NOM X 7	2	1
3.	108 INCHES LONG	2	2
4.	156 INCHES LONG	2	2

NOTES:

- LUMBER, NUMBER 2 COMMON OR BETTER.
- STRAPPING: ASTM D3953, TYPE 1, FINISH B, SIZE 1-1/4 WIDE X .031 THICK.
- NAILING OF BLOCKING PER MIL-STD-1186.
- USE EDGE PROTECTORS AT SHARP CONTACT AREAS.
- POSITION STRAPPING THROUGH THE FOUR TRACK SECTIONS AND ENCIRCLE BUNDLE.
- STRAPPING SHALL ENCIRCLE OUTSIDE PERIMETER OF BUNDLED TRACK SECTIONS.

