

GENERAL NOTES

1. LCG POSITIVE AFT OF FP. TCG POSITIVE PORT OF CL. VCG POSITIVE ABOVE BL.
- 2.
- 3.

3		
2		
1		
NO.	TITLE	DRAWING NO.

REFERENCE PLANS

SPECIAL NOTATIONS

PRELIMINARY DOCUMENT ISSUED TO SUPPORT DRAFT RFP. DOCUMENT IS UNDER DEVELOPMENT, AND NOT APPROVED.

STINFO DESIGNATION

DISTRIBUTION STATEMENT A: APPROVED FOR PUBLIC RELEASE. DISTRIBUTION IS UNLIMITED.



UNITED STATES COAST GUARD WASHINGTON, D.C. 20593

OFFICE OF NAVAL ENGINEERING

69 FT

HSCL

HOMELAND SECURITY CUTTER LIGHT
WEIGHT ESTIMATE

	SIZE	DATE	USCG DRAWING NO.	REV
	A	3/11/2026	69-HSCL-096-001	0

REVISIONS					
REV	ITEM	SWBS	DESCRIPTION	DATE	INITIAL
-	ALL	ALL	PRELIMINARY RELEASE FOR RFP	3/13/2026	SPS

SHEET INDEX	
SHEET	TITLE
1	TITLE
2	REVISIONS
3	SHEET INDEX
4-9	1-DIGIT DELIVERY SUMMARY
10-15	1-DIGIT EOSL SUMMARY
16-27	3-DIGIT SUMMARY
28-43	100 SWBS
44	200 SWBS
45	300 SWBS
46	400 SWBS
47-48	500 SWBS
49-54	600 SWBS
55-60	LOADS
61	MARGINS

United States Coast Guard

HSC-L Design Support

SHEET INDEX

SIZE

PROJECT NO.

DWG. NO.

REV

A

N/A

N/A

-

SCALE:

NTS

SHEET

1

OF

57

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
A	DEPARTURE LOADS W/ ATON	57482.69		6.20	356504.07	32.01 A	1839896.11	0.04 S -2075.64
	DESIGN DEPARTURE LOADS W/ ATON, BOSL	269895.07		7.70	2078950.92	34.01 A	9179925.32	0.00 P 490.96

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE DELIVERY CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	66.53 FEET	15. MOMENT TO ALTER TRIM ONE INCH	402,865.55 FT - LBS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.29 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.70 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	34.01 FEET
4. C.G ABOVE BASELINE	7.70 FEET	18. TRIMMING LEVER	0.73 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	6.14 FT ABL	19. TRIM	0.49 FEET BY STERN
6. POUNDS PER INCH IMMERSION	6088.83 LB / IN	20. L.C.F.	34.97 FEET
7. TRANSVERSE METACENTER (KEEL)	11.78 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.01 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.08 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.28 FEET	FORWARD PERPENDICULAR	5.87 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	6.15 FEET
11. KGv	7.98 FEET	AFT PERPENDICULAR	6.44 FEET
12. GM, WITH FREE SURFACE CORR.	4.36 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	19228.28 FT - LBS		
14. LIST	0.03 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT	
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P	961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C	0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P	385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C	0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P	2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S	-1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P	2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S	359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S	2566.60
B	DEPARTURE LOADS W/O ATON	33222.69		3.77	125333.27	29.89 A	993121.81	0.03 S	-949.24
	DESIGN DEPARTURE LOADS W/O ATON, BOSL	245635.07		7.52	1847780.12	33.92 A	8333151.02	0.01 P	1617.36
		109.658516							

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE DELIVERY CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	65.68 FEET	15. MOMENT TO ALTER TRIM ONE INCH	378,277.16 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.13 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.52 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	33.92 FEET
4. C.G ABOVE BASELINE	7.52 FEET	18. TRIMMING LEVER	0.80 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	5.80 FT ABL	19. TRIM	0.52 FEET BY STERN
6. TONS PER INCH IMMERSION	5940.56 LT / IN	20. L.C.F.	34.87 FEET
7. TRANSVERSE METACENTER (KEEL)	12.00 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.02 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.48 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.31 FEET	FORWARD PERPENDICULAR	5.52 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	5.82 FEET
11. KGv	7.83 FEET	AFT PERPENDICULAR	6.12 FEET
12. GM, WITH FREE SURFACE CORR.	4.79 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	19203.44 FT - TONS		
14. LIST	0.08 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
C	HALF LOADS W/ ATON	37405.69		6.43	240610.61	35.39 A	1323729.24	0.03 S -1073.11
	DESIGN HALF LOADS W/ ATON, BOSL	249818.07		7.86	1963057.46	34.68 A	8663758.45	0.01 P 1493.49

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE DELIVERY CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	66.04 FEET	15. MOMENT TO ALTER TRIM ONE INCH	382,596.38 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.15 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.86 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	34.68 FEET
4. C.G ABOVE BASELINE	7.86 FEET	18. TRIMMING LEVER	1.53 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	5.86 FT ABL	19. TRIM	1.00 FEET BY STERN
6. TONS PER INCH IMMERSION	5967.23 LT / IN	20. L.C.F.	34.88 FEET
7. TRANSVERSE METACENTER (KEEL)	11.96 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.03 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.10 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.30 FEET	FORWARD PERPENDICULAR	5.32 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	5.89 FEET
11. KGv	8.16 FEET	AFT PERPENDICULAR	6.47 FEET
12. GM, WITH FREE SURFACE CORR.	4.41 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	17,889.89 FT - TONS		
14. LIST	0.08 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
D	HALF LOADS W/O ATON	21065.69		3.05	64272.61	27.21 A	573109.24	0.05 S -1073.11
	DESIGN HALF LOADS W/O ATON, BOSL	233478.07		7.65	1786719.46	33.89 A	7913138.45	0.01 P 1493.49

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE DELIVERY CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	66.04 FEET	15. MOMENT TO ALTER TRIM ONE INCH	365,879.70 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.04 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.65 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	33.89 FEET
4. C.G ABOVE BASELINE	7.65 FEET	18. TRIMMING LEVER	0.85 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	5.63 FT ABL	19. TRIM	0.54 FEET BY STERN
6. TONS PER INCH IMMERSION	5862.71 LT / IN	20. L.C.F.	34.82 FEET
7. TRANSVERSE METACENTER (KEEL)	12.13 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.02 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.48 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.32 FEET	FORWARD PERPENDICULAR	5.34 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	5.65 FEET
11. KGv	7.98 FEET	AFT PERPENDICULAR	5.96 FEET
12. GM, WITH FREE SURFACE CORR.	4.80 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	18,246.97 FT - TONS		
14. LIST	0.08 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
E	MIN OP LOADS W/ ATON	31646.69		6.88	217710.74	34.17 A	1081257.44	0.03 S -1100.89
	DESIGN MIN OP LOADS W/ ATON, BOSL	244059.07		7.95	1940157.59	34.51 A	8421286.65	0.01 P 1465.71

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE DELIVERY CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	65.81 FEET	15. MOMENT TO ALTER TRIM ONE INCH	376,648.71 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.12 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.95 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	34.51 FEET
4. C.G ABOVE BASELINE	7.95 FEET	18. TRIMMING LEVER	1.39 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	5.78 FT ABL	19. TRIM	0.90 FEET BY STERN
6. TONS PER INCH IMMERSION	5930.44 LT / IN	20. L.C.F.	34.86 FEET
7. TRANSVERSE METACENTER (KEEL)	12.02 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.03 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.07 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.31 FEET	FORWARD PERPENDICULAR	5.30 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	5.81 FEET
11. KGv	8.26 FEET	AFT PERPENDICULAR	6.33 FEET
12. GM, WITH FREE SURFACE CORR.	4.38 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	17,328.11 FT - TONS		
14. LIST	0.08 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT	
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P	961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C	0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P	385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C	0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P	2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S	-1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P	2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S	359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S	2566.60
F	MIN OP LOADS W/O ATON	15306.69		2.70	41372.74	21.60 A	330637.44	0.07 S	-1100.89
	DESIGN MIN OP LOADS W/O ATON, BOSL	227719.07		7.75	1763819.59	33.68 A	7670666.65	0.01 P	1465.71

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE DELIVERY CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	64.92 FEET	15. MOMENT TO ALTER TRIM ONE INCH	360,011.41 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.00 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.75 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	33.68 FEET
4. C.G ABOVE BASELINE	7.75 FEET	18. TRIMMING LEVER	0.69 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	5.55 FT ABL	19. TRIM	0.43 FEET BY STERN
6. TONS PER INCH IMMERSION	5825.14 LT / IN	20. L.C.F.	34.81 FEET
7. TRANSVERSE METACENTER (KEEL)	12.20 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.02 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.45 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.33 FEET	FORWARD PERPENDICULAR	5.32 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	5.57 FEET
11. KGv	8.08 FEET	AFT PERPENDICULAR	5.81 FEET
12. GM, WITH FREE SURFACE CORR.	4.78 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	17,694.35 FT - TONS		
14. LIST	0.08 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
A	DEPARTURE LOADS W/ ATON	57482.69		6.20	356504.07	32.01 A	1839896.11	0.04 S -2075.64
	DESIGN DEPARTURE LOADS W/ ATON, BOSL	269895.07		7.70	2078950.92	34.01 A	9179925.32	0.00 P 490.96
	SERVICE LIFE ALLOWANCE	15930.93		8.61	137148.98	34.56 A	550502.19	0.01 P 192.50
	DESIGN DEPARTURE LOADS W/ ATON, EOSL	285826.00		7.75	2216099.90	34.04 A	9730427.51	0.00 P 683.46

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE EOSL CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	67.17 FEET	15. MOMENT TO ALTER TRIM ONE INCH	417,925.06 FT - LBS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.39 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.70 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	34.01 FEET
4. C.G ABOVE BASELINE	7.70 FEET	18. TRIMMING LEVER	0.63 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	6.36 FT ABL	19. TRIM	0.43 FEET BY STERN
6. POUNDS PER INCH IMMERSION	6175.37 LB / IN	20. L.C.F.	35.05 FEET
7. TRANSVERSE METACENTER (KEEL)	11.66 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.01 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	3.96 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.28 FEET	FORWARD PERPENDICULAR	6.12 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	6.37 FEET
11. KGv	7.98 FEET	AFT PERPENDICULAR	6.62 FEET
12. GM, WITH FREE SURFACE CORR.	4.24 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	19,742.36 FT - LBS		
14. LIST	0.02 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
B	DEPARTURE LOADS W/O ATON	33222.69		3.77	125333.27	29.89 A	993121.81	0.03 S -949.24
	DESIGN DEPARTURE LOADS W/O ATON, BOSL	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
	SERVICE LIFE ALLOWANCE	15930.93		8.61	137148.98	34.56 A	550502.19	0.01 P 192.50
	DESIGN DEPARTURE LOADS W/O ATON, EOSL	261566.00		7.59	1984929.10	33.96 A	8883653.21	0.01 P 1809.86

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE EOSL CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	66.33 FEET	15. MOMENT TO ALTER TRIM ONE INCH	394,599.25 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.23 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.59 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	33.96 FEET
4. C.G ABOVE BASELINE	7.59 FEET	18. TRIMMING LEVER	0.73 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	6.03 FT ABL	19. TRIM	0.48 FEET BY STEM
6. TONS PER INCH IMMERSION	6040.00 LT / IN	20. L.C.F.	34.94 FEET
7. TRANSVERSE METACENTER (KEEL)	11.85 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.01 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.27 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.29 FEET	FORWARD PERPENDICULAR	5.76 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	6.04 FEET
11. KGv	7.88 FEET	AFT PERPENDICULAR	6.32 FEET
12. GM, WITH FREE SURFACE CORR.	4.55 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	19,474.72 FT - TONS		
14. LIST	0.09 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
C	HALF LOADS W/ ATON	37405.69		6.43	240610.61	35.39 A	1323729.24	0.03 S -1073.11
	DESIGN HALF LOADS W/ ATON, BOSL	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
	SERVICE LIFE ALLOWANCE	15930.93		8.61	137148.98	34.56 A	550502.19	0.01 P 192.50
	DESIGN HALF LOADS W/ ATON, EOSL	265749.00		7.90	2100206.44	34.67 A	9214260.64	0.01 P 1685.99

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE EOSL CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	66.68 FEET	15. MOMENT TO ALTER TRIM ONE INCH	398,778.72 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.26 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.90 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	34.67 FEET
4. C.G ABOVE BASELINE	7.90 FEET	18. TRIMMING LEVER	1.41 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	6.08 FT ABL	19. TRIM	0.94 FEET BY STEM
6. TONS PER INCH IMMERSION	6064.81 LT / IN	20. L.C.F.	34.96 FEET
7. TRANSVERSE METACENTER (KEEL)	11.82 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.03 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	3.92 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.28 FEET	FORWARD PERPENDICULAR	5.56 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	6.11 FEET
11. KGv	8.19 FEET	AFT PERPENDICULAR	6.66 FEET
12. GM, WITH FREE SURFACE CORR.	4.20 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	18,163.15 FT - TONS		
14. LIST	0.09 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
D	HALF LOADS W/O ATON	21065.69		3.05	64272.61	27.21 A	573109.24	0.05 S -1073.11
	DESIGN HALF LOADS W/O ATON, BOSL	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
	SERVICE LIFE ALLOWANCE	15930.93		8.61	137148.98	34.56 A	550502.19	0.01 P 192.50
	DESIGN HALF LOADS W/O ATON, EOSL	249409.00		7.71	1923868.44	33.93 A	8463640.64	0.01 P 1685.99

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE EOSL CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	65.8 FEET	15. MOMENT TO ALTER TRIM ONE INCH	382,174.42 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.15 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.71 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	33.93 FEET
4. C.G ABOVE BASELINE	7.71 FEET	18. TRIMMING LEVER	0.78 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	5.86 FT ABL	19. TRIM	0.51 FEET BY STEM
6. TONS PER INCH IMMERSION	5964.63 LT / IN	20. L.C.F.	34.88 FEET
7. TRANSVERSE METACENTER (KEEL)	11.96 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.02 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.25 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.30 FEET	FORWARD PERPENDICULAR	5.58 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	5.87 FEET
11. KGv	8.02 FEET	AFT PERPENDICULAR	6.17 FEET
12. GM, WITH FREE SURFACE CORR.	4.55 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	18,505.57 FT - TONS		
14. LIST	0.09 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
E	MIN OP LOADS W/ ATON	31646.69		6.88	217710.74	34.17 A	1081257.44	0.03 S -1100.89
	DESIGN MIN OP LOADS W/ ATON, BOSL	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
	SERVICE LIFE ALLOWANCE	15930.93		8.61	137148.98	34.56 A	550502.19	0.01 P 192.50
	DESIGN MIN OP LOADS W/ ATON, EOSL	259990.00		7.99	2077306.57	34.51 A	8971788.84	0.01 P 1658.21

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE EOSL CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	66.46 FEET	15. MOMENT TO ALTER TRIM ONE INCH	393,011.48 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.22 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.99 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	34.51 FEET
4. C.G ABOVE BASELINE	7.99 FEET	18. TRIMMING LEVER	1.29 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	6.00 FT ABL	19. TRIM	0.85 FEET BY STEM
6. TONS PER INCH IMMERSION	6030.51 LT / IN	20. L.C.F.	34.93 FEET
7. TRANSVERSE METACENTER (KEEL)	11.87 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.03 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	3.88 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.29 FEET	FORWARD PERPENDICULAR	5.54 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	6.03 FEET
11. KGv	8.28 FEET	AFT PERPENDICULAR	6.52 FEET
12. GM, WITH FREE SURFACE CORR.	4.17 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	17,598.30 FT - TONS		
14. LIST	0.09 DEG		

HOMELAND SECURITY CUTTER - LIGHT ICEBREAKER

1-DIGIT WEIGHT AND MOMENT ESTIMATE

WEIGHT ESTIMATE

11-Mar

IMPERIAL UNITS - POUNDS, LONG TONS, FEET, LB-FT

SHIP: HSC - L

REFERENCED FROM THE FORWARD PERPENDICULAR, CENTERLINE AND BASELINE

SWBS GROUP	DESCRIPTION	CURRENT WEIGHT	VCG	VERTICAL MOMENT	LCG	LONGITUDINAL MOMENT	TCG	TRANSVERSE MOMENT
	1 STRUCTURE	100805.64		6.97	702143.05	31.74 A	3199243.62	0.01 P 961.91
	2 PROPULSION SYSTEMS	17068.00		4.17	71137.40	42.67 A	728367.51	0.00 C 0.00
	3 ELECTRICAL SYSTEMS	11650.00		5.96	69406.77	39.48 A	459915.86	0.03 P 385.60
	4 COMMAND & SURVEILLANCE	3970.93		16.75	66493.94	21.91 A	87002.28	0.00 C 0.00
	5 AUXILIARY SYSTEMS	27577.53		9.43	260136.40	42.54 A	1173149.49	0.08 P 2236.66
	6 OUTFIT & FURNISHINGS	21571.24		8.96	193194.34	30.77 A	663664.60	0.06 S -1377.27
	LIGHT SHIP, NO MARGINS	182643.34		7.46	1362511.90	34.56 A	6311343.35	0.01 P 2206.90
M	MARGINS	29769.04		12.09	359934.95	34.56 A	1028685.85	0.01 S 359.70
	LIGHT SHIP CONDITION	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
F	MIN OP LOADS W/O ATON	15306.69		2.70	41372.74	21.60 A	330637.44	0.07 S -1100.89
	DESIGN MIN OP LOADS W/O ATON, BOSL	212412.38		8.11	1722446.84	34.56 A	7340029.21	0.01 S 2566.60
	SERVICE LIFE ALLOWANCE	15930.93		8.61	137148.98	34.56 A	550502.19	0.01 P 192.50
	DESIGN MIN OP LOADS W/O ATON, EOSL	243650.00		7.80	1900968.57	33.74 A	8221168.84	0.01 P 1658.21

NOTES: ALL OF THE FOLLOWING QUANTITIES ARE FOR THE EOSL CONDITION USING EVEN KEEL HYDROSTATICS

1. LENGTH BETWEEN PERPENDICULARS	65.58 FEET	15. MOMENT TO ALTER TRIM ONE INCH	376,226.07 FT - TONS
2. BOTTOM KEEL BELOW BASELINE	0 FEET	16. LCB ON EVEN KEEL AT ABOVE WATERLINE	33.11 FEET
3. C.G. ABOVE BOTTOM OF KEEL	7.80 FT ABL	17. LONGITUDINAL CENTER OF GRAVITY	33.74 FEET
4. C.G ABOVE BASELINE	7.80 FEET	18. TRIMMING LEVER	0.63 FEET AFT LCB
5. DRAFT AT LCF FOR ABOVE DISPLACEMENT	5.78 FT ABL	19. TRIM	0.41 FEET BY STEM
6. TONS PER INCH IMMERSION	5927.81 LT / IN	20. L.C.F.	34.86 FEET
7. TRANSVERSE METACENTER (KEEL)	12.02 FEET	21. DIFF IN DRAFT, L.C.F. TO MIDSHIP	0.01 FEET INCREASE
8. GM, WITHOUT FREE SURFACE CORR.	4.22 FEET	22. DRAFTS (+ ABOVE BL):	
9. FREE SURFACE CORR.	0.31 FEET	FORWARD PERPENDICULAR	5.56 FEET
10. INCLINING KG MARGIN	0.00 FEET	MEAN	5.79 FEET
11. KGv	8.11 FEET	AFT PERPENDICULAR	6.02 FEET
12. GM, WITH FREE SURFACE CORR.	4.53 FEET	23. DESIGNED DRAG	0.00 FEET
13. MOMENT TO ALTER HEEL ONE DEGREE	17,943.95 FT - TONS		
14. LIST	0.09 DEG		

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/S	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
1	Hull Structure	100806	6.97	702143	31.74	A	3199244	0.01	P	961.912
111	Shell Plating	34528	4.81	165985	29.70	A	1025327	0.00	C	0.000
114	Shell Appendages	2032	0.10	3454	3.26	A	112694	0.00	C	0.000
115	Stanchions	305	0.05	1733	0.43	A	14724	0.00	C	0.000
116	Longitudinal Framing	2441	0.18	6285	2.44	A	84388	0.00	C	0.000
117	Transverse Framing	10130	1.38	47520	7.80	A	269402	0.00	S	0.000
121	Longitudinal Structural Bulkheads	516	0.01	234	0.46	A	15732	0.00	C	0.000
122	Transverse Structural Bulkheads	7471	1.34	46303	7.08	A	244366	0.00	S	-0.027
123	Trunks and Enclosures	720	0.21	7378	0.53	A	18174	0.00	C	0.000
131	Main Deck	16977	4.85	167331	17.68	A	610505	0.00	C	0.000
149	Flats	3207	0.32	11135	2.46	A	85106	0.00	C	0.000
151	Deckhouse Structure to First Level	8130	3.84	132751	6.35	A	219154	-0.01	S	-227.592
162	Stacks and Macks (Combined Stack and Mast)	1022	0.53	18412	1.05	A	36356	0.00	S	0.000
163	Sea Chests	100	0.01	500	0.07	A	2417	0.00	C	0.000
167	Hull Structural Closures	1538	0.30	10346	1.26	A	43362	0.01	P	243.288
168	Deckhouse Strural Closures	621	0.25	8749	0.51	A	17481	0.03	P	913.715
171	Masts, Towers, Tetrapods	200	0.14	5000	0.17	A	5833	0.00	C	0.000
182	Propulsion Plant Foundations	931	0.05	1839	1.12	A	38547	0.00	C	0.000
183	Electrical Plant Foundations	1400	0.09	3045	1.64	A	56748	0.00	C	0.000
184	Command and Surveillance Foundations	516	0.25	8644	0.44	A	15056	0.00	C	0.000
185	Auxiliary Systems Foundations	2798	0.57	19637	3.46	A	119419	0.00	C	0.000
186	Outfit and Furnishing Foundations	216	0.05	1866	0.19	A	6579	0.00	C	0.000
196	Welding (1.5%)	1437	0.29	10022	1.32	A	45621	0.00	P	13.941
197	Mill Tolerance (2.0)	1916	0.39	13363	1.76	A	60827	0.00	P	18.588
198	Free Flooding Liquids	0	0.00	0	0.00		0	0.00	C	0.000
NA	Brackets & Misc. Structure	1653	0.31	10612	1.49	A	51424	0.00	C	0.000

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
			ft	ft*lb	ft		ft*lb	ft	S	ft*lb
2	Propulsion	17068	4.17	71137	42.67	A	728368	0.00	C	0.000
233	Propulsion Internal Combustion Systems	8598	1.01	34922	9.92	A	342458	0.00	C	0.000
241	Propulsion Reduction Gears	1516	0.12	4177	1.91	A	65838	0.00	C	0.000
242	Propulsion Clutches and Couplings	140	0.02	532	0.19	A	6720	0.00	C	0.000
243	Propulsion Shafting	2240	0.14	4763	3.44	A	118853	0.00	C	0.000
244	Propulsion Shaft Bearings	152	0.01	339	0.22	A	7481	0.00	C	0.000
245	Propulsors	614	0.03	1176	1.08	A	37419	0.00	C	0.000
251	Combustion Air System	300	0.07	2400	0.37	A	12750	0.00	C	0.000
252	Propulsion Control System	150	0.02	551	0.17	A	6000	0.00	C	0.000
256	Cooling Sea Water System	0	0.00	0	0.00		0	0.00	C	0.000
259	Exhaust System	1120	0.41	14195	1.20	A	41349	0.00	C	0.000
261	Fuel Service System	114	0.01	228	0.13	A	4332	0.00	C	0.000
262	Main Propulsion Lube Oil Sytstem	108	0.01	396	0.13	A	4320	0.00	C	0.000
298	Propulsion Plan Operating Fluids	1120	0.12	4173	1.30	A	45008	0.00	C	0.000
299	Propulsion Plan Repair Parts and Special Tools	896	0.10	3285	1.04	A	35840	0.00	C	0.000

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
			ft	ft*lb	ft		ft*lb	ft	S	ft*lb
3	Electric Plant	11650	5.96	69407	39.48	A	459916	0.03	P	385.599
311	Ship Service Power Generation	5770	0.89	30581	7.35	A	253612	0.01	P	366.723
313	Batteries and Service Facilities	1120	0.11	3920	1.17	A	40320	0.00	C	0.000
320	Power Distribution System	2274	0.56	19329	2.31	A	79590	0.00	C	0.000
330	Lighting System	694	0.22	7634	0.65	A	22486	0.00	C	0.000
342	Diesel Support System	1120	0.12	4024	1.07	A	37091	0.00	C	0.000
398	Electric Plan Operating Fluids	448	0.07	2405	0.57	A	19560	0.00	P	18.876
399	Electric Pland Repair Parts and Special Tools	224	0.04	1514	0.21	A	7258	0.00	C	0.000
4	Command and Surveillance	3971	16.75	66494	21.91	A	87002	0.00	C	0.000
411	Data Display Group	448	0.19	6496	0.23	A	8064	0.00	C	0.000
421	Non-Electrical/Electronic Navigation Aids	217	0.10	3541	0.11	A	3906	0.00	C	0.000
422	Electrical Navigation Aids	448	0.21	7311	0.23	A	8064	0.00	C	0.000
426	Electrical Navigation Systems	448	0.19	6496	0.23	A	8064	0.00	C	0.000
434	Entertainment & Training Systems	58	0.02	540	0.04	A	1448	0.00	C	0.000
436	Alarm, Safety, and Warning Systems	448	0.10	3481	0.32	A	11200	0.00	C	0.000
437	Indicating, order, and Metering Systems	224	0.05	1801	0.16	A	5600	0.00	C	0.000
438	Integrated Control System	560	0.16	5538	0.41	A	14000	0.00	C	0.000
441	Radio Systems	448	0.13	4596	0.32	A	11200	0.00	C	0.000
443	Visual and Audible Communication Systems	224	0.12	4283	0.16	A	5600	0.00	C	0.000
446	Security Equipment	0	0.00	0	0.00		0	0.00	C	0.000
451	Surface Search Radar	448	0.65	22409	0.29	A	9856	0.00	C	0.000

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/S	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
5	Auxiliary Systems	27578	9.43	260136	42.54	A	1173149	0.08	P	2236.661
511	Compartment Heating System	184	0.04	1450	0.17	A	5953	0.00	C	0.000
512	Ventilation System	407	0.14	4885	0.31	A	10584	0.00	C	0.000
513	Machinery Space Ventilation System	694	0.42	14582	0.80	A	27776	0.00	C	0.000
514	Air Conditioning System	283	0.10	3392	0.21	A	7350	0.00	C	0.000
516	Refrigeration System	605	0.11	3629	0.26	A	9072	0.00	C	0.000
523	Washdown System	192	0.06	1921	0.23	A	8069	0.00	C	0.000
526	Scuppers and Deck Drains	641	0.19	6606	0.60	A	20759	0.00	C	0.000
529	Drainage and Ballasting System	603	0.07	2297	0.57	A	19536	0.00	C	0.000
532	Cooling Water	2192	0.08	2689	2.73	A	94239	0.00	C	0.000
533	Potable Water	1352	0.16	5407	0.90	A	31090	0.00	C	0.000
555	Fire Extinguishing Systems	850	0.15	5101	0.94	A	32305	0.00	C	0.000
556	Hydraulic System	1965	0.34	11790	2.96	A	102180	0.00	C	0.000
561	Steering Control System	2240	0.39	13440	4.02	A	138880	0.00	C	0.000
562	Rudder	672	0.06	2016	1.24	A	42672	0.00	C	0.000
581	Anchor Handling and Stowage	811	0.24	8337	0.09	A	3206	0.06	P	2004.886
582	Mooring and Towing Systems	763	0.29	10181	0.33	A	11412	-0.01	S	-307.914
583	Boat Handling and Stowage Systems	168	0.09	3110	0.12	A	4137	0.02	P	539.690
589	Crane	10940	4.34	150000	15.12	A	522114	0.00	C	0.000
598	Auxiliary Systems Operating Fluids	0	0.00	0	0.00		0	0.00	C	0.000
593	Environmental Pollution Control Systems	1545	0.20	6952	1.88	A	64883	0.00	C	0.000
599	Auxiliary Systems Repair Parts and Tools	470	0.07	2352	0.49	A	16934	0.00	C	0.000

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
6	Outfit and Furnishings	21571	8.96	193194	30.77	A	663665	0.06	S	-1377.274
611	Hull Fittings	1131	0.35	11947	1.05	A	36422	-0.01	S	-198.794
612	Rails, Stanchions, & Lifelines	854	0.31	10865	0.90	A	30994	0.00	C	0.000
621	Non-Structural Bulkheads	915	0.19	6529	0.70	A	24301	-0.04	S	-1220.313
622	Floors & Gratings	2584	0.26	8915	3.17	A	109615	0.00	S	-5.738
623	Ladders	937	0.24	8407	0.85	A	29179	0.02	P	805.346
624	Non-Structural Closures	365	0.07	2552	0.29	A	9943	-0.05	S	-1864.196
625	Airports, Fixed Portlights, & Windows	1096	1.08	37423	1.49	A	51516	0.00	P	88.975
631	Painting	1528	0.29	10026	1.43	A	49220	0.00	C	0.000
633	Cathodic Protection	300	0.03	900	0.28	A	9720	0.00	C	0.000
634	Deck Coverings	715	0.15	5031	0.49	A	16927	-0.02	S	-542.642
635	Hull Insulation	4242	1.03	35392	3.92	A	135241	0.00	P	91.080
637	Sheathing	696	0.19	6535	0.67	A	23226	0.00	S	-41.760
641	Officer Berthing	848	0.17	5985	0.54	A	18726	-0.01	S	-202.973
642	Enlisted Berthing	948	0.19	6714	0.23	A	8037	0.00	C	0.000
643	Mess Spaces	692	0.11	3728	0.33	A	11252	0.11	P	3868.696
644	Sanitary Spaces & Fixtures	146	0.02	719	0.13	A	4440	-0.02	S	-726.701
651	Commissary Spaces	1137	0.23	7901	0.53	A	18438	-0.11	S	-3814.488
652	Medical Spaces	22	0.01	209	0.02	A	726	0.00	C	0.000
661	Offices Furniture	778	0.32	11025	0.61	A	21050	0.03	P	1136.388
665	Workshop	400	0.08	2709	0.36	A	12480	0.08	P	2933.333
671	Lockers & Special Stowage	452	0.12	4211	0.49	A	16810	-0.05	S	-1683.487
699	Outfit and Furnishing Parts and Special Tools	784	0.16	5472	0.74	A	25402	0.00	C	0.000
Light Ship, No Margins		182643	7.46	1362512	34.56	A	6311343	0.01	P	2207

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
M	Margins	29769	12.09	359935	34.56	A	1028686	0.01	S	359.7024585
M11	Design Margin Weight (10.3%)	18810	7.46	140325	34.56	A	650005	0.01	S	227.288522
M11	Design Margin KG (5.0%)	0	0.37	0	0.00		0			0
M21	Construction Margin Weight (5.0%)	9132	7.46	68126	34.56	A	315567	0.01	S	110.3449471
M21	Construction Margin KG (3.0%)	0	0.22	0	0.00		0			0
M31	Contract Modification Weight (0.7%)	1279	7.46	9538	34.56	A	44179	0.01	S	15.44829259
M31	Contract Modification KG (0.5%)	0	0.04	0	0.00		0			0
M41	Government Furnished Equipment Weight (0.3%)	548	7.46	4088	34.56	A	18934	0.01	S	6.620696826
M41	Government Furnished Equipment KG (0.2%)	0	0.01	0	0.00		0			0
Light Ship Condition		212412	8.11	1722447	34.56	A	7340029	0.01	S	2566.6014

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
A	Departure Loads W/ AtoN	57483	6.20	356504	32.01	A	1839896	0.04	S	-2075.638
A11	Ship's Officers	0	0.00	0	0.00		0	0.00	C	0
A13	Ship's Enlisted Men	7920	1.59	54833	2.78	A	96154	-0.03	S	-1126.4
A29	Special mission Sys.	0	0.00	0	0.00		0	0.00	C	0
A31	Provisions & Pers. Stores	217	0.05	1630	0.09	A	3179	-0.03	S	-1116.158153
A32	General Stores	1750	0.34	11830	0.43	A	14875	0.00	C	0
A41	Diesel Fuel	21207	1.31	45084	18.71	A	645965	0.00	P	166.92
A43	Gasoline	0	0.00	0	0.00		0	0.00	C	0
A46	Lubricating Oil	0	0.00	0	0.00		0	0.00	C	0
A51	Sea Water	0	0.00	0	0.00		0	0.00	C	0
A52	Fresh Water	8160	1.76	60874	7.19	A	248390	0.00	C	0
A54	Hydraulic Fluid	1400	0.16	5532	2.06	A	71296	0.00	C	0
A55	Sanitary Tank Liquid	489	0.01	384	0.27	A	9416	0.00	C	0
A62	Cargo Stores	0	0.00	0	0.00		0	0.00	C	0
A69	Miscellaneous Cargo	16340	5.11	176338	21.74	A	750620	0.00	C	0
Design Departure Loads W/ AtoN, BOSL		269895	7.70	2078951	34.01	A	9179925	0.00	P	491
Service Life Allowance (7.5%)		15931	8.61	137149	34.56	A	550502	0.01	P	192.495105
Design Departure Loads W/ AtoN, EOSL		285826	7.75	2216100	34.04	A	9730428	0.00	P	683

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
B	Departure Loads W/O AtoN	33223	3.77	125333	29.89	A	993122	0.03	S	-949.238
B11	Ship's Officers	0	0.00	0	0.00		0	0.00	C	0
B13	Ship's Enlisted Men	0	0.00	0	0.00		0	0.00	C	0
B29	Special mission Sys.	0	0.00	0	0.00		0	0.00	C	0
B31	Provisions & Pers. Stores	217	0.05	1630	0.09	A	3179	-0.03	S	-1116.158153
B32	General Stores	1750	0.34	11830	0.43	A	14875	0.00	C	0
B41	Diesel Fuel	21207	1.31	45084	18.71	A	645965	0.00	P	166.92
B43	Gasoline	0	0.00	0	0.00		0	0.00	C	0
B46	Lubricating Oil	0	0.00	0	0.00		0	0.00	C	0
B51	Sea Water	0	0.00	0	0.00		0	0.00	C	0
B52	Fresh Water	8160	1.76	60874	7.19	A	248390	0.00	C	0
B54	Hydraulic Fluid	1400	0.16	5532	2.06	A	71296	0.00	C	0
B55	Sanitary Tank Liquid	489	0.01	384	0.27	A	9416	0.00	C	0
B62	Cargo Stores	0	0.00	0	0.00		0	0.00	C	0
B69	Miscellaneous Cargo	0	0.00	0	0.00		0	0.00	C	0
Design Departure Loads W/O AtoN, BOSL		245635	7.52	1847780	33.92	A	8333151	0.01	P	1617
Service Life Allowance (7.5%)		15931	8.61	137149	34.56	A	550502	0.01	P	192.495105
Design Departure Loads W/O AtoN, EOSL		261566	7.59	1984929	33.96	A	8883653	0.01	P	1810

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
C	Half Loads W/ AtoN	37406	6.43	240611	35.39	A	1323729	0.03	S	-1073.108153
C11	Ship's Officers	0	0.00	0	0.00		0	0.00	C	0
C13	Ship's Enlisted Men	0	0.00	0	0.00		0	0.00	C	0
C29	Special mission Sys.	0	0.00	0	0.00		0	0.00	C	0
C31	Provisions & Pers. Stores	217	0.05	1630	0.09	A	3179	-0.03	S	-1116.158153
C32	General Stores	1750	0.34	11830	0.43	A	14875	0.00	C	0
C41	Diesel Fuel	8522	0.35	11956	7.51	A	259436	0.00	P	43.05
C43	Gasoline	0	0.00	0	0.00		0	0.00	C	0
C46	Lubricating Oil	0	0.00	0	0.00		0	0.00	C	0
C51	Sea Water	0	0.00	0	0.00		0	0.00	C	0
C52	Fresh Water	4294	0.75	25936	3.78	A	130581	0.00	C	0
C54	Hydraulic Fluid	1400	0.16	5532	2.06	A	71296	0.00	C	0
C55	Sanitary Tank Liquid	4883	0.21	7389	2.71	A	93742	0.00	C	0
C62	Cargo Stores	0	0.00	0	0.00		0	0.00	C	0
C69	Miscellaneous Cargo	16340	5.11	176338	21.74	A	750620	0.00	C	0
Design Half Loads W/ AtoN, BOSL		249818	7.86	1963057	34.68	A	8663758	0.01	P	1493.493248
Service Life Allowance (7.5%)		15931	8.61	137149	34.56	A	550502	0.01	P	192.495105
Design Half Loads W/ AtoN, EOSL		265749	7.90	2100206	34.67	A	9214261	0.01	P	1685.988353

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
D	Half Loads W/O AtoN	21066	3.05	64273	27.21	A	573109	0.05	S	-1073.108153
D11	Ship's Officers	0	0.00	0	0.00		0	0.00	C	0
D13	Ship's Enlisted Men	0	0.00	0	0.00		0	0.00	C	0
D29	Special mission Sys.	0	0.00	0	0.00		0	0.00	C	0
D31	Provisions & Pers. Stores	217	0.05	1630	0.09	A	3179	-0.03	S	-1116.158153
D32	General Stores	1750	0.34	11830	0.43	A	14875	0.00	C	0
D41	Diesel Fuel	8522	0.35	11956	7.51	A	259436	0.00	P	43.05
D43	Gasoline	0	0.00	0	0.00		0	0.00	C	0
D46	Lubricating Oil	0	0.00	0	0.00		0	0.00	C	0
D51	Sea Water	0	0.00	0	0.00		0	0.00	C	0
D52	Fresh Water	4294	0.75	25936	3.78	A	130581	0.00	C	0
D54	Hydraulic Fluid	1400	0.16	5532	2.06	A	71296	0.00	C	0
D55	Sanitary Tank Liquid	4883	0.21	7389	2.71	A	93742	0.00	C	0
D62	Cargo Stores	0	0.00	0	0.00		0	0.00	C	0
D69	Miscellaneous Cargo	0	0.00	0	0.00		0	0.00	C	0
Design Half Loads W/O AtoN, BOSL		233478	7.65	1786719	33.89	A	7913138	0.01	P	1493.493248
Service Life Allowance (7.5%)		15931	8.61	137149	34.56	A	550502	0.01	P	192.495105
Design Half Loads W/O AtoN, EOSL		249409	7.71	1923868	33.93	A	8463641	0.01	P	1685.988353

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
E	Min Op Loads W/ AtoN	31647	6.88	217711	34.17	A	1081257	0.03	S	-1100.888153
E11	Ship's Officers	0	0.00	0	0.00		0	0.00	C	0
E13	Ship's Enlisted Men	0	0.00	0	0.00		0	0.00	C	0
E29	Special mission Sys.	0	0.00	0	0.00		0	0.00	C	0
E31	Provisions & Pers. Stores	217	0.05	1630	0.09	A	3179	-0.03	S	-1116.158153
E32	General Stores	1750	0.34	11830	0.43	A	14875	0.00	C	0
E41	Diesel Fuel	2234	0.06	1972	1.50	A	51674	0.00	P	15.27
E43	Gasoline	0	0.00	0	0.00		0	0.00	C	0
E46	Lubricating Oil	0	0.00	0	0.00		0	0.00	C	0
E51	Sea Water	0	0.00	0	0.00		0	0.00	C	0
E52	Fresh Water	430	0.05	1862	0.38	A	12965	0.00	C	0
E54	Hydraulic Fluid	1400	0.16	5532	2.06	A	71296	0.00	C	0
E55	Sanitary Tank Liquid	9276	0.54	18547	5.12	A	176649	0.00	C	0
E62	Cargo Stores	0	0.00	0	0.00		0	0.00	C	0
E69	Miscellaneous Cargo	16340	5.11	176338	21.74	A	750620	0.00	C	0
Design Min Op Loads W/ AtoN, BOSL		244059	7.95	1940158	34.51	A	8421287	0.01	P	1465.713248
Service Life Allowance (7.5%)		15931	8.61	137149	34.56	A	550502	0.01	P	192.495105
Design Min Op Loads W/ AtoN, EOSL		259990	7.99	2077307	34.51	A	8971789	0.01	P	1658.208353

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
F	Min Op Loads W/O AtoN	15307	2.70	41373	21.60	A	330637	0.07	S	-1100.888153
F11	Ship's Officers	0	0.00	0	0.00		0	0.00	C	0
F13	Ship's Enlisted Men	0	0.00	0	0.00		0	0.00	C	0
F29	Special mission Sys.	0	0.00	0	0.00		0	0.00	C	0
F31	Provisions & Pers. Stores	217	0.05	1630	0.09	A	3179	-0.03	S	-1116.158153
F32	General Stores	1750	0.34	11830	0.43	A	14875	0.00	C	0
F41	Diesel Fuel	2234	0.06	1972	1.50	A	51674	0.00	P	15.27
F43	Gasoline	0	0.00	0	0.00		0	0.00	C	0
F46	Lubricating Oil	0	0.00	0	0.00		0	0.00	C	0
F51	Sea Water	0	0.00	0	0.00		0	0.00	C	0
F52	Fresh Water	430	0.05	1862	0.38	A	12965	0.00	C	0
F54	Hydraulic Fluid	1400	0.16	5532	2.06	A	71296	0.00	C	0
F55	Sanitary Tank Liquid	9276	0.54	18547	5.12	A	176649	0.00	C	0
F62	Cargo Stores	0	0.00	0	0.00		0	0.00	C	0
F69	Miscellaneous Cargo	0	0.00	0	0.00		0	0.00	C	0
Design Min Op Loads W/O AtoN, BOSL		227719	7.75	1763820	33.68	A	7670667	0.01	P	1465.713248
Service Life Allowance (7.5%)		15931	8.61	137149	34.56	A	550502	0.01	P	192.495105
Design Min Op Loads W/O AtoN, EOSL		243650	7.80	1900969	33.74	A	8221169	0.01	P	1658.208353

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
							ft	ft*lb	ft		ft*lb	ft		ft*lb
			lb	#	lb	A								
11101	1	PLATE, 7/16 IN, STL	17.85	255.11	4553.71	C	9.17	41758	11.75	A	53506	0.00	C	0
11101	2	PLATE, 7/16 IN, STL	17.85	350.01	6247.68	C	4.92	30739	12.78	A	79845	0.00	C	0
11101	3	PLATE, 7/16 IN, STL	17.85	301.67	5384.81	C	1.36	7323	19.61	A	105596	0.00	C	0
11101	4	PLATE, 7/16 IN, STL	17.85	52.34	934.27	C	9.16	8558	31.48	A	29411	0.00	C	0
11101	5	PLATE, 7/16 IN, STL	17.85	66.41	1185.42	C	4.98	5903	31.48	A	37317	0.00	C	0
11101	6	PLATE, 7/16 IN, STL	17.85	143.58	2562.90	C	1.07	2742	31.48	A	80680	0.00	C	0
11102	7	PLATE, 5/16 IN, STL	12.75	133.05	1696.39	C	8.16	13843	53.87	A	91384	0.00	C	0
11102	8	PLATE, 5/16 IN, STL	12.75	502.54	6407.39	C	4.95	31717	54.12	A	346768	0.00	C	0
11102	9	PLATE, 5/16 IN, STL	12.75	318.17	4056.67	C	1.35	5477	43.33	A	175775	0.00	C	0
11103	10	PLATE, 1/4 IN, STL	10.20	95.91	978.28	C	11.82	11565	17.05	A	16676	0.00	C	0
11103	11	PLATE, 1/4 IN, STL	195.55	1.00	195.55	C	11.79	2306	16.34	A	3196	0.00	C	0
11104	12	PIPE, 2 IN, SCH 40	3.65	89.15	325.40	C	12.46	4054	15.90	A	5173	0.00	C	0
11401	1	SKEG	1015.81	2.00	2031.62	E	1.70	3454	55.47	A	112694	0.00	C	0
11501	1	STANCHION, 5 IN, STL	14.60	6.23	90.96	C	5.34	485	44.05	A	4007	5.63	S	-512
11501	2	STANCHION, 5 IN, STL	14.60	6.23	90.96	C	5.34	485	44.05	A	4007	5.63	P	512
11501														
11501	3	STANCHION, 3.5 IN, STL	9.12	5.04	45.96	C	5.95	273	54.50	A	2505	0.00	C	0
11501	4	STANCHION, 3.5 IN, STL	9.12	4.23	38.58	C	6.34	244	54.50	A	2102	6.00	S	-231
11501	5	STANCHION, 3.5 IN, STL	9.12	4.23	38.58	C	6.34	244	54.50	A	2102	6.00	P	231
11601	1	8 X 4 X 10 I-T, STL	7.19	10.38	74.62	C	5.69	425	1.42	A	106	0.00	C	0
11601														
11602	2	8 X 5 1/2 X 21 I-T, STL	13.87	9.67	134.12	C	2.29	307	8.49	A	1139	0.00	C	0
11602	3	8 X 5 1/2 X 21 I-T, STL	13.87	9.77	135.45	C	3.45	467	55.26	A	7485	0.00	C	0
11602														
11603	4	8 X 5 1/2 X 13 T, STL	12.83	13.00	166.79	C	0.52	87	19.49	A	3251	0.00	C	0
11603	5	8 X 5 1/2 X 13 T, STL	12.83	9.00	115.47	C	0.48	55	30.50	A	3522	0.00	C	0
11603	6	8 X 5 1/2 X 13 T, STL	12.83	15.04	192.96	C	0.56	108	42.51	A	8203	0.00	C	0
11603	7	8 X 5 1/2 X 13 T, STL	12.83	30.10	386.18	C	1.84	711	42.51	A	16417	0.00	C	0
11603														
11604	8	8 X 4 X 10 I-T, STL	7.19	10.12	72.74	C	5.29	385	63.01	A	4583	0.00	C	0
11604														
11605	9	7 X 5 X 11 T, STL	10.81	18.98	205.17	C	4.21	864	8.50	A	1744	0.00	C	0
11605	10	7 X 5 X 11 T, STL	10.81	26.18	283.01	C	2.15	608	19.49	A	5516	0.00	C	0
11605	11	7 X 5 X 11 T, STL	10.81	18.68	201.89	C	4.13	834	55.26	A	11157	0.00	C	0
11605														

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
11606	12	6 X 4 X 9.5 T, STL	9.34	30.10	281.13	C	0.98	274	42.52	A	11955	0.00	C	0
11606						C								
11607	13	6 X 4 X 7 T, STL	6.94	21.53	149.44	C	5.23	782	62.42	A	9328	0.00	C	0
11602														
11603	14	2 X 1/4 FB, STL	1.70	3.15	5.35	C	9.78	52	0.54	F	-3	1.49	P	8
11603	15	2 X 1/4 FB, STL	1.70	3.06	5.20	C	9.78	51	0.45	F	-2	1.46	P	8
11603	16	2 X 1/4 FB, STL	1.70	3.12	5.30	C	8.22	44	0.33	F	-2	1.38	P	7
11603	17	2 X 1/4 FB, STL	1.70	3.03	5.15	C	8.22	42	0.24	F	-1	1.36	P	7
11603	18	2 X 1/4 FB, STL	1.70	3.15	5.35	C	9.78	52	0.54	F	-3	1.49	S	-8
11603	19	2 X 1/4 FB, STL	1.70	3.06	5.20	C	9.78	51	0.45	F	-2	1.46	S	-8
11603	20	2 X 1/4 FB, STL	1.70	3.12	5.30	C	8.22	44	0.33	F	-2	1.38	S	-7
11603	21	2 X 1/4 FB, STL	1.70	3.03	5.15	C	8.22	42	0.24	F	-1	1.36	S	-7
11701	1	5 X 4 X 6 T, STL	5.88	4.81	28.30	C	8.99	254	0.48	F	-14	0.96	P	27
11701	2	5 X 4 X 6 T, STL	5.88	1.77	10.42	C	6.26	65	0.32	A	3	0.46	P	5
11701	3	5 X 4 X 6 T, STL	5.88	5.02	29.54	C	8.88	262	0.01	A	0	1.84	P	54
11701	4	5 X 4 X 6 T, STL	5.88	2.71	15.96	C	5.88	94	1.22	A	20	0.84	P	13
11701	5	5 X 4 X 6 T, STL	5.88	5.28	31.07	C	8.78	273	0.59	A	18	2.63	P	82
11701	6	5 X 4 X 6 T, STL	5.88	3.36	19.77	C	5.56	110	2.03	A	40	1.13	P	22
11701	7	5 X 4 X 6 T, STL	5.88	5.54	32.56	C	8.67	282	1.23	A	40	3.33	P	108
11701	8	5 X 4 X 6 T, STL	5.88	3.96	23.28	C	5.26	122	2.83	A	66	1.38	P	32
11701	9	5 X 4 X 6 T, STL	5.88	5.79	34.03	C	8.50	289	1.96	A	67	3.95	P	134
11701	10	5 X 4 X 6 T, STL	5.88	3.41	20.02	C	5.25	105	3.37	A	67	2.04	P	41
11701	11	5 X 4 X 6 T, STL	5.88	6.01	35.36	C	8.39	297	2.72	A	96	4.53	P	160
11701	12	5 X 4 X 6 T, STL	5.88	1.69	9.93	C	5.48	54	3.74	A	37	3.07	P	30
11701	13	5 X 4 X 6 T, STL	5.88	5.73	33.71	C	8.79	296	3.39	A	114	5.27	P	178
11701	14	5 X 4 X 6 T, STL	5.88	4.81	28.30	C	8.99	254	0.48	F	-14	0.96	S	-27
11701	15	5 X 4 X 6 T, STL	5.88	1.77	10.42	C	6.26	65	0.32	A	3	0.46	S	-5
11701	16	5 X 4 X 6 T, STL	5.88	5.02	29.54	C	8.88	262	0.01	A	0	1.84	S	-54
11701	17	5 X 4 X 6 T, STL	5.88	2.71	15.96	C	5.88	94	1.22	A	20	0.84	S	-13
11701	18	5 X 4 X 6 T, STL	5.88	5.28	31.07	C	8.78	273	0.59	A	18	2.63	S	-82
11701	19	5 X 4 X 6 T, STL	5.88	3.36	19.77	C	5.56	110	2.03	A	40	1.13	S	-22
11701	20	5 X 4 X 6 T, STL	5.88	5.54	32.56	C	8.67	282	1.23	A	40	3.33	S	-108
11701	21	5 X 4 X 6 T, STL	5.88	3.96	23.28	C	5.26	122	2.83	A	66	1.38	S	-32
11701	22	5 X 4 X 6 T, STL	5.88	5.79	34.03	C	8.50	289	1.96	A	67	3.95	S	-134
11701	23	5 X 4 X 6 T, STL	5.88	3.41	20.02	C	5.25	105	3.37	A	67	2.04	S	-41
11701	24	5 X 4 X 6 T, STL	5.88	6.01	35.36	C	8.39	297	2.72	A	96	4.53	S	-160
11701	25	5 X 4 X 6 T, STL	5.88	1.69	9.93	C	5.48	54	3.74	A	37	3.07	S	-30
11701	26	5 X 4 X 6 T, STL	5.88	5.73	33.71	C	8.79	296	3.39	A	114	5.27	S	-178
11701														
11702	33	5 X 4 X 7.5 T, STL	7.50	23.10	173.22	C	6.64	1150	5.00	A	866	0.00	C	0
11702	34	5 X 4 X 7.5 T, STL	7.50	24.50	183.77	C	6.35	1167	6.00	A	1103	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
11702	35	5 X 4 X 7.5 T, STL	7.50	25.81	193.58	C	6.08	1177	7.00	A	1355	0.00	C	0
11702	36	5 X 4 X 7.5 T, STL	7.50	27.03	202.75	C	5.83	1182	8.00	A	1622	0.00	C	0
11702	37	5 X 4 X 7.5 T, STL	7.50	28.18	211.33	C	5.59	1182	9.00	A	1902	0.00	C	0
11702	38	5 X 4 X 7.5 T, STL	7.50	29.24	219.31	C	5.37	1178	10.00	A	2193	0.00	C	0
11702	39	5 X 4 X 7.5 T, STL	7.50	24.18	181.37	C	5.91	1072	11.00	A	1995	0.00	C	0
11702														
11703	40	5 X 4 X 8.5 T, STL	8.50	31.09	264.29	C	4.98	1317	12.00	A	3171	0.00	C	0
11703	41	5 X 4 X 8.5 T, STL	8.50	32.55	276.65	C	4.69	1297	14.00	A	3873	0.00	C	0
11703	42	5 X 4 X 8.5 T, STL	8.50	33.14	281.66	C	4.58	1290	15.00	A	4225	0.00	C	0
11703	43	5 X 4 X 8.5 T, STL	8.50	33.66	286.09	C	4.49	1284	16.00	A	4577	0.00	C	0
11703	44	5 X 4 X 8.5 T, STL	8.50	34.13	290.15	C	4.41	1279	17.00	A	4932	0.00	C	0
11703	45	5 X 4 X 8.5 T, STL	8.50	34.58	293.94	C	4.34	1274	18.00	A	5291	0.00	C	0
11703	46	5 X 4 X 8.5 T, STL	8.50	34.99	297.44	C	4.27	1269	19.00	A	5651	0.00	C	0
11703	47	5 X 4 X 8.5 T, STL	8.50	35.37	300.65	C	4.20	1264	20.00	A	6013	0.00	C	0
11703	48	5 X 4 X 8.5 T, STL	8.50	35.72	303.59	C	4.14	1257	21.00	A	6375	0.00	C	0
11703	49	5 X 4 X 8.5 T, STL	8.50	36.03	306.26	C	4.09	1253	22.00	A	6738	0.00	C	0
11703	50	5 X 4 X 8.5 T, STL	8.50	36.32	308.68	C	4.04	1248	23.00	A	7100	0.00	C	0
11703	51	5 X 4 X 8.5 T, STL	8.50	36.57	310.81	C	4.00	1244	24.00	A	7459	0.00	C	0
11703	52	5 X 4 X 8.5 T, STL	8.50	36.78	312.63	C	3.96	1240	25.00	A	7816	0.00	C	0
11703	53	5 X 4 X 8.5 T, STL	8.50	37.10	315.33	C	3.91	1233	27.00	A	8514	0.00	C	0
11703	54	5 X 4 X 8.5 T, STL	8.50	37.19	316.10	C	3.89	1230	28.00	A	8851	0.00	C	0
11703														
11704	55	4 X 4 X 5 T, STL	4.91	37.25	182.91	C	3.85	704	29.00	A	5304	0.00	C	0
11704	56	4 X 4 X 5 T, STL	4.91	37.30	183.12	C	3.83	702	30.50	A	5585	0.00	C	0
11704	57	4 X 4 X 5 T, STL	4.91	37.30	183.14	C	3.83	702	32.00	A	5860	0.00	C	0
11704	58	4 X 4 X 5 T, STL	4.91	37.25	182.89	C	3.84	702	33.50	A	6127	0.00	C	0
11704	59	4 X 4 X 5 T, STL	4.91	32.97	161.88	C	3.10	502	36.50	A	5909	0.00	C	0
11704	60	4 X 4 X 5 T, STL	4.91	32.79	161.00	C	3.13	504	38.00	A	6118	0.00	C	0
11704	61	4 X 4 X 5 T, STL	4.91	32.58	159.95	C	3.17	506	39.50	A	6318	0.00	C	0
11704	62	4 X 4 X 5 T, STL	4.91	32.33	158.74	C	3.21	509	41.00	A	6508	0.00	C	0
11704	63	4 X 4 X 5 T, STL	4.91	13.77	67.61	C	5.87	397	42.50	A	2874	0.00	C	0
11704	64	4 X 4 X 5 T, STL	4.91	31.75	155.87	C	3.31	515	44.00	A	6858	0.00	C	0
11704	65	4 X 4 X 5 T, STL	4.91	31.40	154.16	C	3.37	520	45.50	A	7014	0.00	C	0
11704	66	4 X 4 X 5 T, STL	4.91	30.98	152.10	C	3.47	528	47.00	A	7148	0.00	C	0
11704	67	4 X 4 X 5 T, STL	4.91	30.45	149.52	C	3.62	542	48.50	A	7252	0.00	C	0
11704	68	4 X 4 X 5 T, STL	4.91	29.03	142.56	C	4.11	586	51.50	A	7342	0.00	C	0
11704	69	4 X 4 X 5 T, STL	4.91	28.19	138.39	C	4.46	617	53.00	A	7335	0.00	C	0
11704	70	4 X 4 X 5 T, STL	4.91	27.37	134.39	C	4.80	645	54.50	A	7324	0.00	C	0
11704	71	4 X 4 X 5 T, STL	4.91	26.58	130.51	C	5.14	671	56.00	A	7308	0.00	C	0
11704	72	4 X 4 X 5 T, STL	4.91	25.81	126.74	C	5.44	690	57.50	A	7288	0.00	C	0
11704	73	4 X 4 X 5 T, STL	4.91	24.20	118.81	C	5.50	654	60.50	A	7188	0.00	C	0
11704	74	4 X 4 X 5 T, STL	4.91	23.23	114.05	C	5.84	666	62.00	A	7071	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
11704	75	4 X 4 X 5 T, STL	4.91	21.69	106.50	C	5.90	629	63.50	A	6763	0.00	C	0
11704	76	4 X 4 X 5 T, STL	4.91	19.36	95.05	C	6.08	578	65.00	A	6178	0.00	C	0
11704	77	4 X 4 X 5 T, STL	4.91	15.96	78.35	C	6.68	523	66.50	A	5211	0.00	C	0
11704														
11705	78	8 X 5 1/2 X 13 T, STL	12.83	18.28	234.57	C	1.44	337	42.50	A	9969	0.00	C	0
11707														
11708	79	12 X 6.5 X 26 MT, STL	19.35	2.58	49.82	C	8.24	411	47.00	A	2341	0.00	C	0
11708														0
11709	80	PLATE, 1/4 IN, STL	10.20	0.12	1.24	C	8.50	11	49.50	A	61	0.00	C	0
11709	81	PLATE, 1/4 IN, STL	10.20	0.12	1.24	C	8.50	11	49.50	A	61	0.00	C	0
11709														0
11710	82	PLATE, 1/2 IN, STL	20.40	6.22	126.95	C	8.38	1064	50.02	A	6350	0.00	C	0
12101	1	PLATE, 1/4 IN, STL	10.20	22.08	225.17	C	0.19	43	30.53	A	6874	5.01	S	-1128
12101	2	PLATE, 1/4 IN, STL	10.20	22.08	225.17	C	0.19	43	30.53	A	6874	5.01	P	1128
12101														
12102	3	3 X 2.2 MT, STL	2.20	2.46	5.40	C	2.28	12	27.00	A	146	4.76	P	26
12102	4	3 X 2.2 MT, STL	2.20	2.46	5.40	C	2.28	12	27.00	A	146	4.76	S	-26
12102	5	3 X 2.2 MT, STL	2.20	2.48	5.46	C	2.27	12	28.00	A	153	4.76	P	26
12102	6	3 X 2.2 MT, STL	2.20	2.48	5.46	C	2.27	12	28.00	A	153	4.76	S	-26
12102	7	3 X 2.2 MT, STL	2.20	2.50	5.51	C	2.25	12	29.00	A	160	4.76	P	26
12102	8	3 X 2.2 MT, STL	2.20	2.50	5.51	C	2.25	12	29.00	A	160	4.76	S	-26
12102	9	3 X 2.2 MT, STL	2.20	2.52	5.55	C	2.24	12	30.50	A	169	4.76	P	26
12102	10	3 X 2.2 MT, STL	2.20	2.52	5.55	C	2.24	12	30.50	A	169	4.76	S	-26
12102	11	3 X 2.2 MT, STL	2.20	2.53	5.57	C	2.24	12	32.00	A	178	4.76	P	27
12102	12	3 X 2.2 MT, STL	2.20	2.53	5.57	C	2.24	12	32.00	A	178	4.76	S	-27
12102	13	3 X 2.2 MT, STL	2.20	2.53	5.56	C	2.24	12	33.50	A	186	4.76	P	26
12102	14	3 X 2.2 MT, STL	2.20	2.53	5.56	C	2.24	12	33.50	A	186	4.76	S	-26
12201	1	PLATE, 3/16 IN, STL	7.65	136.30	1042.67	C	7.51	7828	13.00	A	13555	0.00	C	0
12201	2	PLATE, 3/16 IN, STL	7.65	21.41	163.81	C	2.44	399	13.00	A	2130	0.00	C	0
12201	3	PLATE, 3/16 IN, STL	7.65	156.55	1197.60	C	7.35	8807	26.00	A	31138	0.00	C	0
12201	4	PLATE, 3/16 IN, STL	7.65	155.93	1192.87	C	7.36	8781	35.00	A	41750	0.00	C	0
12201	5	PLATE, 3/16 IN, STL	7.65	132.13	1010.79	C	5.61	5668	50.00	A	50540	0.00	C	0
12201	6	PLATE, 3/16 IN, STL	7.65	78.84	603.13	C	6.92	4174	59.00	A	35585	0.00	C	0
12201														
12202	7	PLATE, 1/4 IN, STL	10.20	45.50	464.14	C	2.21	1028	26.00	A	12068	0.00	C	0
12202	8	PLATE, 1/4 IN, STL	10.20	47.06	479.97	C	2.18	1048	35.00	A	16799	0.00	C	0
12202														
12203	9	3 X 2.2 MT, STL	2.20	2.54	5.59	C	9.91	55	3.82	A	21	6.00	P	34
12203	10	3 X 2.2 MT, STL	2.20	5.00	10.99	C	8.71	96	3.82	A	42	4.50	P	50
12203	11	3 X 2.2 MT, STL	2.20	6.11	13.43	C	8.12	109	3.82	A	51	3.00	P	40

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
12203	12	3 X 2.2 MT, STL	2.20	6.75	14.85	C	7.83	116	3.82	A	57	1.50	P	22
12203	13	3 X 2.2 MT, STL	2.20	7.38	16.24	C	7.54	122	3.82	A	62	0.00	C	0
12203	14	3 X 2.2 MT, STL	2.20	6.75	14.85	C	7.83	116	3.82	A	57	1.50	S	-22
12203	15	3 X 2.2 MT, STL	2.20	6.11	13.44	C	8.12	109	3.82	A	51	3.00	S	-40
12203	16	3 X 2.2 MT, STL	2.20	5.00	10.99	C	8.71	96	3.82	A	42	4.50	S	-50
12203	17	3 X 2.2 MT, STL	2.20	2.54	5.59	C	9.91	55	3.82	A	21	6.00	S	-34
12203	18	3 X 2.2 MT, STL	2.20	4.32	9.51	C	8.91	85	12.82	A	122	9.00	P	86
12203	19	3 X 2.2 MT, STL	2.20	6.97	15.33	C	7.62	117	12.82	A	197	7.50	P	115
12203	20	3 X 2.2 MT, STL	2.20	7.91	17.41	C	7.66	133	12.82	A	223	6.00	P	104
12203	21	3 X 2.2 MT, STL	2.20	8.65	19.03	C	7.68	146	12.82	A	244	4.50	P	86
12203	22	3 X 2.2 MT, STL	2.20	9.39	20.66	C	7.69	159	12.82	A	265	3.00	P	62
12203	23	3 X 2.2 MT, STL	2.20	10.13	22.28	C	7.71	172	12.82	A	286	1.50	P	33
12203	24	3 X 2.2 MT, STL	2.20	10.87	23.91	C	7.72	185	12.82	A	307	0.00	C	0
12203	25	3 X 2.2 MT, STL	2.20	10.13	22.28	C	7.71	172	12.82	A	286	1.50	S	-33
12203	26	3 X 2.2 MT, STL	2.20	9.39	20.66	C	7.69	159	12.82	A	265	3.00	S	-62
12203	27	3 X 2.2 MT, STL	2.20	8.65	19.03	C	7.68	146	12.82	A	244	4.50	S	-86
12203	28	3 X 2.2 MT, STL	2.20	7.91	17.41	C	7.66	133	12.82	A	223	6.00	S	-104
12203	29	3 X 2.2 MT, STL	2.20	6.97	15.33	C	7.62	117	12.82	A	197	7.50	S	-115
12203	30	3 X 2.2 MT, STL	2.20	4.32	9.51	C	8.91	85	12.82	A	122	9.00	S	-86
12203	31	3 X 2.2 MT, STL	2.20	0.34	0.75	C	3.34	2	12.82	A	10	6.00	P	4
12203	32	3 X 2.2 MT, STL	2.20	1.05	2.30	C	2.95	7	12.82	A	30	4.50	P	10
12203	33	3 X 2.2 MT, STL	2.20	1.76	3.87	C	2.55	10	12.82	A	50	3.00	P	12
12203	34	3 X 2.2 MT, STL	2.20	2.47	5.44	C	2.16	12	12.82	A	70	1.50	P	8
12203	35	3 X 2.2 MT, STL	2.20	3.19	7.01	C	1.77	12	12.82	A	90	0.00	C	0
12203	36	3 X 2.2 MT, STL	2.20	2.47	5.44	C	2.16	12	12.82	A	70	1.50	S	-8
12203	37	3 X 2.2 MT, STL	2.20	1.76	3.87	C	2.55	10	12.82	A	50	3.00	S	-12
12203	38	3 X 2.2 MT, STL	2.20	1.05	2.30	C	2.95	7	12.82	A	30	4.50	S	-10
12203	39	3 X 2.2 MT, STL	2.20	0.34	0.75	C	3.34	2	12.82	A	10	6.00	S	-4
12203	40	3 X 2.2 MT, STL	2.20	7.53	16.56	C	7.64	127	25.82	A	428	9.00	P	149
12203	41	3 X 2.2 MT, STL	2.20	7.55	16.62	C	7.65	127	25.82	A	429	7.50	P	125
12203	42	3 X 2.2 MT, STL	2.20	7.58	16.68	C	7.67	128	25.82	A	431	6.00	P	100
12203	43	3 X 2.2 MT, STL	2.20	7.61	16.73	C	7.68	128	25.82	A	432	4.50	P	75
12203	44	3 X 2.2 MT, STL	2.20	7.63	16.79	C	7.69	129	25.82	A	433	3.00	P	50
12203	45	3 X 2.2 MT, STL	2.20	7.66	16.85	C	7.71	130	25.82	A	435	1.50	P	25
12203	46	3 X 2.2 MT, STL	2.20	7.68	16.90	C	7.72	130	25.82	A	436	0.00	C	0
12203	47	3 X 2.2 MT, STL	2.20	7.66	16.85	C	7.71	130	25.82	A	435	1.50	S	-25
12203	48	3 X 2.2 MT, STL	2.20	7.63	16.79	C	7.69	129	25.82	A	433	3.00	S	-50
12203	49	3 X 2.2 MT, STL	2.20	7.61	16.73	C	7.68	128	25.82	A	432	4.50	S	-75
12203	50	3 X 2.2 MT, STL	2.20	7.58	16.68	C	7.67	128	25.82	A	431	6.00	S	-100
12203	51	3 X 2.2 MT, STL	2.20	7.55	16.62	C	7.65	127	25.82	A	429	7.50	S	-125
12203	52	3 X 2.2 MT, STL	2.20	7.53	16.56	C	7.64	127	25.82	A	428	9.00	S	-149
12203	53	3 X 2.2 MT, STL	2.20	1.43	3.14	C	2.72	9	25.82	A	81	9.00	P	28

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
12203	54	3 X 2.2 MT, STL	2.20	1.77	3.90	C	2.53	10	25.82	A	101	7.50	P	29
12203	55	3 X 2.2 MT, STL	2.20	2.12	4.66	C	2.34	11	25.82	A	120	6.00	P	28
12203	56	3 X 2.2 MT, STL	2.20	2.46	5.42	C	2.15	12	25.82	A	140	4.50	P	24
12203	57	3 X 2.2 MT, STL	2.20	2.81	6.18	C	1.96	12	25.82	A	160	3.00	P	19
12203	58	3 X 2.2 MT, STL	2.20	3.15	6.94	C	1.77	12	25.82	A	179	1.50	P	10
12203	59	3 X 2.2 MT, STL	2.20	3.50	7.70	C	1.58	12	25.82	A	199	0.00	C	0
12203	60	3 X 2.2 MT, STL	2.20	3.15	6.94	C	1.77	12	25.82	A	179	1.50	S	-10
12203	61	3 X 2.2 MT, STL	2.20	2.81	6.18	C	1.96	12	25.82	A	160	3.00	S	-19
12203	62	3 X 2.2 MT, STL	2.20	2.46	5.42	C	2.15	12	25.82	A	140	4.50	S	-24
12203	63	3 X 2.2 MT, STL	2.20	2.12	4.66	C	2.34	11	25.82	A	120	6.00	S	-28
12203	64	3 X 2.2 MT, STL	2.20	1.77	3.90	C	2.53	10	25.82	A	101	7.50	S	-29
12203	65	3 X 2.2 MT, STL	2.20	1.43	3.14	C	2.72	9	25.82	A	81	9.00	S	-28
12203	66	3 X 2.2 MT, STL	2.20	7.53	16.57	C	7.64	127	34.82	A	577	9.00	P	149
12203	67	3 X 2.2 MT, STL	2.20	7.56	16.63	C	7.65	127	34.82	A	579	7.50	P	125
12203	68	3 X 2.2 MT, STL	2.20	7.58	16.68	C	7.67	128	34.82	A	581	6.00	P	100
12203	69	3 X 2.2 MT, STL	2.20	7.61	16.74	C	7.68	129	34.82	A	583	4.50	P	75
12203	70	3 X 2.2 MT, STL	2.20	7.63	16.79	C	7.69	129	34.82	A	585	3.00	P	50
12203	71	3 X 2.2 MT, STL	2.20	7.66	16.85	C	7.71	130	34.82	A	587	1.50	P	25
12203	72	3 X 2.2 MT, STL	2.20	7.68	16.90	C	7.72	130	34.82	A	589	0.00	C	0
12203	73	3 X 2.2 MT, STL	2.20	7.66	16.85	C	7.71	130	34.82	A	587	1.50	S	-25
12203	74	3 X 2.2 MT, STL	2.20	7.63	16.79	C	7.69	129	34.82	A	585	3.00	S	-50
12203	75	3 X 2.2 MT, STL	2.20	7.61	16.74	C	7.68	129	34.82	A	583	4.50	S	-75
12203	76	3 X 2.2 MT, STL	2.20	7.58	16.68	C	7.67	128	34.82	A	581	6.00	S	-100
12203	77	3 X 2.2 MT, STL	2.20	7.56	16.63	C	7.65	127	34.82	A	579	7.50	S	-125
12203	78	3 X 2.2 MT, STL	2.20	7.53	16.57	C	7.64	127	34.82	A	577	9.00	S	-149
12203	79	3 X 2.2 MT, STL	2.20	1.60	3.52	C	2.62	9	34.82	A	123	9.00	P	32
12203	80	3 X 2.2 MT, STL	2.20	1.92	4.22	C	2.44	10	34.82	A	147	7.50	P	32
12203	81	3 X 2.2 MT, STL	2.20	2.23	4.92	C	2.27	11	34.82	A	171	6.00	P	29
12203	82	3 X 2.2 MT, STL	2.20	2.55	5.61	C	2.10	12	34.82	A	195	4.50	P	25
12203	83	3 X 2.2 MT, STL	2.20	2.87	6.31	C	1.92	12	34.82	A	220	3.00	P	19
12203	84	3 X 2.2 MT, STL	2.20	3.18	7.00	C	1.75	12	34.82	A	244	1.50	P	11
12203	85	3 X 2.2 MT, STL	2.20	3.50	7.70	C	1.58	12	34.82	A	268	0.00	C	0
12203	86	3 X 2.2 MT, STL	2.20	3.18	7.00	C	1.75	12	34.82	A	244	1.50	S	-11
12203	87	3 X 2.2 MT, STL	2.20	2.87	6.31	C	1.92	12	34.82	A	220	3.00	S	-19
12203	88	3 X 2.2 MT, STL	2.20	2.55	5.61	C	2.10	12	34.82	A	195	4.50	S	-25
12203	89	3 X 2.2 MT, STL	2.20	2.23	4.92	C	2.27	11	34.82	A	171	6.00	S	-29
12203	90	3 X 2.2 MT, STL	2.20	1.92	4.22	C	2.44	10	34.82	A	147	7.50	S	-32
12203	91	3 X 2.2 MT, STL	2.20	1.60	3.52	C	2.62	9	34.82	A	123	9.00	S	-32
12203	92	3 X 2.2 MT, STL	2.20	4.57	10.05	C	6.70	67	49.82	A	501	9.00	P	90
12203	93	3 X 2.2 MT, STL	2.20	6.02	13.25	C	5.97	79	49.82	A	660	7.50	P	99
12203	94	3 X 2.2 MT, STL	2.20	6.48	14.25	C	5.74	82	49.82	A	710	6.00	P	85
12203	95	3 X 2.2 MT, STL	2.20	6.93	15.25	C	5.52	84	49.82	A	760	4.50	P	69

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
12203	96	3 X 2.2 MT, STL	2.20	7.39	16.25	C	5.29	86	49.82	A	810	3.00	P	49
12203	97	4 X 4 X 5 MT, STL	4.91	7.84	38.50	C	5.11	197	49.76	A	1916	1.78	P	69
12203	98	4 X 4 X 5 MT, STL	4.91	8.29	40.73	C	4.68	190	49.76	A	2026	0.00	C	0
12203	99	4 X 4 X 5 MT, STL	4.91	7.84	38.50	C	5.11	197	49.82	A	1918	1.78	S	-69
12203	100	3 X 2.2 MT, STL	2.20	7.39	16.25	C	5.29	86	49.82	A	810	3.00	S	-49
12203	101	3 X 2.2 MT, STL	2.20	6.93	15.25	C	5.52	84	49.82	A	760	4.50	S	-69
12203	102	3 X 2.2 MT, STL	2.20	6.48	14.25	C	5.74	82	49.82	A	710	6.00	S	-85
12203	103	3 X 2.2 MT, STL	2.20	6.02	13.25	C	5.97	79	49.82	A	660	7.50	S	-99
12203	104	3 X 2.2 MT, STL	2.20	4.57	10.05	C	6.70	67	49.82	A	501	9.00	S	-90
12203	105	3 X 2.2 MT, STL	2.20	2.81	6.18	C	7.58	47	58.82	A	364	9.00	P	56
12203	106	3 X 2.2 MT, STL	2.20	3.99	8.77	C	6.99	61	58.82	A	516	7.50	P	66
12203	107	3 X 2.2 MT, STL	2.20	4.29	9.45	C	6.84	65	58.82	A	556	6.00	P	57
12203	108	3 X 2.2 MT, STL	2.20	4.34	9.56	C	6.82	65	58.82	A	562	4.50	P	43
12203	109	3 X 2.2 MT, STL	2.20	4.39	9.67	C	6.79	66	58.82	A	569	3.00	P	29
12203	110	3 X 2.2 MT, STL	2.20	4.44	9.78	C	6.76	66	58.82	A	575	1.50	P	15
12203	111	3 X 2.2 MT, STL	2.20	4.49	9.88	C	6.73	67	58.82	A	581	0.00	C	0
12203	112	3 X 2.2 MT, STL	2.20	4.44	9.78	C	6.76	66	58.82	A	575	1.50	S	-15
12203	113	3 X 2.2 MT, STL	2.20	4.39	9.67	C	6.79	66	58.82	A	569	3.00	S	-29
12203	114	3 X 2.2 MT, STL	2.20	4.34	9.56	C	6.82	65	58.82	A	562	4.50	S	-43
12203	115	3 X 2.2 MT, STL	2.20	4.29	9.45	C	6.84	65	58.82	A	556	6.00	S	-57
12203	116	3 X 2.2 MT, STL	2.20	3.99	8.77	C	6.99	61	58.82	A	516	7.50	S	-66
12203	117	3 X 2.2 MT, STL	2.20	2.81	6.18	C	7.58	47	58.82	A	364	9.00	S	-56
12301	1	TRUNKS AND ENCLOSURES	719.76	1.00	719.76	E	10.25	7378	25.25	A	18174	0.00	C	0
13101	1	PLATE, 3/16 IN, STL	7.65	482.32	3689.76	C	11.09	40905	14.23	A	52508	0.00	C	0
13101														
13102	2	PLATE, 1/4 IN, STL	10.20	193.51	1973.81	C	11.08	21865	30.49	A	60182	0.00	C	0
13102	3	PLATE, 1/4 IN, STL	10.20	640.34	6531.46	C	9.00	58790	49.31	A	322049	0.00	C	0
13101														
13103	4	6 X 4 X 7 T, STL	6.94	9.00	62.46	C	10.84	677	1.19	A	74	0.00	C	0
13103	5	6 X 4 X 7 T, STL	6.94	9.00	62.46	C	10.84	677	8.94	A	558	0.00	C	0
13103														
13104	6	7 X 5 X 11 T, STL	10.81	13.00	140.53	C	10.76	1512	19.50	A	2740	0.00	C	0
13104	7	7 X 5 X 11 T, STL	10.81	26.15	282.71	C	10.64	3009	19.48	A	5507	0.00	C	0
13104	8	7 X 5 X 11 T, STL	10.81	7.50	81.08	C	8.54	692	38.75	A	3142	0.00	C	0
13104	9	7 X 5 X 11 T, STL	10.81	30.22	326.71	C	8.56	2796	42.61	A	13919	0.00	C	0
13104	10	7 X 5 X 11 T, STL	10.81	18.37	198.58	C	8.54	1695	54.50	A	10823	0.00	C	0
13104	11	7 X 5 X 11 T, STL	10.81	36.74	397.16	C	8.56	3399	54.58	A	21678	0.00	C	0
13104	12	7 X 5 X 11 T, STL	10.81	9.37	101.29	C	8.54	865	63.69	A	6451	0.00	C	0
13104	13	7 X 5 X 11 T, STL	10.81	16.31	176.31	C	8.55	1508	61.97	A	10927	0.00	C	0
13104														

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
13105	14	6 X 4 X 7 T, STL	6.94	9.00	62.46	C	10.83	677	30.50	A	1905	0.00	C	0
13105	15	6 X 4 X 7 T, STL	6.94	2.64	18.33	C	9.74	179	38.69	A	709	0.00	C	0
13105														
13106	16	5 X 4 X 6 T, STL	5.88	18.00	105.84	C	10.80	1143	8.50	A	900	0.00	C	0
13106	17	5 X 4 X 6 T, STL	5.88	18.00	105.84	C	10.77	1140	30.50	A	3228	0.00	C	0
13106	18	5 X 4 X 6 T, STL	5.88	5.28	31.07	C	9.74	303	38.69	A	1202	0.00	C	0
13106														
13107	19	12 X 6.5 X 26 MT, STL	19.35	4.07	78.83	C	8.33	657	47.00	A	3705	0.00	C	0
13107														
13108	20	PLATE, 1/4 IN, STL	10.20	1.83	18.67	C	8.60	160	47.00	A	877	0.00	C	0
13108	21	PLATE, 1/4 IN, STL	10.20	1.01	10.33	C	8.60	89	43.41	A	448	0.00	C	0
13108														
13109	22	PLATE, 3/8 IN, STL	15.30	1.09	16.65	C	8.22	137	47.00	A	783	0.00	C	0
13109	23	PLATE, 3/8 IN, STL	15.30	0.65	9.98	C	8.21	82	43.38	A	433	0.00	C	0
13109														
13110	24	3 X 2.2 MT, STL	2.20	1.72	3.78	C	10.82	41	1.00	F	-4	0.00	C	0
13110	25	3 X 2.2 MT, STL	2.20	6.71	14.76	C	10.82	160	0.00	A	0	0.00	C	0
13110	26	3 X 2.2 MT, STL	2.20	9.21	20.26	C	10.82	219	1.00	A	20	0.00	C	0
13110	27	3 X 2.2 MT, STL	2.20	11.00	24.20	C	10.82	262	2.00	A	48	0.00	C	0
13110	28	3 X 2.2 MT, STL	2.20	12.42	27.32	C	10.82	296	3.00	A	82	0.00	C	0
13110	29	3 X 2.2 MT, STL	2.20	14.62	32.16	C	10.82	348	5.00	A	161	0.00	C	0
13110	30	3 X 2.2 MT, STL	2.20	15.54	34.19	C	10.82	370	6.00	A	205	0.00	C	0
13110	31	3 X 2.2 MT, STL	2.20	16.40	36.08	C	10.82	390	7.00	A	253	0.00	C	0
13110	32	3 X 2.2 MT, STL	2.20	17.21	37.86	C	10.82	410	8.00	A	303	0.00	C	0
13110	33	3 X 2.2 MT, STL	2.20	17.95	39.49	C	10.82	427	9.00	A	355	0.00	C	0
13110	34	3 X 2.2 MT, STL	2.20	18.62	40.96	C	10.82	443	10.00	A	410	0.00	C	0
13110	35	3 X 2.2 MT, STL	2.20	19.19	42.22	C	10.82	457	11.00	A	464	0.00	C	0
13110	36	3 X 2.2 MT, STL	2.20	19.66	43.25	C	10.82	468	12.00	A	519	0.00	C	0
13110	37	3 X 2.2 MT, STL	2.20	20.37	44.81	C	10.82	485	14.00	A	627	0.00	C	0
13110	38	3 X 2.2 MT, STL	2.20	20.62	45.36	C	10.82	491	15.00	A	680	0.00	C	0
13110	39	3 X 2.2 MT, STL	2.20	20.83	45.83	C	10.82	496	16.00	A	733	0.00	C	0
13110	40	3 X 2.2 MT, STL	2.20	21.00	46.20	C	10.82	500	17.00	A	785	0.00	C	0
13110	41	3 X 2.2 MT, STL	2.20	21.15	46.53	C	10.82	503	18.00	A	838	0.00	C	0
13110	42	3 X 2.2 MT, STL	2.20	21.25	46.75	C	10.82	506	19.00	A	888	0.00	C	0
13110	43	3 X 2.2 MT, STL	2.20	21.28	46.82	C	10.82	507	20.00	A	936	0.00	C	0
13110	44	3 X 2.2 MT, STL	2.20	21.28	46.82	C	10.82	507	21.00	A	983	0.00	C	0
13110	45	3 X 2.2 MT, STL	2.20	21.29	46.84	C	10.82	507	22.00	A	1030	0.00	C	0
13110	46	3 X 2.2 MT, STL	2.20	21.29	46.84	C	10.82	507	23.00	A	1077	0.00	C	0
13110	47	3 X 2.2 MT, STL	2.20	21.30	46.86	C	10.82	507	24.00	A	1125	0.00	C	0
13110	48	3 X 2.2 MT, STL	2.20	21.30	46.86	C	10.82	507	25.00	A	1172	0.00	C	0
13110	49	3 X 2.2 MT, STL	2.20	21.30	46.86	C	10.82	507	27.00	A	1265	0.00	C	0
13110	50	3 X 2.2 MT, STL	2.20	21.30	46.86	C	10.82	507	28.00	A	1312	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
13110	51	3 X 2.2 MT, STL	2.20	21.30	46.86	C	10.82	507	29.00	A	1359	0.00	C	0
13110	52	3 X 2.2 MT, STL	2.20	21.30	46.86	C	10.82	507	30.50	A	1429	0.00	C	0
13110	53	3 X 2.2 MT, STL	2.20	21.31	46.88	C	10.82	507	32.00	A	1500	0.00	C	0
13110	54	3 X 2.2 MT, STL	2.20	21.31	46.88	C	10.82	507	33.50	A	1571	0.00	C	0
13110														
13111	55	4 X 3.25 MT, STL	3.25	20.98	68.19	C	8.77	598	36.50	A	2489	0.00	C	0
13111	56	4 X 3.25 MT, STL	3.25	20.96	68.12	C	8.77	597	38.00	A	2589	0.00	C	0
13111	57	4 X 3.25 MT, STL	3.25	20.94	68.06	C	8.77	597	39.50	A	2688	0.00	C	0
13111	58	4 X 3.25 MT, STL	3.25	20.92	67.99	C	8.77	596	41.00	A	2788	0.00	C	0
13111	59	4 X 3.25 MT, STL	3.25	20.90	67.93	C	8.77	596	42.50	A	2887	0.00	C	0
13111	60	4 X 3.25 MT, STL	3.25	20.88	67.86	C	8.77	595	44.00	A	2986	0.00	C	0
13111	61	4 X 3.25 MT, STL	3.25	16.36	53.17	C	8.77	466	45.50	A	2419	0.00	C	0
13111	62	4 X 3.25 MT, STL	3.25	13.34	43.36	C	8.77	380	47.00	A	2038	0.00	C	0
13111	63	4 X 3.25 MT, STL	3.25	16.31	53.01	C	8.77	465	48.50	A	2571	0.00	C	0
13111	64	4 X 3.25 MT, STL	3.25	20.75	67.44	C	8.77	591	51.50	A	3473	0.00	C	0
13111	65	4 X 3.25 MT, STL	3.25	20.72	67.34	C	8.77	591	53.00	A	3569	0.00	C	0
13111	66	4 X 3.25 MT, STL	3.25	20.65	67.11	C	8.77	589	54.50	A	3658	0.00	C	0
13111	67	4 X 3.25 MT, STL	3.25	20.48	66.56	C	8.77	584	56.00	A	3727	0.00	C	0
13111	68	4 X 3.25 MT, STL	3.25	20.17	65.55	C	8.77	575	57.50	A	3769	0.00	C	0
13111	69	4 X 3.25 MT, STL	3.25	18.94	61.56	C	8.77	540	60.50	A	3724	0.00	C	0
13111	70	4 X 3.25 MT, STL	3.25	17.92	58.24	C	8.77	511	62.00	A	3611	0.00	C	0
13111	71	4 X 3.25 MT, STL	3.25	16.54	53.76	C	8.77	471	63.50	A	3413	0.00	C	0
13111	72	4 X 3.25 MT, STL	3.25	14.65	47.61	C	8.77	418	65.00	A	3095	0.00	C	0
13111	73	4 X 3.25 MT, STL	3.25	11.88	38.61	C	8.77	339	66.50	A	2568	0.00	C	0
13111	74	4 X 3.25 MT, STL	3.25	6.45	20.96	C	8.77	184	68.00	A	1425	0.00	C	0
13111														
13112	75	PLATE, 1/4 IN, STL	10.20	1.62	16.50	C	8.60	142	47.00	A	776	0.00	C	0
13112	76	PLATE, 1/4 IN, STL	10.20	2.35	24.01	C	8.60	206	47.00	A	1128	0.00	C	0
13113														
13113	133	PLATE, 3/8 IN, STL	15.30	1.62	24.75	C	8.22	204	47.00	A	1163	0.00	C	0
13113	134	PLATE, 3/8 IN, STL	15.30	1.49	22.87	C	8.21	188	47.00	A	1075	0.00	C	0
14901	1	PLATE, 3/16 IN, STL	7.65	63.11	482.81	C	3.50	1690	10.00	A	4827	0.00	C	0
14901														
14902	2	PLATE, 5/16 IN, STL	12.75	174.21	2221.22	C	3.50	7774	30.49	A	67734	0.00	C	0
14902														
14903	3	3 X 2.2# MT, STL	2.20	0.99	2.18	C	3.43	7	5.00	A	11	0.00	C	0
14903	4	3 X 2.2# MT, STL	2.20	3.11	6.85	C	3.33	23	6.00	A	41	0.00	C	0
14903	5	3 X 2.2# MT, STL	2.20	4.99	10.98	C	3.33	37	7.00	A	77	0.00	C	0
14903	6	3 X 2.2# MT, STL	2.20	6.68	14.70	C	3.33	49	8.00	A	118	0.00	C	0
14903	7	3 X 2.2# MT, STL	2.20	8.22	18.09	C	3.33	60	9.00	A	163	0.00	C	0
14903	8	3 X 2.2# MT, STL	2.20	9.65	21.23	C	3.33	71	10.00	A	212	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
14903	9	3 X 2.2# MT, STL	2.20	10.98	24.16	C	3.33	80	11.00	A	266	0.00	C	0
14903	10	3 X 2.2# MT, STL	2.20	12.24	26.92	C	3.33	90	12.00	A	323	0.00	C	0
14903														
14904	11	4 X 3.25# MT, STL	3.25	19.38	62.97	C	3.32	209	27.00	A	1700	0.00	C	0
14904	12	4 X 3.25# MT, STL	3.25	19.41	63.09	C	3.32	209	28.00	A	1766	0.00	C	0
14904	13	4 X 3.25# MT, STL	3.25	19.42	63.13	C	3.32	210	29.00	A	1831	0.00	C	0
14904	14	4 X 3.25# MT, STL	3.25	19.41	63.08	C	3.32	209	30.50	A	1924	0.00	C	0
14904	15	4 X 3.25# MT, STL	3.25	19.36	62.91	C	3.32	209	32.00	A	2013	0.00	C	0
14904	16	4 X 3.25# MT, STL	3.25	19.28	62.67	C	3.32	208	33.50	A	2100	0.00	C	0
14904													C	
15101	1	PLATE, 3/16 IN, STL	7.65	275.34	2106.33	C	19.33	40722	25.25	A	53180	0.00	C	0
15101	2	PLATE, 3/16 IN, STL	7.65	109.75	839.56	C	14.93	12533	28.77	A	24157	6.83	P	5737
15101	3	PLATE, 3/16 IN, STL	7.65	109.75	839.56	C	14.93	12533	28.77	A	24157	6.83	S	-5737
15101	4	PLATE, 3/16 IN, STL	7.65	9.45	72.28	C	12.24	885	29.70	A	2147	5.83	P	422
15101	5	PLATE, 3/16 IN, STL	7.65	2.15	16.46	C	12.20	201	27.50	A	453	6.33	P	104
15101	6	PLATE, 3/16 IN, STL	7.65	4.31	32.95	C	13.29	438	29.65	A	977	6.33	P	209
15101	7	PLATE, 3/16 IN, STL	7.65	9.45	72.28	C	12.24	885	29.70	A	2147	5.83	S	-422
15101	8	PLATE, 3/16 IN, STL	7.65	2.15	16.46	C	12.20	201	27.50	A	453	6.33	S	-104
15101	9	PLATE, 3/16 IN, STL	7.65	4.31	32.95	C	13.29	438	29.65	A	977	6.33	S	-209
15101	10	PLATE, 3/16 IN, STL	7.65	12.78	97.80	C	11.58	1133	36.30	A	3550	4.50	P	440
15101	11	PLATE, 3/16 IN, STL	7.65	12.78	97.80	C	11.58	1133	36.30	A	3550	4.50	S	-440
15101	12	PLATE, 3/16 IN, STL	7.65	33.18	253.86	C	13.27	3369	35.00	A	8885	0.80	S	-204
15101	13	PLATE, 3/16 IN, STL	7.65	32.88	251.52	C	17.55	4414	35.81	A	9006	0.06	P	14
15101	14	PLATE, 3/16 IN, STL	7.65	10.71	81.96	C	13.60	1114	36.50	A	2992	5.67	P	464
15101	15	PLATE, 3/16 IN, STL	7.65	5.89	45.04	C	10.60	477	38.00	A	1712	5.67	P	255
15101	16	PLATE, 3/16 IN, STL	7.65	10.71	81.96	C	13.60	1114	36.50	A	2992	5.67	S	-464
15101	17	PLATE, 3/16 IN, STL	7.65	5.89	45.04	C	10.60	477	38.00	A	1712	5.67	S	-255
15101														
15102	18	PLATE, 1/8 IN, STL	5.10	13.80	70.36	C	13.40	943	33.40	A	2350	4.50	P	317
15102	19	PLATE, 1/8 IN, STL	5.10	4.06	20.71	C	16.01	332	33.37	A	691	4.29	P	89
15102	20	PLATE, 1/8 IN, STL	5.10	13.21	67.37	C	17.98	1212	33.62	A	2265	4.08	P	275
15102	21	PLATE, 1/8 IN, STL	5.10	13.80	70.36	C	13.40	943	33.40	A	2350	4.50	S	-317
15102	22	PLATE, 1/8 IN, STL	5.10	4.06	20.71	C	16.01	332	33.37	A	691	4.29	S	-89
15102	23	PLATE, 1/8 IN, STL	5.10	13.21	67.37	C	17.98	1212	33.62	A	2265	4.08	S	-275
15102	24	PLATE, 1/8 IN, STL	5.10	10.28	52.43	C	13.35	700	28.65	A	1502	5.67	P	297
15102	25	PLATE, 1/8 IN, STL	5.10	2.54	12.96	C	16.00	207	28.36	A	368	5.56	P	72
15102	26	PLATE, 1/8 IN, STL	5.10	7.83	39.95	C	17.92	716	28.18	A	1126	5.46	P	218
15102	27	PLATE, 1/8 IN, STL	5.10	10.28	52.43	C	13.35	700	28.65	A	1502	5.67	S	-297
15102	28	PLATE, 1/8 IN, STL	5.10	2.54	12.96	C	16.00	207	28.36	A	368	5.56	S	-72
15102	29	PLATE, 1/8 IN, STL	5.10	7.83	39.95	C	17.92	716	28.18	A	1126	5.46	S	-218
15102	30	PLATE, 1/8 IN, STL	5.10	47.04	239.88	C	19.19	4604	26.07	A	6253	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
15102	31	PLATE, 1/8 IN, STL	5.10	0.08	0.40	C	19.17	8	14.30	A	6	0.00	C	0
15102	32	PLATE, 1/8 IN, STL	5.10	0.08	0.40	C	19.17	8	36.63	A	15	0.00	C	0
15102	33	PLATE, 1/8 IN, STL	5.10	0.08	0.40	C	19.17	8	36.63	A	15	4.08	P	2
15102	34	PLATE, 1/8 IN, STL	5.10	0.08	0.40	C	19.17	8	36.63	A	15	4.08	S	-2
15102	35	PLATE, 1/8 IN, STL	5.10	0.07	0.34	C	19.17	7	20.00	A	7	7.01	P	2
15102	36	PLATE, 1/8 IN, STL	5.10	0.07	0.34	C	19.17	7	26.00	A	9	7.01	P	2
15102	37	PLATE, 1/8 IN, STL	5.10	0.07	0.34	C	19.17	7	31.17	A	11	7.01	P	2
15102	38	PLATE, 1/8 IN, STL	5.10	0.07	0.34	C	19.17	7	20.00	A	7	7.01	S	-2
15102	39	PLATE, 1/8 IN, STL	5.10	0.07	0.34	C	19.17	7	26.00	A	9	7.01	S	-2
15102	40	PLATE, 1/8 IN, STL	5.10	0.07	0.34	C	19.17	7	31.17	A	11	7.01	S	-2
15102														
15103	41	PLATE, 1/4 IN, STL	10.20	27.01	275.54	C	13.31	3667	16.00	A	4409	0.00	C	0
15103	42	PLATE, 1/4 IN, STL	10.20	15.63	159.38	C	17.99	2867	15.03	A	2396	0.00	C	0
15103	43	PLATE, 1/4 IN, STL	10.20	19.17	195.55	C	13.25	2592	17.50	A	3422	5.08	P	994
15103	44	PLATE, 1/4 IN, STL	10.20	8.46	86.27	C	17.90	1545	16.56	A	1428	5.27	P	455
15103	45	PLATE, 1/4 IN, STL	10.20	19.17	195.55	C	13.25	2592	17.50	A	3422	5.08	S	-994
15103	46	PLATE, 1/4 IN, STL	10.20	8.46	86.27	C	17.90	1545	16.56	A	1428	5.27	S	-455
15103	47	PLATE, 1/4 IN, STL	10.20	0.27	2.80	C	18.61	52	25.68	A	72	0.00	C	0
15103	48	PLATE, 1/4 IN, STL	10.20	0.27	2.80	C	18.61	52	26.26	A	73	0.00	C	0
15103	49	PLATE, 1/4 IN, STL	10.20	0.03	0.26	C	18.93	5	26.00	A	7	0.13	P	0
15103	50	PLATE, 1/4 IN, STL	10.20	0.03	0.26	C	18.93	5	26.00	A	7	0.13	S	0
15103														
15104	51	6 X 7 WT, STL	7.07	21.73	153.63	C	18.98	2916	25.50	A	3917	0.00	C	0
15104														
15105	52	5 X 6 WT, STL	6.02	6.67	40.12	C	15.08	605	16.30	A	654	0.00	C	0
15105														
15106	53	5 X 3.75 MT, STL	3.75	7.43	27.84	C	18.22	507	15.47	A	431	0.00	C	0
15106														
15107	54	4 X 3.1 MT, STL	3.10	13.67	42.33	C	19.10	808	20.00	A	847	0.00	C	0
15107	55	4 X 3.1 MT, STL	3.10	13.67	42.33	C	19.10	808	26.00	A	1100	0.00	C	0
15107	56	4 X 3.1 MT, STL	3.10	8.17	25.29	C	19.10	483	31.17	A	788	0.00	C	0
15107	57	4 X 3.1 MT, STL	3.10	4.61	14.28	C	15.08	215	17.71	A	253	4.99	P	71
15107	58	4 X 3.1 MT, STL	3.10	4.61	14.28	C	15.08	215	17.71	A	253	4.99	S	-71
15107	59	4 X 3.1 MT, STL	3.10	4.11	12.72	C	18.22	232	16.52	A	210	5.28	P	67
15107	60	4 X 3.1 MT, STL	3.10	4.11	12.72	C	18.22	232	16.52	A	210	5.28	S	-67
15107	61	4 X 3.1 MT, STL	3.10	7.88	24.40	C	15.06	368	20.00	A	488	6.60	P	161
15107	62	4 X 3.1 MT, STL	3.10	7.88	24.40	C	15.06	368	23.00	A	561	6.60	P	161
15107	63	4 X 3.1 MT, STL	3.10	7.88	24.40	C	15.06	368	26.00	A	635	6.60	P	161
15107	64	4 X 3.1 MT, STL	3.10	5.71	17.69	C	16.14	286	29.00	A	513	6.60	P	117
15107	65	4 X 3.1 MT, STL	3.10	7.88	24.40	C	15.06	368	20.00	A	488	6.60	S	-161
15107	66	4 X 3.1 MT, STL	3.10	7.88	24.40	C	15.06	368	23.00	A	561	6.60	S	-161
15107	67	4 X 3.1 MT, STL	3.10	7.88	24.40	C	15.06	368	26.00	A	635	6.60	S	-161

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
15107	68	4 X 3.1 MT, STL	3.10	5.71	17.69	C	16.14	286	29.00	A	513	6.60	S	-117
15107	69	4 X 3.1 MT, STL	3.10	4.05	12.55	C	13.31	167	34.77	A	436	1.67	P	21
15107	70	4 X 3.1 MT, STL	3.10	4.26	13.19	C	17.33	229	35.78	A	472	1.67	P	22
15107	71	4 X 3.1 MT, STL	3.10	6.17	19.10	C	15.08	288	34.77	A	664	1.42	S	-27
15107	72	4 X 3.1 MT, STL	3.10	5.75	17.81	C	18.15	323	35.78	A	637	1.21	S	-22
15107														
15108	73	3 X 1.85 MT, STL	1.85	3.75	6.95	C	13.21	92	15.18	A	105	0.00	C	0
15108	74	3 X 1.85 MT, STL	1.85	3.98	7.37	C	17.08	126	15.54	A	114	0.00	C	0
15108	75	3 X 1.85 MT, STL	1.85	3.80	7.05	C	13.18	93	15.18	A	107	1.67	P	12
15108	76	3 X 1.85 MT, STL	1.85	3.89	7.21	C	13.14	95	17.16	A	124	4.47	P	32
15108	77	3 X 1.85 MT, STL	1.85	3.93	7.28	C	13.12	96	18.24	A	133	5.74	P	42
15108	78	3 X 1.85 MT, STL	1.85	3.80	7.05	C	13.18	93	15.18	A	107	1.67	S	-12
15108	79	3 X 1.85 MT, STL	1.85	3.89	7.21	C	13.14	95	17.16	A	124	4.47	S	-32
15108	80	3 X 1.85 MT, STL	1.85	3.93	7.28	C	13.12	96	18.24	A	133	5.74	S	-42
15108														
15109	81	2.5 X 3/16 FB, STL	1.59	21.98	35.03	C	19.23	674	25.47	A	892	1.38	P	48
15109	82	2.5 X 3/16 FB, STL	1.59	21.98	35.03	C	19.23	674	25.47	A	892	2.75	P	96
15109	83	2.5 X 3/16 FB, STL	1.59	21.82	34.77	C	19.23	669	25.55	A	888	4.08	P	142
15109	84	2.5 X 3/16 FB, STL	1.59	15.35	24.46	C	19.23	470	23.49	A	575	6.83	P	167
15109	85	2.5 X 3/16 FB, STL	1.59	21.98	35.03	C	19.23	674	25.47	A	892	1.38	S	-48
15109	86	2.5 X 3/16 FB, STL	1.59	21.98	35.03	C	19.23	674	25.47	A	892	2.75	S	-96
15109	87	2.5 X 3/16 FB, STL	1.59	21.82	34.77	C	19.23	669	25.55	A	888	4.08	S	-142
15109	88	2.5 X 3/16 FB, STL	1.59	15.35	24.46	C	19.23	470	23.49	A	575	6.83	S	-167
15109	89	2.5 X 3/16 FB, STL	1.59	2.75	4.38	C	19.23	84	35.17	A	154	5.46	P	24
15109	90	2.5 X 3/16 FB, STL	1.59	2.75	4.38	C	19.23	84	35.17	A	154	5.46	S	-24
15109														
15110	91	2.25 X 1/4 FB, STL	1.91	2.91	5.57	C	11.15	62	36.50	A	203	6.74	P	38
15110	92	2.25 X 1/4 FB, STL	1.91	5.33	10.20	C	12.79	130	34.53	A	352	6.74	P	69
15110	93	2.25 X 1/4 FB, STL	1.91	4.09	7.82	C	14.20	111	33.72	A	264	6.74	P	53
15110	94	2.25 X 1/4 FB, STL	1.91	3.79	7.26	C	16.12	117	33.39	A	242	6.74	P	49
15110	95	2.25 X 1/4 FB, STL	1.91	4.61	8.81	C	17.79	157	33.59	A	296	6.74	P	59
15110	96	2.25 X 1/4 FB, STL	1.91	2.91	5.57	C	11.19	62	36.50	A	203	4.59	P	26
15110	97	2.25 X 1/4 FB, STL	1.91	5.33	10.20	C	12.79	130	34.53	A	352	4.59	P	47
15110	98	2.25 X 1/4 FB, STL	1.91	4.09	7.82	C	14.20	111	33.72	A	264	4.59	P	36
15110	99	2.25 X 1/4 FB, STL	1.91	3.79	7.26	C	16.12	117	33.39	A	242	4.34	P	31
15110	100	2.25 X 1/4 FB, STL	1.91	4.61	8.81	C	17.79	157	33.59	A	296	4.18	P	37
15110	101	2.25 X 1/4 FB, STL	1.91	2.91	5.57	C	11.15	62	36.50	A	203	6.74	S	-38
15110	102	2.25 X 1/4 FB, STL	1.91	5.33	10.20	C	12.79	130	34.53	A	352	6.74	S	-69
15110	103	2.25 X 1/4 FB, STL	1.91	4.09	7.82	C	14.20	111	33.72	A	264	6.74	S	-53
15110	104	2.25 X 1/4 FB, STL	1.91	3.79	7.26	C	16.12	117	33.39	A	242	6.74	S	-49
15110	105	2.25 X 1/4 FB, STL	1.91	4.61	8.81	C	17.79	157	33.59	A	296	6.74	S	-59
15110	106	2.25 X 1/4 FB, STL	1.91	2.91	5.57	C	11.19	62	36.50	A	203	4.59	S	-26

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
15110	107	2.25 X 1/4 FB, STL	1.91	5.33	10.20	C	12.79	130	34.53	A	352	4.59	S	-47
15110	108	2.25 X 1/4 FB, STL	1.91	4.09	7.82	C	14.20	111	33.72	A	264	4.59	S	-36
15110	109	2.25 X 1/4 FB, STL	1.91	3.79	7.26	C	16.12	117	33.39	A	242	4.34	S	-31
15110	110	2.25 X 1/4 FB, STL	1.91	4.61	8.81	C	17.79	157	33.59	A	296	4.18	S	-37
15110	111	2.25 X 1/4 FB, STL	1.91	1.96	3.75	C	12.79	48	37.11	A	139	5.67	P	21
15110	112	2.25 X 1/4 FB, STL	1.91	1.96	3.75	C	14.45	54	35.66	A	134	5.67	P	21
15110	113	2.25 X 1/4 FB, STL	1.91	2.22	4.24	C	16.12	68	35.19	A	149	5.54	P	23
15110	114	2.25 X 1/4 FB, STL	1.91	1.96	3.75	C	12.79	48	37.11	A	139	5.67	S	-21
15110	115	2.25 X 1/4 FB, STL	1.91	1.96	3.75	C	14.45	54	35.66	A	134	5.67	S	-21
15110	116	2.25 X 1/4 FB, STL	1.91	2.22	4.24	C	16.12	68	35.19	A	149	5.54	S	-23
15110														
15111	117	2 X 1/4 FB, STL	1.70	11.61	19.73	C	19.33	381	33.17	A	654	5.46	P	108
15111	118	2 X 1/4 FB, STL	1.70	11.61	19.73	C	19.33	381	33.17	A	654	5.46	S	-108
15111	119	2 X 1/4 FB, STL	1.70	4.17	7.08	C	13.21	94	24.50	A	174	6.75	P	48
15111	120	2 X 1/4 FB, STL	1.70	2.01	3.41	C	14.30	49	27.50	A	94	6.75	P	23
15111	121	2 X 1/4 FB, STL	1.70	2.17	3.68	C	12.20	45	29.00	A	107	6.75	P	25
15111	122	2 X 1/4 FB, STL	1.70	0.83	1.42	C	13.37	19	29.00	A	41	6.08	P	9
15111	123	2 X 1/4 FB, STL	1.70	2.17	3.68	C	12.20	45	30.50	A	112	6.75	P	25
15111	124	2 X 1/4 FB, STL	1.70	0.83	1.42	C	13.37	19	30.50	A	43	6.08	P	9
15111	125	2 X 1/4 FB, STL	1.70	2.01	3.41	C	14.30	49	30.50	A	104	6.75	P	23
15111	126	2 X 1/4 FB, STL	1.70	0.65	1.10	C	15.08	17	19.17	A	21	6.75	P	7
15111	127	2 X 1/4 FB, STL	1.70	8.58	14.58	C	15.29	223	27.29	A	398	6.75	P	98
15111	128	2 X 1/4 FB, STL	1.70	4.17	7.08	C	13.21	94	24.50	A	174	6.75	S	-48
15111	129	2 X 1/4 FB, STL	1.70	2.01	3.41	C	14.30	49	27.50	A	94	6.75	S	-23
15111	130	2 X 1/4 FB, STL	1.70	2.17	3.68	C	12.20	45	29.00	A	107	6.75	S	-25
15111	131	2 X 1/4 FB, STL	1.70	0.83	1.42	C	13.37	19	29.00	A	41	6.08	S	-9
15111	132	2 X 1/4 FB, STL	1.70	2.17	3.68	C	12.20	45	30.50	A	112	6.75	S	-25
15111	133	2 X 1/4 FB, STL	1.70	0.83	1.42	C	13.37	19	30.50	A	43	6.08	S	-9
15111	134	2 X 1/4 FB, STL	1.70	2.01	3.41	C	14.30	49	30.50	A	104	6.75	S	-23
15111	135	2 X 1/4 FB, STL	1.70	0.65	1.10	C	15.08	17	19.17	A	21	6.75	S	-7
15111	136	2 X 1/4 FB, STL	1.70	8.58	14.58	C	15.29	223	27.29	A	398	6.75	S	-98
15111	137	2 X 1/4 FB, STL	1.70	3.75	6.38	C	13.21	84	34.92	A	223	0.00	C	0
15111	138	2 X 1/4 FB, STL	1.70	3.80	6.46	C	13.18	85	34.92	A	226	1.67	S	-11
15111	139	2 X 1/4 FB, STL	1.70	3.85	6.55	C	13.16	86	34.92	A	229	3.33	S	-22
15111	140	2 X 1/4 FB, STL	1.70	0.68	1.16	C	18.53	22	36.08	A	42	0.00	C	0
15111	141	2 X 1/4 FB, STL	1.70	10.83	18.40	C	13.23	244	35.00	A	644	5.67	P	104
15111	142	2 X 1/4 FB, STL	1.70	10.83	18.40	C	13.23	244	35.00	A	644	5.67	S	-104
15111														
15112	143	1.5 X 1/4 FB, STL	1.28	1.96	2.50	C	12.79	32	31.93	A	80	5.67	P	14
15112	144	1.5 X 1/4 FB, STL	1.28	1.96	2.50	C	14.45	36	31.74	A	79	5.67	P	14
15112	145	1.5 X 1/4 FB, STL	1.28	2.21	2.82	C	16.12	45	31.55	A	89	5.54	P	16
15112	146	1.5 X 1/4 FB, STL	1.28	2.38	3.03	C	17.79	54	31.39	A	95	5.46	P	17

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
15112	147	1.5 X 1/4 FB, STL	1.28	1.96	2.50	C	12.79	32	31.93	A	80	5.67	S	-14
15112	148	1.5 X 1/4 FB, STL	1.28	1.96	2.50	C	14.45	36	31.74	A	79	5.67	S	-14
15112	149	1.5 X 1/4 FB, STL	1.28	2.21	2.82	C	16.12	45	31.55	A	89	5.54	S	-16
15112	150	1.5 X 1/4 FB, STL	1.28	2.38	3.03	C	17.79	54	31.39	A	95	5.46	S	-17
15112	151	1.5 X 1/4 FB, STL	1.28	1.33	1.70	C	13.29	23	31.75	A	54	5.17	P	9
15112	152	1.5 X 1/4 FB, STL	1.28	1.33	1.70	C	13.29	23	31.75	A	54	5.17	S	-9
15112	153	1.5 X 1/4 FB, STL	1.28	1.96	2.50	C	11.15	28	37.94	A	95	5.67	P	14
15112	154	1.5 X 1/4 FB, STL	1.28	1.96	2.50	C	11.15	28	37.94	A	95	5.67	S	-14
15113	155	2 SCH 40 PIPE, ASTM A500 B	3.65	7.50	27.38	C	15.08	413	26.00	A	712	0.00	C	0
16201	1	1 X 1 L, STL	0.80	55.94	44.75	C	10.62	475	41.90	A	1875	0.00	C	0
16202	2	PLATE, 1/8 IN, STL	5.10	45.86	233.87	C	10.62	2484	41.90	A	9798	0.00	C	0
16203	3	INTAKE LOUVER	15.00	2.00	30.00	C	10.98	329	41.90	A	1257	0.00	C	0
16204	4	PLATE, 3/16 IN, STL	7.65	9.41	71.97	C	22.33	1607	32.88	A	2366	5.46	P	393
16204	5	PLATE, 3/16 IN, STL	7.65	11.15	85.29	C	20.95	1787	33.07	A	2820	6.83	P	583
16204	6	PLATE, 3/16 IN, STL	7.65	11.15	85.29	C	20.95	1787	33.07	A	2820	4.08	P	348
16204	7	PLATE, 3/16 IN, STL	7.65	8.48	64.87	C	20.88	1354	31.17	A	2022	5.46	P	354
16204	8	PLATE, 3/16 IN, STL	7.65	4.51	34.48	C	20.79	717	34.88	A	1203	5.46	P	188
16204	9	PLATE, 3/16 IN, STL	7.65	9.41	71.97	C	22.33	1607	32.88	A	2366	5.46	S	-393
16204	10	PLATE, 3/16 IN, STL	7.65	11.15	85.29	C	20.95	1787	33.07	A	2820	6.83	S	-583
16204	11	PLATE, 3/16 IN, STL	7.65	11.15	85.29	C	20.95	1787	33.07	A	2820	4.08	S	-348
16204	12	PLATE, 3/16 IN, STL	7.65	8.48	64.87	C	20.88	1354	31.17	A	2022	5.46	S	-354
16204	13	PLATE, 3/16 IN, STL	7.65	4.51	34.48	C	20.79	717	34.88	A	1203	5.46	S	-188
16205	14	2 X 1/4 FB, STL, ABS H36	1.70	2.75	4.68	C	20.83	97	31.25	A	146	5.46	P	26
16205	15	2 X 1/4 FB, STL, ABS H36	1.70	2.99	5.09	C	20.83	106	33.08	A	168	6.75	P	34
16205	16	2 X 1/4 FB, STL, ABS H36	1.70	2.99	5.09	C	20.83	106	33.08	A	168	4.17	P	21
16205	17	2 X 1/4 FB, STL, ABS H36	1.70	2.75	4.68	C	20.83	97	31.25	A	146	5.46	S	-26
16205	18	2 X 1/4 FB, STL, ABS H36	1.70	2.99	5.09	C	20.83	106	33.08	A	168	6.75	S	-34
16205	19	2 X 1/4 FB, STL, ABS H36	1.70	2.99	5.09	C	20.83	106	33.08	A	168	4.17	S	-21
16302	1	SEA CHESTS	100.00	1.00	100.00	E	5.00	500	24.17	A	2417	0.00	C	0
16701	1	DOOR, QAWT, 8 DOG, LH, 26 X 54	255.00	1.00	255.00	C	6.88	1753	12.62	A	3219	0.41	P	104
16701	2	DOOR, QAWT, 8 DOG, LH, 26 X 54	255.00	1.00	255.00	C	6.88	1753	25.62	A	6534	0.41	P	104
16701	3	DOOR, QAWT, 8 DOG, LH, 26 X 54	255.00	1.00	255.00	C	6.88	1753	34.64	A	8834	0.41	P	104
16701														

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
16702	4	HATCH, FLUSH, HINGED, DOG TYPE C, BFHH0 15 X 24	1.00	46.00	46.00	C	11.29	519	1.72	A	79	1.64	S	-76
16702	5	HATCH, FLUSH, HINGED, DOG TYPE C, BFHH0 15 X 24	1.00	46.00	46.00	C	9.00	414	48.72	A	2241	7.60	S	-349
16702	6	HATCH, FLUSH, HINGED, DOG TYPE C, BFHH0 15 X 24	1.00	46.00	46.00	C	9.00	414	51.28	A	2359	7.60	S	-349
16702														
16703	7	HATCH, FLUSH BOLTED, BMHC 15 X 23 F	1.00	98.00	98.00	C	3.49	342	11.79	A	1156	2.24	P	220
16703	8	HATCH, FLUSH BOLTED, BMHC 15 X 23 F	1.00	98.00	98.00	C	3.49	342	27.41	A	2686	4.97	S	-487
16703	9	HATCH, FLUSH BOLTED, BMHC 15 X 23 F	1.00	98.00	98.00	C	3.49	342	28.41	A	2784	6.59	P	645
16703	10	HATCH, FLUSH BOLTED, BMHC 15 X 23 F	1.00	98.00	98.00	C	3.49	342	30.46	A	2985	0.11	P	11
16703														
16704	11	HATCH, YOKE HINGE, 24 X 24	1.00	81.00	81.00	C	11.27	913	11.41	A	924	2.76	S	-223
16704	12	HATCH, YOKE HINGE, 24 X 24	1.00	81.00	81.00	C	9.00	729	57.65	A	4669	3.33	P	270
16704	13	HATCH, YOKE HINGE, 24 X 24	1.00	81.00	81.00	C	9.00	729	60.40	A	4892	3.33	P	270
16801	1	DOOR, WEATHERTIGHT, 2 DOG, RH, 29.5 X 69.5	160.00	1.00	160.00	C	14.85	2375	21.51	A	3441	81.25	S	-13000
16801														0
16802	2	DOOR, WEATHERTIGHT, 2 DOG, LH, 29.5 X 69.5	160.00	1.00	160.00	C	14.85	2375	21.51	A	3441	81.25	P	13000
16802														0
16803	3	DOOR, QAWT, 8 DOG, RH, 30 X 66	301.00	1.00	301.00	C	13.28	3998	35.21	A	10599	3.04	P	914
														0
171	10	MASTS, TOWERS, TETRAPODS	200.00	1.00	200.00	E	25.00	5000	29.17	A	5833	0.00	C	0
18201	1	PROPULSION PLANT FOUNDATIONS	506.19	1.00	506.19	E	2.00	1012	42.00	A	21260	0.00	C	0
18201														
18202	2	PLATE, 5/16 IN, STL	12.75	6.37	81.23	C	1.69	137	38.00	A	3087	0.00	C	0
18202	3	PLATE, 5/16 IN, STL	12.75	3.67	46.85	C	2.15	101	37.92	A	1776	0.00	C	0
18202														
18203	4	PLATE, 1/4 IN, STL	10.20	2.68	27.32	C	1.98	54	42.50	A	1161	0.00	C	0
18203	5	PLATE, 1/4 IN, STL	10.20	3.60	36.77	C	1.81	67	44.00	A	1618	0.00	C	0
18203	6	PLATE, 1/4 IN, STL	10.20	12.10	123.46	C	1.83	225	43.21	A	5334	0.00	C	0
18203														
18204	7	PLATE, 5/32 IN, STL	6.38	7.05	44.97	C	1.67	75	37.93	A	1706	0.00	C	0
18204														
18205	8	PLATE, 3/8 IN, STL	15.30	4.20	64.20	C	2.62	168	40.56	A	2604	0.00	C	0
18205														
18301	1	ELECTRICAL PLANT FOUNDATIONS	1208.68	1.00	1208.68	E	2.00	2417	40.00	A	48347	0.00	C	0
18301														
18302	2	PLATE, 1/4 IN, STL	10.20	8.40	85.67	C	2.89	248	43.94	A	3764	0.00	C	0
18302														
18303	3	PLATE, 5/16 IN, STL	12.75	8.27	105.39	C	3.61	380	44.00	A	4637	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
18303														
18401	1	COMMAND AND SURVEILLANCE FOUNDATIONS (13%)	516.22	1.00	516.22	E	16.75	8644	29.17	A	15056	0.00	C	0
18501	1	PLATE, 1/2 IN, STL	20.40	18.43	375.96	C	9.02	3391	47.00	A	17670	0.00	C	0
18501	2	PLATE, 1/2 IN, STL	20.40	1.72	35.05	C	8.02	281	47.00	A	1647	0.00	C	0
18501	3	PLATE, 1/2 IN, STL	20.40	1.72	35.05	C	8.02	281	47.00	A	1647	0.00	C	0
18501	4	PLATE, 1/2 IN, STL	20.40	7.53	153.65	C	12.01	1846	47.00	A	7221	0.00	C	0
18501	5	PLATE, 1/2 IN, STL	20.40	14.50	295.85	C	9.22	2728	47.00	A	13905	0.00	C	0
18501														
18502	6	12 X 4 X 19 MT, STL	14.14	12.27	173.47	C	8.40	1458	47.02	A	8156	0.00	C	0
18502														
18501	1	AUXILIARY SYSTEMS FOUNDATIONS (10%)	1729.29	1.00	1729.29	E	5.58	9652	40.00	A	69172	0.00	C	0
18601	1	OUTFIT AND FURNISHING FOUNDATIONS (1%)	215.71	1.00	215.71	E	8.65	1866	30.50	A	6579	0.00	C	0
19601		WELDING	1437.00	1.00	1437.00	E	6.97	10022	31.75	A	45621	0.01	P	14
19701	10	MILL TOLERANCE	1915.99	1.00	1915.99	E	6.97	13363	31.75	A	60827	0.01	P	19
198	10													
NA	10	BRACKETS & MISC. STRUCTURE	1652.98	1.00	1652.98	E	6.42	10612	31.11	A	51424	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT lb	NO. UNITS #	CURRENT WEIGHT lb	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
							ft	ft*lb	ft		ft*lb	ft		ft*lb
23301	1	MAIN PROPULSION DIESEL ENGINE, PORT	4299.00	1.00	4299	E	4.06	17461	39.83	A	171229	3.49	P	14993
23301	2	MAIN PROPULSION DIESEL ENGINE, STBD	4299.00	1.00	4299	E	4.06	17461	39.83	A	171229	3.49	S	-14993
24101	1	MARINE GEAR, PORT	758.00	1.00	758	E	2.76	2088	43.43	A	32919	3.50	P	2653
24101	2	MARINE GEAR, STBD	758.00	1.00	758	E	2.76	2088	43.43	A	32919	3.50	S	-2653
24201	1	PROPULSION CLUTCHES AND COUPLINGS	70.00	2.00	140	C	3.80	532	48.00	A	6720	0.00	C	0
24301	1	SHAFT	1120.00	2.00	2240	C	2.13	4763	53.06	A	118853	0.00	C	0
24401	1	SHAFT BEARING	76.00	2.00	152	E	2.23	339	49.22	A	7481	0.00	C	0
24501	1	PROPELLER	307.00	2.00	614	E	1.92	1176	60.94	A	37419	0.00	C	0
25101	1	COMBUSTION AIR SYSTEM	300.00	1.00	300	E	8.00	2400	42.50	A	12750	0.00	C	0
25201	1	PROPULSION CONTROL SYSTEM	150.00	1.00	150	E	3.67	551	40.00	A	6000	0.00	C	0
25601	1	CIRCULATING & COOLING SEA WATER SYSTEM	2492.03	0.00	0	E	1.83	0	38.79	A	0	0.00	C	0
25901	1	SILENCER, MPDE	108.00	2.00	216	E	19.68	4251	32.39	A	6997	0.00	C	0
25902	2	EXHAUST SYSTEM	904.00	1.00	904	E	11.00	9944	38.00	A	34352	0.00	C	0
26101	1	FUEL SERVICE SYSTEM	114.00	1.00	114	E	2.00	228	38.00	A	4332	0.00	C	0
26201	1	MAIN PROPULSION LUBE OIL SYSTEM	108.00	1.00	108	E	3.67	396	40.00	A	4320	0.00	C	0
29801	1	PROPULSION PLANT OPERATING FLUIDS	693.45	1.00	693	E	3.67	2543	40.00	A	27738	0.00	C	0
29802	2	MPDE OIL, PORT	54.25	1.00	54	E	4.06	220	39.83	A	2161	3.49	P	189
29802	3	MPDE OIL, STBD	54.25	1.00	54	E	4.06	220	39.83	A	2161	3.49	S	-189
29803	4	MPDE COOLANT, PORT	120.00	1.00	120	E	4.06	487	39.83	A	4780	3.49	P	419
29803	5	MPDE COOLANT, STBD	120.00	1.00	120	E	4.06	487	39.83	A	4780	3.49	S	-419
29804	6	MARINE GEAR OIL, PORT	39.03	1.00	39	E	2.76	108	43.43	A	1695	3.50	P	137
29804	7	MARINE GEAR OIL, STBD	39.03	1.00	39	E	2.76	108	43.43	A	1695	3.50	S	-137
29901	1	PROPULSION PLANT REPAIR PARTS AND SPECIAL TOOLS	896.00	1.00	896	E	3.67	3285	40.00	A	35840	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT #	NO. UNITS lb	CURRENT WEIGHT lb	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
							ft	ft*lb	ft		ft*lb	ft		ft*lb
31101	1	SSDG DRY WEIGHT, PORT	1.00	2885.00	2885	E	5.30	15291	43.86	A	126550	7.48	P	21589
31102	2	SSDG DRY WEIGHT, STBD	1.00	2885.00	2885	E	5.30	15291	44.04	A	127062	7.36	S	-21222
31301	1	BATTERIES AND SERVICE FACILITIES	1.00	1120.00	1120	E	3.50	3920	36.00	A	40320	0.00	C	0
32001	1	POWER DISTRIBUTION SYSTEM	1.00	2274.00	2274	E	8.50	19329	35.00	A	79590	0.00	C	0
33001	1	LIGHTING SYSTEM	1.00	694.00	694	E	11.00	7634	32.40	A	22486	0.00	C	0
34201	1	SILENCER, SSDG	2.00	54.00	108	E	7.65	826	39.83	A	4302	0.00	C	0
34201														
34202	2	DIESEL SUPPORT SYSTEM	1.00	1012.00	1012	E	3.16	3198	32.40	A	32789	0.00	C	0
39801	1	ELECTRIC PLANT OPERATING FLUIDS	1.00	151.00	151	E	5.50	831	43.08	A	6506	0.00	C	0
39801														
39802	2	SSDG WET OIL, PORT	1.00	38.50	39	E	5.30	204	43.86	A	1689	7.48	P	288
39802	3	SSDG WET OIL, STBD	1.00	38.50	39	E	5.30	204	44.04	A	1696	7.36	S	-283
39802														
39803	4	SSDG COOLANT, PORT	1.00	110.00	110	E	5.30	583	43.86	A	4825	7.48	P	823
39803	5	SSDG COOLANT, STBD	1.00	110.00	110	E	5.30	583	44.04	A	4845	7.36	S	-809
39901	1	ELECTRIC PLANT REPAIR PARTS & SPECIAL TOOLS	1.00	224.00	224	E	6.76	1514	32.40	A	7258	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT lb	NO. UNITS #	CURRENT WEIGHT lb	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
							ft	ft*lb	ft		ft*lb	ft		ft*lb
41101	1	DATA DISPLAY GROUP	448.00	1.00	448	E	14.50	6496	18.00	A	8064	0.00	C	0
42101	1	NON-ELECTRICAL/ELECTRONIC NAVIGATION AIDS	217.00	1.00	217	E	16.32	3541	18.00	A	3906	0.00	C	0
42201	1	ELECTRICAL NAVIGATION AIDS	448.00	1.00	448	E	16.32	7311	18.00	A	8064	0.00	C	0
42601	1	ELECTRICAL NAVIGATION SYSTEMS	448.00	1.00	448	E	14.50	6496	18.00	A	8064	0.00	C	0
43401	1	ENTERTAINMENT & TRAINING SYSTEMS	57.93	1.00	58	E	9.33	540	25.00	A	1448	0.00	C	0
43601	1	ALARM, SAFETY, AND WARNING SYSTEMS	448.00	1.00	448	E	7.77	3481	25.00	A	11200	0.00	C	0
43701	1	INDICATING, ORDER, AND METERING SYSTEMS	224.00	1.00	224	E	8.04	1801	25.00	A	5600	0.00	C	0
43801	1	INTEGRATED CONTROL SYSTEM	560.00	1.00	560	E	9.89	5538	25.00	A	14000	0.00	C	0
44101	1	RADIO SYSTEMS	448.00	1.00	448	E	10.26	4596	25.00	A	11200	0.00	C	0
44301	1	VISUAL AND AUDIBLE COMMUNICATION SYSTEMS	224.00	1.00	224	E	19.12	4283	25.00	A	5600	0.00	C	0
44601	1	SECURITY EQUIPMENT						0			0			0
45101	1	SURFACE SEARCH RADAR	448.00	1.00	448	E	50.02	22409	22.00	A	9856	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
							ft	ft*lb	ft					
			lb	#	lb						ft*lb	ft		ft*lb
51101	1	COMPARTMENT HEATING SYSTEM	183.74	1.00	184	E	7.89	1450	32.40	A	5953	0.00	C	0
51201	1	VENTILATION SYSTEM	407.06	1.00	407	E	12.00	4885	26.00	A	10584	0.00	C	0
51301	1	MACHINERY SPACE VENTILATION SYSTEM	694.40	1.00	694	E	21.00	14582	40.00	A	27776	0.00	C	0
51401	1	AIR CONDITIONING SYSTEM	282.68	1.00	283	E	12.00	3392	26.00	A	7350	0.00	C	0
51601	1	REFRIGERATION SYSTEM	604.80	1.00	605	E	6.00	3629	15.00	A	9072	0.00	C	0
52301	1	WASHDOWN SYSTEM	192.11	1.00	192	E	10.00	1921	42.00	A	8069	0.00	C	0
52601	1	SCUPPERS AND DECK DRAINS	640.71	1.00	641	E	10.31	6606	32.40	A	20759	0.00	C	0
52901	1	DRAINAGE AND BALLASTING SYSTEM	602.96	1.00	603	E	3.81	2297	32.40	A	19536	0.00	C	0
53201	1	KEEL COOLER FOR ENGINE JACKET WATER	200.00	2.00	400	E	1.83	732	38.79	A	15516	0.00	C	0
53202	2	KEEL COOLER FOR ENGINE AFTER COOLER AND MARINE GEAR	209.00	2.00	418	E	2.45	1025	46.19	A	19308	0.00	C	0
53203	3	KEEL COOLER FOR GENERATOR	200.00	2.00	400	E	0.54	218	38.01	A	15206	0.00	C	0
53204	4	COOLING WATER	487.20	2.00	974	E	0.73	715	45.37	A	44209	0.00	C	0
53301	1	POTABLE WATER	1351.72	1.00	1352	E	4.00	5407	23.00	A	31090	0.00	C	0
55501	1	FIRE EXTINGUISHING SYSTEMS	850.12	1.00	850	E	6.00	5101	38.00	A	32305	0.00	C	0
55601	1	HYDRAULIC SYSTEM	1965.00	1.00	1965	E	6.00	11790	52.00	A	102180	0.00	C	0
56101	1	STEERING CONTROL SYSTEM	2240.00	1.00	2240	E	6.00	13440	62.00	A	138880	0.00	C	0
56201	1	RUDDER	336.00	2.00	672	E	3.00	2016	63.50	A	42672	0.00	C	0
58101	1	ANCHOR	32.00	1.00	32	E	12.36	395	5.94	A	190	6.73	S	-215
58101														
58102	2	ANCHOR LINE REEL	45.88	1.00	46	C	14.08	646	16.08	A	738	1.92	P	88
58102														
58103	3	ANCHOR ROPE LINE	2.12	275.00	583	C	9.72	5666	1.47	A	857	3.25	P	1897
58103														
58104	4	ANCHOR CHAIN AND SHACKLE	2.50	25.00	63	C	9.72	607	1.47	A	92	3.25	P	203
58104														
58105	5	ELECTRIC CAPSTAN	88.00	1.00	88	C	11.62	1023	15.11	A	1330	0.36	P	31
58105														
58201	1	MOORING LINES	2.12	360.00	763	C	13.34	10181	14.95	A	11412	0.40	S	-308
58201														
58301	1	LIFERAFT, VIKING 12, LOW PROFILE	135.00	1.00	135	E	19.94	2691	22.73	A	3068	4.00	P	540
58301														
58302	2	LIFE RING, 30 IN	5.50	2.00	11	E	13.39	147	8.18	A	90	0.00	C	0
58302	3	LIFE RING, 30 IN	5.50	2.00	11	E	12.99	143	25.01	A	275	0.00	C	0
58302	4	LIFE RING, 30 IN	5.50	2.00	11	E	11.67	128	63.93	A	703	0.00	C	0

58901	1	WORKING DECK CRANE	8400.00	1.00	8400	E	15.00	126000	47.00	A	394800	0.00	C	0
58902	2	CROSS DECK WINCH	370.00	2.00	740	E	9.81	7260	56.51	A	41814	0.00	C	0
58903	3	CHAIN STOPPER	900.00	2.00	1800	E	9.30	16740	47.50	A	85500	0.00	C	0
58901	1	AUXILIARY SYSTEMS OPERATING FLUIDS			0	E	2.55	0	44.00	A	0	0.00	C	0
59301	1	ENVIRONMENTAL POLLUTION CONTROL SYSTEMS	1544.83	1.00	1545	E	4.50	6952	42.00	A	64883	0.00	C	0
59901	1	AUXILIARY SYSTEMS REPAIR PARTS AND TOOLS	470.40	1.00	470	E	5.00	2352	36.00	A	16934	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb		ft	ft*lb	ft		ft*lb	ft		ft*lb
61101	1	CHOCK	69.93	1.00	70	E	11.75	822	0.62	F	-43	0.00	C	0
61101	2	CHOCK	69.93	2.00	140	E	11.75	1643	2.37	A	331	0.00	C	0
61101	3	CHOCK	69.93	2.00	140	E	11.75	1643	24.81	A	3470	0.00	C	0
61101	4	CHOCK	69.93	2.00	140	E	9.60	1343	58.98	A	8250	0.00	C	0
61101	5	CHOCK	69.93	1.00	70	E	9.60	671	67.97	A	4753	0.00	C	0
61101														
61102	6	DOUBLE BOLLARD	100.00	1.00	100	E	11.62	1162	1.25	A	125	0.00	C	0
61102	7	DOUBLE BOLLARD	100.00	2.00	200	E	11.45	2291	14.59	A	2918	0.00	C	0
61102	8	DOUBLE BOLLARD	100.00	2.00	200	E	9.44	1888	64.93	A	12986	0.00	C	0
61102														
61103	9	FENDERS	12.00	6.00	72	E	6.72	484	50.45	A	3632	2.76	S	-199
61201	1	PIPE, 1 1/4" NPS, SCHED 40	2.27	24.55	56	C	14.67	818	3.75	A	210	0.00	C	0
61201	2	PIPE, 1 1/4" NPS, SCHED 40	2.27	41.05	93	C	14.67	1368	23.56	A	2198	0.00	C	0
61201	3	PIPE, 1 1/4" NPS, SCHED 40	2.27	31.06	71	C	12.57	887	64.76	A	4572	0.00	C	0
61201	4	PIPE, 1 1/4" NPS, SCHED 40	2.27	42.07	96	C	14.49	1385	24.36	A	2330	0.00	C	0
61201														
61202	5	PIPE, 3/4" NPS, SCHED 40	1.13	24.55	28	C	13.67	379	3.75	A	104	0.00	C	0
61202	6	PIPE, 3/4" NPS, SCHED 40	1.13	41.05	46	C	13.67	634	23.56	A	1094	0.00	C	0
61202	7	PIPE, 3/4" NPS, SCHED 40	1.13	31.06	35	C	11.57	406	64.76	A	2275	0.00	C	0
61202	8	PIPE, 3/4" NPS, SCHED 40	1.13	20.85	24	C	10.57	249	64.76	A	1527	0.00	C	0
61202														
61203	9	PIPE, 1 1/4" NPS, SCHED 40	2.27	36.00	82	C	13.73	1123	15.13	A	1238	0.00	C	0
61203	10	PIPE, 1 1/4" NPS, SCHED 40	2.27	75.00	170	C	10.72	1828	55.78	A	9509	0.00	C	0
61203														
61204	11	PLATE, 7.65#	7.65	1.55	12	C	9.13	108	55.78	A	661	0.00	C	0
61204														
61205	12	D HOOK	0.15	74.00	11	C	11.67	130	38.02	A	422	0.00	C	0
61205														
61206	13	1/4" CHAIN	0.75	123.17	92	C	11.67	1078	38.02	A	3512	0.00	C	0
61206														
61207	14	ROD 5/16" DIA (STAPLE)	0.10	74.00	7	C	11.67	86	38.02	A	281	0.00	C	0
61207														
61208	15	SHEET, 0.188", 3" DIA	0.50	17.00	9	C	14.49	123	24.80	A	211	0.00	C	0
61208														
61209	16	SHACKLE, ANCOR W/ SCREW PIN 3/8" DIA	0.30	74.00	22	C	11.67	259	38.02	A	844	0.00	C	0
61209														
61210	17	COMPRESSION SLEEVE - N-TYPE (OVAL) 1/16" CABLE SIZE	0.00	74.00	0	C	11.67	1	38.02	A	4	0.00	C	0
61210														
62101	1	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	50.12	65	C	7.44	484	19.51	A	1269	6.75	S	-439
62101	2	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	48.75	63	C	7.26	459	22.76	A	1441	3.42	S	-216
62101	3	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	81.13	105	C	6.58	693	21.57	A	2272	2.22	S	-234
62101	4	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	48.66	63	C	7.26	458	22.75	A	1438	1.67	P	105
62101	5	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	63.47	82	C	7.41	611	19.51	A	1608	5.86	P	483
62101	6	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	80.85	105	C	7.40	777	30.50	A	3202	8.88	S	-933
62101	7	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	53.92	70	C	7.44	521	31.07	A	2176	5.30	S	-371

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb		ft	ft*lb	ft		ft*lb	ft		ft*lb
62101	8	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	67.50	88	C	7.25	636	30.50	A	2673	1.67	S	-146
62101	9	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	63.68	83	C	7.04	582	30.43	A	2516	1.67	P	138
62101	10	JOINER PANEL, ALUMINUM HONEYCOMB, 5/8"	1.30	80.85	105	C	7.40	777	30.50	A	3202	8.88	P	933
62101														
62102	2	STAINLESS STEEL SHOWER PARTITIONS, FIXTURE, BASE & CURTAINS (LARGE HEAD)	85.00	1.00	85	C	6.23	530	29.46	A	2504	6.35	S	-540
62201	1	ALUMINUM TREAD PLATE	2.65	14.32	38	C	6.00	228	2.78	A	105	0.00	C	0
62201	2	ALUMINUM TREAD PLATE	2.65	144.89	384	C	1.97	756	41.49	A	15931	0.00	C	0
62201	3	ALUMINUM TREAD PLATE	2.65	90.35	239	C	4.35	1041	52.63	A	12600	0.00	C	0
62201	4	ALUMINUM TREAD PLATE	2.65	11.91	32	C	4.72	149	55.35	A	1747	0.00	C	0
62201	5	ALUMINUM TREAD PLATE	2.65	59.09	157	C	5.07	794	57.13	A	8947	0.00	C	0
62201	6	ALUMINUM TREAD PLATE	2.65	87.31	231	C	5.30	1226	62.09	A	14367	0.00	C	0
62201														
62202	7	FLOORPLATE SUPPORT STRUCTURE	29.97	1.00	30	C	5.00	150	2.78	A	83	0.00	C	0
62202	8	FLOORPLATE SUPPORT STRUCTURE	303.32	1.00	303	C	0.97	294	41.49	A	12586	0.00	C	0
62202	9	FLOORPLATE SUPPORT STRUCTURE	189.15	1.00	189	C	3.35	633	52.63	A	9954	0.00	C	0
62202	10	FLOORPLATE SUPPORT STRUCTURE	24.93	1.00	25	C	3.72	93	55.35	A	1380	0.00	C	0
62202	11	FLOORPLATE SUPPORT STRUCTURE	123.71	1.00	124	C	4.07	504	57.13	A	7068	0.00	C	0
62202	12	FLOORPLATE SUPPORT STRUCTURE	182.78	1.00	183	C	4.30	786	62.09	A	11350	0.00	C	0
62202														
62203	13	2 X 1/4 FB, AL, 6061	0.60	73.23	44	C	3.41	150	21.21	A	932	0.25	P	11
62203								0						0
62204	14	2 X 2 X 3/16 ANGLE, AL, 6061	0.85	25.36	22	C	3.44	74	21.98	A	474	0.00	C	0
62204	15	2 X 2 X 3/16 ANGLE, AL, 6061	0.85	132.90	113	C	3.44	389	19.85	A	2242	0.05	S	-5
62204								0						0
62204	16	0.188 PLATE, AL, ASTM B632	2.85	165.26	471	C	3.50	1647	20.91	A	9848	0.02	S	-11
62301	1	VERTICAL LADDER	2.59	4.81	12	C	8.51	106	3.66	A	46	1.72	S	-21
62301	2	VERTICAL LADDER	2.59	7.41	19	C	7.21	138	12.82	A	246	2.76	S	-53
62301	3	VERTICAL LADDER	2.59	4.64	12	C	5.50	66	49.85	A	598	6.92	S	-83
62301	4	VERTICAL LADDER	2.59	4.64	12	C	5.50	66	50.15	A	602	6.92	S	-83
62301	5	VERTICAL LADDER	2.59	4.00	10	C	6.89	71	60.34	A	624	0.00	P	0
62301	6	VERTICAL LADDER	2.59	4.00	10	C	6.89	71	60.34	A	624	0.00	P	0
62301	7	VERTICAL LADDER	2.59	8.75	23	C	15.88	359	26.26	A	594	5.01	P	113
62301	8	VERTICAL LADDER FOUNDATION	9.89	1.00	10	C	9.25	92	38.76	A	384	0.27	P	3
62301														
62302	9	INCLINED LADDER	14.73	9.00	133	C	8.42	1117	20.29	A	2690	0.00	C	0
62302	10	INCLINED LADDER	14.73	6.92	102	C	7.41	755	32.00	A	3260	3.03	P	309
62302	11	INCLINED LADDER FOUNDATION	23.45	1.00	23	C	7.98	187	25.39	A	595	1.32	P	31
62302														
62303	12	WORKING DECK STEP UP	91.43	2.00	183	C	10.29	1882	35.95	A	6574	0.00	C	0
62303	13	WORKING DECK STEP UP FOUNDATION	18.29	1.00	18	C	10.29	188	35.95	A	657	0.00	C	0
62303														
62304	14	MACHINERY ROOM STEP UP	65.00	1.00	65	C	3.05	199	35.80	A	2327	0.00	C	0
62304	15	MACHINERY ROOM STEP UP FOUNDATION	6.50	1.00	7	C	3.05	20	35.80	A	233	0.00	C	0
62304														
62305	16	WORKING DECK TO PILOT HOUSE STEP UP	165.00	1.00	165	C	9.64	1591	36.22	A	5976	3.25	P	537
62305	17	FOSCLE DECK TO PILOT HOUSE STEP UP	53.00	2.00	106	C	11.49	1218	21.92	A	2323	0.00	C	0

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb	A	ft	ft*lb	ft		ft*lb	ft		ft*lb
62305	18	PILOUT HOUSE STEP UP FOUNDATION	27.10	1.00	27	C	10.38	281	30.48	A	826	1.95	P	53
62401	1	DOOR, METAL JOINER, TY-E, LH, 26 X 78	64.00	1.00	64	C	6.93	443	24.42	A	1563	1.68	P	107
62401														
62402	2	DOOR, METAL JOINER, TY-E, RH, 26 X 78	64.00	1.00	64	C	6.93	443	24.36	A	1559	22.27	S	-1425
62402	3	DOOR, METAL JOINER, TY-E, RH, 26 X 78	64.00	1.00	64	C	6.93	443	27.57	A	1765	1.68	P	107
62402	4	DOOR, METAL JOINER, TY-E, RH, 26 X 78	64.00	1.00	64	C	6.93	443	29.56	A	1892	6.93	S	-443
62402	5	DOOR, METAL JOINER, TY-E, RH, 26 X 78	64.00	1.00	64	C	6.93	443	33.38	A	2136	1.68	S	-107
62402														
62403	6	DOOR, METAL JOINER, TY-E, RH, 20 X 64	45.00	1.00	45	C	7.44	335	22.86	A	1029	2.29	S	-103
62501	1	WINDOW, FRONT CENTRAL PORT	7.48	10.93	82	C	16.74	1369	15.49	A	1266	1.85	P	151
62501	2	WINDOW, FRONT CENTRAL STARBOARD	7.48	10.93	82	C	16.74	1369	15.49	A	1266	1.85	S	-151
62501	3	WINDOW, FRONT OUTBOARD PORT	9.59	11.84	114	C	16.74	1901	16.99	A	1928	5.10	P	579
62501	4	WINDOW, FRONT OUTBOARD STARBOARD	9.59	11.84	114	C	16.74	1901	16.99	A	1928	5.10	S	-579
62501	5	WINDOW, PORT 1	2.54	7.29	19	C	16.79	311	19.24	A	356	6.83	P	127
62501	6	WINDOW, PORT 2	6.25	7.29	46	C	16.79	765	24.50	A	1116	6.83	P	311
62501	7	WINDOW, PORT 3	6.25	7.29	46	C	16.79	765	27.50	A	1252	6.83	P	311
62501	8	WINDOW, PORT 4	4.38	7.29	32	C	16.79	535	30.13	A	960	6.83	P	218
62501	9	WINDOW, STARBOARD 1	2.54	7.29	19	C	16.79	311	19.24	A	356	6.83	S	-127
62501	10	WINDOW, STARBOARD 2	6.25	7.29	46	C	16.79	765	24.50	A	1116	6.83	S	-311
62501	11	WINDOW, STARBOARD 3	6.25	7.29	46	C	16.79	765	27.50	A	1252	6.83	S	-311
62501	12	WINDOW, STARBOARD 4	4.38	7.29	32	C	16.79	535	30.13	A	960	6.83	S	-218
62501	13	WINDOW, BACK PORT	5.21	7.29	38	C	16.74	635	35.51	A	1348	2.88	P	109
62501	14	WINDOW, BACK STARBOARD	12.71	10.02	127	C	16.74	2132	35.51	A	4522	1.21	S	-154
62501														
62502	15	WIPER, FRONT CENTRAL PORT	11.00	1.00	11	E	16.74	1369	15.49	A	1266	1.85	P	20
62502	16	WIPER, FRONT CENTRAL STARBOARD	11.00	1.00	11	E	16.74	1369	15.49	A	1266	1.85	S	-20
62502	17	WIPER, FRONT OUTBOARD PORT	11.00	1.00	11	E	16.74	1901	16.99	A	1928	5.10	P	56
62502	18	WIPER, FRONT OUTBOARD STARBOARD	11.00	1.00	11	E	16.74	1901	16.99	A	1928	5.10	S	-56
62502	19	WIPER, BACK PORT	11.00	1.00	11	E	16.74	635	35.51	A	1348	2.88	P	32
62502	20	WIPER, BACK STARBOARD	11.00	1.00	11	E	16.74	2132	35.51	A	4522	1.21	S	-13
62502														
62503	21	HEATER, FRONT CENTRAL PORT	2.00	11.08	22	E	16.74	1369	15.49	A	1266	1.85	P	41
62503	22	HEATER, FRONT CENTRAL STARBOARD	2.00	8.49	17	E	16.74	1369	15.49	A	1266	1.85	S	-31
62503	23	HEATER, FRONT OUTBOARD PORT	2.00	8.49	17	E	16.74	1901	16.99	A	1928	5.10	P	87
62503	24	HEATER, FRONT OUTBOARD STARBOARD	2.00	4.26	9	E	16.74	1901	16.99	A	1928	5.10	S	-43
62503	25	HEATER, PORT 1	2.00	6.24	12	E	16.79	311	19.24	A	356	6.83	P	85
62503	26	HEATER, PORT 2	2.00	6.24	12	E	16.79	765	24.50	A	1116	6.83	P	85
62503	27	HEATER, PORT 3	2.00	6.24	12	E	16.79	765	27.50	A	1252	6.83	P	85
62503	28	HEATER, PORT 4	2.00	7.11	14	E	16.79	535	30.13	A	960	6.83	P	97
62503	29	HEATER, STARBOARD 1	2.00	4.26	9	E	16.79	311	19.24	A	356	6.83	S	-58
62503	30	HEATER, STARBOARD 2	2.00	6.24	12	E	16.79	765	24.50	A	1116	6.83	S	-85
62503	31	HEATER, STARBOARD 3	2.00	6.24	12	E	16.79	765	27.50	A	1252	6.83	S	-85
62503	32	HEATER, STARBOARD 4	2.00	6.24	12	E	16.79	535	30.13	A	960	6.83	S	-85
62503	33	HEATER, BACK PORT	2.00	7.11	14	E	16.74	635	35.51	A	1348	2.88	P	41
62503	34	HEATER, BACK STARBOARD	2.00	7.11	14	E	16.74	2132	35.51	A	4522	1.21	S	-17

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT lb	NO. UNITS #	CURRENT WEIGHT lb	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG ft	MOMENT ft*lb	LCG ft	S	MOMENT ft*lb	TCG ft	S	MOMENT ft*lb
63101	1	PAINT	1528.07	1.00	1528	C	6.56	10026	32.21	A	49220	0.00	C	0
63301	1	CATHODIC PROTECTION	300.00	1.00	300	E	3.00	900	32.40	A	9720	0.00	C	0
63401	1	POLYVINAL CHLORIDE SHEETING, MIL-M-15562-F TYPE I, 0.125" THICK	1.00	63.71	64	C	3.50	223	10.00	A	637	0.00	C	0
63401	2	POLYVINAL CHLORIDE SHEETING, MIL-M-15562-F TYPE I, 0.125" THICK	1.00	138.60	139	C	3.50	485	17.91	A	2482	0.00	C	0
63401	3	POLYVINAL CHLORIDE SHEETING, MIL-M-15562-F TYPE I, 0.125" THICK	1.00	50.11	50	C	3.50	175	22.80	A	1143	5.53	S	-277
63401	4	POLYVINAL CHLORIDE SHEETING, MIL-M-15562-F TYPE I, 0.125" THICK	1.00	50.11	50	C	3.50	175	22.80	A	1143	5.53	P	277
63401	5	POLYVINAL CHLORIDE SHEETING, MIL-M-15562-F TYPE I, 0.125" THICK	1.00	30.00	30	C	3.50	105	30.50	A	915	0.00	C	0
63401	6	POLYVINAL CHLORIDE SHEETING, MIL-M-15562-F TYPE I, 0.125" THICK	1.00	199.08	199	C	12.54	2496	26.25	A	5226	0.18	S	-36
63401														
63402	7	POLYVINAL CHLORIDE SHEETING, MIL-M-15562-F TYPE III, 0.187" THICK	1.50	59.58	89	C	3.50	312	30.50	A	2718	4.98	S	-444
63402														
63403	8	BASE, WALL, VINYL, 0.08" GAUGE, 4"	0.26	72.07	19	C	12.54	235	26.25	A	492	0.18	S	-3
63403														
63404	9	MAT, FLOOR, STANDING, UNICELLUAR FOAM BASE, 30" X 60" X 1/2"	23.00	1.00	23	C	12.54	288	32.09	A	738	1.16	S	-27
63404														
63405	10	MAT, FLOOR, STANDING, UNICELLUAR FOAM BASE, 30" X 36" X 1/2"	13.80	2.00	28	C	12.54	346	21.07	A	581	0.00	C	0
63405														
63406	11	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	4.00	2	C	9.00	18	37.36	A	75	0.00	C	0
63406	12	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	4.00	2	C	9.00	18	39.08	A	78	0.00	C	0
63406	13	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	2.00	1	C	9.00	9	47.36	A	47	9.02	S	-9
63406	14	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	2.00	1	C	9.00	9	56.35	A	56	0.00	C	0
63406	15	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	4.00	2	C	9.00	18	51.34	A	103	6.96	S	-14
63406	16	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	4.00	2	C	9.00	18	60.42	A	121	0.00	C	0
63406	17	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	4.00	2	C	11.05	22	22.00	A	44	0.00	C	0
63406	18	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	4.00	2	C	11.15	22	11.50	A	23	2.78	S	-6
63406	19	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	2.00	1	C	11.17	11	4.26	A	4	1.74	S	-2
63406	20	SAFETY WALK, NON-SLIP FABRIC CLEATS, TYPE "B" MED, GRIT, 6" X 24", MIL-D-17951	0.50	2.00	1	C	9.00	9	38.14	A	38	3.25	P	3
63406														
63407	21	DECK COVERING, ONE-STEP, SEAMLESS, EPOXY BASE, MIL-D-24613 TYPE III	0.04	35.44	1	C	3.50	4	28.68	A	37	5.50	S	-7
63407	22	DECK COVERING, ONE-STEP, SEAMLESS, EPOXY BASE, MIL-D-24613 TYPE III	0.04	24.14	1	C	3.50	3	33.18	A	29	5.50	S	-5
63407														
63408	23	TAPE, ELECTRIC, DOUBLE SIDED, 4" X 20 MIL	0.11	31.24	3	C	3.50	12	30.50	A	105	4.98	P	17
63408														
63409	24	FUSION STRIP, WITH ITEM 1, 500 FT ROLL	0.01	35.18	0	C	3.50	1	10.00	A	2	0.00	C	0
63409	25	FUSION STRIP, WITH ITEM 1, 500 FT ROLL	0.01	58.28	0	C	3.50	1	17.91	A	5	0.00	C	0
63409	26	FUSION STRIP, WITH ITEM 1, 500 FT ROLL	0.01	28.31	0	C	3.50	1	22.80	A	3	5.53	P	1
63409	27	FUSION STRIP, WITH ITEM 1, 500 FT ROLL	0.01	28.31	0	C	3.50	1	22.80	A	3	5.53	S	-1
63409	28	FUSION STRIP, WITH ITEM 1, 500 FT ROLL	0.01	24.67	0	C	3.50	0	30.50	A	4	0.00	C	0
63409	29	FUSION STRIP, WITH ITEM 1, 500 FT ROLL	0.01	72.07	0	C	12.54	5	26.25	A	10	0.18	S	0
63409								0			0			0
63410	30	SEALER, WITH ITEM 8, EPOXY TYPE	0.04	35.44	1	C	3.50	4	28.68	A	37	5.50	S	-7
63410	31	SEALER, WITH ITEM 8, EPOXY TYPE	0.04	24.14	1	C	3.50	3	33.18	A	29	5.50	S	-5
63410														
63501	1	THERMAL INSULATION	1058.00	1.00	1058	C	9.10	9628	28.82	A	30492	0.02	P	21
63501														

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT lb	NO. UNITS #	CURRENT WEIGHT lb	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG ft	MOMENT ft*lb	LCG ft	S	MOMENT ft*lb	TCG ft	S	MOMENT ft*lb
63502	2	FIRE PROTECTION	1992.00	1.00	1992	C	7.93	15797	33.16	A	66055	0.01	P	20
63502														
63503	3	ACOUSTIC INSULATION	192.13	1.00	192	C	7.48	1438	35.00	A	6725	0.00	C	0
63503														
63504	4	FASTENERS, SECUREMENT, INSULATION STOP	1000.00	1.00	1000	C	8.53	8530	31.97	A	31970	0.05	P	50
63701	1	SHEATHING	696.00	1.00	696	C	9.39	6535	33.37	A	23226	0.06	S	-42
64101	1	PORT BERTHING BUNKS	300.00	1.00	300	C	7.18	2153	22.66	A	6799	8.10	P	2430
64101	2	PORT BERTHING LOCKERS (2)	62.00	2.00	124	C	6.77	840	20.71	A	2567	2.87	P	356
64101	3	STBD BERTHING BUNKS	300.00	1.00	300	C	7.18	2153	22.67	A	6800	8.05	S	-2416
64101	4	STBD BERTHING LOCKERS (2)	62.00	2.00	124	C	6.77	840	20.65	A	2560	4.62	S	-573
64201	1	FWD BERTHING BUNKS (4)	700.00	1.00	700	C	7.29	5100	9.69	A	6781	0.00	C	0
64202	2	CREW BERTHING LOCKERS (4)	62.00	4.00	248	C	6.51	1615	5.07	A	1256	0.00	C	0
64302	1	B-3F-1 BENCH W/ BACKREST, STOWAGE UNDER	301.00	1.00	301	C	5.28	1591	18.67	A	5620	5.72	P	1721
64302	2	B-3F-1 BENCH W/ BACKREST, STOWAGE UNDER	301.00	1.00	301	C	5.28	1591	13.85	A	4170	5.48	P	1649
64302	3	B-4B-2 TABLE, MESS, CREW	90.00	1.00	90	C	6.08	547	16.25	A	1462	5.54	P	499
64401	1	LAVATORY UNIT, SINK B-2A-2 (LARGE HEAD)	43.10	1.00	43	C	5.65	244	27.04	A	1165	2.34	S	-101
64401	2	LAVATORY UNIT, SINK B-2A-2 (SMALL HEAD)	43.10	1.00	43	C	5.65	244	34.28	A	1477	4.62	S	-199
64401														
64402	3	TOILET (LARGE HEAD)	30.00	1.00	30	C	3.86	116	27.29	A	819	7.11	S	-213
64402	4	TOILET (SMALL HEAD)	30.00	1.00	30	C	3.86	116	32.61	A	978	7.11	S	-213
65101	1	GALLEY EQUIP, CABINET, COUNTERTOP, FIDGE & OVERHEAD CAB	950.00	1.00	950	C	6.52	6197	16.48	A	15651	5.56	S	-5282
65101														
65102	2	ENTERTAINMENT RACK	97.00	1.00	97	C	9.03	876	16.02	A	1554	9.21	P	894
65102														
65103	3	MESS OVERHEAD STOWAGE	90.00	1.00	90	C	9.19	827	13.70	A	1233	6.38	P	574
65201	1	MEDICAL SPACES	22.40	1.00	22		9.31	209	32.40	A	726	0.00	C	0
66101	1	CHART TABLE B-4D-6 28W X 36D X 36.75H (DECKHOUSE)	125.00	1.00	125	C	14.39	1799	27.03	A	3378	4.93	S	-617
66101														
66102	2	B-3F-1 BENCH W/ BACKREST, STOWAGE UNDER	301.00	1.00	301	C	13.63	4101	30.08	A	9055	3.26	P	982
66102														
66103	3	B-3F-2 BENCHES WITH STOWAGE UNDER, PADDED	56.00	2.00	112	C	13.37	1498	26.01	A	2913	3.70	P	414
66103														
66104	4	B-4B-2 TABLE, MESS, CREW	90.00	1.00	90	C	15.07	1357	27.80	A	2502	3.96	P	357
66104														
66105	5	HELMSMAN CHAIR	75.00	2.00	150	C	15.14	2271	21.34	A	3202	0.00	C	0
66501	1	WORKSHOP WORKBENCH AND LOCKERS (DECONTAMINATION SPACE)	400.00	1.00	400	C	6.77	2709	31.20	A	12480	7.33	P	2933
67101	1	CHAIN STOWAGE BIN & STOWAGE BOX	100.00	1.00	100	C	6.54	654	54.29	A	5429	8.17	S	-817
67101														

SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	E C A	VERTICAL		LONGITUDINAL			TRANSVERSE		
							VCG	MOMENT	LCG	S	MOMENT	TCG	S	MOMENT
			lb	#	lb		ft	ft*lb	ft		ft*lb	ft		ft*lb
67102	2	WC STORAGE	35.00	1.00	35	C	6.77	237	30.76	A	1077	5.04	S	-176
67102														
67103	3	MAIN DECK STOWAGE FWD	94.00	1.00	94	C	12.29	1155	16.75	A	1574	4.45	S	-418
67103														
67104	4	MAIN DECK STOWAGE AFT PORT	94.00	1.00	94	C	10.26	965	40.05	A	3764	9.24	P	868
67104														
67105	5	MAIN DECK STOWAGE AFT STBD	94.00	1.00	94	C	10.24	963	40.01	A	3761	9.24	S	-868
67105														
67106	6	HEAD STORAGE	35.00	1.00	35	C	6.77	237	34.44	A	1205	7.76	S	-272
69901		OUTFIT AND FURNISHING PARTS AND SPECIAL TOOLS	784.00	1.00	784		6.98	5472	32.40	A	25402	0.00	C	0

Departure W/ AtoN Load													
SWBS #	ITEM	DESCRIPTION	UNIT	NO.	CURRENT	Vertical		Longitudinal			Transverse		
			WEIGHT	UNITS	WEIGHT	VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
			lb	#	lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
A1301	1	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.68	A	4770	5.48	P	1206.516667
A1301	2	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.66	A	4764	6.34	S	-1394.25
A1301	3	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	4	880	6.90	6071	7.38	A	6491	0.00	C	0
A2901					0		0			0			0
A3101	1	DRY PROVISIONS	107	1	107	9.603	1028	15.289	A	1637	7.610504	S	-814.6283116
A3102	2	CHILL PROVISIONS	55	1	55	4.500	248	14.064	A	777	2.749858	S	-151.8495745
A3103	3	FREEZE PROVISIONS	54	1	54	6.500	354	14.064	A	766	2.749858	S	-149.6802666
A32	1	GENERAL STORES	1750	1	1750	6.760	11830	8.500	A	14875	0	C	0
A4101	1	DIESEL TANK	11179	1	11179	1.880	21017	30.460	A	340512	0	C	0
A4101	2	DIESEL TANK	5027	1	5027	2.400	12065	30.460	A	153122	6.42	P	32273.34
A4101	3	DIESEL TANK	5001	1	5001	2.400	12002	30.460	A	152330	6.42	S	-32106.42
A4301	1		0	1	0		0			0			0
A4601	1		0	1	0		0			0			0
A51	1	BALLAST WATER	0	1	0		0			0			0
A5201	1	POTABLE WATER	4080	1	4080	7.460	30437	30.440	A	124195	7.46	P	30436.8
A5201	2	POTABLE WATER	4080	1	4080	7.460	30437	30.440	A	124195	7.46	S	-30436.8
A5401	1	HYDRAULIC FLUID	1400	1	1400	3.951	5532	50.926	A	71296	0	C	0
A5501	1	BLACK WATER	44	1	44	0.640	28	24.570	A	1081	0	C	0
A5502	2	GREY WATER	445	1	445	0.800	356	18.730	A	8335	0	C	0
A62					0		0			0			0
A69	1	5X11 BUOY	3000	2	6000	12.000	72000	51.000	A	306000	0	C	0
A69	2	BUOY BRIDLE	120	2	240	9.200	2208	43.000	A	10320	0	C	0
A69	3	MOORING CHAIN	1050	2	2100	11.300	23730	43.000	A	90300	0	C	0
A69	4	SINKER	4000	2	8000	9.800	78400	43.000	A	344000	0	C	0

Departure W/O AtoN Load													
SWBS #	ITEM	DESCRIPTION	UNIT	NO.	CURRENT	Vertical		Longitudinal			Transverse		
			WEIGHT	UNITS	WEIGHT	VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
			lb	#	lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
A1301	1	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.68	A	4770	5.48	P	1206.516667
A1301	2	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.66	A	4764	6.34	S	-1394.25
A1301	3	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	4	880	6.90	6071	7.38	A	6491	0.00	C	0
B2901					0		0			0			0
B3101	1	DRY PROVISIONS	107	1	107	9.603	1028	15.289	A	1637	7.610504	S	-814.6283116
B3102	2	CHILL PROVISIONS	55	1	55	4.500	248	14.064	A	777	2.749858	S	-151.8495745
B3103	3	FREEZE PROVISIONS	54	1	54	6.500	354	14.064	A	766	2.749858	S	-149.6802666
B32	1	GENERAL STORES	1750	1	1750	6.760	11830	8.500	A	14875	0	C	0
B4101	1	DIESEL TANK	11179	1	11179	1.880	21017	30.460	A	340512	0	C	0
B4101	2	DIESEL TANK	5027	1	5027	2.400	12065	30.460	A	153122	6.42	P	32273.34
B4101	3	DIESEL TANK	5001	1	5001	2.400	12002	30.460	A	152330	6.42	S	-32106.42
B4301	1		0	1	0		0			0			0
B4601	1		0	1	0		0			0			0
B51	1	BALLAST WATER	0	1	0		0			0			0
B5201	1	POTABLE WATER	4080	1	4080	7.46	30436.8	30.44	A	124195	7.46	P	30436.8
B5201	2	POTABLE WATER	4080	1	4080	7.46	30436.8	30.44	A	124195	7.46	S	-30436.8
B5401	1	HYDRAULIC FLUID	1400	1	1400	3.951	5532	50.926	A	71296	0	C	0
B5501	1	BLACK WATER	44	1	44	0.640	28	24.570	A	1081	0	C	0
B5502	2	GREY WATER	445	1	445	0.800	356	18.730	A	8335	0	C	0
B62					0		0			0			0
B69	1	5X11 BUOY	3000	0	0	12.000	0	51.000	A	0			0
B69	2	BUOY BRIDLE	120	0	0	9.200	0	43.000	A	0			0
B69	3	MOORING CHAIN	1050	0	0	11.300	0	43.000	A	0			0
B69	4	SINKER	4000	0	0	9.800	0	43.000	A	0			0
					0		0			0			0

Mid W/ AtoN													
SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	Vertical		Longitudinal			Transverse		
			lb	#	lb	VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
						ft	ft*lb	ft		ft*lb	ft	S	ft*lb
A1301	1	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.68	A	4770	5.48	P	1206.516667
A1301	2	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.66	A	4764	6.34	S	-1394.25
A1301	3	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	4	880	6.90	6071	7.38	A	6491	0.00	C	0
C2901					0		0			0			0
C3101	1	DRY PROVISIONS	107	1	107	9.603	1028	15.289	A	1637	7.610504	S	-814.6283116
C3102	2	CHILL PROVISIONS	55	1	55	4.500	248	14.064	A	777	2.749858	S	-151.8495745
C3103	3	FREEZE PROVISIONS	54	1	54	6.500	354	14.064	A	766	2.749858	S	-149.6802666
C32	1	GENERAL STORES	1750	1	1750	6.760	11830	8.500	A	14875	0	C	0
C4101	1	DIESEL TANK	5883	1	5883	1.180	6942	30.440	A	179079	0	C	0
C4101	2	DIESEL TANK	2646	0.5	1323	1.900	2514	30.450	A	40285	6.15	P	8136.45
C4101	3	DIESEL TANK	2632	0.5	1316	1.900	2500	30.450	A	40072	6.15	S	-8093.4
C4301	1		0	1	0		0			0			0
C4601	1		0	1	0		0			0			0
C51	1	BALLAST WATER	0	1	0		0			0			0
C5201	1	POTABLE WATER	2147	1	2147	6.04	12967.88	30.41	A	65290.27	6.04	P	12967.88
C5201	2	POTABLE WATER	2147	1	2147	6.04	12967.88	30.41	A	65290.27	6.04	S	-12967.88
C5401	1	HYDRAULIC FLUID	1400	1	1400	3.951	5532	50.926	A	71296	0	C	0
C5501	1	BLACK WATER	436	1	436	1.240	541	24.580	A	10717	0	C	0
C5502	2	GREY WATER	4447	1	4447	1.540	6848	18.670	A	83025	0	C	0
C62					0		0			0			0
C69	1	5X11 BUOY	3000	2	6000	12.000	72000	51.000	A	306000			0
C69	2	BUOY BRIDLE	120	2	240	9.200	2208	43.000	A	10320			0
C69	3	MOORING CHAIN	1050	2	2100	11.300	23730	43.000	A	90300			0
C69	4	SINKER	4000	2	8000	9.800	78400	43.000	A	344000			0
					0		0			0			0

Mid W/O AtoN													
SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	Vertical		Longitudinal			Transverse		
			lb	#	lb	VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/ S	TMOM
						ft	ft*lb	ft		ft*lb	ft		ft*lb
A1301	1	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.68	A	4770	5.48	P	1206.516667
A1301	2	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.66	A	4764	6.34	S	-1394.25
A1301	3	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	4	880	6.90	6071	7.38	A	6491	0.00	C	0
D2901					0		0			0			0
D3101	1	DRY PROVISIONS	107	1	107	9.603	1028	15.289	A	1637	7.610504	S	-814.6283116
D3102	2	CHILL PROVISIONS	55	1	55	4.500	248	14.064	A	777	2.749858	S	-151.8495745
D3103	3	FREEZE PROVISIONS	54	1	54	6.500	354	14.064	A	766	2.749858	S	-149.6802666
D32	1	GENERAL STORES	1750	1	1750	6.760	11830	8.500	A	14875	0	C	0
D4101	1	DIESEL TANK	5883	1	5883	1.180	6942	30.440	A	179079	0	C	0
D4101	2	DIESEL TANK	2646	0.5	1323	1.900	2514	30.450	A	40285	6.15	P	8136.45
D4101	3	DIESEL TANK	2632	0.5	1316	1.900	2500	30.450	A	40072	6.15	S	-8093.4
D4301	1		0	1	0		0			0			0
D4601	1		0	1	0		0			0			0
D51	1	BALLAST WATER	0	1	0		0			0			0
D5201	1	POTABLE WATER	2147	1	2147	6.04	12967.88	30.41	A	65290.27	6.04	P	12967.88
D5201	2	POTABLE WATER	2147	1	2147	6.04	12967.88	30.41	A	65290.27	6.04	S	-12967.88
D5401	1	HYDRAULIC FLUID	1400	1	1400	3.951	5532	50.926	A	71296	0	C	0
D5501	1	BLACK WATER	436	1	436	1.240	541	24.580	A	10717	0	C	0
D5502	2	GREY WATER	4447	1	4447	1.540	6848	18.670	A	83025	0	C	0
D62					0		0			0			0
D69	1	5X11 BUOY	3000	0	0	12.000	0	51.000	A	0			0
D69	2	BUOY BRIDLE	120	0	0	9.200	0	43.000	A	0			0
D69	3	MOORING CHAIN	1050	0	0	11.300	0	43.000	A	0			0
D69	4	SINKER	4000	0	0	9.800	0	43.000	A	0			0
					0		0			0			0

Min-Op W/ AtoN													
SWBS #	ITEM	DESCRIPTION	UNIT WEIGHT	NO. UNITS	CURRENT WEIGHT	Vertical		Longitudinal			Transverse		
			lb	#	lb	VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/ S	TMOM
						ft	ft*lb	ft		ft*lb	ft		ft*lb
A1301	1	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.68	A	4770	5.48	P	1206.516667
A1301	2	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.66	A	4764	6.34	S	-1394.25
A1301	3	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	4	880	6.90	6071	7.38	A	6491	0.00	C	0
E2901					0		0			0			0
E3101	1	DRY PROVISIONS	107	1	107	9.603	1028	15.289	A	1637	7.610504	S	-814.6283116
E3102	2	CHILL PROVISIONS	55	1	55	4.500	248	14.064	A	777	2.749858	S	-151.8495745
E3103	3	FREEZE PROVISIONS	54	1	54	6.500	354	14.064	A	766	2.749858	S	-149.6802666
E32	1	GENERAL STORES	1750	1	1750	6.760	11830	8.500	A	14875	0	C	0
E4101	1	DIESEL TANK	1177	1	1177	0.490	577	30.220	A	35569	0	C	0
E4101	2	DIESEL TANK	530	1	530	1.320	700	30.330	A	16075	5.09	P	2697.7
E4101	3	DIESEL TANK	527	1	527	1.320	696	30.320	A	30	5.09	S	-2682.43
E4301	1		0	1	0		0			0			0
E4601	1		0	1	0		0			0			0
E51	1	BALLAST WATER	0	1	0		0			0			0
E5201	1	POTABLE WATER	215	1	215	4.33	930.95	30.15	A	6482.25	8.94	P	1922.1
E5201	2	POTABLE WATER	215	1	215	4.33	930.95	30.15	A	6482.25	8.94	S	-1922.1
E5401	1	HYDRAULIC FLUID	1400	1	1400	3.951	5532	50.926	A	71296	0	C	0
E5501	1	BLACK WATER	828	1	828	1.790	1482	24.590	A	20361	0	C	0
E5502	2	GREY WATER	8448	1	8448	2.020	17065	18.500	A	156288	0	C	0
E62					0		0			0			0
E69	1	5X11 BUOY	3000	2	6000	12.000	72000	51.000	A	306000			0
E69	2	BUOY BRIDLE	120	2	240	9.200	2208	43.000	A	10320			0
E69	3	MOORING CHAIN	1050	2	2100	11.300	23730	43.000	A	90300			0
E69	4	SINKER	4000	2	8000	9.800	78400	43.000	A	344000			0
					0		0			0			0

Min-Op W/O AtoN													
SWBS #	ITEM	DESCRIPTION	UNIT	NO.	CURRENT	Vertical		Longitudinal			Transverse		
			WEIGHT	UNITS	WEIGHT	VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
			lb	#	lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
A1301	1	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.68	A	4770	5.48	P	1206.516667
A1301	2	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	1	220	6.97	1534	21.66	A	4764	6.34	S	-1394.25
A1301	3	ENLISTED WEIGHT AND PERSONAL EFFECTS	220	4	880	6.90	6071	7.38	A	6491	0.00	C	0
F2901					0		0			0			0
F3101	1	DRY PROVISIONS	107	1	107	9.603	1028	15.289	A	1637	7.610504	S	-814.6283116
F3102	2	CHILL PROVISIONS	55	1	55	4.500	248	14.064	A	777	2.749858	S	-151.8495745
F3103	3	FREEZE PROVISIONS	54	1	54	6.500	354	14.064	A	766	2.749858	S	-149.6802666
F32	1	GENERAL STORES	1750	1	1750	6.760	11830	8.500	A	14875	0	C	0
F4101	1	DIESEL TANK	1177	1	1177	0.490	577	30.220	A	35569	0	C	0
F4101	2	DIESEL TANK	530	1	530	1.320	700	30.330	A	16075	5.09	P	2697.7
F4101	3	DIESEL TANK	527	1	527	1.320	696	30.320	A	30	5.09	S	-2682.43
F4301	1		0	1	0		0			0			0
F4601	1		0	1	0		0			0			0
F51	1	BALLAST WATER	0	1	0		0			0			0
F5201	1	POTABLE WATER	215	1	215	4.33	930.95	30.15	A	6482.25	8.94	P	1922.1
F5201	2	POTABLE WATER	215	1	215	4.33	930.95	30.15	A	6482.25	8.94	S	-1922.1
F5401	1	HYDRAULIC FLUID	1400	1	1400	3.951	5532	50.926	A	71296	0	C	0
F5501	1	BLACK WATER	828	1	828	1.790	1482	24.590	A	20361	0	C	0
F5502	2	GREY WATER	8448	1	8448	2.020	17065	18.500	A	156288	0	C	0
F62					0		0			0			0
F69	1	5X11 BUOY	3000	0	0	12.000	0	51.000	A	0			0
F69	2	BUOY BRIDLE	120	0	0	9.200	0	43.000	A	0			0
F69	3	MOORING CHAIN	1050	0	0	11.300	0	43.000	A	0			0
F69	4	SINKER	4000	0	0	9.800	0	43.000	A	0			0
					0		0			0			0

SWBS #	SWBS Name	Applied Weight	Vertical		Longitudinal			Transverse		
			VCG ABL	VMOM	LCG	F/A	LMOM	TCG	P/C/	TMOM
		lb	ft	ft*lb	ft		ft*lb	ft	S	ft*lb
	Light Ship, No Margins	182643	7.46	1362512	34.56	A	6311343	0.01	P	2206.899
	Design Margin									
M11	Design Margin Weight (10.3%)	18810	7.46	140325	34.56	A	650005	0.01	S	227.289
M11	Design Margin KG (5.0%)		0.37							
	Construction Margin									
M21	Construction Margin Weight (5.0%)	9132	7.46	68126	34.56	A	315567	0.01	S	110.345
M21	Construction Margin KG (3.0%)		0.22							
	Contract Modification									
M31	Contract Modification Weight (0.7%)	1279	7.46	9538	34.56	A	44179	0.01	S	15.448
M31	Contract Modification KG (0.5%)		0.04							
	Government Furnished Equipment									
M41	Government Furnished Equipment Weight (0.3%)	548	7.46	4088	34.56	A	18934	0.01	S	6.621
M41	Government Furnished Equipment KG (0.2%)		0.01							
M	Margins	29769	12.09	359935	34.56	A	1028686	0.01	S	359.702
	Light Ship Condition	212412	8.11	1722447	34.56	A	7340029	0.01	S	2566.601