

[illegible]

Section A - Solicitation/Contract Form

6022ZN01 and 6022ZN02 Pure Water Tanks

Section B - Supplies or Services & Prices or Costs

Additional Information/Notes

Item	Supplies/Service	Quantity	Unit	Unit Price	Amount
0001	PURE WATER TANK, 800 GALLON, MANUFACTURED IN ACCORDANCE WITH ATTACHEMENT (A) SOW SPECIFICATIONS CERTIFICATIONS REQUIRED PER ATTACHMENT (B) NOTE: The requirements in DFARS 252.211-7003, Item Identification and Valuation, are applicable for this line item. The contractor shall provide DoD unique identification or a DoD recognized unique identification equivalent. Pricing Arrangement: Firm Fixed Price	1	Each		
0002	PURE WATER TANK 800 GALLON, MANUFACTURED IN ACCORDANCE WITH ATTACHEMENT (A) SOW SPECIFICATIONS CERTIFICATIONS REQUIRED PER ATTACHMENT (B) NOTE: The requirements in DFARS 252.211-7003, Item Identification and Valuation, are applicable for this line item. The contractor shall provide DoD unique identification or a DoD recognized unique identification equivalent. Pricing Arrangement: Firm Fixed Price	1	Each		

Section C - Description/Specifications/Statement of Work

Extended Description

Clin 0001 -0002 - Extended Description

**PURE WATER TANK, (2)
800 GALLON,
MANUFACTURED IN ACCORDANCE WITH ATTACHEMENT (A) SOW SPECIFICATIONS
CERTIFICATIONS REQUIRED PER ATTACHMENT (B)
CERTIFICATE OF COMPLIANCE REQUIRED
MERCURY FREE CLAUSE INVOKED**

STATEMENT OF WORK

SPECIFICATION FOR PROCUREMENT OF 800 GALLON PURE WATER TANK

JML REFERENCE: 6022ZN01-ZN02

1. **SCOPE:** Provide an eight hundred (800) Gallon Stainless Steel low pressure horizontally oriented cylindrical tank with elliptical end caps. Tank assembly will include tank saddle with integral lift lugs (tank & saddle) and fork lift tubes within the saddle base. Tank assembly shall be outfitted with continuous level & temperature indication, along with service connections detailed within this statement of work (inlet, outlet, vent, sample, nitrogen supply, etc.). Overall tank height and dimensions shall allow placement within a standard width and height Conex box/Sealand container.

2. **REFERENCES:**

- 2.1 ASME Boiler and Pressure Vessel Code, Section VIII Division 1
- 2.2 MIL-STD-2041, Control of Detrimental Materials
- 2.3 MIL-STD-767, Control of Hardware Cleanliness
- 2.4 ASME Boiler and Pressure Vessel Code, Section II Part A (Material Specification SA-240)
- 2.5 ASTM A500, Standard Specification for Cold-formed Welded and Seamless Carbon Steel Structural Tubing in Rounds and Shapes.
- 2.6 ASTM A36, Standard Specification for Carbon Structural Steel.
- 2.7 ASTM A240/A240M, Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels.
- 2.8 ASTM A276/A276M, Standard Specification for Stainless Steel Bars and Shapes
- 2.9 ASTM A511/A511M, Standard Specification for Seamless Stainless-Steel Mechanical

Tubing and Hollow Bar.

2.10 MIL-PRF-23236, Coating Systems for Ship Structures

2.11 A-A-59326D, Coupling Halves, Quick-Disconnect, Dam-Locking Type, General Specification Form.

2.12 ASME B16.5 Pipe Flanges and Flange Fittings

2.13 ASTM A312, Standard Specification for Seamless, Welded, and Heavily Cold Worked Austenitic Stainless-Steel Pipes

2.14 ASME B16.9 Factory-Made Wrought Buttwelding Fittings

2.15 ANSI N14.6-1993, Special Lifting Devices for Shipping Containers Weighing 10000 Pounds (4500 kg) or More.

2.16 NAVSEA Technical Publication T9074-AS-GIB-010/271, Requirements for nondestructive Testing Methods.

2.17 MIL-STD-2035A, Non-Destructive Testing Acceptance Criteria.

2.18 ASTM A967/A967M, Standard Specification for Chemical Passivation Treatments for Stainless Steel Parts.

2.19 SAE J514, Hydraulic Tube Fittings

2.20 AWS D1.1, Structural Welding Code - Steel

2.21 AWS D1.2, Structural Welding Code - Aluminum

2.22 AWS D1.6, Structural Welding Code - Stainless Steel

2.23 MIL-STD-22, Welded Joint Design

3. GENERAL REQUIREMENTS:

3.1 Where specifications and/or standards are specified or referenced, the latest revision shall be used unless otherwise specified.

3.2 Tank design, fabrication and testing shall be in accordance with reference 2.1. Tank shall be stamped with the code "U" symbol.

3.3 Formal NNSY approval, via signature, of tank assembly drawings, with material list(s), shall be obtained prior to beginning fabrication.

3.4 All internal and/or fluid contacting surfaces/materials of the tank assembly (tank body, end caps, piping, etc.) and its components (e.g., valves, level/temperature transmitter assembly, etc).

shall meet detrimental material and cleanliness requirements of references 2.2 and 2.3.

3.4.1 Interior tank and piping surfaces (i.e., fluid contacting surfaces) shall be cleaned to remove debris, foreign materials, markings, corrosion, weld spatter, paint, preservatives, oils, greases, lubricates, etc. in accordance with requirements of reference 2.3.

3.4.2 All lubricants for component operation (valve, fittings, etc.) or shop assembly shall meet detrimental material requirements of reference 2.2 or be completely removed per 3.4.1.

3.4.3 All Lubricants used for moving parts within valves/fittings/components shall be formally authorized and agreed to, via signature, between NNSY and the vendor.

3.5 All equipment/components furnished shall NOT contain mercury. In addition, equipment/components furnished shall NOT have come into direct contact with mercury or mercury containing components during fabrication or testing.

3.6 Tank shell/body and elliptical end caps shall be stainless steel, Grade 316 (Reference 2.4 or equivalent).

3.7 Tank assembly saddle, lift lugs, base with forklift tubes and framing for process meter enclosure mounting shall be fabricated from carbon steel (references 2.5, 2.6 or equivalent) or grade 304/316 stainless steel (references 2.7, 2.8, 2.9 or equivalent).

3.8 Coating systems (i.e., paints and primers) used on carbon steel structural/framing components shall be non-hazardous per Resource Conservation and Recovery Act (RCRA) requirements.

3.8.1 Norfolk Naval Shipyard (NNSY) shall approve coating system, via signature, prior to coating system use/application. Coating systems per reference 2.10 are approved for use.

3.8.2 Prohibited colors are yellow, magenta, purple, gold, red and orange.

3.9 Markings (e.g., weight, lift points, serial numbers, etc.), when referenced to this paragraph, shall be made using 1-inch-tall letters and highly contrasting color paint (e.g., black frame with white lettering). Label plates/placards made using Gravotech Gravoply, or equivalent poly/composite material providing high contrast (e.g., black background with white lettering) may be used for marking on stainless steel structures and components.

3.10 The use of cadmium plated components/fittings is prohibited.

3.11 The use of brass/bronze components or fittings is prohibited. Any use of brass/bronze

components or fittings shall be formally authorized and agreed to, via signature, between NNSY and the vendor.

3.12 Teflon tape or any type of thread sealant/locker shall NOT be used on any fluid contacting components (e.g., NPT Joints, etc.) unless formally authorized and agreed to, via signature, between NNSY and the vendor. Loctite 5772 is an authorized thread sealant/locker which may be used on fluid contacting components.

3.13 All Camlock fittings shall be stainless steel and meet requirements of reference 2.11. Rings and pins on camlock arms shall NOT be cadmium plated.

3.14 All Flanges shall be stainless steel (grade 316), raised face with weld neck ends for connection to piping per reference 2.12.

3.15 All piping assembly end fittings (open end of assembly for connecting temporary equipment/systems) shall be provided with a mechanical cap/blank installed (i.e., SAE J514 flare cap, blind flange, union blank) as applicable.

3.15.1 All Camlock closure dust caps shall be Dixon Cam and Groove EZ-Link armless dust caps. Caps shall be installed on all pipe assembly ends containing male Camlock adapters.

3.15.2 All mechanical caps/blanks shall be attached to their respective piping assembly via lanyard (stainless steel braided wire (1/16 - 1/8-inch diameter) and Nico press sleeving). Flange blanks are not required to be attached via lanyard.

3.16 All piping shall be seamless stainless steel (grade 316) in accordance with reference 2.13. Minimum pipe schedule allowed is SCH 40.

3.17 All pipe fittings shall be stainless steel (grade 316) butt weld end prep per reference 2.14, unless otherwise specified in this statement of work or authorized by NNSY.

3.18 Valves shall be three-piece stainless steel (grade 316) full port ball valves with butt weld ends. Seats, seals and packing shall be PTFE. All valves shall be Swagelok 60 series or Bray 7000/8000 series, with locking lever handles, meeting component design pressures.

3.19 TANK ASSEMBLY /OPERATING PRESSURES, FLOWRATES & TEMPERATURE REQUIREMENTS ARE AS SPECIFIED BELOW:

3.19.1 Design pressure: 30 psig.

3.19.2 Vacuum pressure, design: 29 inches Hg/full vacuum.

3.19.3 Normal operating pressure: 20 psig maximum.

3.19.4 Flowrate via low point suction connections: 60 GPM.

3.19.5 Design temperature is -20 Fahrenheit to 120 Fahrenheit ambient outside air temperature.

Fluid will be at ambient temperature (e.g., typically 50 Fahrenheit or greater with freeze protection).

3.20 Overall tank dimensions shall allow tank to be located within a standard Conex/Sealand container. Dimensions on one end of the tank assembly (height and width) shall allow it to pass through a standard Conex/Sealand container door opening (width - 92 inches, height -89 inches).

3.21 Use of the following during preparation and fabrication of the tank is prohibited.

3.21.1 Oil or other cutting fluids.

3.21.2 Metal removal or finishing tools made of materials which may cross contaminate surfaces or cause surface corrosion staining of stainless-steel surface, when exposed to water or a moist atmosphere.

3.21.3 Power driven tools or wire brushes that tend to smear metal.

3.21.4 Tools or abrasive materials which have previously been used on low alloy steels, aluminum, lead or other low melting point materials.

3.22 All testing requiring liquid supplied to the tank and piping internals shall be performed using deionized water.

3.23 Vendor shall provide NNSY representative(s) the opportunity to perform an inspection of the accessible internal and external surfaces of the tank assembly. NNSY reserves the right to witness fabrication and testing of the tank assembly.

4. TANK ASSEMBLY BASE PLATE, FRAMING & SADDLE:

4.1 Tank assembly, saddle and any support component mounting frames (i.e., process meter enclosure, power box) shall be built on a main assembly base plate/frame.

4.2 Base plate/frame shall be constructed from plate/shaped structural carbon steel (references 2.5, 2.6 or equivalent) of grade 304/316 stainless steel (references 2.7, 2.8, 2.9 or equivalent).

4.3 Base plate/frame/lift lugs shall be coated to prevent corrosion per requirements of paragraph 3.8. This requirement is not applicable to stainless steel plate/frame/lift lug materials.

4.4 Base plate/frame shall be outfitted with forklift tubes which run in both directions (length and width of base) to allow movement of the assembly via forklift from all sides

4.5 Base plate/frame shall be sized to ensure the tank assembly (all components, piping, valves and saddle with tank at 90% fill volume) shall not create a floor/ground loading which exceeds 400 lbs./ft². Base plate/frame shall be sized to transit through a standard Conex/Sealand container door opening width of 92 inches on one end.

4.6 All exterior surfaces of base plate, framing and saddle shall be smooth and all sharp edges rounded/chamfered.

5. TANK ASSEMBLY LIFT LUGS/RIGGING ATTACHMENT POINTS & NON-DESTRUCTIVE TEST DETAILS:

5.1 Tank assembly shall be outfitted with lift lugs/rigging attachment points to allow entire assembly (tank and base plate/frame) to be lifted via an overhead crane.

5.1.1 Lift lugs/rigging attachment points shall be permanently attached to the base plate/frame or the tank saddle support members.

5.1.2 Lift lugs/rigging attachment points shall be oriented to allow use of a single overhead crane attachment point or a spreader beam.

5.2 Integral lift lugs/rigging attachment points shall meet the requirements of reference 2.15.

5.3 Vendor shall provide certification and results of the drop weight test per ASTM E208 or a Charpy Impact test per ASTM A370. The anticipated minimum service temperature for the tank assembly and integral lift lugs/rigging attachment points is 20 Fahrenheit.

5.4 Lift lugs/rigging attachment points and load-bearing members shall be capable of supporting a load three times the combined weight of the empty tank assembly (3:1 yield), without generating a combined shear stress or maximum tensile stress at any point in the device exceeding the corresponding minimum tensile yield strength of the materials of construction.

5.5 Lift lugs/rigging attachment points and load-bearing members shall also be capable of lifting five times the weight of the empty tank assembly (5:1 ultimate) without exceeding the ultimate tensile strength of the materials of construction.

5.6 Load Testing and Non-Destructive Testing (NDT) of the lift lugs/rigging attachment points.

5.6.1 Vendor shall perform pre and post load test visual inspection of the lift lugs/rigging

attachment points; no signs of cracked, broken, worn, distorted, corroded, deteriorated, binding or loose parts are allowed.

5.6.2 Vendor shall perform pre and post load test magnetic particle or liquid penetrant (stainless steel materials) inspections of the entire lift lugs/rigging attachment points and attachment welds. Magnetic particle or liquid penetrant inspections shall be performed in accordance with reference 2.16 with acceptance criteria per reference 2.17 (Class 3 or equivalent for welds). Certified report required.

5.6.3 Vendor shall perform a load test of the integral lift lugs/rigging attachment points. Test load shall be performed at 150% (+5/-0%) of the maximum service load. Maximum service load for this application is the weight of the empty tank assembly. Load test shall be held for a minimum of 10 minutes. Certified report required.

5.7 Vendor shall provide a lifting/rigging diagram detailing the preferred configuration (sling lengths, angles, minimum pendant/component capacity, etc.).

6. TANK DETAILS:

6.1 Tank shall be an eight hundred (800) gallon nominal capacity horizontal cylindrical tank with elliptical end caps.

6.2 Tank shell, including elliptical end caps shall be stainless steel (grade 304/316) per reference 2.4, or an equivalent stainless steel plate specification. Minimum acceptable plate thickness for the shell and elliptical end caps is 5/16 inch. Plate with a No. 4 or finer finish, for use on the inside tank surface, shall be used to facilitate obtaining the required interior surface roughness/finish of paragraph 6.3.

6.3 Interior tank surface (including piping and components) shall have a surface roughness/finish of 32 Ra or better. All pits, gouges, scratches, tool marks, weld spatter, etc., shall be fired into the surrounding surface.

6.4 Interior tank weld surface(s) (including piping and components) shall have a roughness/finish of 32 Ra or better. Welds shall be free of undercut and shall not snag and/or tear a cleaning cloth when wiped in any direction.

6.5 A GAR S-22 micro finish comparator surface roughness scale (GAR Electroforming Division Danbury, CT) www.garelectroforming.com or similar comparator shall be used

to verify interior tank and weld surface finish.

6.6 Tank shall have a personnel access for tank entry which is a minimum of 18 inches in diameter. Closure seal shall utilize a Buna-N gasket. Use of cork-rubber gaskets is prohibited.

6.7 Interior and exterior of the tank shell and elliptical end caps shall be free of embedded ferrous or aluminum particles resulting from rolling and/or forming. Rollers and/or forming equipment used exclusively on stainless steel should be used to form the tank.

6.7.1 Rollers or other forming machines that have been used on ferrous or aluminum metals may be used to form the tank shell and end caps provided special precautions are taken to ensure a satisfactory barrier is located between the rollers/forming machines and the tank shell or elliptical end cap materials.

6.7.2 The contractor shall submit a written request to NNSY for use of rollers or other forming machines discussed in paragraph 6.7.1 and obtain/receive written approval from NNSY. Request shall specify why use of the paragraph 6.7.1 equipment is required and provide details of the special precautions which will be in place ensuring contact between the tank shell/elliptical end cap material and the rollers/forming equipment does not occur.

6.8 Tank shell and elliptical end cap base materials and weld areas (prior to and after completion of welding) shall be passivated per reference 2.18, or other equivalent specification. Solutions and passivation process shall maintain compliance with requirements of references 2.2 and 2.3. Certified report required.

7. PIPING ASSEMBLIES AND CONNECTION DETAILS:

7.1 Tank shall contain two (2) drain/suction piping assemblies connected to tank via bottom connections/penetrations and terminate with end caps on the same tank end.

7.1.1 Piping assemblies shall be 1 1/2-inch SCH 40 per paragraph 3.16.

7.1.2 Piping assemblies shall have a 1 1/2-inch full port ball valve, per paragraph 3.18, between tank penetration/connection and end fitting.

7.1.3 Process connection end fitting shall be a 1 1/2 inch male camlock per paragraph 3.13.

Fitting shall be provided with an end cap closure per paragraph 3.15.

7.1.4 Each penetration (inlet to discharge piping assembly inside tank) shall have a vortex break

installed.

7.1.5 One piping assembly tank penetration shall be on longitudinal centerline of tank bottom and the other shall be slightly off centerline and parallel with the other assembly (see figure 1). See figure 2 for general piping assembly arrangement.

7.2 Tank shall contain a single piping assembly for obtaining liquid samples, connected to tank via bottom connection/penetration and terminate with end cap at same tank end as paragraph 7.1 piping assemblies (see figure 1). See figure 2 for general piping assembly arrangement.

7.2.1 Piping assembly shall be 3/8-inch SCH 40 per paragraph 3.16.

7.2.2 Piping assembly shall have a 3/8-inch full port ball valve, per paragraph 3.18, between tanks penetration/connection and end fitting.

7.2.3 Process connection end fitting shall be a 3/8-inch 37-degree flare fitting per reference 2.19 (i.e., SSP PN BM6-6J or equivalent). Fitting shall be provided with an end cap closure per paragraph 3.15 (i.e., SSP PN AS6Z-2 or equivalent).

7.2.4 Tank penetration shall be slightly off centerline of tank bottom longitudinal; piping assembly shall also parallel assemblies of paragraph 7.1 (see figure 1). See figure 2 for general piping assembly arrangement.

PLEASE SEE ATTACHED STATEMENT OF WORK TO VIEW:

FIGURE (1): DRAIN/ SUCTION AND SAMPLE LINE ARRANGEMENT, VIEWED FROM TANK END

FIGURE (2): GENERAL PIPING ASSEMBLY ARRANGEMENT FOR DRAIN/ SUCTION AND SAMPLE LINE DRAIN/SUCTION ASSEMBLIES

7.3 Tank shall contain a single fill line assembly connected to tank via top connection/penetration and terminate with end cap on the same tank end (See figure 3).

See figure 4 for general piping assembly arrangement

7.3.1 Fill assembly shall be located at the tank end opposite the piping assemblies of paragraphs 7.1 and 7.2.

7.3.2 Piping assembly shall be 2-inch SCH 40 per paragraph 3.16.

7.3.3 Piping assembly shall have a 2 inch full port ball valve, per paragraph 3.18, between tank penetration/connection and end fitting.

7.3.4 Process connection end fitting shall be a 2 inch male camlock x butt weld, per paragraph

3.13. Piping assembly shall be supplied with an end cap closure fitting per paragraph 3.15.

7.3.5 Piping assembly shall maintain a constant downward slope from piping assembly camlock connection to tank top penetration.

7.3.6 Piping assembly shall be slightly off centerline and parallel with the piping assembly of paragraph 7.4. See figures 3 and 4 for piping assembly arrangement details.

7.4 Tank shall contain a single piping assembly for discharge receipt from a relief valve.; connected to tank via top connection/penetration and terminate with end cap at same tank end as the paragraph 7.3 piping assembly (see figure 3). See figure 4 for general piping assembly arrangement.

7.4.1 Piping shall be 1 inch SCH 40 per paragraph 3.16.

7.4.2 Piping assembly shall have a 1 inch full port ball valve, per paragraph 3.18, between tank penetration/connection and end fitting.

7.4.3 Process connection end fitting shall be a 1 inch 37 degree flare fitting per reference 2.19 (i.e., SSP PN BM16-16J or equivalent). Fitting shall be provided with an end cap closure per paragraph 3.15 (i.e., SS PN AS16Z-2 or equivalent).

7.4.4 Piping assembly shall maintain a constant downward slope from piping assembly 37 degree flare connection to tank top penetration.

7.4.5 Piping assembly shall be slightly off centerline and parallel with piping assembly of paragraph 7.3.

PLEASE SEE ATTACHED STATEMENT OF WORK TO VIEW

FIGURE (3) FILL AND RELIEF VALVE DISCHARGE RECEIPT LINES, VIEWING FROM TANK END

FIGURE (4) GENERAL PIPING ASSEMBLY ARRANGEMENT FOR FILL AND RELIEF VALVE DISCHARGE RECEIPT LINES.

7.5 Tank shall contain a single piping assembly connected via tank top connection/penetration for a nitrogen supply and installation/connection of a make-up air assembly. See figure 5 for piping assembly arrangement.

7.5.1 Piping for nitrogen supply shall be 1 inch SCH 40, per paragraph 3.16.

7.5.2 Piping for nitrogen supply shall have a 1-inch full port ball valve per paragraph 3.18, between tank penetration/connection and end fitting.

7.5.3 Piping for make-up air assembly shall be 1 inch SCH 40, minimum, per paragraph 3.16.

Piping shall be sized to ensure that negative pressure/vacuum condition is not created during liquid removal from tank at 60 GPM.

7.5.4 Piping assembly end fittings shall be a 150 Class raised face flange per paragraph 3.14.

Tank assembly shall be supplied with a blank flange closure fitting per paragraph 3.15.

Temporary closure gasket for storage/shipping shall be Buna-N.

PLEASE SEE ATTACHED STATEMENT OF WORK TO VIEW

FIGURE (5): NITROGEN SUPPLY AND MAKE UP AIR PIPING ASSEMBLY ARRANGEMENT

7.6 Tank shall contain a single piping assembly connected via tank top connection/penetration for installation/connection of a relief valve assembly. See figure 6 for piping assembly arrangement.

7.6.1 Piping assembly shall be 1 inch SCH 40 per paragraph 3.16.

7.6.2 Piping assembly end fitting shall be a 150 Class raised face flange per paragraph 3.14.

piping assembly shall be supplied with a blank flange closure fitting per paragraph 3.15.

Temporary closure gasket for storage/shipping shall be Buna-N.

PLEASE SEE ATTACHED STATEMENT OF WORK TO VIEW

FIGURE (6): RELIEF VALVE PIPING ASSEMBLY ARRANGEMENT

7.7 Tank shall contain a single piping assembly connected via tank top penetration for venting the tank to atmospheric pressure supporting, filling, draining and pump down operations.

7.7.1 Vent assembly shall be located at the tank end opposite the fill assembly of paragraph 7.3.

7.7.2 Vent assembly shall be 2 inch SCH 40 per paragraph 3.16.

7.7.3 Vent assembly piping end open to atmosphere shall terminate in a downward facing direction (see figure 7).

7.7.4 A stainless steel (Grade 316) 75-micron screen shall be welded to the vent piping end open to atmosphere (alternate methods to secure mesh screen in place may be proposed in contractors drawing submitted for NNSY approval per paragraph 3.3.).

7.7.5 Vent assembly shall have a 2 inch full port ball valve, per paragraph 3.18, between tank penetration/connection and the piping end open to atmosphere.

PLEASE SEE ATTACHED STATEMENT OF WORK TO VIEW

FIGURE (7): TANK VENT PIPING ASSEMBLY ARRANGEMENT

7.8 Tank shall contain a single piping assembly connected via tank top penetration for monitoring tank internal pressure. Piping assembly shall be outfitted with a compound gauge assembly (see figure 8).

7.8.1 Piping assembly shall be 3/8 inch SCH 40 per paragraph 3.16.

7.8.2 Piping assembly shall have a 3/8-inch full port ball valve, per paragraph 3.18 between tanks penetration/connection and the gauge assembly.

7.8.3 Gage assembly shall be a compound type (e.g. capable of indicating vacuum/suction pressure) with a digital pressure display (Ametek/Crystal Engineering XP2I 0-100 psi; VPN 100PSIXP2I or equivalent).

PLEASE SEE ATTACHED STATEMENT OF WORK TO VIEW

FIGURE (8): TANK VENT PIPING ASSEMBLY ARRANGEMENT

8 MONITORING EQUIPMENT

8.1 Tank shall be outfitted with a Temposonics/MTS Level Plus (MR Model) or Refine ME (LPR Model) analog liquid level/volume sensor/transmitter with resistance temperature detector located 16 inches from bottom of sensor assembly. Assembly shall utilize a rigid stainless steel probe with welded flange mounting and a 3/4" NPT conduit/cabling connection. All wetted parts of the sensing element shall be grade 304/316 stainless steel.

8.2 Liquid level float shall be a Temposonics/MTS float (Model 201248-2, or equivalent), constructed from grade 316/304 stainless steel having a magnet located at the top of the float to allow level indication at lowest level possible.

8.3 Tank volume/liquid level process meter shall be a Precision Digital (Model PD6000-6R5 with red display).

8.4 Tank effluent temperature process meter shall be a Precision Digital (Model PD6000-6R0 with red display). Temperature range for RTD is 20 Fahrenheit - 240 Fahrenheit.

8.5 Process meters shall be contained/mounted within a Hoffman (Model CSD242410W) concept enclosure with a NEMA 4 rating. Enclosure shall have include a concept panel (Hoffman CP2424) and a concept swing-out panel (CSP2424). Enclosure shall contain the process meters of paragraphs 8.3 and 8.4. Enclosure shall be mounted to the tank assembly via a separate free standing frame integral with the base plate our it can be

mounted to the elliptical end cap where the discharge and sample connections are located.

Alternate NEMA 4 rated enclosures are acceptable with NNSY approval of drawing per paragraph 3.3.

8.6 Main power to process meters, liquid level sensor and temperature detector shall be via a disconnect safety switch (120V AC, NEMA 4X enclosure) with associated power cord (8 ft long) outfitted with a twist lock plug end.

9 WELDING DETAILS:

9.1 Welding (tank shell and end caps, tank piping penetrations and any welded attachments to end caps/shell) shall be in accordance with the requirements of reference 2.1.

9.2 Longitudinal and circumferential welds to assemble the tank shell and circumferential joints between the shell and elliptical end caps shall be full penetration welds, welded from the outside and inside. Welds shall be back gouged to sound metal, and all slag removed prior to welding from second side.

9.3 Weld surfaces on interior of tank shell (including exterior welds on any piping internal to the tank) shall be ground flush and be free of weld spatter, scratches, burrs, rust and slag. Surface shall not snag or tear a cleaning cloth when wiped in any direction. Edges of welds shall be smoothy blended with base metal.

9.4 Welds (tank shell, end caps and any welded attachments to end caps/shell) shall be liquid penetrant inspected, at a minimum, per requirements of reference 2.1. Certification report required.

9.5 All structural welding shall be in accordance with references 2.20, 2.21 and 2.22 as appropriate.

9.6 All piping/pipe fitting welds shall be full penetration butt weld joints (i.e., use of consumable inserts allowed), per reference 2.23 or equivalent standard/specification.

9.7 All pipe to tank shell welds shall be full penetration welds.

9.8 All burrs and weld spatter shall be removed from all exterior tank and frame welds. All rough edges shall be rounded or removed.

9.9 Vendor shall certify that any/all weld spatter and slag has been removed and that the tank assembly internal and external surfaces are free of weld spatter and slag. No weld spatter or

slag shall be present on tank assembly internal or external surfaces.

10 TANK ASSEMBLY TESTING DETAILS:

10.1 Vendor shall hydrostatically pressure test the tank assembly to 33 +2/-0 psig (test boundary shall include all piping assemblies, valves and personnel access/manway). Test pressure shall be held for 30 minutes (no leaks, damage or permanent deformation allowed). Tank assembly shall have completed all non-destructive testing and shall be secured in its saddle with base plate assembly during testing. Certified report required.

10.2 Vendor shall perform a calibrated fill of the tank to 90% fill volume (see paragraph 3.22). Level data (gallons) shall be recorded for each 1 inch change in level height. Level data shall be provided to NNSY. Certified report required.

10.3 Vendor shall perform level checks of the tank assembly utilizing the analog liquid level/volume sensor/transmitter of paragraph 8.1 to validate accurate operation of the sensor/transmitter and associated process meter of paragraph 8.3. Certified report required.

10.4 Vendor shall perform an operational check/test to validate operation and accuracy of the resistance temperature detector of paragraph 8.1 and its associated process meter of paragraph 8.4. Certified report required.

10.5 After completion of hydrostatic testing and level checks, the tank and piping assembly internals shall be dried by wiping and/or by blowing dry filtered air/nitrogen through internals. Certified report required.

10.6 Weigh entire tank assembly empty and filled to 90% capacity (tank with all piping assemblies attached and secured in its saddle with base plate assembly). Load indicating device shall be calibrated within +/- 2% of the devices full scale. Certified report required.

11 TANK ASSEMBLY MARKING REQUIREMENT:

11.1 Tank assembly shall be marked in two locations on its saddle with base plate/frame. Marking shall provide the following information as a minimum. Markings shall be made per details of paragraph 3.9.

11.1.1 Purchase Order Number

11.1.2 Tank Serial Number; RDPWT-1, RDPWT-2, etc.

11.2 Process meters shall be labeled using solid label plates (black background with white lettering).

Label plates shall be made from a hard composite material (phenolic, poly, gravoply, etc.).

11.2.1 Liquid level process meter shall have a label plate stating, "Liquid Level (Gallons)".

11.2.2 Temperature process meter shall have a label plate stating, "Temperature (Degrees Fahrenheit)".

11.3 Tank assembly shall have a label plate attached to shell (one location). Label plate backing shall be constructed from stainless steel/aluminum with black block style lettering. Label plate shall contain the following information.

11.3.1 Design Pressure: 30 psig

11.3.2 Design Temperature: 120 F

11.3.3 Hydro Test Pressure: 33 +2/-0 psig

11.3.4 Hydro Test Date: __-__-____

11.3.5 Full Tank Capacity: _____Gallons

11.3.6 Empty Weight: _____Pounds

11.3.7 Full Weight: _____Pounds

11.4 Lifting attachment points shall be marked per paragraph 3.9 with the following verbiage, "LIFT POINT".

12 VENDORS SHALL PROVIDE THE FOLLOWING CERTIFICATION OF COMPLIANCE, INSPECTION /TEST REPORTS AND ADDITIONAL INFORMATION:

12.1 Certification of Compliance.

12.2 Inspection/Test Reports.

12.2.1 Mercury exclusion certification (see paragraph 3.5).

12.2.2 Drop Weight Test (ASTM E208) or a Charpy Impact test (ASTM A370) results/reports for integral lift lugs/rigging attachment points (see paragraph 5.3).

12.2.3 Pre and post load test magnetic particle or liquid penetrant inspection reports (see paragraph 5.6.2).

12.2.4 Lift lug/rigging attachment load test report (see paragraph 5.6.3).

12.2.5 Liquid penetrant inspection reports for tank welds (see paragraph 9.4).

12.2.6 Certify that no weld spatter or slag is present on tank internal/external surfaces (see paragraph 9.9).

12.2.7 Hydrostatic test of tank assembly (see paragraph 10.1).

12.2.8 Calibrated fill of tank to 90% fill volume (see paragraph 10.2).

12.2.9 Tank level check using analog liquid level/volume sensor/transmitter and process meter (see paragraph 10.3).

12.2.10 Operational check of resistance temperature detector and process meter (see paragraph 10.4).

- 12.2.11 Certify tank internals fully dried after testing (see paragraph 10.5).
- 12.2.12 Certify weight of entire tank assembly empty and filled to 90% capacity (see paragraph 10.6).
- 12.2.13 All fluid contacting components/materials meet detrimental material and cleanliness requirements of references 2.2 and 2.3 (see paragraph 3.4).
- 12.2.14 All lubricants used on fluid contacting components shall meet detrimental material requirements of reference 2.2. Any factory lubricants that do not meet detrimental material requirements of reference 2.2 have been removed, surfaces cleaned per requirements of reference 2.3 and lubricants replaced with one which is compliant with reference 2.2 (see paragraph 3.4).
- 12.2.15 Certify tank shell and elliptical end cap base materials and weld areas are passivated (see paragraph 6.8).
- 12.3 Additional information.
- 12.3.1 Operating and maintenance manual for liquid level sensor/transmitter, resistance temperature detector and process meters.
- 12.3.2 Rigging diagram for lifting tank assembly using and overhead crane (see paragraph 5.7).
- 12.3.3 Tank assembly drawing with material list (see paragraph 3.3).
- 12.3.4 List of lubricants (brand name information) utilized for final assembly (i.e., inside ball valves, etc.) along with associated Safety Data Sheets (SDS) and material specifications.

Requirements

Pure Water Tanks

Additional Regulation or Supplemental Clauses Incorporated by Full Text

C-202-H001 ADDITIONAL DEFINITIONS--BASIC

(Oct 2018)

- (a) Department means the Department of the Navy.
- (b) Commander, Naval Sea Systems Command means the Commander of the Naval Sea Systems Command of the Department of the Navy or his duly appointed successor.
- (c) References to The Federal Acquisition Regulation (FAR) All references to the FAR in this contract shall be deemed to also reference the appropriate sections of the Defense FAR Supplement (DFARS), unless clearly indicated otherwise.

(d) National Stock Numbers Whenever the term Federal Item Identification Number and its acronym FIIN or the term Federal Stock Number and its acronym FSN appear in the contract, order or their cited specifications and standards, the terms and acronyms shall be interpreted as National Item Identification Number (NIIN) and National Stock Number (NSN) respectively which shall be defined as follows:

(1) National Item Identification Number (NIIN). The number assigned to each approved Item Identification under the Federal Cataloging Program. It consists of nine numeric characters, the first two of which are the National Codification Bureau (NCB) Code. The remaining positions consist of a seven digit nonsignificant number.

(2) National Stock Number (NSN). The National Stock Number (NSN) for an item of supply consists of the applicable four-position Federal Supply Class (FSC) plus the applicable nine-position NIIN assigned to the item of supply.

(End of Text)

C-204-H001 USE OF NAVY SUPPORT CONTRACTORS FOR OFFICIAL CONTRACT FILES (Oct 2018)

(a) NAVSEA may use a file room management support contractor, hereinafter referred to as "the support contractor", to manage its file room, in which all official contract files, including the official file supporting this procurement, are retained. These official files may contain information that is considered a trade secret, proprietary, business sensitive or otherwise protected pursuant to law or regulation, hereinafter referred to as "protected information". File room management services consist of any of the following: secretarial or clerical support; data entry; document reproduction, scanning, imaging, or destruction; operation, management, or maintenance of paper-based or electronic mail rooms, file rooms, or libraries; and supervision in connection with functions listed herein.

(b) The cognizant Contracting Officer will ensure that any NAVSEA contract under which these file room management services are acquired will contain a requirement that:

(1) The support contractor not disclose any information;

(2) Individual employees are to be instructed by the support contractor regarding the sensitivity of the official contract files;

(3) The support contractor performing these services be barred from providing any other supplies and/or services, or competing to do so, to NAVSEA for the period of performance of its contract and for an additional three years thereafter unless otherwise provided by law or regulation; and,

(4) In addition to any other rights the contractor may have, it is a third party beneficiary who has the right of direct action against the support contractor, or any person to whom the support contractor has released or disclosed protected information, for the unauthorized duplication, release, or disclosure of such protected information.

(c) Execution of this contract by the contractor is considered consent to NAVSEA's permitting access to any information, irrespective of restrictive markings or the nature of the information submitted, by its file room management support contractor for the limited purpose of executing its file room support contract responsibilities.

(d) NAVSEA may, without further notice, enter into contracts with other contractors for these services. Contractors should enter into separate non-disclosure agreements with the file room contractor. Contact the Procuring Contracting Officer for contractor specifics. However, any such agreement will not be considered a prerequisite before information submitted is stored in the file room or otherwise encumber the government.

(End of Text)

C-209-H001 FIRST ARTICLE (CONTRACTOR TESTING) (NAVSEA) (APR 2024) (Apr 2024)

(a) The First Article shall conform in every respect to the requirements of this contract. The First Article shall be manufactured with tools, materials, and methods which are the same as the tools, material and methods which will be used to manufacture the production units. All items delivered under the contract shall be manufactured under the same conditions and quality established by the First Article. Any changes to tools, material, or methods after the first article approval shall be documented by the contractor and approved by the Contracting Officer before they are used.

(b) The Contractor shall make a record of all data obtained during such tests in a form similar to the guidance provided in MIL-HDBK-831A dated 25 June 2013.

(c) Pursuant to paragraph (e) of the clause entitled "First Article Approval--Contractor Testing" (FAR 52.209-3), the First Article shall not be delivered as part of the production quantity.

(End of Text)

C-211-H018 APPROVAL BY THE GOVERNMENT (NAVSEA) (JAN 2019)

(Jan 2019)

Approval by the Government as required under this contract and applicable specifications shall not relieve the Contractor of its obligation to comply with the specifications and with all other requirements of the contract, nor shall it impose upon the Government any liability it would not have had in the absence of such approval.

(End of Text)

C-223-H003 EXCLUSION OF MERCURY (NAVSEA) (MAR 2019)

(Mar 2019)

(a) Definitions. As used in this text:

Article means a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use does not release more than very small quantities, e.g., minute or trace amounts of a hazardous chemical, and does not pose a physical hazard or health risk to employees.

Boundary of containment means a continuous tight seal (barrier) to prevent the release of functional mercury during normal operation and maintenance. Examples include the exterior of a fluorescent lamp, glass capsule of a mercury switch, and container for mercury reagents. A double boundary of containment consists of two independent seals.

Functional mercury means mercury or mercury compound(s) contained in equipment that is required for the equipment to operate properly, such as that found in mercury switches, fluorescent lamps, flat-panel monitors, thermostats, thermostat probes, small coin type batteries, barometers, and dental amalgams.

Hardware means any article, container, piece of material, individual part, subassembly, assembly, component, or system to which mercury control requirements apply.

Mercury-free means hardware that does not contain functional mercury and is not contaminated by mercury or mercury compounds.

Portable means items that are frequently transported during normal operation. Desk lamps, shop lights, and hand-held instruments are considered portable, while bulbs in stationary light fixtures are not. In general, items that require transport only during maintenance, installation, and removal of the items are not considered portable.

(b) The Contractor, and all subcontractors and vendors, shall ensure that mercury or mercury containing compounds are not intentionally added to, or come in direct contact with, hardware or supplies furnished under this contract.

(1) The Contractor shall ensure that mercury and mercury compounds are not taken onboard naval vessels by Contractor, subcontractor, or vendor personnel except for functional mercury used in batteries, dental amalgams, fluorescent lamps, flat-panel monitors, required instruments, sensors or controls, weapon systems, and chemical analysis reagents specified by the Naval Sea Systems Command (NAVSEA).

(2) Portable fluorescent lamps and portable instruments containing elemental mercury must be shock-proof in accordance with MIL-DTL-901E entitled Requirements for Shock Tests, H.I. (High Impact) Shipboard Machinery, Equipment, and Systems and have mercury enclosed by a double boundary of containment. Some devices with liquid crystal display (LCD) screens utilize a fluorescent bulb backlight to illuminate the LCD screen. No additional restrictions or controls apply to devices with LCD screens; however, the Contractor shall remove the LCD screen and seal it in plastic following any evidence that the backlight failed.

(3) For Submarines, any use of mercury containing items must be approved as required by the Nuclear Powered Submarine Atmosphere Control Manual (S9510-AB-ATM-010/U) Volume 1.

(4) The Contractor shall ensure that mercury and mercury compounds do not contact hardware surfaces in systems covered by NAVSEA Manual NAVSEA 0989-064-3000 entitled Cleanliness Requirements for Nuclear Propulsion Plant Maintenance and Construction, submarine air systems, level I systems per NAVSEA Publication 0948-LP-045-7010, NAVSEA Material Control Standard, or the submarine safety program (SUBSAFE) surfaces during maintenance or repair. Such hardware is designated as mercury-free. The Contractor shall ensure that all other hardware that could be structurally degraded by contamination with elemental mercury or reactive mercury compounds is separated from it by sufficient distance, or boundaries of containment that effectively prevents contact in all but the most extreme circumstances.

(5) The Contractor shall check any hardware surfaces in the above systems which are known or suspected to have come in contact with mercury or mercury compounds for evidence of structural degradation and external mercury contamination. The existence of external mercury contamination can be determined following MIL-STD-2041D entitled Control of Detrimental Materials.

(6) The presence of mercury in a product may be determined by checking product labeling on material safety data sheets or safety data sheets. Chemical analysis is not required.

(7) The Contractor shall dispose of any mercury and mercury compounds in accordance with OPNAV Manual (OPNAV M-5090.1) entitled Environmental Readiness Program Manual of 10 January 2014.

(8) If the use of mercury or mercury compounds cannot be avoided, a risk assessment and waiver request, if required, must be performed and submitted per the NAVSEA Hazardous Material Avoidance Process (T9070-AL-DPC-020/077-2). For systems covered by the NAVSEA Manual NAVSEA 0989-064-3000 entitled Cleanliness Requirements for Nuclear Propulsion Plant Maintenance and Construction, submit the risk assessment and waiver request, if required to Nuclear Propulsion (NAVSEA 08).

(c) In all cases where mercury or a mercury compound has contacted hardware surfaces required to be mercury-free the Contractor shall immediately provide a report to the NAVSEA Dry Environmental Systems and Hazardous Materials (NAVSEA 05P5) via the cognizant contract administration safety office. Reports concerning systems covered by NAVSEA Manual 0989-064-3000 must include NAVSEA Nuclear Propulsion Directorate (SEA 08) in the distribution. Reports must be in letter form and include the date and details of the contact, the surfaces contacted, the recovery actions taken, and the status of the affected surfaces.

(End of Text)

Section D - Packaging and Marking

Additional Regulation or Supplemental Clauses Incorporated by Full Text

D-247-H002 PACKAGING OF SUPPLIES—BASIC (NAVSEA) (DEC 2020)

(Dec 2020)

Item(s) 0001 The supplies furnished hereunder shall be packaged in accordance with ASTM-D-3951-18, Standard Practice for Commercial Packing.

(End of Text)

Section E - Inspection and Acceptance

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.246-1	Contractor Inspection Requirements.	Apr 1984		
Overall Contract Inspection/Acceptance Locations				

0001	Inspection and Acceptance Location Both Destination Instructions: Please contact Receiving Officer for delivery information. DoDAAC: N42158 CountryCode: USA NORFOLK NAVAL SHIPYARD GF 1 NORFOLK NAVAL SHIPYARD, BUILDING 276 PORTSMOUTH, VA 23709-1001 UNITED STATES David Love, Technical Engineer - Receiving Officer Email: david.m.love5.civ@us.navy.mil Telephone: 757-396-3061
0002	Inspection and Acceptance Location Both Destination Instructions: Please contact the Receiving Officer, and or Alternate Receiving Officer JARRAD TAYLOR (808-473-8000 EXT. 4878) if you have any questions or concerns pertaining to delivery. DoDAAC: N32253 CountryCode: USA PEARL HARBOR NAVAL SHIPYARD IMF 667 SAFEGUARD STREET, BLDG 167-1 RECV 808-473-8000X4961 PEARL HARBOR, HI 96860-5033 UNITED STATES Shordon Lopes, Technical Engineer - Receiving Officer Email: shordon.k.lopes.civ@us.navy.mil Telephone: 808-754-9134

Section F - Deliveries or Performance

REQUIREMENTS FOR ACCESS TO NNSY

Commander, Navy Installations Command (CNIC), has established the Defense Biometric Identification System, (DBIDS), a standardized process for granting unescorted access privileges to vendors, contractors, suppliers and service providers not otherwise entitled to the issuance of a Common Access Card (CAC) who seek access to and can provide justification to enter Navy installations and facilities. Participation in the DBIDS is not mandatory, and if the Contractor chooses to not participate, the Contractor's personnel will have to obtain daily passes, be subject to daily mandatory vehicle inspection and will have limited access to the installation. The Government will not be responsible for any cost or lost time associated with obtaining daily passes or added vehicle inspections incurred by non-participants in the DBIDS. Alternatively, if the vendor so chooses, it may voluntarily elect to obtain long-term credentials through enrollment, registration, background vetting, screening, issuance of credentials, and electronic validation of credentials. Further information regarding DBIDS can be found at

<https://www.cnic.navy.mil/om/dbids.html>.

NOTE: Bldg. 276 TELEPHONE: 757-396-5815 (or 5095)

Overall Contract Delivery Period

Contractor

Destination

Line Item	Delivery Schedule	Quantity	Address and POC	Special Handling/Notes
0001	Delivery On Or Before Delivery Date 30 Jun 2026	1 Each	Ship To DoDAAC: N42158 CountryCode: USA NORFOLK NAVAL SHIPYARD GF 1 NORFOLK NAVAL SHIPYARD, BUILDING 276 PORTSMOUTH, VA 23709-1001 UNITED STATES David Love, Technical Engineer - Receiving Officer Email: david.m.love5.civ@us.navy.mil Telephone: 757-396-3061	FoB Details Contractor Destination
0002	Delivery On Or Before Delivery Date 30 Jun 2026	1 Each	Ship To DoDAAC: N32253 CountryCode: USA PEARL HARBOR NAVAL SHIPYARD IMF 667 SAFEGUARD STREET, BLDG 167-1 RECV 808-473-8000X4961 PEARL HARBOR, HI 96860-5033 UNITED STATES Shordon Lopes, Receiving Officer Email: shordon.k.lopes.civ@us.navy.mil Telephone: 808-754-9134	FoB Details Contractor Destination

Section G - Contract Administration Data

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.232-7003	Electronic Submission of Payment Requests and Receiving Reports.	Dec 2018		

DFARS Clauses Incorporated by Full Text

252.232-7006 Wide Area WorkFlow Payment Instructions. (Jan 2023)

WIDE AREA WORKFLOW PAYMENT INSTRUCTIONS (JAN 2023)

(a) *Definitions.* As used in this clause-

"Department of Defense Activity Address Code (DoDAAC)" is a six position code that uniquely identifies a unit, activity, or organization.

"Document type" means the type of payment request or receiving report available for creation in Wide Area WorkFlow (WAWF).

"Local processing office (LPO)" is the office responsible for payment certification when payment certification is done external to the entitlement system.

"Payment request" and "receiving report" are defined in the clause at 252.232-7003, Electronic Submission of Payment Requests and Receiving Reports.

(b) *Electronic invoicing.* The WAWF system provides the method to electronically process vendor payment requests and receiving reports, as authorized by Defense Federal Acquisition Regulation Supplement (DFARS) 252.232-7003, Electronic Submission of Payment Requests and Receiving Reports.

(c) *WAWF access.* To access WAWF, the Contractor shall-

(1) Have a designated electronic business point of contact in the System for Award Management at <https://www.sam.gov>; and

(2) Be registered to use WAWF at <https://wawf.eb.mil/> following the step-by-step procedures for self-registration available at this web site.

(d) *WAWF training.* The Contractor should follow the training instructions of the WAWF Web-Based Training Course and use the Practice Training Site before submitting payment requests through WAWF. Both can be accessed by selecting the "Web Based Training" link on the WAWF home page at <https://wawf.eb.mil/>

(e) *WAWF methods of document submission.* Document submissions may be via web entry, Electronic Data Interchange, or File Transfer Protocol.

(f) *WAWF payment instructions.* The Contractor shall use the following information when submitting payment requests and receiving reports in WAWF for this contract or task or delivery order:

(1) *Document type.* The Contractor shall submit payment requests using the following document type(s):

(i) For cost-type line items, including labor-hour or time-and-materials, submit a cost voucher.

(ii) For fixed price line items-

(A) That require shipment of a deliverable, submit the invoice and receiving report specified by the Contracting Officer.

(Contracting Officer: Insert applicable invoice and receiving report document type(s) for fixed price line items that require shipment of a deliverable.)

(B) For services that do not require shipment of a deliverable, submit either the Invoice 2in1, which meets the requirements for the invoice and receiving report, or the applicable invoice and receiving report, as specified by the Contracting Officer.

(Contracting Officer: Insert either "Invoice 2in1" or the applicable invoice and receiving report document type(s) for fixed price line items for services.)

(iii) For customary progress payments based on costs incurred, submit a progress payment request.

(iv) For performance based payments, submit a performance based payment request.

(v) For commercial financing, submit a commercial financing request.

(2)) Fast Pay requests are only permitted when Federal Acquisition Regulation (FAR) 52.213-1 is included in the contract.

[Note: The Contractor may use a WAWF "combo" document type to create some combinations of invoice and receiving report in one step.]

(3) Document routing. The Contractor shall use the information in the Routing Data Table below only to fill in applicable fields in WAWF when creating payment requests and receiving reports in the system.

Routing Data Table*

Field Name in WAWF	Data to be entered in WAWF
Pay Official DoDAAC	==
Issue By DoDAAC	==
Admin DoDAAC	==
Inspect By DoDAAC	==
Ship To Code	==
Ship From Code	==
Mark For Code	==
Service Approver (DoDAAC)	==
Service Acceptor (DoDAAC)	==
Accept at Other DoDAAC	==
LPO DoDAAC	==
DCAA Auditor DoDAAC	==
Other DoDAAC(s)	==

(*Contracting Officer: Insert applicable DoDAAC information. If multiple ship to/acceptance locations apply, insert "See Schedule" or "Not applicable.")

(**Contracting Officer: If the contract provides for progress payments or performance-based payments, insert the DoDAAC for the contract administration office assigned the functions under FAR 42.302(a)(13).)

(4) *Payment request.* The Contractor shall ensure a payment request includes documentation appropriate to the type of payment request in accordance with the payment clause, contract financing clause, or Federal Acquisition Regulation 52.216-7, Allowable Cost and Payment, as applicable.

(5) *Receiving report.* The Contractor shall ensure a receiving report meets the requirements of DFARS Appendix F.

(g) *WAWF point of contact.*

(1) The Contractor may obtain clarification regarding invoicing in WAWF from the following contracting activity's WAWF point of contact.

(Contracting Officer: Insert applicable information or "Not applicable.")

(2) Contact the WAWF helpdesk at 866-618-5988, if assistance is needed.

(End of clause)

Additional Regulation or Supplemental Clauses Incorporated by Full Text

G-232-H002 H002 PAYMENT INSTRUCTIONS (NAVSEA) (FEB 2024)

(Feb 2024)

Payment office allocation methods can be found in the table at DFARS PGI 204.7108(b)(2) (https://www.acq.osd.mil/dpap/dars/pgi/pgi_hm/current/PGI204_71.htm#payment_instructions).

(End of text)

G-242-H001 GOVERNMENT CONTRACT ADMINISTRATION POINTS-OF-CONTACT AND RESPONSIBILITIES (NAVSEA) (OCT 2023)

(Oct 2023)

(a) The Government reserves the right to administratively substitute any of the points of contact listed below at any time.

(b) The contracting officer is the only person authorized to change this contract or orders issued thereunder. The Contractor shall not comply with any order, direction or request of Government personnel - that would constitute a change - unless it is issued in writing and signed by the Contracting Officer or is pursuant to specific authority otherwise included as part of this contract. If, in the opinion of the contractor, an effort outside the existing scope of this contract is requested, the contractor shall promptly comply with the Notification of Changes clause of this contract.

(c) The points of contact are as follows:

(i) The Procuring Contracting Officer (PCO) is:

Name: Carolyn Burns
Address: Norfolk Naval Shipyard Building 65 1st Floor Rm 101
Portsmouth, Virginia, 23709-5000
Phone: 757-967-2922
E-mail: carolyn.f.burns.civ@us.navy.mil

(ii) The Contract Specialist is:

Name: Zakiya Clark
Address: Norfolk Naval Shipyard Building 65 1st Floor Rm 101
Portsmouth, Virginia, 23709-5000
Phone: 757-967-5090
E-mail: zakiya.a.clark.civ@us.navy.mil

(iii) The Administrative Contracting Officer (ACO) is:

Name: Carolyn Burns
Address: Norfolk Naval Shipyard Building 65 1st Floor Rm 101
Portsmouth, Virginia, 23709-5000
Phone: 757-967-2922
E-mail: carolyn.f.burns.civ@us.navy.mil

(d) The Contracting Officer's Representative (COR) is the contracting officer's appointed representative for technical matters. The COR is not a contracting officer and does not have the authority to direct the accomplishment of effort which is beyond the scope of the contract or to otherwise change any contract requirements. An informational copy of the COR appointment letter, which provides a delineation of COR authority and responsibilities, will be provided upon award of this contract.

The Contracting Officer's Representative (COR) is:

NOT APPLICABLE

(e) The Alternate Contracting Officer's Representative (ACOR) is responsible for COR responsibilities and functions in the event that the COR is unavailable due to leave, illness, or other official business. The ACOR is appointed by the contracting officer; a copy of the ACOR appointment will be provided upon award of this contract.

The Alternate Contracting Officer's Representative (ACOR) is:

NOT APPLICABLE

(f) The Technical Point of Contact (TPOC) is the contracting officer's representative for technical matters when a COR is not appointed. The TPOC is responsible for technical issues of contract administration, such as providing all items of Government Furnished Information (GFI), Government Furnished Material (GFM) and Government Furnished Equipment (GFE) if specified in the contract as well as the inspection and acceptance of all contract deliverables.

The Technical Point of Contact (TPOC) is:

Name: TBD
Address: [*Street]
[*City, State, Zip]
Phone: (Area Code) xxx- [xxxx]
E-mail: [*]

(g) The Alternate Technical Point of Contact (ATPOC) is responsible for TPOC responsibilities and functions in the event that the TPOC is unavailable due to leave, illness, or other official business.

The Alternate Technical Point of Contact (ATPOC) is:

NOT APPLICABLE

(h) The Authorized Ordering Person(s) for Per-Call Maintenance is responsible for issuing and maintaining records for any per-call orders for remedial maintenance placed under this contract. No per-call order shall be placed outside the scope of this contract and the cumulative total of all orders shall not be in excess of any not-to-exceed amount specified in the contract. Per-call orders shall not, in any way, modify any terms and conditions of the contract.

(i) The Authorized Ordering Person(s) for Per-Call Maintenance is:

NOT APPLICABLE

(j) The Contractor's point of contact for performance under this contract is:

Name: TBD
Address:
[*Street]
[*City, State, Zip]
Phone: (Area Code) xxx- [xxxx]
E-mail: [*]

[*] To be completed at contract award

(End of Text)

G-242-H002 HOURS OF OPERATION AND HOLIDAY SCHEDULE (NAVSEA) (JUL 2021)

(Jul 2021)

(a) The policy of this activity is to schedule periods of reduced operations or shutdown during holiday periods. Deliveries will not be accepted on Saturdays, Sundays or Holidays except as specifically requested by the [insert activity name]. All goods or services attempted to be delivered on a Saturday, Sunday or Holiday without specific instructions from the Contracting Officer or his duly appointed representative will be returned to the contractor at the contractor's expense with no cost or liability to the U. S. Government.

(b) The federal Government observes public Holidays that have been established under 5 U.S.C. 6103. The actual date of observance for each of the holidays, for a specific calendar year, may be obtained from the OPM website at OPM.GOV or by using the following direct link: <https://www.opm.gov/policy-data-oversight/pay-leave/federal-holidays/>.

(c) Delayed Opening, Early Dismissal and Closure of Government Facilities. When a Government facility has a delayed opening, is closed or Federal employees are dismissed early (due to severe weather, security threat, security exercise, or a facility related problem) that prevents personnel from working, onsite contractor personnel regularly assigned to work at that facility shall follow the same reporting and/or departure directions given to Government personnel. The contractor shall not direct charge to the contract for such time off, but shall follow parent company policies regarding taking leave (administrative or other). Non-essential contractor personnel, who are not required to remain at or report to the facility, shall follow their parent company policy regarding whether they should go/stay home or report to another company facility. Subsequent to an early dismissal, delayed opening, or during periods of inclement weather, onsite contractors should monitor the OPM website as well as radio and television announcements before departing for work to determine if the facility is closed or operating on a delayed arrival basis.

(d) When Federal employees are excused from work due to a holiday or a special event (that is unrelated to severe weather, a security threat, or a facility related problem), on site contractors shall continue working established work hours or take leave in accordance with parent company policy. Those contractor employees who take leave shall not direct charge the non-working hours to the contract. Contractors are responsible for predetermining and disclosing their charging practices for early dismissal, delayed openings, or closings in accordance with the FAR, applicable cost accounting standards, and the company's established policy and procedures. Contractors shall follow their disclosed charging practices during the contract period of performance, and shall not follow any verbal directions to the contrary. The Contracting Officer will make the determination of cost allowability for time lost due to facility closure in accordance with FAR, applicable Cost Accounting Standards, and the Contractor's established accounting policy and procedures.

(e) If you intend to visit the Contracts Office, it is advised that you call for an appointment at least 24 hours in advance.

(f) The hours of operation are as follows:

AREA	FROM	TO
<i>Norfolk Naval Shipyard</i>	<i>0700</i>	<i>1630</i>
<i>Receiving Officer Bldg. 276</i>		

(g) All deliveries to the Receiving Officer, *Norfolk Naval Shipyard Bldg. 276 Beatty Street Portsmouth, VA.*, shall be made Monday through Friday from 0700 to 1630, local time. Deliveries will not be accepted after 1630. No deliveries will be accepted on federal government holidays.

(End of Text)

Section H - Special Contract Requirements

Additional Regulation or Supplemental Clauses Incorporated by Full Text

H-223-N001 INFORMATION ON EXPOSURE TO HAZARDOUS MATERIAL (NAVSEA) (JUL 2024) (Jul 2024)

Per 29 CFR 1910.1200, Hazard Communication, you, as a contractor employer with employees working at a Government facility, are hereby informed of the hazardous materials used at the Government facility which your employees may be exposed to while working here and also to suggest appropriate protective measures. Your own responsibilities as an employer, if any, are given in 29 CFR 1910.1200.

1. Hazardous materials your employees may be exposed to. Hazardous materials are materials which are cancer causing agents, toxic or highly toxic agents, reproductive toxins, irritants, corrosives, sensitizers, liver toxins, kidney toxins, agents which act on the blood forming system, and agents which damage the lungs, skins, eyes or mucous membranes. There are many potentially hazardous chemicals present at the Government facility which, unless controlled properly, could present a safety and health problem. The presence of many potentially hazardous materials may be apparent from the manufacturer's warning label on the hazardous material containers. The presence of many potentially hazardous materials may also be apparent due to their physical characteristics, such as the visual appearance of abrasive blasting dust or the distinctive smell of many solvents. These hazardous materials range in type and quantity. Typical hazardous materials include, but are not limited to:

- a. Metals, e.g., mercury, lead, chromium
- b. Paints and adhesives, e.g., varnishes and related products, sealing compounds, asphalt, deck and floor coverings, deck compounds
- c. Corrosives, e.g., acids, alkalis
- d. Compressed and liquefied gas, e.g., nitrogen, argon, oxygen, acetylene
- e. Lubricants and oils, e.g., greases, cutting oils, hydraulic oils, miscellaneous waxes and fats
- f. Fuels, e.g., liquid propellants, fuel oils, oxidizers, solid fuels
- g. Particulates, e.g., asbestos fiberglass, dust, fumes, mist

Depending on the material involved, materials such as these can present physical hazards and or health hazards.

2. Labeling of Hazardous Material. Containers of potentially hazardous chemicals bear manufacturer's labeling, which identifies the chemical and its manufacturer, and provides appropriate hazard warnings. In addition, some materials may be labeled with the National Protection Association (NFPA) 704 label. This label uses a system of color coded symbols and numbers to convey the potential hazard of the material. The contractor should obtain information from NFPA concerning the interpretation of the 704 label.

3. Safety Data Sheets (SDS). The Safety Office maintains copies of manufacturers' SDS for potentially hazardous chemicals/materials that are known to be present in the Government facility. The contractor may,

upon request to the Safety Office, review SDS for any specific materials to which contractor employees may be exposed while performing work in the Government facility. This information may be reviewed in the Safety Office.

4. Appropriate Protective Measures. Exposure to potentially hazardous material may occur from inhalation, ingestion or skin contact with the material; therefore, the following precautions should be taken:

- a. Obey signs, directions and warning labels;
- b. Do not use unknown or labeled materials;
- c. Only operate equipment that you are authorized to operate, familiar with, and qualified to operate;
- d. If any health effects (skin rash, trouble breathing, etc.) occur, which you feel are caused by exposure to hazardous material, contact the Safety Office.

5. The Safety Office points of contact are as follows:

Information on the materials may be obtained from the Shipyard Safety and Health Office, Code 106.1, phone number (757-396-3702 or 757-396-7912).

Ref. NAVSHIPDNORIMST PS100.56 VOL VI CHAPTER II PARA. 7-J (3)

(End of Text)

Section I - Contract Clauses

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.203-19	Prohibition on Requiring Certain Internal Confidentiality Agreements or Statements.	Jan 2017		
52.204-10	Reporting Executive Compensation and First-Tier Subcontract Awards. (Deviation)	Feb 2026		
52.204-13	System for Award Management-Maintenance. (Deviation)	Feb 2026		
52.204-19	Incorporation by Reference of Representations and Certifications.	Dec 2014		
52.209-6	Protecting the Government's Interest When Subcontracting With Contractors Debarred, Suspended, Proposed for Debarment, or Voluntarily Excluded. (Deviation)	Feb 2026		
52.209-10	Prohibition on Contracting With Inverted Domestic Corporations. (Deviation)	Feb 2026		
52.212-4	Terms and Conditions-Commercial Products and Commercial Services. (Deviation)	Feb 2026		
52.219-6	Notice of Total Small Business Set-Aside. (Deviation)	Feb 2026		
52.222-3	Convict Labor. (Deviation)	Feb 2026		
52.222-19	Child Labor-Cooperation with Authorities and Remedies. (Deviation)	Feb 2026		
52.222-35	Equal Opportunity for Veterans. (Deviation)	Feb 2026		
52.222-36	Equal Opportunity for Workers with Disabilities. (Deviation)	Feb 2026		
52.222-37	Employment Reports on Veterans. (Deviation)	Feb 2026		
52.222-50	Combating Trafficking in Persons. (Deviation)	Feb 2026		
52.222-54	Employment Eligibility Verification. (Deviation)	Feb 2026		
52.223-23	Sustainable Products. (Deviation)	Feb 2026		
52.226-8	Encouraging Contractor Policies to Ban Text Messaging While Driving.	May 2024		
52.229-12	Tax on Certain Foreign Procurements.	Feb 2021		
52.232-39	Unenforceability of Unauthorized Obligations.	Jun 2013		
52.232-40	Providing Accelerated Payments to Small Business Subcontractors.	Mar 2023		
52.233-3	Protest after Award. (Deviation)	Feb 2026		
52.233-4	Applicable Law for Breach of Contract Claim. (Deviation)	Feb 2026		
52.240-91	Security Prohibitions and Exclusions. (Deviation)	Feb 2026		
52.244-6	Subcontracts for Commercial Products and Commercial Services. (Deviation)	Feb 2026		

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.203-7000	Requirements Relating to Compensation of Former DoD Officials.	Sep 2011		
252.203-7002	Requirement to Inform Employees of Whistleblower Rights.	Dec 2022		
252.204-7003	Control of Government Personnel Work Product.	Apr 1992		
252.204-7004	Antiterrorism Awareness Training for Contractors.	Jan 2023		
252.204-7012	Safeguarding Covered Defense Information and Cyber Incident Reporting.	May 2024		
252.204-7015	Notice of Authorized Disclosure of Information for Litigation Support.	Jan 2023		
252.204-7018	Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services.	Jan 2023		
252.204-7020	NIST SP 800-171 DoD Assessment Requirements.	Nov 2023		
252.223-7008	Prohibition of Hexavalent Chromium.	Jan 2023		
252.225-7001	Buy American and Balance of Payments Program.	Feb 2024		
252.225-7002	Qualifying Country Sources as Subcontractors.	Mar 2022		
252.225-7012	Preference for Certain Domestic Commodities.	Apr 2022		
252.225-7013	Duty-Free Entry.	Aug 2025		
252.225-7048	Export-Controlled Items.	Jun 2013		
252.225-7056	Prohibition Regarding Business Operations with the Maduro Regime.	Jan 2023		
252.225-7060	Prohibition on Certain Procurements from the Xinjiang Uyghur Autonomous Region.	Jun 2023		
252.225-7972	Prohibition on the Procurement of Foreign-Made Unmanned Aircraft Systems. (DEVIATION 2024-O0014)	Aug 2024	Deviation 2024-O0014	Aug 2024
252.232-7010	Levies on Contract Payments.	Dec 2006		
252.244-7000	Subcontracts for Commercial Products or Commercial Services.	Nov 2023		
252.246-7008	Sources of Electronic Parts.	Jan 2023		
252.247-7023	Transportation of Supplies by Sea.	Oct 2024		

FAR Clauses Incorporated by Full Text

52.252-2 **Clauses Incorporated by Reference. (Tailored)** **(Mar 2026)**

Clauses Incorporated By Reference (Feb 1998)

This contract incorporates one or more clauses by reference, with the same force and effect as if they were given in full text. Upon request, the Contracting Officer will make their full text available. Also, the full text of a clause may be accessed electronically at this/these address(es):

DASN(P) site: <https://www.secnave.navy.mil/rda/DASN-P/Pages/NMCARS.aspx>
DFARS Clauses: <https://www.acq.osd.mil/dpap/dars/dfarspgi/current/index.html>
FAR Clauses: <https://acquisition.gov>

(End of clause)

52.252-6 Authorized Deviations in Clauses. (Mar 2026)

Authorized Deviations in Clauses (Nov 2020)

(a) The use in this solicitation or contract of any Federal Acquisition Regulation (48 CFR Chapter 1) clause with an authorized deviation is indicated by the addition of "(DEVIATION)" after the date of the clause.

(b) The use in this solicitation or contract of any **Defense Federal Acquisition Regulation** (48 CFR **Chapter 2**) clause with an authorized deviation is indicated by the addition of "(DEVIATION)" after the name of the regulation.

(End of clause)

DFARS Clauses Incorporated by Full Text

252.204-7021 Contractor Compliance with the Cybersecurity Maturity Model Certification Level Requirements. (Nov 2025)

CONTRACTOR COMPLIANCE WITH THE CYBERSECURITY MATURITY MODEL CERTIFICATION LEVEL REQUIREMENTS (NOV 2025)

(a) *Definitions.* As used in this clause-

"Controlled unclassified information" means information the Government creates or possesses, or information an entity creates or possesses for or on behalf of the Government, that a law, regulation, or Governmentwide policy requires or permits an agency to handle using safeguarding or dissemination controls (32 CFR 2002.4(h)).

"Current" means-

(1) With regard to Conditional Cybersecurity Maturity Model Certification (CMMC) Status-

(i) Not older than 180 days for Conditional Level 2 (Self) assessments and Conditional Level 2 (certified third-party assessment organization (C3PAO)) assessments, with-

(A) No changes in compliance with the requirements at 32 CFR part 170 since the Conditional CMMC Status date (see 32 CFR 170.16 and 170.17); and

(B) A corresponding affirmation of continuous compliance by an affirming official (see 32 CFR 170.4); and

(ii) Not older than 180 days for Conditional Level 3 (Defense Industrial Base Cybersecurity Assessment Center (DIBCAC)) assessments, with-

(A) No changes in compliance with the requirements at 32 CFR part 170 since the Conditional CMMC Status date (see 32 CFR 170.18); and

(B) A corresponding affirmation of continuous compliance by an affirming official;

(2) With regard to Final CMMC Status-

(i) Not older than 1 year for Final Level 1 (Self), with-

(A) No changes in compliance with the requirements at 32 CFR part 170 since the Final CMMC Status date (see 32 CFR 170.15); and

(B) A corresponding affirmation of continuous compliance, not older than 1 year, by an affirming official;

(ii) Not older than 3 years for Final Level 2 (Self) assessments and Final Level 2 (C3PAO) assessments, with-

(A) No changes in compliance with the requirements at 32 CFR part 170 since the Final CMMC Status date (see 32 CFR 170.16 and 170.17); and

(B) A corresponding affirmation of continuous compliance, not older than 1 year, by an affirming official; and

(iii) Not older than 3 years for Final Level 3 (DIBCAC) assessments, with-

(A) No changes in compliance with the requirements at 32 CFR part 170 since the Final CMMC Status date (see 32 CFR 170.18); and

(B) A corresponding affirmation of continuous compliance, not older than 1 year, by an affirming official; and

(3) With regard to affirmation of continuous compliance (32 CFR 170.22), not older than 1 year with no changes in compliance with the requirements at 32 CFR part 170.

"Cybersecurity Maturity Model Certification (CMMC) status" means the result of meeting or exceeding the minimum required score for the corresponding assessment. The potential statuses are as follows:

- (1) Final Level 1 (Self).
- (2) Conditional Level 2 (Self).
- (3) Final Level 2 (Self).
- (4) Conditional Level 2 (C3PAO).
- (5) Final Level 2 (C3PAO).
- (6) Conditional Level 3 (DIBCAC).
- (7) Final Level 3 (DIBCAC).

"Cybersecurity Maturity Model Certification unique identifier (CMMC UID)" means 10 alpha-numeric characters assigned to each CMMC assessment and reflected in the Supplier Performance Risk System (SPRS) for each contractor information system.

"Federal contract information (FCI)" means information, not intended for public release, that is provided by or generated for the Government under a contract to develop or deliver a product or service to the Government. It does not include information provided by the Government to the public, such as on public websites, or simple transactional information, such as information necessary to process payments.

"Plan of action and milestones" means a document that identifies tasks to be accomplished. It details resources required to accomplish the elements of the plan, any milestones in meeting the tasks, and scheduled completion dates for the milestones, as defined in National Institute of Standards and Technology Special Publication 800-115 (32 CFR 170.21).

(b) *Framework.* The Cybersecurity Maturity Model Certification (CMMC) is a framework for assessing a contractor's compliance with applicable information security protections (see 32 CFR part 170).

(c) *Duplication.* The CMMC assessments will not duplicate efforts from any other comparable DoD assessment, except for rare circumstances when a reassessment may be necessary, for example, when there are indications of issues with cybersecurity and/or compliance with CMMC requirements.

(d) *Requirements.* The Contractor shall-

(1)(i) Have and maintain for the duration of the contract a current CMMC status at the following CMMC level, or higher: _____
Contracting Officer insert: CMMC Level 1 (Self); CMMC Level 2 (Self); CMMC Level 2 (C3PAO); or CMMC Level 3 (DIBCAC) for all information systems used in performance of the contract, task order, or delivery order that process, store, or transmit FCI or CUI; and

(ii) Consult 32 CFR 170.23 related to the flowdown of the CMMC requirements, and flow down the correct CMMC level to subcontracts and other contractual instruments;

(2) Only process, store, or transmit FCI or CUI on contractor information systems that have a CMMC status at the CMMC level required in paragraph (d)(1) of this clause, or higher;

(3) Complete on an annual basis, and maintain as current, an affirmation, by the affirming official (see 32 CFR 170.4), of continuous compliance with the requirements associated with the CMMC level required in paragraph (d)(1) of this clause in the Supplier Performance Risk System (SPRS) (<https://piee.eb.mil>) for each CMMC UID applicable to each of the contractor information systems that process, store, or transmit FCI or CUI and that are used in performance of the contract;

(4) Ensure all subcontractors and suppliers complete prior to subcontract award, and maintain on an annual basis, an affirmation, by the affirming official (see 32 CFR 170.4), of continuous compliance with the requirements associated with the CMMC level required for the subcontract or other contractual instrument for each of the subcontractor information systems that process, store, or transmit FCI or CUI and that are used in performance of the subcontract; and

(5) If the Contractor has a CMMC Status of Conditional, successfully close out a valid plan of action and milestones (32 CFR 170.21) to achieve a CMMC Status of Final.

(e) *Reporting.* The Contractor shall-

(1) Submit to the Contracting Officer-

(i) The CMMC UID(s) issued by SPRS for contractor information systems that will process, store, or transmit FCI or CUI during performance of the contract; and

(ii) Any changes in the CMMC UIDs generated in SPRS throughout the life of the contract, task order, or delivery order, if applicable;

(2) Enter into SPRS the results of a current self-assessment for each CMMC UID, not covered by a C3PAO assessment or DIBCAC assessment, applicable to each of the contractor information systems that process, store, or transmit FCI or CUI and that are used in performance of the contract; and

(3) Complete in SPRS on an annual basis and maintain as current an affirmation of continuous compliance by the affirming official (see 32 CFR 170.4) for each self-assessment, C3PAO assessment, or DIBCAC assessment required under the contract in SPRS.

(f) *Subcontracts.* The Contractor shall-

(1) Insert the substance of this clause, including this paragraph (f) and excluding paragraph (e)(1), in subcontracts and other contractual instruments, including those for the acquisition of commercial products or commercial services, excluding commercially available off-the-shelf items, if the subcontract or other contractual instrument will contain a requirement to process, store, or transmit FCI or CUI; and

(2) Prior to awarding a subcontract or other contractual instrument, ensure that the subcontractor has a current CMMC certificate or current CMMC status at the CMMC level that is appropriate for the information that is being flowed down to the subcontractor based on the requirements at 32 CFR 170.23.

(End of clause)

252.211-7003 Item Unique Identification and Valuation.

(Jan 2023)

ITEM UNIQUE IDENTIFICATION AND VALUATION (JAN 2023)

(a) *Definitions.* As used in this clause-

"Automatic identification device" means a device, such as a reader or interrogator, used to retrieve data encoded on machine-readable media.

"Concatenated unique item identifier" means-

(1) For items that are serialized within the enterprise identifier, the linking together of the unique identifier data elements in order of the issuing agency code, enterprise identifier, and unique serial number within the enterprise identifier; or

(2) For items that are serialized within the original part, lot, or batch number, the linking together of the unique identifier data elements in order of the issuing agency code; enterprise identifier; original part, lot, or batch number; and serial number within the original part, lot, or batch number.

"Data matrix" means a two-dimensional matrix symbology, which is made up of square or, in some cases, round modules arranged within a perimeter finder pattern and uses the Error Checking and Correction 200 (ECC200) specification found within International Standards Organization (ISO)/International Electrotechnical Commission (IEC) 16022.

"Data qualifier" means a specified character (or string of characters) that immediately precedes a data field that defines the general category or intended use of the data that follows.

"DoD recognized unique identification equivalent" means a unique identification method that is in commercial use and has been recognized by DoD. All DoD recognized unique identification equivalents are listed at <https://www.acq.osd.mil/asda/dpc/ce/ds/unique-id.html>.

"DoD item unique identification" means a system of marking items delivered to DoD with unique item identifiers that have machine-readable data elements to distinguish an item from all other like and unlike items. For items that are serialized within the enterprise identifier, the unique item identifier shall include the data elements of the enterprise identifier and a unique serial number. For items that are serialized within the part, lot, or batch number within the enterprise identifier, the unique item identifier shall include the data elements of the enterprise identifier; the original part, lot, or batch number; and the serial number.

"Enterprise" means the entity (e.g., a manufacturer or vendor) responsible for assigning unique item identifiers to items.

"Enterprise identifier" means a code that is uniquely assigned to an enterprise by an issuing agency.

"Government's unit acquisition cost" means-

(1) For fixed-price type line, subline, or exhibit line items, the unit price identified in the contract at the time of delivery;

(2) For cost-type or undefinitized line, subline, or exhibit line items, the Contractor's estimated fully burdened unit cost to the Government at the time of delivery; and

(3) For items produced under a time-and-materials contract, the Contractor's estimated fully burdened unit cost to the Government at the time of delivery.

"Issuing agency" means an organization responsible for assigning a globally unique identifier to an enterprise, as indicated in the Register of Issuing Agency Codes for ISO/IEC 15459, located at http://www.aimglobal.org/?Reg_Authority15459.

"Issuing agency code" means a code that designates the registration (or controlling) authority for the enterprise identifier.

"Item" means a single hardware article or a single unit formed by a grouping of subassemblies, components, or constituent parts.

"Lot or batch number" means an identifying number assigned by the enterprise to a designated group of items, usually referred to as either a lot or a batch, all of which were manufactured under identical conditions.

"Machine-readable" means an automatic identification technology media, such as bar codes, contact memory buttons, radio frequency identification, or optical memory cards.

"Original part number" means a combination of numbers or letters assigned by the enterprise at item creation to a class of items with the same form, fit, function, and interface.

"Parent item" means the item assembly, intermediate component, or subassembly that has an embedded item with a unique item identifier or DoD recognized unique identification equivalent.

"Serial number within the enterprise identifier" means a combination of numbers, letters, or symbols assigned by the enterprise to an item that provides for the differentiation of that item from any other like and unlike item and is never used again within the enterprise.

"Serial number within the part, lot, or batch number" means a combination of numbers or letters assigned by the enterprise to an item that provides for the differentiation of that item from any other like item within a part, lot, or batch number assignment.

"Serialization within the enterprise identifier" means each item produced is assigned a serial number that is unique among all the tangible items produced by the enterprise and is never used again. The enterprise is responsible for ensuring unique serialization within the enterprise identifier.

"Serialization within the part, lot, or batch number" means each item of a particular part, lot, or batch number is assigned a unique serial number within that part, lot, or batch number assignment. The enterprise is responsible for ensuring unique serialization within the part, lot, or batch number within the enterprise identifier.

"Type designation" means a combination of letters and numerals assigned by the Government to a major end item, assembly or subassembly, as appropriate, to provide a convenient means of differentiating between items having the same basic name and to indicate modifications and changes thereto.

"Unique item identifier" means a set of data elements marked on items that is globally unique and unambiguous. The term includes a concatenated unique item identifier or a DoD recognized unique identification equivalent.

"Unique item identifier type" means a designator to indicate which method of uniquely identifying a part has been used. The current list of accepted unique item identifier types is maintained at <https://www.acq.osd.mil/asda/dpc/ce/ds/unique-id.html>.

(b) The Contractor shall deliver all items under a contract line, subline, or exhibit line item.

(c) *Unique item identifier.*

(1) The Contractor shall provide a unique item identifier for the following:

(i) Delivered items for which the Government's unit acquisition cost is \$5,000 or more, except for the following line items:

Contract Line, Subline, or

Exhibit Line Item Number

Item Description

=====	=====
=====	=====
=====	=====

(ii) Items for which the Government's unit acquisition cost is less than \$5,000 that are identified in the Schedule or the following table:

Contract Line, Subline, or

Exhibit Line Item Number

Item Description

=====	=====
=====	=====
=====	=====

(If items are identified in the Schedule, insert "See Schedule in this table.")

(iii) Subassemblies, components, and parts embedded within delivered items, items with warranty requirements, DoD serially managed reparables and DoD serially managed nonreparables as specified in Attachment Number ____.

(iv) Any item of special tooling or special test equipment as defined in FAR 2.101 that have been designated for preservation and storage for a Major Defense Acquisition Program as specified in Attachment Number ____.

(v) Any item not included in (i), (ii), (iii), or (iv) for which the contractor creates and marks a unique item identifier for traceability.

(2) The unique item identifier assignment and its component data element combination shall not be duplicated on any other item marked or registered in the DoD Item Unique Identification Registry by the contractor.

(3) The unique item identifier component data elements shall be marked on an item using two dimensional data matrix symbology that complies with ISO/IEC International Standard 16022, Information technology - International symbology specification - Data matrix; ECC200 data matrix specification.

(4) *Data syntax and semantics of unique item identifiers.* The Contractor shall ensure that-

(i) The data elements (except issuing agency code) of the unique item identifier are encoded within the data matrix symbol that is marked on the item using one of the following three types of data qualifiers, as determined by the Contractor:

(A) Application Identifiers (AIs) (Format Indicator 05 of ISO/IEC International Standard 15434), in accordance with ISO/IEC International Standard 15418, Information Technology - EAN/UCC Application Identifiers and Fact Data Identifiers and Maintenance and ANSI MH 10.8.2 Data Identifier and Application Identifier Standard.

(B) Data Identifiers (DIs) (Format Indicator 06 of ISO/IEC International Standard 15434), in accordance with ISO/IEC International Standard 15418, Information Technology - EAN/UCC Application Identifiers and Fact Data Identifiers and Maintenance and ANSI MH 10.8.2 Data Identifier and Application Identifier Standard.

(C) Text Element Identifiers (TEIs) (Format Indicator 12 of ISO/IEC International Standard 15434), in accordance with the Air Transport Association Common Support Data Dictionary; and

(ii) The encoded data elements of the unique item identifier conform to the transfer structure, syntax, and coding of messages and data formats specified for Format Indicators 05, 06, and 12 in ISO/IEC International Standard 15434, Information Technology - Transfer Syntax for High Capacity Automatic Data Capture Media.

(5) *Unique item identifier.*

(i) The Contractor shall-

(A) Determine whether to-

(1) Serialize within the enterprise identifier;

(2) Serialize within the part, lot, or batch number; or

(3) Use a DoD recognized unique identification equivalent (e.g. Vehicle Identification Number); and

(B) Place the data elements of the unique item identifier (enterprise identifier; serial number; DoD recognized unique identification equivalent; and for serialization within the part, lot, or batch number only: original part, lot, or batch number) on items requiring marking by paragraph (c)(1) of this clause, based on the criteria provided in MIL-STD-130, Identification Marking of U.S. Military Property, latest version;

(C) Label shipments, storage containers and packages that contain uniquely identified items in accordance with the requirements of MIL-STD-129, Military Marking for Shipment and Storage, latest version; and

(D) Verify that the marks on items and labels on shipments, storage containers, and packages are machine readable and conform to the applicable standards. The contractor shall use an automatic identification technology device for this verification that has been programmed to the requirements of Appendix A, MIL-STD-130, latest version.

(ii) The issuing agency code-

(A) Shall not be placed on the item; and

(B) Shall be derived from the data qualifier for the enterprise identifier.

(d) For each item that requires item unique identification under paragraph (c)(1)(i), (ii), or (iv) of this clause or when item unique identification is provided under paragraph (c)(1)(v), in addition to the information provided as part of the Material Inspection and Receiving Report specified elsewhere in this contract, the Contractor shall report at the time of delivery, as part of the Material Inspection and Receiving Report, the following information:

- (1) Unique item identifier.
- (2) Unique item identifier type.
- (3) Issuing agency code (if concatenated unique item identifier is used).
- (4) Enterprise identifier (if concatenated unique item identifier is used).
- (5) Original part number (if there is serialization within the original part number).
- (6) Lot or batch number (if there is serialization within the lot or batch number).
- (7) Current part number (optional and only if not the same as the original part number).
- (8) Current part number effective date (optional and only if current part number is used).
- (9) Serial number (if concatenated unique item identifier is used).
- (10) Government's unit acquisition cost.
- (11) Unit of measure.
- (12) Type designation of the item as specified in the contract schedule, if any.
- (13) Whether the item is an item of Special Tooling or Special Test Equipment.
- (14) Whether the item is covered by a warranty.

(e) For embedded subassemblies, components, and parts that require DoD item unique identification under paragraph (c)(1)(iii) of this clause or when item unique identification is provided under paragraph (c)(1)(v), the Contractor shall report as part of the Material Inspection and Receiving Report specified elsewhere in this contract, the following information:

part.

- (1) Unique item identifier of the parent item under paragraph (c)(1) of this clause that contains the embedded subassembly, component, or

- (2) Unique item identifier of the embedded subassembly, component, or part.

- (3) Unique item identifier type.**

- (4) Issuing agency code (if concatenated unique item identifier is used).**

- (5) Enterprise identifier (if concatenated unique item identifier is used).**

- (6) Original part number (if there is serialization within the original part number).**

- (7) Lot or batch number (if there is serialization within the lot or batch number).**

- (8) Current part number (optional and only if not the same as the original part number).**

- (9) Current part number effective date (optional and only if current part number is used).**

- (10) Serial number (if concatenated unique item identifier is used).**

- (11) Description.

** Once per item.

(f) The Contractor shall submit the information required by paragraphs (d) and (e) of this clause as follows:

(1) End items shall be reported using the receiving report capability in Wide Area WorkFlow (WAWF) in accordance with the clause at 252.232-7003. If WAWF is not required by this contract, and the contractor is not using WAWF, follow the procedures at <http://dodprocurementtoolbox.com/site/uidregistry/>.

(2) Embedded items shall be reported by one of the following methods-

(i) Use of the embedded items capability in WAWF;

(ii) Direct data submission to the IUID Registry following the procedures and formats at <http://dodprocurementtoolbox.com/site/uidregistry/>; or

(iii) Via WAWF as a deliverable attachment for exhibit line item number (fill in) _____, Unique Item Identifier Report for Embedded Items, Contract Data Requirements List, DD Form 1423.

(g) *Subcontracts*. If the Contractor acquires by subcontract, any item(s) for which item unique identification is required in accordance with paragraph (c)(1) of this clause, the Contractor shall include this clause, including this paragraph (g), in the applicable subcontract(s), including subcontracts for commercial products or commercial services.

(End of clause)

Section J - List of Attachments

Attachments:

Number	Attachment Name	Attachment Description	Reference Identifier	Date
02	TECHNICAL CAPABILITIES STATEMENT	Performance Work Statement		10 Mar 2026
03	52-212-1 Addendum			10 Mar 2026

Section K - Representations, Certification, & Other Statements

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.203-11	Certification and Disclosure Regarding Payments to Influence Certain Federal Transactions.	Sep 2024		
52.240-90	Security Prohibitions and Exclusions Representations and Certifications. (Deviation)	Feb 2026		

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.203-7005	Representation Relating to Compensation of Former DoD Officials.	Sep 2022		
252.204-7008	Compliance with Safeguarding Covered Defense Information Controls.	Oct 2016		
252.225-7031	Secondary Arab Boycott of Israel .	Jun 2005		
252.225-7055	Representation Regarding Business Operations with the Maduro Regime.	May 2022		

FAR Clauses Incorporated by Full Text

52.222-18 Certification Regarding Knowledge of Child Labor for Listed End Products. (Feb 2021)
CERTIFICATION REGARDING KNOWLEDGE OF CHILD LABOR FOR LISTED END PRODUCTS (FEB 2021)

(a) *Definition.*

Forced or indentured child labor means all work or service-

(1) Exacted from any person under the age of 18 under the menace of any penalty for its nonperformance and for which the worker does not offer himself voluntarily; or

(2) Performed by any person under the age of 18 pursuant to a contract the enforcement of which can be accomplished by process or penalties.

(b) *Listed end products.* The following end product(s) being acquired under this solicitation is (are) included in the List of Products Requiring Contractor Certification as to Forced or Indentured Child Labor, identified by their country of origin. There is a reasonable basis to believe that listed end products from the listed countries of origin may have been mined, produced, or manufactured by forced or indentured child labor.

Listed End Product	Listed Countries of Origin
==	==
==	==

(c) *Certification.* The Government will not make award to an offeror unless the offeror, by checking the appropriate block, certifies to either paragraph (c)(1) or paragraph (c)(2) of this provision.

(1) ☐ The offeror will not supply any end product listed in paragraph (b) of this provision that was mined, produced, or manufactured in a corresponding country as listed for that end product.

(2) ☐ The offeror may supply an end product listed in paragraph (b) of this provision that was mined, produced, or manufactured in the corresponding country as listed for that product. The offeror certifies that it has made a good faith effort to determine whether forced or indentured child labor was used to mine, produce, or manufacture such end product. On the basis of those efforts, the offeror certifies that it is not aware of any such use of child labor.

(End of provision)

52.229-11 Tax on Certain Foreign Procurements-Notice and Representation.

(Mar 2026)

Tax on Certain Foreign Procurements-Notice and Representation (Jun 2020)

(a) *Definitions.* As used in this provision-

Foreign person means any person other than a United States person.

Specified Federal procurement payment means any payment made pursuant to a contract with a foreign contracting party that is for goods, manufactured or produced, or services provided in a foreign country that is not a party to an international procurement agreement with the United States. For purposes of the prior sentence, a foreign country does not include an outlying area of the United States.

United States person as defined in 26 U.S.C. 7701(a)(30) means

(1) A citizen or resident of the United States;

(2) A domestic partnership;

(3) A domestic corporation;

(4) Any estate (other than a foreign estate, within the meaning of 26 U.S.C. 701(a)(31)); and

(5) Any trust if-

(i) A court within the United States is able to exercise primary supervision over the administration of the trust; and

(ii) One or more United States persons have the authority to control all substantial decisions of the trust.

(b) Unless exempted, there is a 2 percent tax of the amount of a specified Federal procurement payment on any foreign person receiving such payment. See 26 U.S.C. 5000C and its implementing regulations at 26 CFR 1.5000C-1 through 1.5000C-7.

(c) Exemptions from withholding under this provision are described at 26 CFR 1.5000C-1(d)(5) through (7). The Offeror may claim an exemption from the withholding by using the Department of the Treasury Internal Revenue Service (IRS) Form W-14, Certificate of Foreign Contracting Party Receiving Federal Procurement Payments, available at www.irs.gov/w14. Any exemption claimed and self-certified on the IRS Form W-14 is subject to audit by the IRS. Any disputes regarding the imposition and collection of the 26 U.S.C. 5000C tax are adjudicated by the IRS as the 26 U.S.C. 5000C tax is a tax matter, not a contract issue. The IRS Form W-14 is provided to the acquiring agency rather than to the IRS.

(d) For purposes of withholding under 26 U.S.C. 5000C, the Offeror represents that

(1) It [] is [] is not a foreign person; and

(2) If the Offeror indicates "is" in paragraph (d)(1) of this provision, then the Offeror represents that-I am claiming on the IRS Form W-14 [] a full exemption, or [] partial or no exemption [*Offeror must select one*] from the excise tax.

(e) If the Offeror represents it is a foreign person in paragraph (d)(1) of this provision, then-

(1) The clause at FAR 52.229-12, Tax on Certain Foreign Procurements, will be included in any resulting contract; and

(2) The Offeror shall submit with its offer the IRS Form W-14. If the IRS Form W-14 is not submitted with the offer, exemptions will not be applied to any resulting contract and the Government will withhold a full 2 percent of each payment.

(f) If the Offeror selects "is" in paragraph (d)(1) and "partial or no exemption" in paragraph (d)(2) of this provision, the Offeror will be subject to withholding in accordance with the clause at FAR 52.229-12, Tax on Certain Foreign Procurements, in any resulting contract.

(g) A taxpayer may, for a fee, seek advice from the IRS as to the proper tax treatment of a transaction. This is called a private letter ruling. Also, the IRS may publish a revenue ruling, which is an official interpretation by the IRS of the Internal Revenue Code, related statutes, tax treaties, and regulations. A revenue ruling is the conclusion of the IRS on how the law is applied to a specific set of facts. For questions relating to the interpretation of the IRS regulations go to <https://www.irs.gov/help/tax-law-questions>.

(End of provision)

DFARS Clauses Incorporated by Full Text

252.204-7016 Covered Defense Telecommunications Equipment or Services-Representation.

(Dec 2019)

COVERED DEFENSE TELECOMMUNICATIONS EQUIPMENT OR SERVICES-REPRESENTATION (DEC 2019)

(a) *Definitions.* As used in this provision, "covered defense telecommunications equipment or services" has the meaning provided in the clause 252.204-7018, Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services.

(b) *Procedures.* The Offeror shall review the list of excluded parties in the System for Award Management (SAM) (<https://www.sam.gov>) for entities excluded from receiving federal awards for "covered defense telecommunications equipment or services".

(c) *Representation.* The Offeror represents that it ☐ does, ☐ does not provide covered defense telecommunications equipment or services as a part of its offered products or services to the Government in the performance of any contract, subcontract, or other contractual instrument.

(End of provision)

252.204-7017 Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services-Representation. (May 2021)

PROHIBITION ON THE ACQUISITION OF COVERED DEFENSE TELECOMMUNICATIONS EQUIPMENT OR SERVICES-REPRESENTATION (MAY 2021)

The Offeror is not required to complete the representation in this provision if the Offeror has represented in the provision at 252.204-7016, Covered Defense Telecommunications Equipment or Services-Representation, that it "does not provide covered defense telecommunications equipment or services as a part of its offered products or services to the Government in the performance of any contract, subcontract, or other contractual instrument."

(a) *Definitions.* "Covered defense telecommunications equipment or services," "covered mission," "critical technology," and "substantial or essential component," as used in this provision, have the meanings given in the 252.204-7018 clause, Prohibition on the Acquisition of Covered Defense Telecommunications Equipment or Services, of this solicitation.

(b) *Prohibition.* Section 1656 of the National Defense Authorization Act for Fiscal Year 2018 (Pub. L. 115-91) prohibits agencies from procuring or obtaining, or extending or renewing a contract to procure or obtain, any equipment, system, or service to carry out covered missions that uses covered defense telecommunications equipment or services as a substantial or essential component of any system, or as critical technology as part of any system.

(c) *Procedures.* The Offeror shall review the list of excluded parties in the System for Award Management (SAM) at <https://www.sam.gov> for entities that are excluded when providing any equipment, system, or service to carry out covered missions that uses covered defense telecommunications equipment or services as a substantial or essential component of any system, or as critical technology as part of any system, unless a waiver is granted.

(d) *Representation.* If in its annual representations and certifications in SAM the Offeror has represented in paragraph (c) of the provision at 252.204-7016, Covered Defense Telecommunications Equipment or Services-Representation, that it "does" provide covered defense telecommunications equipment or services as a part of its offered products or services to the Government in the performance of any contract, subcontract, or other contractual instrument, then the Offeror shall complete the following additional representation:

The Offeror represents that it ☐ will ☐ will not provide covered defense telecommunications equipment or services as a part of its offered products or services to DoD in the performance of any award resulting from this solicitation.

(e) *Disclosures.* If the Offeror has represented in paragraph (d) of this provision that it "will provide covered defense telecommunications equipment or services," the Offeror shall provide the following information as part of the offer:

(1) A description of all covered defense telecommunications equipment and services offered (include brand or manufacturer; product, such as model number, original equipment manufacturer (OEM) number, manufacturer part number, or wholesaler number; and item description, as applicable).

(2) An explanation of the proposed use of covered defense telecommunications equipment and services and any factors relevant to determining if such use would be permissible under the prohibition referenced in paragraph (b) of this provision.

(3) For services, the entity providing the covered defense telecommunications services (include entity name, unique entity identifier, and Commercial and Government Entity (CAGE) code, if known).

(4) For equipment, the entity that produced or provided the covered defense telecommunications equipment (include entity name, unique entity identifier, CAGE code, and whether the entity was the OEM or a distributor, if known).

(End of provision)

252.225-7000 Buy American--Balance of Payments Program Certificate. (Feb 2024)

BUY AMERICAN-BALANCE OF PAYMENTS PROGRAM CERTIFICATE-BASIC (FEB 2024)

(a) *Definitions.* "Commercially available off-the-shelf (COTS) item," "component," "critical component," "critical item," "domestic end product," "foreign end product," "qualifying country," "qualifying country end product," and "United States," as used in this provision, have the meanings given in the 252.225-7001, Buy American and Balance of Payments Program-Basic clause of this solicitation.

(b) *Evaluation.* The Government-

(1) Will evaluate offers in accordance with the policies and procedures of Part 225 of the Defense Federal Acquisition Regulation Supplement; and

(2) Will evaluate offers of qualifying country end products without regard to the restrictions of the Buy American statute or the Balance of Payments Program.

(c) *Certifications and identification of country of origin.*

(1) For all line items subject to the Buy American and Balance of Payments Program-Basic clause of this solicitation, the Offeror certifies that-

(i) Each end product, except those listed in paragraphs (c)(2) or (3) of this provision, is a domestic end product and that each domestic end product listed in paragraph (c)(4) of this provision contains a critical component or a critical item; and

(ii) For end products other than COTS items, components of unknown origin are considered to have been mined, produced, or manufactured outside the United States or a qualifying country. For those end products that do not consist wholly or predominantly of iron or steel or a combination of both, the Offeror shall also indicate whether these foreign end products exceed 55 percent domestic content, except for those that are COTS items. If the percentage of the domestic content is unknown, select "no".

(2) The Offeror certifies that the following end products are qualifying country end products:

Line Item Number	Country of Origin
_____	_____
_____	_____
_____	_____

(3) The following end products are other foreign end products, including end products manufactured in the United States that do not qualify as domestic end products. For those foreign end products that do not consist wholly or predominantly of iron or steel or a combination of both, the Offeror shall also indicate whether these foreign end products exceed 55 percent domestic content, except for those that are COTS items. If the percentage of the domestic content is unknown, select "no".

Line Item Number	Country of Origin (If known)	Exceeds 55% Domestic Content (yes/no)
_____	_____	_____
_____	_____	_____
_____	_____	_____

(4) The Offeror shall separately list the line item numbers of domestic end products that contain a critical component or a critical item (see Federal Acquisition Regulation 25.105).

Domestic end products containing a critical component or a critical item:

Line Item Number _____

[List as necessary]

(End of provision)

Section L - Instructions, Conditions, & Notices to Offerors or Quoters

FAR Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
52.212-1	Instructions to Offerors-Commercial Products and Commercial Services. (Deviation)	Feb 2026		

DFARS Clauses Incorporated by Reference

Number	Title	Effective Date	Alternate/ Deviation	Variation Effective Date
252.204-7019	Notice of NIST SP 800-171 DoD Assessment Requirements.	Nov 2023		
252.204-7024	Notice on the Use of the Supplier Performance Risk System.	Mar 2023		

FAR Clauses Incorporated by Full Text

52.252-1 Solicitation Provisions Incorporated by Reference. (Mar 2026)

Solicitation Provisions Incorporated by Reference (Feb 1998)

This solicitation incorporates one or more solicitation provisions by reference, with the same force and effect as if they were given in full text. Upon request, the Contracting Officer will make their full text available. The offeror is cautioned that the listed provisions may include blocks that must be completed by the offeror and submitted with its quotation or offer. In lieu of submitting the full text of those provisions, the offeror may identify the provision by paragraph identifier and provide the appropriate information with its quotation or offer. Also, the full text of a solicitation provision may be accessed electronically at this/these address(es):

DASN(P) site: <https://www.secnave.navy.mil/rda/DASN-P/Pages/NMCARS.aspx>

DFARS Clauses: <https://www.acq.osd.mil/dpap/dars/dfarspgi/current/index.html>

FAR Clauses: <https://acquisition.gov>

(End of provision)

52.252-5 Authorized Deviations in Provisions. (Mar 2026)

Authorized Deviations in Provisions (Nov 2020)

(a) The use in this solicitation of any Federal Acquisition Regulation (48 CFR Chapter 1) provision with an authorized deviation is indicated by the addition of "(DEVIATION)" after the date of the provision.

(b) The use in this solicitation of any **Defense Federal Acquisition Regulation** (48 CFR **Chapter 2**) provision with an authorized deviation is indicated by the addition of "(DEVIATION)" after the name of the regulation.

(End of provision)

Additional Regulation or Supplemental Clauses Incorporated by Full Text

L-204-H003 NOTIFICATION OF USE OF NAVY SUPPORT CONTRACTORS FOR OFFICIAL CONTRACT FILES (NAVSEA) (APR 2019) (Apr 2019)

(a) NAVSEA may use a contractor to manage official contract files here in after referred to as "the support contractor", including the official file supporting this procurement. These official files may contain information that is considered a trade secret, proprietary, business sensitive or otherwise protected pursuant to law or regulation, here in after referred to as "protected information". File management services consist of any of the following: secretarial or clerical support; data entry; document reproduction, scanning, imaging, or destruction; operation, management, or maintenance of paper-based or electronic mail rooms, file rooms, or libraries; and supervision in connection with functions listed herein.

(b) The cognizant Contracting Officer will ensure that any NAVSEA contract under which these file management services are acquired will contain a requirement that

- (1) The support contractor not disclose any information;
 - (2) Individual employees are to be instructed by the support contractor regarding the sensitivity of the official contract files;
 - (3) The support contractor performing these services be barred from providing any other supplies and/or services, or competing to do so, to NAVSEA for the period of performance of its contract and for an additional three years thereafter unless otherwise provided by law or regulation; and,
 - (4) In addition to any other rights the offeror may have, it is a third party beneficiary who has the right of direct action against the support contractor, or any person to whom the support contractor has released or disclosed Protected Information, for the unauthorized duplication, release, or disclosure of such Protected Information.
- (c) Submission of a proposal will be considered as consent to NAVSEA's permitting access to any information, irrespective of restrictive markings or the nature of the information submitted, by its file management support contractor for the limited purpose of executing its file support contract responsibilities.
- (d) NAVSEA may, without further notice, enter into contracts with other contractors for these services. Offerors are free to enter into separate non-disclosure agreements with the file support contractor. Contact the Procuring Contracting Officer for contractor specifics. However, any such agreement will not be considered a prerequisite before information submitted is stored in the files or otherwise encumber the government.

(End of Provision)

Section M - Evaluation Factors for Award

FAR Clauses Incorporated by Full Text

52.212-2 Evaluation-Commercial Products and Commercial Services. (Deviation)

(Mar 2026)

Evaluation-Commercial Products and Commercial Services (Feb 2026) (Deviation)

(a) Evaluation factors. The Government will award a contract resulting from this solicitation to the responsible Offeror whose offer conforming to the solicitation will be most advantageous to the Government, price and other factors considered. The following factors will be used to evaluate offers:

- **Technical Submission** (Technical Capability Certification Chart within Attachment A)
- **Price**
- **Past Performance**

Award(s) will be made for the technically acceptable item or combination of technically acceptable items that result in the lowest aggregate price to the Government.

Technical Acceptability: Will be determined by reviewing the technical capability certification chart (per Attachment A)

submitted for each item (or specification) to ensure that all of the technical requirements identified are met.

Technical acceptability will be defined as follows:

Technical Ratings	
Rating	Description
Acceptable	Quote meets all of the requirements identified.
Unacceptable	Quote does not meet all of the requirements identified.

Failure to meet any technical requirement for an item (or specification) will make the quotation unacceptable for that item (or that specification).

If an item (or specification) is determined to be technically unacceptable, the quotation will be considered technically unacceptable and not eligible for award.

Price: The estimated amount for each line item will be added together to determine the total estimated price which will become the evaluated price.

Past Performance:

(1) The offeror's past performance shall be evaluated in accordance with FAR 13.106-2 or 15.305(a)(2), as applicable. This procurement is subject to Supplier Performance Risk System (SPRS), authorized by the Department of Defense for use by participating activities during the acquisition of supplies and services.

(2) The purpose of the SPRS is to provide contracting personnel with quantifiable past performance information regarding delivery and quality, as collected from existing DoD reporting systems. SPRS uses the past performance data collected to classify each supplier's performance by Federal Supply Class(es) or Service Code(s).

(3) Quality: The method used in SPRS to classify the quality of a supplier's past performance is a comparison of quality records among all suppliers who have provided goods or services to the Federal Government which are categorized in the same Federal Supply Class or Service Class (FSC). Based on the comparison among suppliers in a specific FSC group, suppliers are classified by SPRS into a color rating that represents the supplier's overall quality performance for that specific Federal Supply Class or Service Class. The following is a summarization of the SPRS classification colors:

1. Dark Blue: Top 5% of suppliers in FSC group*
2. Purple: Next 10% of suppliers in FSC group*
3. Green: Next 70% of suppliers in FSC group*
4. Yellow: Next 10% of suppliers in FSC group*
5. Red: Bottom 5% of suppliers in FSC group*

* If all supplier performance ratings for an entire FSC group are equal, all suppliers in that group will be classified Green.

(4) Delivery: Supplier delivery past performance is classified in SPRS by the supplier's percentage of on time deliveries. On time deliveries are calculated using the number of line items delivered and a weighting factor which reflects the length of time a delivery was overdue.

(5) SPRS classifications are established monthly for each supplier and can be reviewed at <https://sprs.csd.disa.mil/>. Suppliers are granted access to SPRS for their own classifications. Offerors are encouraged to review their own classifications as well as the SPRS reporting procedures and methodology detailed in the PPIRS-SR Procedures Manual and the SPRS User Guide available at <https://sprs.csd.disa.mil/>. The method to challenge a rating is also found on the identified website.

(6) Suppliers with no history in SPRS will be considered to have a neutral SPRS rating.

(b) Options. N/A

(c) A written notice of award or acceptance of an offer, mailed or otherwise furnished to the successful offeror within the time for acceptance specified in the offer, shall result in a binding contract without further action by either party. Before the offer's specified expiration time, the Government may accept an offer (or part of an offer), whether or not there are negotiations after its receipt, unless a written notice of withdrawal is received before award.

The offeror's proposed price will be evaluated on the basis of price reasonableness, in accordance with FAR 13.106-3. All prices must be considered fair and reasonable as determined by the Government. Price quote shall be held firm for sixty (30) days.

(End of provision)