

Salient characteristics
Manual Blast Cabinet System – Facility 721

1.0. DESCRIPTION OF EQUIPMENT CHARACTERISTICS . The contractor shall provide a Manual Blast Cabinet System with the following specifications and components.

1.1. EQUIPMENT SPECIFICATIONS

1.1.1. Blast Enclosure

Feature	Description
Dimensions	26" deep x 36" wide x 28" high
Construction	#14 gauge Steel Cabinet
Access Door	(1) 20" deep x 22" high Dual Panel Swing Door with OSHA Interlock (Right Side)
Viewing Window	14" x 22" Safety-Glass with Rounded Corners and tool-free replacement
Operator Access	Ergonomic 8" Glove Rings with Arm Rest and Positive Seal
Lighting	(2) 16W LED Flood Lamps (1,280 lumens each)
Floor	1,000 lb. capacity, 3/16" thick Perforated Steel
Utility	Manual Blow-Off Gun (OSHA-Compliant) and 18" wide Pneumatic Foot Treadle

1.1.2. Suction Blast Media Delivery

Component	Description
Hopper	1 cubic foot Media Storage Hopper
Controls	Front-Mounted ½" Modular Piping with Pressure Regulator, Gauge, and Blast Control Valve
Filtration	General Purpose Filter with Sight Glass and Manual Drain
Blast Gun	MH-2 Long-Handle Blast Gun with 5/16" Ceramic Nozzle
Flow Regulator	SAR-2 Media Flow Regulator with Clean-Out Plug

1.1.3. Media Recovery & Dust Collection

Component	Description
Reclaimer	600 cfm Externally Tunable, Cyclonic Reclaimer

Hoses	8' Media Recovery Hose (4" dia.) and 11' Dust Hose (6" dia.)
Dust Collector	600 cfm Cartridge Dust Collector (CDC-6)
Blower	1 ½ hp Blower (clean air side)
Features	Minihelic Gauge, 16-Gallon Dust Drum, Pushbutton Reverse-Pulse Filter Cleaning

1.3. CERTIFICATIONS, STANDARDS, & REQUIREMENTS

Requirement	Specification
Certifications	All electrical work to be completed by a licensed electrician.
Standards	All electrical work will comply with the 2023 edition NFPA 70 National Electric Code (NEC).
Electrical Power	13 Amps at 230 volt, 60 Hz, 1 phase (for 1 ½ hp Blower Motor)
Blast Air	37 scfm clean, dry air at 80 psi with 40°F dew point (See Appendix 1)
