

**SALIENT CHARACTERISTICS
FOR
JLG High-Reach Vehicle Repairs**

SUPPORT REQUIREMENT:

Swing Drive Hub	Part#1001248468	Qty:1EA
Upper Lift Cylinder	Part#1001251004	Qty:1EA
LH Wheel 36X14-2	Part#1001207345	Qty:2EA
RH Wheel 36X14-2	Part#1001207346	Qty:2EA

GENERAL SPECIFICATIONS/CHARACTERISTICS:

Swing Drive Hub Replacement

- Safely secure the boom and turret against movement.
- Remove the existing, non-functional swing drive hub.
- Install the new OEM Swing Drive Hub (Part #1001248468).
- Ensure proper meshing with the swing gear and torque all fasteners to JLG specifications.
- Functionally test the 360-degree swing function to ensure smooth and controlled operation.

Upper Lift Cylinder Replacement

- Mechanically support the upper boom section to relieve all pressure from the lift cylinder.
- Safely relieve hydraulic pressure from the cylinder lines.
- Disconnect hydraulic lines and remove the cylinder mounting pins.
- Remove the faulty Upper Lift Cylinder.
- Install the new OEM Upper Lift Cylinder (Part #1001251004).
- Reconnect hydraulic lines and bleed the system of any air in accordance with the manufacturer's service manual.
- Test the lift and lower functions throughout their full range of motion.

Wheel and Tire Assembly Replacement

- Lift and safely support the man lift chassis using appropriate stands.
- Remove all four existing wheel assemblies.
- Install two (2) new OEM LH Wheel assemblies (Part #1001207345) on the left side of the unit.
- Install two (2) new OEM RH Wheel assemblies (Part #1001207346) on the right side of the unit.
- Torque all lug nuts to the manufacturer's specified value.

Final Testing and Inspection

- Upon completion of all repairs, the contractor shall conduct a full functional test of the man lift, including drive, steering, lift, and swing functions.
- The contractor shall perform a final inspection to ensure there are no hydraulic leaks and all components are secure.
- The work area shall be cleaned of all debris, and the man lift shall be returned in a ready-to-use condition.