

BLDG 368 DOOR SCHEDULE

DOOR NO.

TOTAL WIDTH

HEIGHT

THICKNESS

TYPE

MATERIAL

TYPE

MATERIAL

HEAD

JAMB

SILL

FIRE RATING

HARDWARE

COMMENTS

FIRST FLOOR

101A

6'-0"

7'-0"

1' - 0 3/4"

D2

ALUM/GLASS

SF3

ALUM

A3/AE704

B2/AE704

C1/AE704

101B

6'-0"

7'-0"

1' - 0 3/4"

D2

ALUM/GLASS

SF3

ALUM

A3/AE704 SIM

B2/AE704

C1/AE704

102

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

S5

60 MIN

HDW-8

9,10,14

103

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

60 MIN

HDW-8

9,10,14

104A

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

-

HDW-8

9,10,14,17

104B

12'-0"

10'-0"

D6

-

-

-

H5 SIM

J3 SIM

S6 SIM

HDW-3

1,13

105

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

-

HDW-8

9,10,14

106

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

-

HDW-10

9,10,14,17

107A

3'-6"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

-

HDW-8

9,10,14

107B

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H4

H4 SIM

S9

60 MIN

HDW-1

1,2,9,10,14

108

6'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

-

HDW-14

109

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

S5

60 MIN

HDW-11.1

2

111

3'-6"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

S5

60 MIN

HDW-8

9,10,14

112A

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H4

H4 SIM

S9

-

HDW-8

9,10,14,18

112B

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H3

H3 SIM

S9

-

HDW-1

9,10,14

112C

14'-0"

14'-0"

D6

-

-

-

H5

J3

S6

HDW-3

1,13

112D

12'-0"

10'-0"

D6

-

-

-

H5

J3

S6 SIM

-

HDW-4

1,13,18

113

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

S5

-

HDW-13

9,14,17

114A

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

-

HDW-8

9,10,14

114B

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H4

H4 SIM

S9

-

HDW-8

9,10,14,18

115

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

S3

-

HDW-13

7

116

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

90 MIN

HDW-13

2,11

117A

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

S3

-

HDW-12

117B

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

S3

-

HDW-12

120

6'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H3 SIM

H3 SIM

S9

-

HDW-2

1,7,9

121A

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

-

-

HDW-8

9,10,14

121B

3'-0"

7'-0"

1 3/4"

D1

STL

F2

STL

H3 SIM

H3 SIM

S9

-

HDW-1

9,10,14

122A

3'-0"

7'-0"

1 3/4"

D1

WD

F2

STL

H2

J2

60 MIN

HDW-11.1

2

122B

8'-0"

7'-0"

D6

STL

D6

STL

H6 SIM

J4

S7

60 MIN

HDW-4

1,13

122C

8'-0"

7'-0"

D6

STL

D6

STL

H6 SIM

J4

S7

60 MIN

HDW-4

1,13,18

122D

3'-0"

7'-0"

1 3/4"

D3

STL

F1

STL

H3

H3 SIM

S9

-

HDW-1

1,2,9,10,14

123A

3'-0"

7'-0"

1 3/4"

D1

STL

F2

STL

H2

J2

S9 SIM

-

HDW-8

9,10,18

123B

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H3

H3 SIM

S9

60 MIN

HDW-1

1,2,9,10,14

123C

16'-0"

16'-0"

D6

STL

-

STL

H5

J3

S6

-

HDW-3

1,13

124A

4'-0"

7'-0"

1 3/4"

D1

STL

F2

STL

H2

J2

S5

-

HDW-8

9,10,14

124B

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H4

H4 SIM

S9

-

HDW-1

9,10,14

124C

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H4

H4 SIM

S9

60 MIN

HDW-1

1,2,9,10,14

124D

16'-0"

16'-0"

D6

STL

-

STL

H5 SIM

J3 SIM

S6 SIM

-

HDW-3

1,13

124E

16'-0"

16'-0"

D6

STL

-

STL

H5 SIM

J3 SIM

S6 SIM

-

HDW-3

1,13

125

6'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H4

H4 SIM

S9

60 MIN

HDW-2

1,2,7,9

SECOND FLOOR

201

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-8

9,10

202

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-9

203

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-9

205

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-13

9,17

206A

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-8

9,10,14

206B

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-13

207A

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-8

9,10,14

207B

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-8

9,10,14

208

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-7

4,9,10,14

209

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-9

9,10,17

210A

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-9

9,10,17

210B

2'-8"

7'-0"

1 3/8"

ETR

ETR

ETR

ETR

ETR

12

211

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-9

9,10,17

212

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H2

J2

60 MIN

HDW-11

2

215

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S3

-

HDW-13

17

216

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S3

-

HDW-12

10

217

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S3

-

HDW-12

10

218A

3'-0"

7'-0"

1 3/4"

D1

STL

F1

STL

H1

J1

-

HDW-7.1

9,10,14

218B

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-7

4,9,10,14

219

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9

9,10,17

220

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9

9,10

221

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9

9,10,17

222

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-7

223

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-13

9,10,14,17

224

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S4

-

HDW-9.1

4,11,16

226

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

-

HDW-13

227

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H2

J2

S4

60 MIN

HDW-11.1

2

228

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-8

9,10

229

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9.1

17

230

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9

9,10,17

231

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9

9,10,17

232

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9

9,10,17

233

3'-0"

7'-0"

1 3/4"

D1

WD

F1

STL

H1

J1

S5

-

HDW-9

9,10,17

2

DOOR SCHEDULE COMMENTS

1. INSULATED DOOR & FRAME ASSEMBLY

2. UNDERWRITERS LABORATORIES (UL) LABELED DOOR / FRAME RATED ASSEMBLY.

3. REMOVABLE (KEYED) MULLION AT PAIR BLAST / HURRICANE RESISTANT DOOR & FRAME ASSEMBLY. KEYED TO MATCH DOOR LOCKSET AND COORDINATED WITH GOVERNMENT SELECTED KEYING SYSTEM.

4. (MAIN ENTRY) LOCKSET TO BE FED SPEC FF-L-2890C (TYPE III) & EXIT DEVICE WITH INTEGRAL FED SPEC FF-L-2740 ELECTROMECHANICAL COMBINATION LOCK, OUTSIDE CARD READER WITH PIN PAD, INSIDE CARD READER WITHOUT PIN PAD AND DOOR FRAME MOUNTED BALANCED MAGNETIC SWITCH. COORDINATE REMAINDER OF HARDWARE WITH SPEC SECTION 08 71 00.

5. (EXIT ONLY) LOCKSET TO BE FED SPEC FF-L-2890C (TYPE III) & EXIT DEVICE WITH NO EXTERIOR TRIM ON OUTSIDE OF DOOR, LOCAL SOUNDING DOOR OPEN ALARM (SEPARATE FROM IDS SYSTEM) AND DOOR FRAME MOUNTED BALANCED MAGNETIC SWITCH. COORDINATE REMAINDER OF HARDWARE WITH SPEC SECTION 08 71 00.

6. EXIT ONLY DOOR

7. DOOR ASTRAGAL FOR SECURITY & SOUND REQUIREMENTS

8. CARD READER & BALANCED MAGNETIC SWITCH

9. CARD READER W/ PIN PAD & BALANCED MAGNETIC SWITCH

10. SOUND RATED ASSEMBLY, STC 45 (MIN) - SOUND GROUP 3

11. SOUND RATED ASSEMBLY, STC 50 (MIN) - SOUND GROUP 4

12. EXISTING DOOR TO REMAIN

13. OVERHEAD COILING SERVICE DOOR TO BE ELECTRICALLY OPERATED WITH CHAIN HOIST SECONDARY OPERATION.

14. NON-REMOVABLE PIN (NRP) HEAVY DUTY HINGES

15. EXISTING OVERHEAD DOOR TO REMAIN

16. DOOR FACE STEEL TO BE 18 GA (MIN), HINGES REINFORCED TO 7 GA (MIN), DOOR CLOSER REINFORCED TO 12 GA (MIN), & LOCK AREA REINFORCED TO 10 GA (MIN).

17. UNDERCUT DOOR 3/4"

18. PROVIDE TRAFFIC RATED EXPANSION JOINT ASSEMBLY WITH HEAVY DUTY STEEL COVER PLATE @ FLOOR JOINT FROM EXISTING TO ADDITION @ DOOR ASSEMBLY

GENERAL NOTES

THIS SHEET ONLY

A. REFER TO DOOR DETAILS ON SHEETS AE701 - AE702.

B. REFER TO GLAZING SCHEDULE, AE602, FOR DOOR LITE ("GL_") INFORMATION.

C. ALL DOOR HARDWARE, FASTENERS AND EXPOSED METAL MATERIALS TO BE TYPE 316 STAINLESS STEEL, UNLESS OTHERWISE NOTED.

D. SOUND TRANSMISSION CLASS (STC) RATING MINIMUM LEVEL TO BE EQUAL TO WALL SOUND ATTENUATION RATING, UNLESS OTHERWISE NOTED.

E. REFER TO SPECIFICATION SECTION 08 71 00 "HARDWARE SETS" FOR REMAINDER OF HARDWARE NOT SPECIFICALLY NOTED IN DOOR SCHEDULE COMMENTS.

F. REFER TO FINISH SCHEDULE GENERAL NOTES FOR INTERIOR DOOR & FRAME FINISH INFORMATION ON SHEET AF601.

G. EXTERIOR DOOR & FRAME FINISH TO MATCH EXISTING DOOR & FRAME ASSEMBLIES.

H. COORDINATE ELECTRONIC INTEGRATION OF SECURITY HARDWARE WITH ELECTRICAL SECURITY "TN" DRAWINGS.

I. WIRE MESH PERSONNEL GATE, PREPARED FOR DOOR HARDWARE. WIRE MESH PARTITION WIRE MESH AND FRAMING TO BE FULLY WELDED & EXPOSED WELDS GROUND SMOOTH. HARDWARE & FASTENERS TO BE STAINLESS STEEL. ALL GAPS IN & AROUND GATE ASSEMBLY TO BE SIZED TO PREVENT "REACH-IN" SECURITY THREAT. PROVIDE DOOR STRIKE LATCH GUARD COVER PLATE FOR SECURITY. SEE DOOR TYPE ELEVATIONS FOR SWING & SLIDE GATE TYPES.

CLARK NEXSEN

A JMT Company

4525 MAIN STREET

SUITE 1400

VIRGINIA BEACH, VA 23462

757-455-5800 FAX 757-455-5638

WWW.CLARKNEXSEN.COM

APPROVED

FOR COMMANDER NAVFAC

ACTIVITY

Approved by Don Bryant, PE, N10

Facilities Engineer, NSWWDG

via Email

SATISFACTORY TO DATE

07/09/2025

DES

DJH

DRW

DJH

CHK

RAM

PM/DM

JT/SW

BRANCH MANAGER

DJD

CHIEF ENGINEER

JWJ

FIRE PROTECTION

HPN

DEPARTMENT OF THE NAVY

NAVAL FACILITIES ENGINEERING SYSTEMS COMMAND

NAVAL FACILITIES ENGINEERING SYSTEMS COMMAND ~ MID-ATLANTIC

NAVAL STATION - NORFOLK, VA

NAS OCEANA, DAM NECK ANNEX

Q-1075 SOF OPERATIONS BUILDING ADDITION

DOOR SCHEDULE

SCALE: AS NOTED

PROJECT NO.

1625040

CONSTR. CONTR. NO.

N40085-19-D-9041

NAVFAC DRAWING NO.

12928998

SHEET

93

OF

239

AE601