

Product datasheet

Vertical lifting fabric door

ASSA ABLOY VL3190

ASSA ABLOY
Entrance Systems

Experience a safer
and more open world



Copyright and Disclaimer Notice

Although the contents of this publication have been compiled with the greatest possible care, ASSA ABLOY cannot accept liability for any damage that might arise from errors or omissions in this publication. We also reserve the right to make appropriate technical modifications/replacements without prior notice.

No rights can be derived from the contents of this document.

Color guides: Color differences may occur due to different printing and publication methods.

ASSA ABLOY as word and logo are trademarks belonging to the ASSA ABLOY Group.

No part of this publication may be copied or published by means of scanning, printing, photocopying, microfilm or any other process whatsoever without prior permission in writing by ASSA ABLOY.

© ASSA ABLOY 2006-2024.

All rights reserved.

Technical facts

Features

Max size: (W/H) depending on wind load*	19000 x 20000 mm
Door leaf thickness:	290 mm
Fabric types:	Standard: Polyester (coating: plasticised PVC) Options: Arctic, sound reduction, heat resistant, security
Color:	9 standard colours
Guide rails material:	Aluminium
Windows:	Vision panels (width 800 mm standard)
Seals:	Bottom, side and top seal
Operation:	Standard: Electrical operator Optional: Automated operation, Access control, Safety functions

*Other sizes available on request.

Note! For larger openings, see ASSA ABLOY Special Doors with virtually no size limitations other than what is practical. ASSA ABLOY Special Doors can be delivered as large single belt doors (with 2-motor drive), large single wire rope doors or multiple door systems.

Performance

Operating speed:	0.15-0.25 m/s
Wind load resistance: (differential pressure)	Can withstand almost any wind load by varying the size and the spacing of the intermediate sections.
Wind speed, door in motion:	< 20 m/s
Sound reduction (standard):	15 dB Rw (ISO 717)
Water resistance:	Class 3 (EN 12425, 0.11 kPa (for a closed door)
Air permeability:	Class 2-3 (EN 12426)
Operating environment temperature range:	-35 °C to +70 °C
Thermal transmittance:	Depending on door size. Specific data on request.