

04 MARCH 2026

MILITARY SEALIFT COMMAND NORFOLK, STRATEGIC SEALIFT PROGRAM SUPPORT
OFFICE, N103A

SOURCES SOUGHT NOTICE NO: N32205-SS-N321-26-068

SUBJECT: 90-DAY DRY CARGO TIME CHARTER WITH ONE 90-DAY OPTION PERIOD

1. THIS IS MARKET RESEARCH CONDUCTED BY THE STRATEGIC SEALIFT PROGRAM OFFICE OF MSC. IT IS A REQUEST FOR INFORMATION ONLY AND YOUR RESPONSE WILL NOT BE CONSIDERED AN OFFER. THIS REQUEST FOR INFORMATION DOES NOT COMMIT THE GOVERNMENT TO PAY ANY COSTS INCURRED IN THE PREPARATION OR SUBMISSION TO THIS SOURCES SOUGHT NOTICE OR TO CONTRACT FOR SERVICES.

2. MSC REQUESTS INFORMATION ABOUT THE PRICE AND AVAILABILITY OF ONE U.S. OR FOREIGN-FLAG SELF-SUSTAINING COMBINATION CONTAINER/BREAKBULK VESSEL CAPABLE OF CARRYING A MINIMUM OF 250 TEU'S.

3. VESSEL SPECIFICATIONS:

- THE VESSEL SHALL HAVE A MINIMUM SPEED OF ADVANCE (SOA) OF 15 KNOTS OR FASTER (LADEN)
- THE VESSEL SHALL HAVE A MINIMUM OPERATING RANGE OF 8,000 NAUTICAL MILES.
- THE VESSEL'S MAXIMUM DRAFT SHALL NOT EXCEED 35 FEET

4. CARGO DESCRIPTION:

- CONTAINER CAPACITY. THE VESSEL SHALL ACCOMMODATE A MINIMUM OF 250 TWENTY-FOOT EQUIVALENT UNIT (TEU) CONTAINERS. WITHIN THE SPECIFIED 250 TEU CAPACITY, THE VESSEL SHALL BE ABLE TO ACCOMMODATE VARIOUS COMBINATIONS OF TWENTY-FOOT AND FORTY-FOOT CONTAINERS WITH THE ABILITY TO CARRY A COMBINATION OF AT LEAST 80 FORTY-FOOT CONTAINERS AND 70 TWENTY-FOOT CONTAINERS.
- VESSEL SHALL BE CAPABLE OF CARRYING A MAXIMUM LOAD AVERAGING 14 METRIC TONS PER CONTAINER, 100 OF WHICH MAY WEIGH 22 METRIC TONS, WITHIN ACCEPTABLE LIMITS FOR OVERALL DISPLACEMENT (LOAD LINE), TRIM, STABILITY AND HULL STRESS AS SPECIFIED BY THE REGULATORY AGENCY FOR THAT VESSEL.
- THE VESSEL MUST BE ABLE TO CARRY 150,000 CUBIC FEET OF CARGO WITH A MINIMUM 10FT OVERHEAD CLEARANCE.
- THE TEU AND CUBE REQUIREMENTS ARE EXCLUSIVE OF EACH OTHER (I.E. SHIP SHALL BE CAPABLE OF 250 TEUS OR 150,000 CUBIC FEET).
- REFRIGERATED CONTAINER OUTLETS. WITHIN THE 250 TEU CAPACITY SPECIFIED ABOVE, VESSEL SHALL ACCOMMODATE A MINIMUM OF 50 REEFER CONTAINERS (TWENTY-FOOT OR FORTY-FOOT) WITH OUTLETS, SUPPLIED FROM THE SHIP'S INTERNAL ELECTRICAL DISTRIBUTION SYSTEM, CAPABLE OF SUSTAINING REFRIGERATED TEU CONTAINERS OPERATING ON:
 - 200 VAC, 3 PHASE, 50/60 HZ
 - 220 VAC, 3 PHASE, 60 HZ

- 380-415 VAC, 3 PHASE, 50 HZ
 - 440 VAC, 3 PHASE, 60 HZ
- BREAKBULK CAPACITY. THE VESSEL SHALL HAVE A MINIMUM BREAKBULK CARGO CAPACITY OF 150,000 CUBIC FEET BALE WITH A MINIMUM 10 FEET OF CLEARANCE EXCLUSIVE OF CAPACITY REQUIREMENTS SET FORTH ABOVE. VESSEL SHALL BE CAPABLE OF CARRYING BREAKBULK AMMUNITION WITH PROPER SEGREGATION. THE GOVERNMENT WILL SHEATH HOLDS AS REQUIRED. THE VESSEL WILL BE PROVIDED WITH SUFFICIENT TIE-DOWN POINTS (PAD EYES, D-RINGS, ETC.) TO SECURE VARIOUS TYPES OF BREAKBULK CARGO OR VEHICLES.
- CARGO STOWAGE. THE VESSEL SHALL BE ABLE TO ACCOMMODATE ALL STANDARD TYPES OF DRY CARGO CONTAINERS, REFRIGERATED CONTAINERS, FLATRACKS, AND ISO TANK CONTAINERS.
- THE VESSEL SHALL BE EQUIPPED WITH SUFFICIENT QUANTITIES OF MATCHING STACKING CONES, AUTOMATIC TWIST LOCKS (SATL/IBC), CONTAINER DECK SOCKETS, “D” RING FITTINGS FOR CONTAINER DECK SOCKETS CAPABLE OF LASHING BREAKBULK CARGO, CHAINS AND BINDERS FOR LASHING BREAKBULK CARGO AND LASHING GEAR FOR CARRIAGE AND SECURING OF ALL CONTAINERS IN STACKS OF TWO-HIGH MINIMUM ON DECK.
- HAZARDOUS MATERIAL. THE VESSEL SHALL BE CAPABLE OF CARRYING ALL TYPES OF HAZARDOUS CARGO WITH PROPER SEGREGATIONS.
- CARGO GEAR. THE VESSEL MUST BE SELF-SUSTAINING FOR LOADING AND DISCHARGING BREAKBULK, CONTAINERIZED AND VEHICLE CARGOES. VESSEL’S GEAR SHALL CONSIST OF AT LEAST TWO BOOMS OR CRANES WITH A MINIMUM OF 30 LT SWL LIFTING CAPACITY AT ALL HATCHES WHERE TWENTY/FORTY FOOT CONTAINERS ARE STOWED AND THE CAPABILITY OF LIFTING 50 LT IN TANDEM.
- VESSEL MUST BE EQUIPPED WITH CERTIFIED TWENTY- AND FORTY-FOOT SPREADER BARS. SUCH SPREADER BARS SHALL BE SUPPLIED BY THE VESSEL OWNER.
- ALL LASHING AND SECURING GEAR FOR CONTAINERS ARE TO BE PROVIDED BY THE VESSEL OWNER INCLUDING ITEMS SUCH AS ADEQUATE DEVICES, I.E. TWIST LOCKS, STRAPS, CHAINS, ETC. TO ENSURE SAFE STOWAGE.
- DECK LOADING. TANK TOPS INTENDED FOR STOWAGE SHALL BE DESIGNED TO ACCOMMODATE HEAVY VEHICLES, UP TO AND INCLUDING THE M-1 TANK WITH A UNIFORMLY DISTRIBUTED LOAD OF MINIMUM 525 PSF. THESE DECKS SHALL BE CAPABLE OF SUPPORTING THE LOCAL LOADS IMPOSED BY SUCH VEHICLES WITHOUT RECOURSE TO MANDATORY PARKING PATTERNS. THESE DECKS SHALL ALSO BE CAPABLE OF SUPPORTING LIGHTER VEHICLES WITH SMALL FOOTPRINTS (WHICH MAY IMPOSE MORE SEVERE LOCAL LOADING AND SPECIFIC DECK STRUCTURES) SUCH AS FULLY LOADED 2.5-TON TRUCKS OR FORKLIFT TRUCKS. NO GRATING IS PERMITTED ON DECKS INTENDED FOR CARGO STOWAGE.

5. PLACE / RANGE OF DELIVERY: SINGAPORE, SINGAPORE

6. PLACE / RANGE OF REDELIVERY: SINGAPORE, SINGAPORE

7. LAYDAYS: PROMPT (RESPONDENTS PROVIDE DATE OF EARLIEST AVAILABILITY)

8. CHARTER PERIOD: ONE 90-DAY TIME CHARTER PERIOD WITH ONE 90-DAY OPTION PERIOD.

9. SPECIAL REQUIREMENTS: NONE

10. INTERESTED PARTIES ARE REQUESTED TO PROVIDE THE FOLLOWING INFORMATION:

- A. NAME AND COMPLETE DESCRIPTION OF THE VESSEL.
- B. PROPOSED LAYDAY(S).
- C. DAILY CHARTER HIRE RATE AND ANY DELIVERY/REDELIVERY BONUSES, IF APPLICABLE
- D. COMPANY'S NAME AND UNIQUE ENTITY IDENTIFIER.
- E. BUSINESS SIZE. REQUEST LARGE BUSINESSES PROVIDE DETAILS REGARDING POSSIBLE SUB-CONTRACTING OPPORTUNITIES.
- F. FUEL CONSUMPTION RATES IN METRIC TONS (BOTH UNDERWAY AND INPORT WORKING.)
- G. STATEMENT OR INFORMATION AFFIRMING THAT VESSEL MEETS OR EXCEEDS ALL REQUIREMENTS IN NUMBER 1-8 OF THIS REQUEST
- H. ANY OTHER PERTINENT QUESTIONS OR COMMENTS

11. THE FEDERAL ACQUISITION REGULATION 19.102 ESTABLISHES THE SMALL BUSINESS SIZE STANDARD FOR THIS TYPE OF WATER TRANSPORTATION SERVICE AS NAICS "483111" WITH A SMALL BUSINESS SIZE LIMITATION OF 1,050 EMPLOYEES. PLEASE INDICATE IF BUSINESS IS A SMALL BUSINESS CONCERN.

12. RESPONSES ARE REQUESTED, VIA EMAIL, PRIOR TO **1100 HOURS, EASTERN TIME, FRIDAY, 06 MARCH 2026**. THE POINT OF CONTACT IS TIFFANY GALLON, EMAIL TIFFANY.N.GALLON.CIV@US.NAVY.MIL, OR TEL (564) 226-8986.

SIGNED: CHRISTOPHER TOMLIN, CONTRACTING OFFICER, MSC, N103A