

SALIENT CHARACTERISTICS

PURCHASE UP TO THREE ROLLOVER SNOWPLOW

MUST MEET OR EXCEED ALL CHARACTERISTICS

1. FREIGHTLINER 108SD CHASSIS OR EQUIVALENT
2. MUST HAVE MECHANICAL DRIVE AWD
3. TRANSFER CASE MUST ALLOW 20 INCHES OF GROUND CLEARANCE (MINIMUM) TO ACCOMMODATE BELLY BLADE INSTALL.
4. CUMMINS L9 DIESEL ENGINE OR EQUIVALENT
5. 370 HP WITH 1250 FT-LBS OF TORQUE (MINIMUM)
6. ALLISON AUTOMATIC TRANSMISSION WITH PTO PROVISIONS OR EQUIVALENT
7. 20K POUND MECHANICAL DRIVE FRONT AXLE (MINIMUM)
8. 26K POUND REAR AXLE (MINIMUM)
9. SINGLE REAR AXLE WITH DUAL TIRES TO LIMIT THE OVERALL WHEELBASE OF THE TRUCK
10. 180 INCH WHEELBASE (MAXIMUM)
11. FRONT MOUNTED ROLLOVER PLOW, 12 FOOT BLADE (MINIMUM)
12. 12 FOOT (MINIMUM) UNDER BODY SCRAPER WITH POWER REVERSE ANGLE
13. CONSTANT RUNNING FRONT MOUNTED GEAR PUMP
14. IN CAB AIR CONTROLS FOR ROLLOVER AND UNDERBODY ATTACHMENT
15. MUST HAVE FACTORY BEACON LIGHTS AND FORWARD-FACING HID WORK LIGHTS
16. AMBER SNOW FIGHTER LIGHTS FRONT MOUNTED
17. FULL WARNING LIGHT PACKAGE TO INCLUDE BEACONS AND HEATED REAR STROBE LIGHTS IF LED
18. FULL WORK LIGHT PACKAGE TO INCLUDE HEATED LEDS LENSES FOR THE UNDER BODY SCRAPER AND REVERSE LIGHTS AS WELL AS CANNON LIGHTS ON THE ROOF LIGHT BAR
19. STAINLESS STEEL BOX WITH DUMP CAPABILITIES TO ALLOW BALLAST TO BE CHANGED AND BED TO BE CLEANED FOR CORROSION PREVENTION
20. AM/FM RADIO
21. AIR RIDE SEATS
22. FRONT AND REAR TOW POINTS FOR VEHICLE RECOVERY
23. COMPLETE FRONT AND REAR SPARE TIRES
24. INDIVIDUAL UNIQUE IDENTIFICATION (IUID) LABEL REGISTERED IN WAAF
25. 2 PHYSICAL BOOK COPIES OF ALL PARTS, SERVICE, AND OPERATORS' MANUALS
26. MUST HAVE 1 YEAR WARRANTY ON UNIT EFFECTIVE FROM THE TIME OF DELIVERY (MINIMUM)
27. MUST HAVE A 2 YEAR WARRANTY ON THE ENGINE EFFECTIVE FROM THE TIME OF DELIVERY (MINIMUM)
28. DELIVERED TO FORT DRUM, NY