

All products must meet standards greater than or equal too.

Name of Item: Skid Steer (CTL) Plus attachments listed in this Statement of Work

Salient Characteristics:

Engine

Gross Power - SAE J1995: must be at least 122hp

Bore: 4.7 inches

Displacement: 221 in

Net Power: ISO 120 hp

Net Power - SAE 82 hp

Peak Torque : 406 lb/ft

Stroke: 3.9 inches

Operating Specifications

Rated Operating Capacities - 35% Tipping Load: 4205 lbs.

Breakout Force - Lift Cylinder: 6422 lbs.

Breakout Force - Tilt Cylinder 9963 lbs.

Ground Pressure - With 450 mm/17.7 in Track: 4.5 psi

Rated Operating Capacities - 50% Tipping Load: 4033 lbs.

Rated Operating Capacity with Optional Counterweight 2996 lbs.

Tipping Load 12015 lbs.

Weights

Operating Weight 12705 lbs.

Dimensions

Clearance at Maximum Lift and Dump: 106.1 inches

Ground Clearance: 11 inches

Height - Top of Cab: 87.8 inches

Length - Track on Ground: 72.3 inches

Length - With Bucket on Ground: 152.8 inches

Maximum Overall Height: 165.1 inches

Overall Length - with Track: 75.8 inches

Turning Radius from Center - Bucket (racked) 91.3 in

Turning Radius from Center - Coupler 60.3 in

Turning Radius from Center - Machine Rear 76 in

Vehicle Width (450 mm/17.7 in tracks): 77.8 in

Maximum Dump Angle: 44.7°

Service Refill Capacities

Cooling System: 4.6 gal.

4.6 gal (US)

Engine Crankcase: 2.4 gal.

Fuel Tank: 36.9 gal.

Hydraulic System: 10.8 gal

Hydraulic Tank: 6.9 gal.

Diesel Exhaust Fluid (DEF) Tank: 2.9 gal.

Power Train

Travel Speed - Forward or Reverse - One Speed: 5.2 mile/h

Travel Speed - Forward or Reverse - Two Speed: 7.8 mile/h

Hydraulic System

Hydraulic Flow - XE - Maximum Loader Hydraulic Pressure: 4496 psi

Hydraulic Flow - XE - Maximum Loader Hydraulic Flow: maximum 40 gal/min

Hydraulic Flow - XE - Hydraulic Power (calculated): 103.9 hp

Attachments and Other Specifications Needed

Two copies of Owners/Operating Manual and One digital copy of parts manual

Warranty of 5 years/2000 hrs.

LM2 Land Management Package LM2 (HD1 + increased fuel capacity (220 L/58 gal), turbo guard, exhaust stack wrap, DPF/Emission component wraps, light guarding, quick disconnect guarding, hydraulic lines guard cover (under step), screw-to-connect auxiliary hydraulic couplings, and engine air inlet pre-cleaner.) This option will include:

Part number 609-9666 Auxiliary hydraulic cooler kit

Part number 637-3002 Reversing fan kit

Dealer installed options

Part number 638-6745 Amber Warning beacon kit

Part number 596-6898 Fire suppression system

Dealer procured and Installed 2.5 lb ABC Fire Extinguisher, mounted for emergency access

Part number 596-6898 Fire suppression system

Part number 475-2800 MH418 67-inch-wide working width Mulcher Head attachment

Part number 610-2780 BRX418 72-inch-wide cutting width Brush Hog attachment

Part number 627-8751 Grapple Bucket 80-inch wide Skeleton Grapple Bucket attachment

Part number 541-0940 79-inch wide 6-way blade attachment

86-inch Multipurpose bucket w/ 1 piece bolt-on cutting edge, and spill guard to prevent material spillage over back of bucket

Part number 532-7810 Class 2 Heavy Duty Fork Carriage attachment

Part number 540-1433 Class 2 Heavy Duty Forks

Delivery location and Point of Contacts

Dealer provides Delivery to Mountain Home Air Force Base:

1350 Liberator St. Bldg. 1352 Mountain Home AFB, 83648

POC: Bryson Gundlach 208-901-2794 first then Brent Higbee 208-912-5421 as a secondary contact

Four-hour Machine Orientation on site

Service and Safe operation techniques